

Cisco

Exam Questions 300-610

Designing Cisco Data Center Infrastructure (DCID)



NEW QUESTION 1

Which feature provides a sandbox to convert NX-OS CLI commands to REST-based scripts on Cisco Nexus 7700 Series Switches?

- A. NX-API
- B. Postman
- C. Bash shell
- D. Guest shell

Answer: A

NEW QUESTION 2

Drag and drop the SAN components from the left onto the correct design considerations on the right.

fabric logins	used to logically separate a SAN fabric
ISL	must be considered for the end-to-end oversubscription ratio
VSAN	these exchanges increase as a result of server virtualization
zone	must be considered when implementing access control

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

fabric logins	VSAN
ISL	ISL
VSAN	fabric logins
zone	zone

NEW QUESTION 3

The management of the Cisco Nexus switches is provided over an isolated put-of-band network. The VDC feature is configured on the Cisco Nexus core switches. How is out-of-band management access provided for each VDC?

- A. All the VDC have the same out-of-band IP address.
- B. Each VDC has a dedicated out-of-band Ethernet management port.
- C. Each VDC has a unique out-of-band IP address from the same IP subnet.
- D. Each VDC has a unique out-of-band IP address from different IP subnets among VDCs.

Answer: C

NEW QUESTION 4

Which type of encoding is used on 8-Gbps links as compared to 10-Gbps links?

- A. 8-Gbps links use 64B/66B encoding, and 10-Gbps links use 8B/10B encoding.
- B. 8-Gbps links use 8B/10B encoding, and 10-Gbps links use 64B/66B encoding.
- C. 8-Gbps links and 10-Gbps links use 8B/10B encoding.
- D. 8-Gbps links and 10-Gbps links use 64B/66B encoding.

Answer: B

NEW QUESTION 5

What can be implemented on Cisco Nexus 5600 Series Switches for link redundancy within a Fibre Channel fabric?

- A. vPC+
- B. E-Trunk
- C. SAN port channel
- D. LACP port channel

Answer: D

NEW QUESTION 6

What is an advantage of using OTV as compared to VPLS for data center redundancy?

- A. prevents loops on point-to-point links
- B. provides head-end replication
- C. uses a proactive MAC advertisement
- D. provides full-mesh connectivity

Answer: A

NEW QUESTION 7

What are two functions of a Network Services Orchestrator in an NFV environment? (Choose two.)

- A. It operates at the resource-facing services layer and provides overall lifecycle management at the network service level.
- B. It provides an API-based northbound interface for transparent integration with systems that operate at the resource-facing services layer.
- C. It provides a standards-based southbound interface for transparent integration with systems that operate at the customer-facing services layer.
- D. It provides a standards-based northbound interface for transparent integration with systems that operate at the customer-facing services layer.
- E. It operates at the customer-facing services layer and provides the management interface for the virtual network devices.

Answer: AB

NEW QUESTION 8

Which Cisco HyperFlex feature provides virtual machine-level cost scaling for desktop virtualization growth?

- A. HyperFlex Edge support
- B. encryption offload cards
- C. dedicated compute nodes
- D. fabric interconnects

Answer: A

NEW QUESTION 9


Which two configurations are available by using a service profile template in Cisco UCS Manager? (Choose two.)

- A. number of vHBAs
- B. ARP entries
- C. UUID assignment
- D. VXLAN membership
- E. target server

Answer: AC

NEW QUESTION 10

Refer to the exhibit.



An engineer must assign multiple Fibre Channel IDs to a single port channel. Which two features must be enabled this goal? (Choose two.)

- A. SAN Pin Groups on the Cisco UCS Fabric Interconnects.
- B. NPV feature on the Cisco MDS Series.
- C. end-host mode feature on the Cisco UCS Fabric Interconnects
- D. NPIV feature on the Cisco MDS Series
- E. Smart Zoning feature on the Cisco UCS Fabric Interconnects

Answer: BD

NEW QUESTION 10

Which orchestration tool should be used for the management and analytics of servers across multiple sites?

- A. Cisco Intersight
- B. Cisco Nexus Fabric Manager
- C. Cisco UCS Manager
- D. Cisco Data Center Network Manager

Answer: A

NEW QUESTION 14

Which factor determines the choice of platform designing a Cisco HyperFlex infrastructure to support computer-aided design applications?

- A. network speed
- B. GPU support
- C. storage capacity
- D. processor count

Answer: C

NEW QUESTION 17

Which multicast rendezvous point redundancy mode is valid for Bidirectional PIM?

- A. Embedded RP
- B. Phantom RP
- C. MSDP
- D. PIM anycast RP

Answer: D

NEW QUESTION 19

What is a design consideration when implementing FSPF?

- A. Routes are based on the domain ID.
- B. Routes are based on the distance vector protocol.
- C. FSPF runs only on F Ports.
- D. FSPF runs on a per-chassis basis.

Answer: A

NEW QUESTION 20

Which two vSphere features must be included in the design of a Cisco HyperFlex systems stretched cluster? (Choose two.)

- A. HA
- B. VSS
- C. FT
- D. VDP
- E. DRS

Answer: AE

NEW QUESTION 25

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-610 Practice Exam Features:

- * 300-610 Questions and Answers Updated Frequently
- * 300-610 Practice Questions Verified by Expert Senior Certified Staff
- * 300-610 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 300-610 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-610 Practice Test Here](#)