

## DVA-C02 Dumps

### DVA-C02

<https://www.certleader.com/DVA-C02-dumps.html>



**NEW QUESTION 1**

A company is migrating legacy internal applications to AWS. Leadership wants to rewrite the internal employee directory to use native AWS services. A developer needs to create a solution for storing employee contact details and high-resolution photos for use with the new application.

Which solution will enable the search and retrieval of each employee's individual details and high-resolution photos using AWS APIs?

- A. Encode each employee's contact information and photos using Base64. Store the information in an Amazon DynamoDB table using a sort key.
- B. Store each employee's contact information in an Amazon DynamoDB table along with the object keys for the photos stored in Amazon S3.
- C. Use Amazon Cognito user pools to implement the employee directory in a fully managed software-as-a-service (SaaS) method.
- D. Store employee contact information in an Amazon RDS DB instance with the photos stored in Amazon Elastic File System (Amazon EFS).

**Answer: B**

**NEW QUESTION 2**

A developer has written the following IAM policy to provide access to an Amazon S3 bucket:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:PutObject"
      ],
      "Resource": "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    },
    {
      "Effect": "Deny",
      "Action": "s3:*",
      "Resource": "arn:aws:s3:::DOC-EXAMPLE-BUCKET/secrets*"
    }
  ]
}
```

Which access does the policy allow regarding the s3:GetObject and s3:PutObject actions?

- A. Access on all buckets except the "DOC-EXAMPLE-BUCKET" bucket
- B. Access on all buckets that start with "DOC-EXAMPLE-BUCKET" except the "DOC-EXAMPLE-BUCKET/secrets" bucket
- C. Access on all objects in the "DOC-EXAMPLE-BUCKET" bucket along with access to all S3 actions for objects in the "DOC-EXAMPLE-BUCKET" bucket that start with "secrets"
- D. Access on all objects in the "DOC-EXAMPLE-BUCKET" bucket except on objects that start with "secrets"

**Answer: D**

**NEW QUESTION 3**

A developer is creating an application that will give users the ability to store photos from their cellphones in the cloud. The application needs to support tens of thousands of users. The application uses an Amazon API Gateway REST API that is integrated with AWS Lambda functions to process the photos. The application stores details about the photos in Amazon DynamoDB.

Users need to create an account to access the application. In the application, users must be able to upload photos and retrieve previously uploaded photos. The photos will range in size from 300 KB to 5 MB.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Cognito user pools to manage user account
- B. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP
- C. Use the Lambda function to store the photos and details in the DynamoDB tabl
- D. Retrieve previously uploaded photos directly from the DynamoDB table.
- E. Use Amazon Cognito user pools to manage user account
- F. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP
- G. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the DynamoDB tabl
- H. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- I. Create an IAM user for each user of the application during the sign-up proces
- J. Use IAM authentication to access the API Gateway AP
- K. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the DynamoDB tabl
- L. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- M. Create a users table in DynamoD
- N. Use the table to manage user account
- O. Create a Lambda authorizer that validates user credentials against the users tabl
- P. Integrate the Lambda authorizer with API Gateway to control access to the AP
- Q. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as par of the photo details in the DynamoDB tabl
- R. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.

**Answer: B**

**NEW QUESTION 4**

A company is using an AWS Lambda function to process records from an Amazon Kinesis data stream. The company recently observed slow processing of the records. A developer notices that the iterator age metric for the function is increasing and that the Lambda run duration is constantly above normal.

Which actions should the developer take to increase the processing speed? (Choose two.)

- A. Increase the number of shards of the Kinesis data stream.
- B. Decrease the timeout of the Lambda function.
- C. Increase the memory that is allocated to the Lambda function.
- D. Decrease the number of shards of the Kinesis data stream.
- E. Increase the timeout of the Lambda function.

**Answer:** AC

#### NEW QUESTION 5

A developer is creating an application that will store personal health information (PHI). The PHI needs to be encrypted at all times. An encrypted Amazon RDS for MySQL DB instance is storing the data. The developer wants to increase the performance of the application by caching frequently accessed data while adding the ability to sort or rank the cached datasets.

Which solution will meet these requirements?

- A. Create an Amazon ElastiCache for Redis instance.
- B. Enable encryption of data in transit and at rest.
- C. Store frequently accessed data in the cache.
- D. Create an Amazon ElastiCache for Memcached instance.
- E. Enable encryption of data in transit and at rest. Store frequently accessed data in the cache.
- F. Create an Amazon RDS for MySQL read replica.
- G. Connect to the read replica by using SSL.
- H. Configure the read replica to store frequently accessed data.
- I. Create an Amazon DynamoDB table and a DynamoDB Accelerator (DAX) cluster for the table.
- J. Store frequently accessed data in the DynamoDB table.

**Answer:** A

#### NEW QUESTION 6

A company is running a custom application on a set of on-premises Linux servers that are accessed using Amazon API Gateway. AWS X-Ray tracing has been enabled on the API test stage.

How can a developer enable X-Ray tracing on the on-premises servers with the LEAST amount of configuration?

- A. Install and run the X-Ray SDK on the on-premises servers to capture and relay the data to the X-Ray service.
- B. Install and run the X-Ray daemon on the on-premises servers to capture and relay the data to the X-Ray service.
- C. Capture incoming requests on-premises and configure an AWS Lambda function to pull, process, and relay relevant data to X-Ray using the PutTraceSegments API call.
- D. Capture incoming requests on-premises and configure an AWS Lambda function to pull, process, and relay relevant data to X-Ray using the PutTelemetryRecords API call.

**Answer:** B

#### NEW QUESTION 7

A developer has an application that makes batch requests directly to Amazon DynamoDB by using the BatchGetItem low-level API operation. The responses frequently return values in the UnprocessedKeys element.

Which actions should the developer take to increase the resiliency of the application when the batch response includes values in UnprocessedKeys? (Choose two.)

- A. Retry the batch operation immediately.
- B. Retry the batch operation with exponential backoff and randomized delay.
- C. Update the application to use an AWS software development kit (AWS SDK) to make the requests.
- D. Increase the provisioned read capacity of the DynamoDB tables that the operation accesses.
- E. Increase the provisioned write capacity of the DynamoDB tables that the operation accesses.

**Answer:** BD

#### NEW QUESTION 8

A developer has an application that stores data in an Amazon S3 bucket. The application uses an HTTP API to store and retrieve objects. When the PutObject API operation adds objects to the S3 bucket the developer must encrypt these objects at rest by using server-side encryption with Amazon S3 managed keys (SSE-S3).

Which solution will meet this requirement?

- A. Create an AWS Key Management Service (AWS KMS) key.
- B. Assign the KMS key to the S3 bucket.
- C. Set the x-amz-server-side-encryption header when invoking the PutObject API operation.
- D. Provide the encryption key in the HTTP header of every request.
- E. Apply TLS to encrypt the traffic to the S3 bucket.

**Answer:** B

#### NEW QUESTION 9

A company is offering APIs as a service over the internet to provide unauthenticated read access to statistical information that is updated daily. The company uses Amazon API Gateway and AWS Lambda to develop the APIs. The service has become popular, and the company wants to enhance the responsiveness of the APIs.

Which action can help the company achieve this goal?

- A. Enable API caching in API Gateway.

- B. Configure API Gateway to use an interface VPC endpoint.
- C. Enable cross-origin resource sharing (CORS) for the APIs.
- D. Configure usage plans and API keys in API Gateway.

**Answer:** A

#### NEW QUESTION 10

A developer is building a web application that uses Amazon API Gateway to expose an AWS Lambda function to process requests from clients. During testing, the developer notices that the API Gateway times out even though the Lambda function finishes under the set time limit. Which of the following API Gateway metrics in Amazon CloudWatch can help the developer troubleshoot the issue? (Choose two.)

- A. CacheHitCount
- B. IntegrationLatency
- C. CacheMissCount
- D. Latency
- E. Count

**Answer:** BD

#### NEW QUESTION 10

A developer has created an AWS Lambda function that is written in Python. The Lambda function reads data from objects in Amazon S3 and writes data to an Amazon DynamoDB table. The function is successfully invoked from an S3 event notification when an object is created. However, the function fails when it attempts to write to the DynamoDB table. What is the MOST likely cause of this issue?

- A. The Lambda function's concurrency limit has been exceeded.
- B. DynamoDB table requires a global secondary index (GSI) to support writes.
- C. The Lambda function does not have IAM permissions to write to DynamoDB.
- D. The DynamoDB table is not running in the same Availability Zone as the Lambda function.

**Answer:** D

#### NEW QUESTION 14

A company is planning to securely manage one-time fixed license keys in AWS. The company's development team needs to access the license keys in automaton scripts that run in Amazon EC2 instances and in AWS CloudFormation stacks. Which solution will meet these requirements MOST cost-effectively?

- A. Amazon S3 with encrypted files prefixed with “config”
- B. AWS Secrets Manager secrets with a tag that is named SecretString
- C. AWS Systems Manager Parameter Store SecureString parameters
- D. CloudFormation NoEcho parameters

**Answer:** C

#### NEW QUESTION 19

An Amazon Kinesis Data Firehose delivery stream is receiving customer data that contains personally identifiable information. A developer needs to remove pattern-based customer identifiers from the data and store the modified data in an Amazon S3 bucket. What should the developer do to meet these requirements?

- A. Implement Kinesis Data Firehose data transformation as an AWS Lambda functio
- B. Configure the function to remove the customer identifier
- C. Set an Amazon S3 bucket as the destination of the delivery stream.
- D. Launch an Amazon EC2 instanc
- E. Set the EC2 instance as the destination of the delivery strea
- F. Run an application on the EC2 instance to remove the customer identifier
- G. Store the transformed data in anAmazon S3 bucket.
- H. Create an Amazon OpenSearch Service instanc
- I. Set the OpenSearch Service instance as the destination of the delivery strea
- J. Use search and replace to remove the customer identifier
- K. Export the data to an Amazon S3 bucket.
- L. Create an AWS Step Functions workflow to remove the customer identifier
- M. As the last step in the workflow, store the transformed data in an Amazon S3 bucke
- N. Set the workflow as the destination of the delivery stream.

**Answer:** A

#### NEW QUESTION 21

A company receives food orders from multiple partners. The company has a microservices application that uses Amazon API Gateway APIs with AWS Lambda integration. Each partner sends orders by calling a customized API that is exposed through API Gateway. The API call invokes a shared Lambda function to process the orders.

Partners need to be notified after the Lambda function processes the orders. Each partner must receive updates for only the partner's own orders. The company wants to add new partners in the future with the fewest code changes possible. Which solution will meet these requirements in the MOST scalable way?

- A. Create a different Amazon Simple Notification Service (Amazon SNS) topic for each partne
- B. Configure the Lambda function to publish messages for each partner to the partner's SNS topic.
- C. Create a different Lambda function for each partne
- D. Configure the Lambda function to notify each partner's service endpoint directly.



- E. Create an Amazon Simple Notification Service (Amazon SNS) topic
- F. Configure the Lambda function to publish messages with specific attributes to the SNS topic
- G. Subscribe each partner to the SNS topic
- H. Apply the appropriate filter policy to the topic subscriptions.
- I. Create one Amazon Simple Notification Service (Amazon SNS) topic
- J. Subscribe all partners to the SNS topic.

**Answer:** C

#### NEW QUESTION 23

A company wants to deploy and maintain static websites on AWS. Each website's source code is hosted in one of several version control systems, including AWS CodeCommit, Bitbucket, and GitHub.

The company wants to implement phased releases by using development, staging, user acceptance testing, and production environments in the AWS Cloud. Deployments to each environment must be started by code merges on the relevant Git branch. The company wants to use HTTPS for all data exchange. The company needs a solution that does not require servers to run continuously.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Host each website by using AWS Amplify with a serverless backend
- B. Connect the repository branches that correspond to each of the desired environment
- C. Start deployments by merging code changes to a desired branch.
- D. Host each website in AWS Elastic Beanstalk with multiple environment
- E. Use the EB CLI to link each repository branch
- F. Integrate AWS CodePipeline to automate deployments from version control code merges.
- G. Host each website in different Amazon S3 buckets for each environment
- H. Configure AWS CodePipeline to pull source code from version control
- I. Add an AWS CodeBuild stage to copy source code to Amazon S3.
- J. Host each website on its own Amazon EC2 instance
- K. Write a custom deployment script to bundle each website's static asset
- L. Copy the assets to Amazon EC2. Set up a workflow to run the script when code is merged.

**Answer:** A

#### NEW QUESTION 25

A company is migrating an on-premises database to Amazon RDS for MySQL. The company has read-heavy workloads. The company wants to refactor the code to achieve optimum read performance for queries.

Which solution will meet this requirement with LEAST current and future effort?

- A. Use a multi-AZ Amazon RDS deployment
- B. Increase the number of connections that the code makes to the database or increase the connection pool size if a connection pool is in use.
- C. Use a multi-AZ Amazon RDS deployment
- D. Modify the code so that queries access the secondary RDS instance.
- E. Deploy Amazon RDS with one or more read replicas
- F. Modify the application code so that queries use the URL for the read replicas.
- G. Use open source replication software to create a copy of the MySQL database on an Amazon EC2 instance
- H. Modify the application code so that queries use the IP address of the EC2 instance.

**Answer:** B

#### NEW QUESTION 29

For a deployment using AWS Code Deploy, what is the run order of the hooks for in-place deployments?

- A. BeforeInstall -> ApplicationStop -> ApplicationStart -> AfterInstall
- B. ApplicationStop -> BeforeInstall -> AfterInstall -> ApplicationStart
- C. BeforeInstall -> ApplicationStop -> ValidateService -> ApplicationStart
- D. ApplicationStop -> BeforeInstall -> ValidateService -> ApplicationStart

**Answer:** A

#### NEW QUESTION 34

A developer is creating a mobile app that calls a backend service by using an Amazon API Gateway REST API. For integration testing during the development phase, the developer wants to simulate different backend responses without invoking the backend service.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create an AWS Lambda function
- B. Use API Gateway proxy integration to return constant HTTP responses.
- C. Create an Amazon EC2 instance that serves the backend REST API by using an AWS CloudFormation template.
- D. Customize the API Gateway stage to select a response type based on the request.
- E. Use a request mapping template to select the mock integration response.

**Answer:** B

#### NEW QUESTION 39

A company has an Amazon S3 bucket that contains sensitive data. The data must be encrypted in transit and at rest. The company encrypts the data in the S3 bucket by using an AWS Key Management Service (AWS KMS) key. A developer needs to grant several other AWS accounts the permission to use the S3 GetObject operation to retrieve the data from the S3 bucket.

How can the developer enforce that all requests to retrieve the data provide encryption in transit?

- A. Define a resource-based policy on the S3 bucket to deny access when a request meets the condition "aws:SecureTransport": "false".

- B. Define a resource-based policy on the S3 bucket to allow access when a request meets the condition “aws:SecureTransport”: “false”.
- C. Define a role-based policy on the other accounts' roles to deny access when a request meets the condition of “aws:SecureTransport”: “false”.
- D. Define a resource-based policy on the KMS key to deny access when a request meets the condition of “aws:SecureTransport”: “false”.

**Answer:** A

#### NEW QUESTION 40

A financial company must store original customer records for 10 years for legal reasons. A complete record contains personally identifiable information (PII). According to local regulations, PII is available to only certain people in the company and must not be shared with third parties. The company needs to make the records available to third-party organizations for statistical analysis without sharing the PII.

A developer wants to store the original immutable record in Amazon S3. Depending on who accesses the S3 document, the document should be returned as is or with all the PII removed. The developer has written an AWS Lambda function to remove the PII from the document. The function is named removePii.

What should the developer do so that the company can meet the PII requirements while maintaining only one copy of the document?

- A. Set up an S3 event notification that invokes the removePii function when an S3 GET request is made. Call Amazon S3 by using a GET request to access the object without PII.
- B. Set up an S3 event notification that invokes the removePii function when an S3 PUT request is made. Call Amazon S3 by using a PUT request to access the object without PII.
- C. Create an S3 Object Lambda access point from the S3 console.
- D. Select the removePii function.
- E. Use S3 Access Points to access the object without PII.
- F. Create an S3 access point from the S3 console.
- G. Use the access point name to call the GetObjectLegalHold S3 API function.
- H. Pass in the removePii function name to access the object without PII.

**Answer:** C

#### NEW QUESTION 45

A development team wants to build a continuous integration/continuous delivery (CI/CD) pipeline. The team is using AWS CodePipeline to automate the code build and deployment. The team wants to store the program code to prepare for the CI/CD pipeline.

Which AWS service should the team use to store the program code?

- A. AWS CodeDeploy
- B. AWS CodeArtifact
- C. AWS CodeCommit
- D. Amazon CodeGuru

**Answer:** C

#### NEW QUESTION 50

A developer is migrating some features from a legacy monolithic application to use AWS Lambda functions instead. The application currently stores data in an Amazon Aurora DB cluster that runs in private subnets in a VPC. The AWS account has one VPC deployed. The Lambda functions and the DB cluster are deployed in the same AWS Region in the same AWS account.

The developer needs to ensure that the Lambda functions can securely access the DB cluster without crossing the public internet.

Which solution will meet these requirements?

- A. Configure the DB cluster's public access setting to Yes.
- B. Configure an Amazon RDS database proxy for the Lambda functions.
- C. Configure a NAT gateway and a security group for the Lambda functions.
- D. Configure the VPC, subnets, and a security group for the Lambda functions.

**Answer:** D

#### NEW QUESTION 55

A developer wants to insert a record into an Amazon DynamoDB table as soon as a new file is added to an Amazon S3 bucket.

Which set of steps would be necessary to achieve this?

- A. Create an event with Amazon EventBridge that will monitor the S3 bucket and then insert the records into DynamoDB.
- B. Configure an S3 event to invoke an AWS Lambda function that inserts records into DynamoDB.
- C. Create an AWS Lambda function that will poll the S3 bucket and then insert the records into DynamoDB.
- D. Create a cron job that will run at a scheduled time and insert the records into DynamoDB.

**Answer:** B

#### NEW QUESTION 58

A company has deployed infrastructure on AWS. A development team wants to create an AWS Lambda function that will retrieve data from an Amazon Aurora database. The Amazon Aurora database is in a private subnet in company's VPC. The VPC is named VPC1. The data is relational in nature. The Lambda function needs to access the data securely.

Which solution will meet these requirements?

- A. Create the Lambda function.
- B. Configure VPC1 access for the function.
- C. Attach a security group named SG1 to both the Lambda function and the database.
- D. Configure the security group inbound and outbound rules to allow TCP traffic on Port 3306.
- E. Create and launch a Lambda function in a new public subnet that is in a new VPC named VPC2. Create a peering connection between VPC1 and VPC2.
- F. Create the Lambda function.
- G. Configure VPC1 access for the function.
- H. Assign a security group named SG1 to the Lambda function.

- I. Assign a second security group named SG2 to the databas
- J. Add an inbound rule to SG1 to allow TCP traffic from Port 3306.
- K. Export the data from the Aurora database to Amazon S3. Create and launch a Lambda function in VPC1. Configure the Lambda function query the data from Amazon S3.

**Answer:** B

#### NEW QUESTION 59

A company has a multi-node Windows legacy application that runs on premises. The application uses a network shared folder as a centralized configuration repository to store configuration files in .xml format. The company is migrating the application to Amazon EC2 instances. As part of the migration to AWS, a developer must identify a solution that provides high availability for the repository.

Which solution will meet this requirement MOST cost-effectively?

- A. Mount an Amazon Elastic Block Store (Amazon EBS) volume onto one of the EC2 instance
- B. Deploy a file system on the EBS volum
- C. Use the host operating system to share a folde
- D. Update the application code to read and write configuration files from the shared folder.
- E. Deploy a micro EC2 instance with an instance store volum
- F. Use the host operating system to share a folde
- G. Update the application code to read and write configuration files from the shared folder.
- H. Create an Amazon S3 bucket to host the repositor
- I. Migrate the existing .xml files to the S3 bucket.Update the application code to use the AWS SDK to read and write configuration files from Amazon S3.
- J. Create an Amazon S3 bucket to host the repositor
- K. Migrate the existing .xml files to the S3 bucket.Mount the S3 bucket to the EC2 instances as a local volum
- L. Update the application code to read andwrite configuration files from the disk.

**Answer:** C

#### NEW QUESTION 62

A developer is creating a template that uses AWS CloudFormation to deploy an application. The application is serverless and uses Amazon API Gateway, Amazon DynamoDB, and AWS Lambda.

Which AWS service or tool should the developer use to define serverless resources in YAML?

- A. CloudFormation serverless intrinsic functions
- B. AWS Elastic Beanstalk
- C. AWS Serverless Application Model (AWS SAM)
- D. AWS Cloud Development Kit (AWS CDK)

**Answer:** C

#### NEW QUESTION 63

A developer is creating an AWS CloudFormation template to deploy Amazon EC2 instances across multiple AWS accounts. The developer must choose the EC2 instances from a list of approved instance types.

How can the developer incorporate the list of approved instance types in the CloudFormation template?

- A. Create a separate CloudFormation template for each EC2 instance type in the list.
- B. In the Resources section of the CloudFormation template, create resources for each EC2 instance type in the list.
- C. In the CloudFormation template, create a separate parameter for each EC2 instance type in the list.
- D. In the CloudFormation template, create a parameter with the list of EC2 instance types as AllowedValues.

**Answer:** D

#### NEW QUESTION 64

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your DVA-C02 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/DVA-C02-dumps.html>