

Exam Questions SCS-C01

AWS Certified Security- Specialty

<https://www.2passeasy.com/dumps/SCS-C01/>



NEW QUESTION 1

An IT department currently has a Java web application deployed on Apache Tomcat running on Amazon EC2 instances. All traffic to the EC2 instances is sent through an internet-facing Application Load Balancer (ALB)

The Security team has noticed during the past two days thousands of unusual read requests coming from hundreds of IP addresses. This is causing the Tomcat server to run out of threads and reject new connections

Which the SIMPLEST change that would address this server issue?

- A. Create an Amazon CloudFront distribution and configure the ALB as the origin
- B. Block the malicious IPs with a network access list (NACL).
- C. Create an IAM Web Application Firewall (WAF). and attach it to the ALB
- D. Map the application domain name to use Route 53

Answer: A

Explanation:

this is the simplest change that can address the server issue. CloudFront is a service that provides a global network of edge locations that cache and deliver web content. Creating a CloudFront distribution and configuring the ALB as the origin can help reduce the load on the Tomcat server by serving cached content to the end users. CloudFront can also provide protection against distributed denial-of-service (DDoS) attacks by filtering malicious traffic at the edge locations. The other options are either ineffective or complex for solving the server issue.

NEW QUESTION 2

A company discovers a billing anomaly in its AWS account. A security consultant investigates the anomaly and discovers that an employee who left the company 30 days ago still has access to the account.

The company has not monitored account activity in the past.

The security consultant needs to determine which resources have been deployed or reconfigured by the employee as quickly as possible.

Which solution will meet these requirements?

- A. In AWS Cost Explorer, filter chart data to display results from the past 30 day
- B. Export the results to a data tabl
- C. Group the data table by re-source.
- D. Use AWS Cost Anomaly Detection to create a cost monito
- E. Access the detec-tion histor
- F. Set the time frame to Last 30 day
- G. In the search area, choose the service category.
- H. In AWS CloudTrail, filter the event history to display results from the past 30 day
- I. Create an Amazon Athena table that contains the dat
- J. Parti-tion the table by event source.
- K. Use AWS Audit Manager to create an assessment for the past 30 day
- L. Apply a usage-based framework to the assessmen
- M. Configure the assessment to as-sess by resource.

Answer: C

NEW QUESTION 3

A company manages three separate IAM accounts for its production, development, and test environments, Each Developer is assigned a unique IAM user under the development account. A new application hosted on an Amazon EC2 instance in the developer account requires read access to the archived documents stored in an Amazon S3 bucket in the production account.

How should access be granted?

- A. Create an IAM role in the production account and allow EC2 instances in the development account to assume that role using the trust polic
- B. Provide read access for the required S3 bucket to this role.
- C. Use a custom identity broker to allow Developer IAM users to temporarily access the S3 bucket.
- D. Create a temporary IAM user for the application to use in the production account.
- E. Create a temporary IAM user in the production account and provide read access to Amazon S3. Generate the temporary IAM user's access key and secret key and store these on the EC2 instance used by the application in the development account.

Answer: A

Explanation:

<https://IAM.amazon.com/premiumsupport/knowledge-center/cross-account-access-s3/>

NEW QUESTION 4

A company wants to protect its website from man in-the-middle attacks by using Amazon CloudFront. Which solution will meet these requirements with the LEAST operational overhead?

- A. Use the SimpleCORS managed response headers policy.
- B. Use a Lambda@Edge function to add the Strict-Transport-Security response header.
- C. Use the SecurityHeadersPolicy managed response headers policy.
- D. Include the X-XSS-Protection header in a custom response headers policy.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/using-managed-response-headers-poli> The SecurityHeadersPolicy is a managed policy provided by Amazon CloudFront that includes a set of recommended security headers to enhance the security of your website. These headers help protect against various types of attacks, including man-in-the-middle attacks. By applying the SecurityHeadersPolicy to your CloudFront distribution, the necessary security headers will be automatically added to the responses sent by CloudFront. This reduces operational overhead because you don't have to manually configure or manage the headers yourself.

NEW QUESTION 5

A company deploys a set of standard IAM roles in AWS accounts. The IAM roles are based on job functions within the company. To balance operational efficiency and security, a security engineer implemented AWS Organizations SCPs to restrict access to critical security services in all company accounts.

All of the company's accounts and OUs within AWS Organizations have a default FullAWSAccess SCP that is attached. The security engineer needs to ensure that no one can disable Amazon GuardDuty and AWS Security Hub. The security engineer also must not override other permissions that are granted by IAM policies that are defined in the accounts.

Which SCP should the security engineer attach to the root of the organization to meet these requirements? A)

```
    "Version": "2012-10-17",
    "Statement": [
      {
        "Effect": "Deny",
        "Action": [
          "guardduty:DeleteDetector",
          "guardduty:UpdateDetector",
          "securityhub:DisableSecurityHub"
        ],
        "Resource": [
          "*"
        ]
      }
    ]
  }
```

B)

```
    {
      "Version": "2012-10-17",
      "Statement": [
        {
          "Effect": "Deny",
          "Action": "*",
          "Resource": "*"
        },
        {
          "Effect": "Allow",
          "NotAction": [
            "guardduty:DeleteDetector",
            "guardduty:UpdateDetector",
            "securityhub:DisableSecurityHub"
          ],
          "Resource": [
            "*"
          ]
        }
      ]
    }
```

C)

```
    {
      "Version": "2012-10-17",
      "Statement": [
        {
          "Effect": "Allow",
          "Action": "*",
          "Resource": "*"
        },
        {
          "Effect": "Deny",
          "NotAction": [
            "guardduty:DeleteDetector",
            "guardduty:UpdateDetector",
            "securityhub:DisableSecurityHub"
          ],
          "Resource": [
            "*"
          ]
        }
      ]
    }
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "NotAction": [
        "guardduty:DeleteDetector",
        "guardduty:UpdateDetector",
        "securityhub:DisableSecurityHub"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 6

A security engineer wants to use Amazon Simple Notification Service (Amazon SNS) to send email alerts to a company's security team for Amazon GuardDuty findings that have a High severity level. The security engineer also wants to deliver these findings to a visualization tool for further examination. Which solution will meet these requirements?

- A. Set up GuardDuty to send notifications to an Amazon CloudWatch alarm with two targets in CloudWatc
- B. From CloudWatch, stream the findings through Amazon Kinesis Data Streams into an Amazon OpenSearch Service domain as the first target for deliver
- C. Use Amazon QuickSight to visualize the finding
- D. Use OpenSearch queries for further analysi
- E. Deliver email alerts to the security team by configuring an SNS topic as a second target for the CloudWatch alar
- F. Use event pattern matching with an Amazon EventBridge event rule to send only High severity findings in the alerts.
- G. Set up GuardDuty to send notifications to AWS CloudTrail with two targets in CloudTrai
- H. From CloudTrail, stream the findings through Amazon Kinesis Data Firehose into an Amazon OpenSearch Service domain as the first target for deliver
- I. Use OpenSearch Dashboards to visualize the finding
- J. Use OpenSearch queries for further analysi
- K. Deliver email alerts to the security team by configuring an SNS topic as a second target for CloudTrai
- L. Use event pattern matching with a CloudTrail event rule to send only High severity findings in the alerts.
- M. Set up GuardDuty to send notifications to Amazon EventBridge with two target
- N. From EventBridge, stream the findings through Amazon Kinesis Data Firehose into an Amazon OpenSearch Service domain as the first target for deliver
- O. Use OpenSearch Dashboards to visualize the finding
- P. Use OpenSearch queries for further analysi
- Q. Deliver email alerts to the security team by configuring an SNS topic as a second target for EventBridg
- R. Use event pattern matching with an EventBridge event rule to send only High severity findings in the alerts.
- S. Set up GuardDuty to send notifications to Amazon EventBridge with two target
- T. From EventBridge, stream the findings through Amazon Kinesis Data Streams into an Amazon OpenSearch Service domain as the first target for deliver
- . Use Amazon QuickSight to visualize the finding
- . Use OpenSearch queries for further analysi
- . Deliver email alerts to the security team by configuring an SNS topic as a second target for EventBridg
- . Use event pattern matching with an EventBridge event rule to send only High severity findings in the alerts.

Answer: C

NEW QUESTION 7

A large corporation is creating a multi-account strategy and needs to determine how its employees should access the IAM infrastructure. Which of the following solutions would provide the MOST scalable solution?

- A. Create dedicated IAM users within each IAM account that employees can assume through federationbased upon group membership in their existing identity provider
- B. Use a centralized account with IAM roles that employees can assume through federation with their existing identity provider Use cross-account roles to allow the federated users to assume their target role in the resource accounts.
- C. Configure the IAM Security Token Service to use Kerberos tokens so that users can use their existing corporate user names and passwords to access IAM resources directly
- D. Configure the IAM trust policies within each account's role to set up a trust back to the corporation's existing identity provider allowing users to assume the role based off their SAML token

Answer: B

Explanation:

the most scalable solution for accessing the IAM infrastructure in a multi-account strategy. A multi-account strategy is a way of organizing your AWS resources into multiple IAM accounts for security, billing, and management purposes. Federation is a process that allows users to access AWS resources using credentials from an external identity provider such as Active Directory or SAML. IAM roles are sets of permissions that grant access to AWS resources. Cross-account roles are IAM roles that allow users in one account to access resources in another account. By using a centralized account with IAM roles that employees can assume through federation with their existing identity provider, you can simplify and streamline the access management process. By using cross-account roles to allow the

federated users to assume their target role in the resource accounts, you can enable granular and flexible access control across multiple accounts. The other options are either less scalable or less secure for accessing the IAM infrastructure in a multi-account strategy.

NEW QUESTION 8

A company wants to migrate its static primary domain website to AWS. The company hosts the website and DNS servers internally. The company wants the website to enforce SSL/TLS encryption block IP addresses from outside the United States (US), and take advantage of managed services whenever possible. Which solution will meet these requirements?

- A. Migrate the website to Amazon S3 Import a public SSL certificate to an Application Load Balancer
- B. Balancer with rules to block traffic from outside the US Migrate DNS to Amazon Route 53.
- C. Migrate the website to Amazon EC2 Import a public SSL certificate that is created by AWS Certificate Manager (ACM) to an Application Load Balancer with rules to block traffic from outside the US Update DNS accordingly.
- D. Migrate the website to Amazon S3. Import a public SSL certificate to Amazon CloudFront Use AWS WAF rules to block traffic from outside the US Update DNS accordingly
- E. Migrate the website to Amazon S3 Import a public SSL certificate that is created by AWS Certificate Manager (ACM) to Amazon CloudFront
- F. CloudFront Configure CloudFront to block traffic from outside the US
- G. Migrate DNS to Amazon Route 53.

Answer: D

Explanation:

To migrate the static website to AWS and meet the requirements, the following steps are required:

- Migrate the website to Amazon S3, which is a highly scalable and durable object storage service that can host static websites. To do this, create an S3 bucket with the same name as the domain name of the website, enable static website hosting for the bucket, upload the website files to the bucket, and configure the bucket policy to allow public read access to the objects. For more information, see [Hosting a static website on Amazon S3](#).
 - Import a public SSL certificate that is created by AWS Certificate Manager (ACM) to Amazon CloudFront, which is a global content delivery network (CDN) service that can improve the performance and security of web applications. To do this, request or import a public SSL certificate for the domain name of the website using ACM, create a CloudFront distribution with the S3 bucket as the origin, and associate the SSL certificate with the distribution. For more information, see [Using alternate domain names and HTTPS](#).
 - Configure CloudFront to block traffic from outside the US, which is one of the requirements. To do this, create a CloudFront web ACL using AWS WAF, which is a web application firewall service that lets you control access to your web applications. In the web ACL, create a rule that uses a geo match condition to block requests that originate from countries other than the US. Associate the web ACL with the CloudFront distribution. For more information, see [How AWS WAF works with Amazon CloudFront features](#).
 - Migrate DNS to Amazon Route 53, which is a highly available and scalable cloud DNS service that can route traffic to various AWS services. To do this, register or transfer your domain name to Route 53, create a hosted zone for your domain name, and create an alias record that points your domain name to your CloudFront distribution. For more information, see [Routing traffic to an Amazon CloudFront web distribution by using your domain name](#).
- The other options are incorrect because they either do not implement SSL/TLS encryption for the website (A), do not use managed services whenever possible (B), or do not block IP addresses from outside the US (C). [Verified References:](#)

- <https://docs.aws.amazon.com/AmazonS3/latest/userguide/HostingWebsiteOnS3Setup.html>
- <https://docs.aws.amazon.com/waf/latest/developerguide/waf-cloudfront.html>
- <https://docs.aws.amazon.com/Route53/latest/DeveloperGuide/routing-to-cloudfront-distribution.html>

NEW QUESTION 9

A company uses SAML federation to grant users access to AWS accounts. A company workload that is in an isolated AWS account runs on immutable infrastructure with no human access to Amazon EC2. The company requires a specialized user known as a break glass user to have access to the workload AWS account and instances in the case of SAML errors. A recent audit discovered that the company did not create the break glass user for the AWS account that contains the workload.

The company must create the break glass user. The company must log any activities of the break glass user and send the logs to a security team. Which combination of solutions will meet these requirements? (Select TWO.)

- A. Create a local individual break glass IAM user for the security team
- B. Create a trail in AWS CloudTrail that has Amazon CloudWatch Logs turned on
- C. Use Amazon EventBridge to monitor local user activities.
- D. Create a break glass EC2 key pair for the AWS account
- E. Provide the key pair to the security team
- F. Use AWS CloudTrail to monitor key pair activities
- G. Send notifications to the security team by using Amazon Simple Notification Service (Amazon SNS).
- H. Create a break glass IAM role for the account
- I. Allow security team members to perform the AssumeRoleWithSAML operation
- J. Create an AWS Cloud Trail trail that has Amazon CloudWatch Logs turned on
- K. Use Amazon EventBridge to monitor security team activities.
- L. Create a local individual break glass IAM user on the operating system level of each workload instance. Configure unrestricted security groups on the instances to grant access to the break glass IAM users.
- M. Configure AWS Systems Manager Session Manager for Amazon EC2. Configure an AWS Cloud Trail filter based on Session Manager
- N. Send the results to an Amazon Simple Notification Service (Amazon SNS) topic.

Answer: AE

Explanation:

The combination of solutions that will meet the requirements are:

- A. Create a local individual break glass IAM user for the security team. Create a trail in AWS CloudTrail that has Amazon CloudWatch Logs turned on. Use Amazon EventBridge to monitor local user activities. This is a valid solution because it allows the security team to access the workload AWS account and instances using a local IAM user that does not depend on SAML federation. It also enables logging and monitoring of the break glass user activities using AWS CloudTrail, Amazon CloudWatch Logs, and Amazon EventBridge.
- E. Configure AWS Systems Manager Session Manager for Amazon EC2. Configure an AWS CloudTrail filter based on Session Manager. Send the results to an Amazon Simple Notification Service (Amazon SNS) topic. This is a valid solution because it allows the security team to access the workload instances without opening any inbound ports or managing SSH keys or bastion hosts. It also enables logging and notification of the break glass user activities using AWS CloudTrail, Session Manager, and Amazon SNS.

The other options are incorrect because:

- B. Creating a break glass EC2 key pair for the AWS account and providing it to the security team is not a valid solution, because it requires opening inbound ports on the instances and managing SSH keys, which increases the security risk and complexity7.
- C. Creating a break glass IAM role for the account and allowing security team members to perform the AssumeRoleWithSAML operation is not a valid solution, because it still depends on SAML federation, which might not work in case of SAML errors8.
- D. Creating a local individual break glass IAM user on the operating system level of each workload instance and configuring unrestricted security groups on the instances to grant access to the break glass IAM users is not a valid solution, because it requires opening inbound ports on the instances and managing multiple local users, which increases the security risk and complexity9.

References:

1: Creating an IAM User in Your AWS Account 2: Creating a Trail - AWS CloudTrail 3: Using Amazon EventBridge with AWS CloudTrail 4: Setting up Session Manager - AWS Systems Manager 5: Logging Session Manager sessions - AWS Systems Manager 6: Amazon Simple Notification Service 7: Connecting to your Linux instance using SSH - Amazon Elastic Compute Cloud 8: AssumeRoleWithSAML - AWS Security Token Service 9: IAM Users - AWS Identity and Access Management

NEW QUESTION 10

A security team is developing an application on an Amazon EC2 instance to get objects from an Amazon S3 bucket. All objects in the S3 bucket are encrypted with an AWS Key Management Service (AWS KMS) customer managed key. All network traffic for requests that are made within the VPC is restricted to the AWS infrastructure. This traffic does not traverse the public internet.

The security team is unable to get objects from the S3 bucket Which factors could cause this issue? (Select THREE.)

- A. The IAM instance profile that is attached to the EC2 instance does not allow the s3 ListBucket action to the S3: bucket in the AWS accounts.
- B. The IAM instance profile that is attached to the EC2 instance does not allow the s3 ListParts action to the S3; bucket in the AWS accounts.
- C. The KMS key policy that encrypts the object in the S3 bucket does not allow the kms; ListKeys action to the EC2 instance profile ARN.
- D. The KMS key policy that encrypts the object in the S3 bucket does not allow the kms Decrypt action to the EC2 instance profile ARN.
- E. The security group that is attached to the EC2 instance is missing an outbound rule to the S3 managed prefix list over port 443.
- F. The security group that is attached to the EC2 instance is missing an inbound rule from the S3 managed prefix list over port 443.

Answer: ADE

Explanation:

<https://docs.aws.amazon.com/vpc/latest/userguide/security-group-rules.html>

To get objects from an S3 bucket that are encrypted with a KMS customer managed key, the security team needs to have the following factors in place:

- The IAM instance profile that is attached to the EC2 instance must allow the s3:GetObject action to the S3 bucket or object in the AWS account. This permission is required to read the object from S3. Option A is incorrect because it specifies the s3:ListBucket action, which is only required to list the objects in the bucket, not to get them.
- The KMS key policy that encrypts the object in the S3 bucket must allow the kms:Decrypt action to the EC2 instance profile ARN. This permission is required to decrypt the object using the KMS key. Option D is correct.
- The security group that is attached to the EC2 instance must have an outbound rule to the S3 managed prefix list over port 443. This rule is required to allow HTTPS traffic from the EC2 instance to S3 within the AWS infrastructure. Option E is correct. Option B is incorrect because it specifies the s3:ListParts action, which is only required for multipart uploads, not for getting objects. Option C is incorrect because it specifies the kms:ListKeys action, which is not required for getting objects. Option F is incorrect because it specifies an inbound rule from the S3 managed prefix list, which is not required for getting objects. Verified References:

➤ <https://docs.aws.amazon.com/kms/latest/developerguide/control-access.html>

➤ <https://docs.aws.amazon.com/vpc/latest/userguide/vpc-endpoints-s3.html>

NEW QUESTION 10

An Incident Response team is investigating an IAM access key leak that resulted in Amazon EC2 instances being launched. The company did not discover the incident until many months later The Director of Information Security wants to implement new controls that will alert when similar incidents happen in the future Which controls should the company implement to achieve this? (Select TWO.)

- A. Enable VPC Flow Logs in all VPCs Create a scheduled IAM Lambda function that downloads and parses the logs, and sends an Amazon SNS notification for violations.
- B. Use IAM CloudTrail to make a trail, and apply it to all Regions Specify an Amazon S3 bucket to receive all the CloudTrail log files
- C. Add the following bucket policy to the company's IAM CloudTrail bucket to prevent log tampering{"Version": "2012-10-17-","Statement": { "Effect": "Deny","Action": "s3:PutObject", "Principal": "-", "Resource": "arn:iam:s3:::cloudtrail/IAMLogs/111122223333/*"}}Create an Amazon S3 data event for an PutObject attempts, which sends notifications to an Amazon SNS topic.
- D. Create a Security Auditor role with permissions to access Amazon CloudWatch Logs m all Regions Ship the logs to an Amazon S3 bucket and make a lifecycle policy to ship the logs to Amazon S3 Glacier.
- E. Verify that Amazon GuardDuty is enabled in all Regions, and create an Amazon CloudWatch Events rule for Amazon GuardDuty findings Add an Amazon SNS topic as the rule's target

Answer: AE

NEW QUESTION 12

A company is designing a multi-account structure for its development teams. The company is using AWS Organizations and AWS Single Sign-On (AWS SSO). The company must implement a solution so that the development teams can use only specific AWS Regions and so that each AWS account allows access to only specific AWS services.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS SSO to set up service-linked roles with IAM policy statements that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.
- B. Deactivate AWS Security Token Service (AWS STS) in Regions that the developers are not allowed to use.
- C. Create SCPs that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.
- D. For each AWS account, create tailored identity-based policies for AWS SS
- E. Use statements that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.

Answer: C

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps_syntax.html#scp-eleme

NEW QUESTION 17

A company wants to monitor the deletion of AWS Key Management Service (AWS KMS) customer managed keys. A security engineer needs to create an alarm that will notify the company before a KMS key is deleted. The security engineer has configured the integration of AWS CloudTrail with Amazon CloudWatch. What should the security engineer do next to meet these requirements?

- A. Specify the deletion time of the key material during KMS key creatio
- B. Create a custom AWS Config rule to assess the key's scheduleddeletio
- C. Configure the rule to trigger upon a configuration chang
- D. Send a message to an Amazon Simple Notification Service (Amazon SNS) topic if the key is scheduled for deletion.
- E. Create an Amazon EventBridge rule to detect KMS API calls of DeleteAlia
- F. Create an AWS Lambda function to send an Amazon Simple Notification Service (Amazon SNS) message to the compan
- G. Add the Lambda function as the target of the EventBridge rule.
- H. Create an Amazon EventBridge rule to detect KMS API calls of DisableKey and ScheduleKeyDeletion.Create an AWS Lambda function to send an Amazon Simple Notification Service (Amazon SNS) message to the compan
- I. Add the Lambda function as the target of the EventBridge rule.
- J. Create an Amazon Simple Notification Service (Amazon SNS) policy to detect KMS API calls of RevokeGrant and ScheduleKeyDeletion.Create an AWS Lambda function to generate the alarm and send the notification to the compan
- K. Add the Lambda function as the target of the SNS policy.

Answer: C

Explanation:

The AWS documentation states that you can create an Amazon EventBridge rule to detect KMS API calls of DisableKey and ScheduleKeyDeletion. You can then create an AWS Lambda function to send an Amazon Simple Notification Service (Amazon SNS) message to the company. You can add the Lambda function as the target of the EventBridge rule. This method will meet the requirements.

References: : AWS KMS Developer Guide

NEW QUESTION 20

Which of the following are valid configurations for using SSL certificates with Amazon CloudFront? (Select THREE)

- A. Default AWS Certificate Manager certificate
- B. Custom SSL certificate stored in AWS KMS
- C. Default CloudFront certificate
- D. Custom SSL certificate stored in AWS Certificate Manager
- E. Default SSL certificate stored in AWS Secrets Manager
- F. Custom SSL certificate stored in AWS IAM

Answer: ABC

Explanation:

The key length for an RSA certificate that you use with CloudFront is 2048 bits, even though ACM supports larger keys. If you use an imported certificate with CloudFront, your key length must be 1024 or 2048 bits and cannot exceed 2048 bits. You must import the certificate in the US East (N. Virginia) Region. You must have permission to use and import the SSL/TLS certificate

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/cnames-and-https-requirements.html>

NEW QUESTION 21

A security engineer recently rotated all IAM access keys in an AWS account. The security engineer then configured AWS Config and enabled the following AWS Config managed rules; mfa-enabled-for-iam-console-access, iam-user-mfa-enabled, access-key-rotated, and iam-user-unused-credentials-check. The security engineer notices that all resources are displaying as noncompliant after the IAM GenerateCredentialReport API operation is invoked. What could be the reason for the noncompliant status?

- A. The IAM credential report was generated within the past 4 hours.
- B. The security engineer does not have the GenerateCredentialReport permission.
- C. The security engineer does not have the GetCredentialReport permission.
- D. The AWS Config rules have a MaximumExecutionFrequency value of 24 hours.

Answer: D

Explanation:

The correct answer is D. The AWS Config rules have a MaximumExecutionFrequency value of 24 hours. According to the AWS documentation¹, the MaximumExecutionFrequency parameter specifies the maximum frequency with which AWS Config runs evaluations for a rule. For AWS Config managed rules, this value can be one of the following:

- One_Hour
- Three_Hours
- Six_Hours
- Twelve_Hours
- TwentyFour_Hours

If the rule is triggered by configuration changes, it will still run evaluations when AWS Config delivers the configuration snapshot. However, if the rule is triggered periodically, it will not run evaluations more often than the specified frequency.

In this case, the security engineer enabled four AWS Config managed rules that are triggered periodically. Therefore, these rules will only run evaluations every 24 hours, regardless of when the IAM credential report is generated. This means that the resources will display as noncompliant until the next evaluation cycle, which could take up to 24 hours after the IAM access keys are rotated.

The other options are incorrect because:

- A. The IAM credential report can be generated at any time, but it will not affect the compliance status of the resources until the next evaluation cycle of the AWS Config rules.

- B. The security engineer was able to invoke the IAM GenerateCredentialReport API operation, which means they have the GenerateCredentialReport permission. This permission is required to generate a credential report that lists all IAM users in an AWS account and their credential status2.
- C. The security engineer does not need the GetCredentialReport permission to enable or evaluate AWS Config rules. This permission is required to retrieve a credential report that was previously generated by using the GenerateCredentialReport operation2.

References:

1: AWS::Config::ConfigRule - AWS CloudFormation 2: IAM: Generate and retrieve IAM credential reports

NEW QUESTION 22

A company uses AWS Organizations to manage several AWS accounts. The company processes a large volume of sensitive data. The company uses a serverless approach to microservices. The company stores all the data in either Amazon S3 or Amazon DynamoDB. The company reads the data by using either AWS Lambda functions or container-based services that the company hosts on Amazon Elastic Kubernetes Service (Amazon EKS) on AWS Fargate.

The company must implement a solution to encrypt all the data at rest and enforce least privilege data access controls. The company creates an AWS Key Management Service (AWS KMS) customer managed key.

What should the company do next to meet these requirements?

- A. Create a key policy that allows the kms:Decrypt action only for Amazon S3 and DynamoDB
- B. Create an SCP that denies the creation of S3 buckets and DynamoDB tables that are not encrypted with the key.
- C. Create an IAM policy that denies the kms:Decrypt action for the key
- D. Create a Lambda function that runs on a schedule to attach the policy to any new role
- E. Create an AWS Config rule to send alerts for resources that are not encrypted with the key.
- F. Create a key policy that allows the kms:Decrypt action only for Amazon S3, DynamoDB, Lambda, and Amazon EKS
- G. Create an SCP that denies the creation of S3 buckets and DynamoDB tables that are not encrypted with the key.
- H. Create a key policy that allows the kms:Decrypt action only for Amazon S3, DynamoDB, Lambda, and Amazon EKS
- I. Create an AWS Config rule to send alerts for resources that are not encrypted with the key.

Answer: B

NEW QUESTION 24

A Security Engineer receives alerts that an Amazon EC2 instance on a public subnet is under an SFTP brute force attack from a specific IP address, which is a known malicious bot. What should the Security Engineer do to block the malicious bot?

- A. Add a deny rule to the public VPC security group to block the malicious IP
- B. Add the malicious IP to IAM WAF blocked IPs
- C. Configure Linux iptables or Windows Firewall to block any traffic from the malicious IP
- D. Modify the hosted zone in Amazon Route 53 and create a DNS sinkhole for the malicious IP

Answer: D

Explanation:

What the Security Engineer should do to block the malicious bot. SFTP is a protocol that allows secure file transfer over SSH. EC2 is a service that provides virtual servers in the cloud. A public subnet is a subnet that has a route to an internet gateway, which allows it to communicate with the internet. A brute force attack is a type of attack that tries to guess passwords or keys by trying many possible combinations. A malicious bot is a software program that performs automated tasks for malicious purposes. Route 53 is a service that provides DNS resolution and domain name registration. A DNS sinkhole is a technique that redirects malicious or unwanted traffic to a different destination, such as a black hole server or a honeypot. By modifying the hosted zone in Route 53 and creating a DNS sinkhole for the malicious IP, the Security Engineer can block the malicious bot from reaching the EC2 instance on the public subnet. The other options are either ineffective or inappropriate for blocking the malicious bot.

NEW QUESTION 28

A company uses AWS Organizations to manage a multi-account AWS environment in a single AWS Region. The organization's management account is named management-01. The company has turned on AWS Config in all accounts in the organization. The company has designated an account named security-01 as the delegated administrator for AWS Config.

All accounts report the compliance status of each account's rules to the AWS Config delegated administrator account by using an AWS Config aggregator. Each account administrator can configure and manage the account's own AWS Config rules to handle each account's unique compliance requirements.

A security engineer needs to implement a solution to automatically deploy a set of 10 AWS Config rules to all existing and future AWS accounts in the organization. The solution must turn on AWS Config automatically during account creation.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Create an AWS CloudFormation template that contains the 10 required AWS Config rules
- B. Deploy the template by using CloudFormation StackSets in the security-01 account.
- C. Create a conformance pack that contains the 10 required AWS Config rules
- D. Deploy the conformance pack from the security-01 account.
- E. Create a conformance pack that contains the 10 required AWS Config rules
- F. Deploy the conformance pack from the management-01 account.
- G. Create an AWS CloudFormation template that will activate AWS Config
- H. Deploy the template by using CloudFormation StackSets in the security-01 account.
- I. Create an AWS CloudFormation template that will activate AWS Config
- J. Deploy the template by using CloudFormation StackSets in the management-01 account.

Answer: BE

NEW QUESTION 33

A company used a lift-and-shift approach to migrate from its on-premises data centers to the AWS Cloud. The company migrated on-premises VMS to Amazon EC2 instances. Now the company wants to replace some of the components that are running on the EC2 instances with managed AWS services that provide similar functionality.

Initially, the company will transition from load balancer software that runs on EC2 instances to AWS Elastic Load Balancers. A security engineer must ensure that after this transition, all the load balancer logs are centralized and searchable for auditing. The security engineer must also ensure that metrics are generated to show which ciphers are in use.

Which solution will meet these requirements?

- A. Create an Amazon CloudWatch Logs log group
- B. Configure the load balancers to send logs to the log group
- C. Use the CloudWatch Logs console to search the log
- D. Create CloudWatch Logs filters on the logs for the required metrics.
- E. Create an Amazon S3 bucket
- F. Configure the load balancers to send logs to the S3 bucket
- G. Use Amazon Athena to search the logs that are in the S3 bucket
- H. Create Amazon CloudWatch filters on the S3 log files for the required metrics.
- I. Create an Amazon S3 bucket
- J. Configure the load balancers to send logs to the S3 bucket
- K. Use Amazon Athena to search the logs that are in the S3 bucket
- L. Create Athena queries for the required metric
- M. Publish the metrics to Amazon CloudWatch.
- N. Create an Amazon CloudWatch Logs log group
- O. Configure the load balancers to send logs to the log group
- P. Use the AWS Management Console to search the log
- Q. Create Amazon Athena queries for the required metric
- R. Publish the metrics to Amazon CloudWatch.

Answer: C

Explanation:

- Amazon S3 is a service that provides scalable, durable, and secure object storage. You can use Amazon S3 to store and retrieve any amount of data from anywhere on the web¹
- AWS Elastic Load Balancing is a service that distributes incoming application or network traffic across multiple targets, such as EC2 instances, containers, or IP addresses. You can use Elastic Load Balancing to increase the availability and fault tolerance of your applications²
- Elastic Load Balancing supports access logging, which captures detailed information about requests sent to your load balancer. Each log contains information such as the time the request was received, the client's IP address, latencies, request paths, and server responses. You can use access logs to analyze traffic patterns and troubleshoot issues³
- You can configure your load balancer to store access logs in an Amazon S3 bucket that you specify. You can also specify the interval for publishing the logs, which can be 5 or 60 minutes. The logs are stored in a hierarchical folder structure by load balancer name, IP address, year, month, day, and time.
- Amazon Athena is a service that allows you to analyze data in Amazon S3 using standard SQL. You can use Athena to run ad-hoc queries and get results in seconds. Athena is serverless, so there is no infrastructure to manage and you pay only for the queries that you run.
- You can use Athena to search the access logs that are stored in your S3 bucket. You can create a table in Athena that maps to your S3 bucket and then run SQL queries on the table. You can also use the Athena console or API to view and download the query results.
- You can also use Athena to create queries for the required metrics, such as the number of requests per cipher or protocol. You can then publish the metrics to Amazon CloudWatch, which is a service that monitors and manages your AWS resources and applications. You can use CloudWatch to collect and track metrics, create alarms, and automate actions based on the state of your resources.
- By using this solution, you can meet the requirements of ensuring that all the load balancer logs are centralized and searchable for auditing and that metrics are generated to show which ciphers are in use.

NEW QUESTION 34

A security engineer is configuring a mechanism to send an alert when three or more failed sign-in attempts to the AWS Management Console occur during a 5-minute period. The security engineer creates a trail in AWS CloudTrail to assist in this work. Which solution will meet these requirements?

- A. In CloudTrail, turn on Insights events on the trail
- B. Configure an alarm on the insight with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Configure a threshold of 3 and a period of 5 minutes.
- C. Configure CloudTrail to send events to Amazon CloudWatch Log
- D. Create a metric filter for the relevant log group
- E. Create a filter pattern with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Create a CloudWatch alarm with a threshold of 3 and a period of 5 minutes.
- F. Create an Amazon Athena table from the CloudTrail event
- G. Run a query for eventName matching ConsoleLogin and for errorMessage matching "Failed authentication". Create a notification action from the query to send an Amazon Simple Notification Service (Amazon SNS) notification when the count equals 3 within a period of 5 minutes.
- H. In AWS Identity and Access Management Access Analyzer, create a new analyzer
- I. Configure the analyzer to send an Amazon Simple Notification Service (Amazon SNS) notification when a failed sign-in event occurs 3 times for any IAM user within a period of 5 minutes.

Answer: B

Explanation:

The correct answer is B. Configure CloudTrail to send events to Amazon CloudWatch Logs. Create a metric filter for the relevant log group. Create a filter pattern with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Create a CloudWatch alarm with a threshold of 3 and a period of 5 minutes.

This answer is correct because it meets the requirements of sending an alert when three or more failed sign-in attempts to the AWS Management Console occur during a 5-minute period. By configuring CloudTrail to send events to CloudWatch Logs, the security engineer can create a metric filter that matches the desired pattern of failed sign-in events. Then, by creating a CloudWatch alarm based on the metric filter, the security engineer can set a threshold of 3 and a period of 5 minutes, and choose an action such as sending an email or an Amazon Simple Notification Service (Amazon SNS) message when the alarm is triggered¹². The other options are incorrect because:

- A. Turning on Insights events on the trail and configuring an alarm on the insight is not a solution, because Insights events are used to analyze unusual activity in management events, such as spikes in API call volume or error rates. Insights events do not capture failed sign-in attempts to the AWS Management Console³.
- C. Creating an Amazon Athena table from the CloudTrail events and running a query for failed sign-in events is not a solution, because it does not provide a mechanism to send an alert based on the query results. Amazon Athena is an interactive query service that allows analyzing data in Amazon S3 using standard SQL, but it does not support creating notifications or alarms from queries⁴.
- D. Creating an analyzer in AWS Identity and Access Management Access Analyzer and configuring it to send an Amazon SNS notification when a failed sign-in

event occurs 3 times for any IAM user within a period of 5 minutes is not a solution, because IAM Access Analyzer is not a service that monitors sign-in events, but a service that helps identify resources that are shared with external entities. IAM Access Analyzer does not generate findings for failed sign-in attempts to the AWS Management Console.

References:

1: Sending CloudTrail Events to CloudWatch Logs - AWS CloudTrail 2: Creating Alarms Based on Metric Filters - Amazon CloudWatch 3: Analyzing unusual activity in management events - AWS CloudTrail 4: What is Amazon Athena? - Amazon Athena 5: Using AWS Identity and Access Management Access Analyzer - AWS Identity and Access Management

NEW QUESTION 35

A security engineer needs to implement a write-once-read-many (WORM) model for data that a company will store in Amazon S3 buckets. The company uses the S3 Standard storage class for all of its S3 buckets. The security engineer must ensure that objects cannot be overwritten or deleted by any user, including the AWS account root user.

Which solution will meet these requirements?

- A. Create new S3 buckets with S3 Object Lock enabled in compliance mod
- B. Place objects in the S3 buckets.
- C. Use S3 Glacier Vault Lock to attach a Vault Lock policy to new S3 bucket
- D. Wait 24 hours to complete the Vault Lock proces
- E. Place objects in the S3 buckets.
- F. Create new S3 buckets with S3 Object Lock enabled in governance mod
- G. Place objects in the S3 buckets.
- H. Create new S3 buckets with S3 Object Lock enabled in governance mod
- I. Add a legal hold to the S3 bucket
- J. Place objects in the S3 buckets.

Answer: A

NEW QUESTION 39

An international company wants to combine AWS Security Hub findings across all the company's AWS Regions and from multiple accounts. In addition, the company

wants to create a centralized custom dashboard to correlate these findings with operational data for deeper analysis and insights. The company needs an analytics tool to search and visualize Security Hub findings. Which combination of steps will meet these requirements? (Select THREE.)

- A. Designate an AWS account as a delegated administrator for Security Hu
- B. Publish events to Amazon CloudWatch from the delegated administrator account, all member accounts, and required Regions that are enabled for Security Hub findings.
- C. Designate an AWS account in an organization in AWS Organizations as a delegated administrator for Security Hu
- D. Publish events to Amazon EventBridge from the delegated administrator account, all member accounts, and required Regions that are enabled for Security Hub findings.
- E. In each Region, create an Amazon EventBridge rule to deliver findings to an Amazon Kinesis data strea
- F. Configure the Kinesis data streams to output the logs to a single Amazon S3 bucket.
- G. In each Region, create an Amazon EventBridge rule to deliver findings to an Amazon Kinesis Data Firehose delivery strea
- H. Configure the Kinesis Data Firehose delivery streams to deliver the logs to a single Amazon S3 bucket.
- I. Use AWS Glue DataBrew to crawl the Amazon S3 bucket and build the schem
- J. Use AWS Glue Data Catalog to query the data and create views to flatten nested attribute
- K. Build Amazon QuickSight dashboards by using Amazon Athena.
- L. Partition the Amazon S3 dat
- M. Use AWS Glue to crawl the S3 bucket and build the schem
- N. Use Amazon Athena to query the data and create views to flatten nested attribute
- O. Build Amazon QuickSight dashboards that use the Athena views.

Answer: BDF

Explanation:

The correct answer is B, D, and F. Designate an AWS account in an organization in AWS Organizations as a delegated administrator for Security Hub. Publish events to Amazon EventBridge from the delegated administrator account, all member accounts, and required Regions that are enabled for Security Hub findings. In each Region, create an Amazon EventBridge rule to deliver findings to an Amazon Kinesis Data Firehose delivery stream. Configure the Kinesis Data Firehose delivery streams to deliver the logs to a single Amazon S3 bucket. Partition the Amazon S3 data. Use AWS Glue to crawl the S3 bucket and build the schema. Use Amazon Athena to query the data and create views to flatten nested attributes. Build Amazon QuickSight dashboards that use the Athena views.

According to the AWS documentation, AWS Security Hub is a service that provides you with a comprehensive view of your security state across your AWS accounts, and helps you check your environment against security standards and best practices. You can use Security Hub to aggregate security findings from various sources, such as AWS services, partner products, or your own applications.

To use Security Hub with multiple AWS accounts and Regions, you need to enable AWS Organizations with all features enabled. This allows you to centrally manage your accounts and apply policies across your organization. You can also use Security Hub as a service principal for AWS Organizations, which lets you designate a delegated administrator account for Security Hub. The delegated administrator account can enable Security Hub automatically in all existing and future accounts in your organization, and can view and manage findings from all accounts.

According to the AWS documentation, Amazon EventBridge is a serverless event bus that makes it easy to connect applications using data from your own applications, integrated software as a service (SaaS) applications, and AWS services. You can use EventBridge to create rules that match events from various sources and route them to targets for processing.

To use EventBridge with Security Hub findings, you need to enable Security Hub as an event source in EventBridge. This will allow you to publish events from Security Hub to EventBridge in the same Region. You can then create EventBridge rules that match Security Hub findings based on criteria such as severity, type, or resource. You can also specify targets for your rules, such as Lambda functions, SNS topics, or Kinesis Data Firehose delivery streams.

According to the AWS documentation, Amazon Kinesis Data Firehose is a fully managed service that delivers real-time streaming data to destinations such as Amazon S3, Amazon Redshift, Amazon Elasticsearch Service (Amazon ES), and Splunk. You can use Kinesis Data Firehose to transform and enrich your data before delivering it to your destination.

To use Kinesis Data Firehose with Security Hub findings, you need to create a Kinesis Data Firehose delivery stream in each Region where you have enabled Security Hub. You can then configure the delivery stream to receive events from EventBridge as a source, and deliver the logs to a single S3 bucket as a destination. You can also enable data transformation or compression on the delivery stream if needed.

According to the AWS documentation, Amazon S3 is an object storage service that offers scalability, data availability, security, and performance. You can use S3 to store and retrieve any amount of data from anywhere on the web. You can also use S3 features such as lifecycle management, encryption, versioning, and

replication to optimize your storage.

To use S3 with Security Hub findings, you need to create an S3 bucket that will store the logs from Kinesis Data Firehose delivery streams. You can then partition the data in the bucket by using prefixes such as account ID or Region. This will improve the performance and cost-effectiveness of querying the data.

According to the AWS documentation, AWS Glue is a fully managed extract, transform, and load (ETL) service that makes it easy to prepare and load your data for analytics. You can use Glue to crawl your data sources, identify data formats, and suggest schemas and transformations. You can also use Glue Data Catalog as a central metadata repository for your data assets.

To use Glue with Security Hub findings, you need to create a Glue crawler that will crawl the S3 bucket and build the schema for the data. The crawler will create tables in the Glue Data Catalog that you can query using standard SQL.

According to the AWS documentation, Amazon Athena is an interactive query service that makes it easy to analyze data in Amazon S3 using standard SQL.

Athena is serverless, so there is no infrastructure to manage, and you pay only for the queries that you run. You can use Athena with Glue Data Catalog as a metadata store for your tables.

To use Athena with Security Hub findings, you need to create views in Athena that will flatten nested attributes in the data. For example, you can create views that extract fields such as account ID, Region, resource type, resource ID, finding type, finding title, and finding description from the JSON data. You can then query the views using SQL and join them with other tables if needed.

According to the AWS documentation, Amazon QuickSight is a fast, cloud-powered business intelligence service that makes it easy to deliver insights to everyone in your organization. You can use QuickSight to create and publish interactive dashboards that include machine learning insights. You can also use QuickSight to connect to various data sources, such as Athena, S3, or RDS.

To use QuickSight with Security Hub findings, you need to create QuickSight dashboards that use the Athena views as data sources. You can then visualize and analyze the findings using charts, graphs, maps, or tables. You can also apply filters, calculations, or aggregations to the data. You can then share the dashboards with your users or embed them in your applications.

NEW QUESTION 43

A security engineer is designing an IAM policy to protect AWS API operations. The policy must enforce multi-factor authentication (MFA) for IAM users to access certain services in the AWS production account. Each session must remain valid for only 2 hours. The current version of the IAM policy is as follows:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": [
      "ec2:DescribeInstances",
      "ec2:StopInstances",
      "ec2:TerminateInstances"
    ],
    "Resource": ["*"]
  }]
}
```

Which combination of conditions must the security engineer add to the IAM policy to meet these requirements? (Select TWO.)

- A. "Bool" : { "aws : Multi FactorAuthPresent": "true" }
- B. "B001" : { "aws : MultiFactorAuthPresent": "false" }
- C. "NumericLessThan" : { "aws : Multi FactorAuthAge" : "7200" }
- D. "NumericGreaterThan" : { "aws : MultiFactorAuthAge" : "7200" }
- E. "NumericLessThan" : { "MaxSessionDuration" : "7200" }

Answer: AC

Explanation:

The correct combination of conditions to add to the IAM policy is A and C. These conditions will ensure that IAM users must use MFA to access certain services in the AWS production account, and that each session will expire after 2 hours.

- Option A: "Bool" : { "aws:MultiFactorAuthPresent" : "true" } is a valid condition that checks if the principal (the IAM user) has authenticated with MFA before making the request. This condition will enforce MFA for the IAM users to access the specified services. This condition key is supported by all AWS services that support IAM policies¹.
- Option B: "Bool" : { "aws:MultiFactorAuthPresent" : "false" } is the opposite of option A. This condition will allow access only if the principal has not authenticated with MFA, which is not the desired requirement. This condition key is supported by all AWS services that support IAM policies¹.
- Option C: "NumericLessThan" : { "aws:MultiFactorAuthAge" : "7200" } is a valid condition that checks if the time since the principal authenticated with MFA is less than 7200 seconds (2 hours). This condition will enforce the session duration limit for the IAM users. This condition key is supported by all AWS services that support IAM policies¹.
- Option D: "NumericGreaterThan" : { "aws:MultiFactorAuthAge" : "7200" } is the opposite of option C. This condition will allow access only if the time since the principal authenticated with MFA is more than 7200 seconds (2 hours), which is not the desired requirement. This condition key is supported by all AWS services that support IAM policies¹.
- Option E: "NumericLessThan" : { "MaxSessionDuration" : "7200" } is not a valid condition key.

MaxSessionDuration is a property of an IAM role, not a condition key. It specifies the maximum session duration (in seconds) for the role, which can be between 3600 and 43200 seconds (1 to 12 hours). This property can be set when creating or modifying a role, but it cannot be used as a condition in a policy².

NEW QUESTION 44

A Network Load Balancer (NLB) target instance is not entering the InService state. A security engineer determines that health checks are failing. Which factors could cause the health check failures? (Select THREE.)

- A. The target instance's security group does not allow traffic from the NLB.
- B. The target instance's security group is not attached to the NLB.

- C. The NLB's security group is not attached to the target instance.
- D. The target instance's subnet network ACL does not allow traffic from the NLB.
- E. The target instance's security group is not using IP addresses to allow traffic from the NLB.
- F. The target network ACL is not attached to the NLB.

Answer: ACD

NEW QUESTION 49

A security team is working on a solution that will use Amazon EventBridge (Amazon CloudWatch Events) to monitor new Amazon S3 objects. The solution will monitor for public access and for changes to any S3 bucket policy or setting that result in public access. The security team configures EventBridge to watch for specific API calls that are logged from AWS CloudTrail. EventBridge has an action to send an email notification through Amazon Simple Notification Service (Amazon SNS) to the security team immediately with details of the API call. Specifically, the security team wants EventBridge to watch for the s3:PutObjectAcl, s3:DeleteBucketPolicy, and s3:PutBucketPolicy API invocation logs from CloudTrail. While developing the solution in a single account, the security team discovers that the s3:PutObjectAcl API call does not invoke an EventBridge event. However, the s3:DeleteBucketPolicy API call and the s3:PutBucketPolicy API call do invoke an event. The security team has enabled CloudTrail for AWS management events with a basic configuration in the AWS Region in which EventBridge is being tested. Verification of the EventBridge event pattern indicates that the pattern is set up correctly. The security team must implement a solution so that the s3:PutObjectAcl API call will invoke an EventBridge event. The solution must not generate false notifications. Which solution will meet these requirements?

- A. Modify the EventBridge event pattern by selecting Amazon S3. Select All Events as the event type.
- B. Modify the EventBridge event pattern by selecting Amazon S3. Select Bucket Level Operations as the event type.
- C. Enable CloudTrail Insights to identify unusual API activity.
- D. Enable CloudTrail to monitor data events for read and write operations to S3 buckets.

Answer: D

Explanation:

The correct answer is D. Enable CloudTrail to monitor data events for read and write operations to S3 buckets. According to the AWS documentation¹, CloudTrail data events are the resource operations performed on or within a resource. These are also known as data plane operations. Data events are often high-volume activities. For example, Amazon S3 object-level API activity (such as GetObject, DeleteObject, and PutObject) is a data event.

By default, trails do not log data events. To record CloudTrail data events, you must explicitly add the supported resources or resource types for which you want to collect activity. For more information, see Logging data events in the Amazon S3 User Guide². In this case, the security team wants EventBridge to watch for the s3:PutObjectAcl API invocation logs from CloudTrail. This API uses the acl subresource to set the access control list (ACL) permissions for a new or existing object in an S3 bucket³. This is a data event that affects the S3 object resource type. Therefore, the security team must enable CloudTrail to monitor data events for read and write operations to S3 buckets in order to invoke an EventBridge event for this API call. The other options are incorrect because:

- > A. Modifying the EventBridge event pattern by selecting Amazon S3 and All Events as the event type will not capture the s3:PutObjectAcl API call, because this is a data event and not a management event. Management events provide information about management operations that are performed on resources in your AWS account. These are also known as control plane operations⁴.
- > B. Modifying the EventBridge event pattern by selecting Amazon S3 and Bucket Level Operations as the event type will not capture the s3:PutObjectAcl API call, because this is a data event that affects the S3 object resource type and not the S3 bucket resource type. Bucket level operations are management events that affect the configuration or metadata of an S3 bucket⁵.
- > C. Enabling CloudTrail Insights to identify unusual API activity will not help the security team monitor new S3 objects or changes to any S3 bucket policy or setting that result in public access. CloudTrail Insights helps AWS users identify and respond to unusual activity associated with API calls and API error rates by continuously analyzing CloudTrail management events⁶. It does not analyze data events or generate EventBridge events.

References:

1: CloudTrail log event reference - AWS CloudTrail 2: Logging data events - AWS CloudTrail 3: PutObjectAcl - Amazon Simple Storage Service 4: [Logging management events - AWS CloudTrail] 5: [Amazon S3 Event Types - Amazon Simple Storage Service] 6: Logging Insights events for trails - AWS CloudTrail

NEW QUESTION 53

A security engineer needs to build a solution to turn IAM CloudTrail back on in multiple IAM Regions in case it is ever turned off. What is the MOST efficient way to implement this solution?

- A. Use IAM Config with a managed rule to trigger the IAM-EnableCloudTrail remediation.
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) event with a cloudtrail.amazonaws.com event source and a StartLogging event name to trigger an IAM Lambda function to call the StartLogging API.
- C. Create an Amazon CloudWatch alarm with a cloudtrail.amazonaws.com event source and a StopLogging event name to trigger an IAM Lambda function to call the StartLogging API.
- D. Monitor IAM Trusted Advisor to ensure CloudTrail logging is enabled.

Answer: B

NEW QUESTION 57

A company recently had a security audit in which the auditors identified multiple potential threats. These potential threats can cause usage pattern changes such as DNS access peak, abnormal instance traffic, abnormal network interface traffic, and unusual Amazon S3 API calls. The threats can come from different sources and can occur at any time. The company needs to implement a solution to continuously monitor its system and identify all these incoming threats in near-real time. Which solution will meet these requirements?

- A. Enable AWS CloudTrail logs, VPC flow logs, and DNS log
- B. Use Amazon CloudWatch Logs to manage these logs from a centralized account.
- C. Enable AWS CloudTrail logs, VPC flow logs, and DNS log
- D. Use Amazon Macie to monitor these logs from a centralized account.
- E. Enable Amazon GuardDuty from a centralized account
- F. Use GuardDuty to manage AWS CloudTrail logs, VPC flow logs, and DNS logs.
- G. Enable Amazon Inspector from a centralized account
- H. Use Amazon Inspector to manage AWS CloudTrail logs, VPC flow logs, and DNS logs.

Answer: C

Explanation:

Q: Which data sources does GuardDuty analyze? GuardDuty analyzes CloudTrail management event logs, CloudTrail S3 data event logs, VPC Flow Logs, DNS query logs, and Amazon EKS audit logs. GuardDuty can also scan EBS volume data for possible malware when GuardDuty Malware Protection is enabled and identifies suspicious behavior indicative of malicious software in EC2 instance or container workloads. The service is optimized to consume large data volumes for near real-time processing of security detections. GuardDuty gives you access to built-in detection techniques developed and optimized for the cloud, which are maintained and continuously improved upon by GuardDuty engineering.

NEW QUESTION 58

A company is implementing a new application in a new IAM account. A VPC and subnets have been created for the application. The application has been peered to an existing VPC in another account in the same IAM Region for database access. Amazon EC2 instances will regularly be created and terminated in the application VPC, but only some of them will need access to the databases in the peered VPC over TCP port 1521. A security engineer must ensure that only the EC2 instances that need access to the databases can access them through the network.

How can the security engineer implement this solution?

- A. Create a new security group in the database VPC and create an inbound rule that allows all traffic from the IP address range of the application VP
- B. Add a new network ACL rule on the database subnet
- C. Configure the rule to TCP port 1521 from the IP address range of the application VP
- D. Attach the new security group to the database instances that the application instances need to access.
- E. Create a new security group in the application VPC with an inbound rule that allows the IP address range of the database VPC over TCP port 1521. Create a new security group in the database VPC with an inbound rule that allows the IP address range of the application VPC over port 1521. Attach the new security group to the database instances and the application instances that need database access.
- F. Create a new security group in the application VPC with no inbound rule
- G. Create a new security group in the database VPC with an inbound rule that allows TCP port 1521 from the new application security group in the application VP
- H. Attach the application security group to the application instances that need database access, and attach the database security group to the database instances.
- I. Create a new security group in the application VPC with an inbound rule that allows the IP address range of the database VPC over TCP port 1521. Add a new network ACL rule on the database subnet
- J. Configure the rule to allow all traffic from the IP address range of the application VP
- K. Attach the new security group to the application instances that need database access.

Answer: C

NEW QUESTION 62

To meet regulatory requirements, a Security Engineer needs to implement an IAM policy that restricts the use of AWS services to the us-east-1 Region. What policy should the Engineer implement?

A.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

B. A computer code with black text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    }
  ]
}
```

C. A computer code with black text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

D. A computer code with text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "NotAction": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

Answer: C

Explanation:

https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_examples_aws_deny-requested-region.h

NEW QUESTION 66

A developer is building a serverless application hosted on AWS that uses Amazon Redshift as a data store. The application has separate modules for readwrite and read-only functionality. The modules need their own database users for compliance reasons. Which combination of steps should a security engineer implement to grant appropriate access? (Select TWO.)

- A. Configure cluster security groups for each application module to control access to database users that are required for read-only and readwrite
- B. Configure a VPC endpoint for Amazon Redshift. Configure an endpoint policy that maps database users to each application module, and allow access to the tables that are required for read-only and read/write
- C. Configure an IAM policy for each module. Specify the ARN of an Amazon Redshift database user that allows the GetClusterCredentials API call
- D. Create local database users for each module
- E. Configure an IAM policy for each module. Specify the ARN of an IAM user that allows the GetClusterCredentials API call

Answer: A

Explanation:

To grant appropriate access to separate modules for read-write and read-only functionality in a serverless application hosted on AWS that uses Amazon Redshift as a data store, a security engineer should configure cluster security groups for each application module to control access to database users that are required for read-only and readwrite, and configure an IAM policy for each module specifying the ARN of an IAM user that allows the GetClusterCredentials API call.

References: : Amazon Redshift - Amazon Web Services : Amazon Redshift - Amazon Web Services : Identity and Access Management - AWS Management Console : AWS Identity and Access Management - AWS Management Console

NEW QUESTION 71

A company has a single AWS account and uses an Amazon EC2 instance to test application code. The company recently discovered that the instance was compromised. The instance was serving up malware. The analysis of the instance showed that the instance was compromised 35 days ago. A security engineer must implement a continuous monitoring solution that automatically notifies the company's security team about compromised instances through an email distribution list for high severity findings. The security engineer must implement the solution as soon as possible. Which combination of steps should the security engineer take to meet these requirements? (Choose three.)

- A. Enable AWS Security Hub in the AWS account.
- B. Enable Amazon GuardDuty in the AWS account.

- C. Create an Amazon Simple Notification Service (Amazon SNS) topic
- D. Subscribe the security team's email distribution list to the topic.
- E. Create an Amazon Simple Queue Service (Amazon SQS) queue
- F. Subscribe the security team's email distribution list to the queue.
- G. Create an Amazon EventBridge (Amazon CloudWatch Events) rule for GuardDuty findings of high severity
- H. Configure the rule to publish a message to the topic.
- I. Create an Amazon EventBridge (Amazon CloudWatch Events) rule for Security Hub findings of high severity
- J. Configure the rule to publish a message to the queue.

Answer: BCE

NEW QUESTION 75

A company deployed Amazon GuardDuty in the us-east-1 Region. The company wants all DNS logs that relate to the company's Amazon EC2 instances to be inspected. What should a security engineer do to ensure that the EC2 instances are logged?

- A. Use IPv6 addresses that are configured for hostnames.
- B. Configure external DNS resolvers as internal resolvers that are visible only to IAM.
- C. Use IAM DNS resolvers for all EC2 instances.
- D. Configure a third-party DNS resolver with logging for all EC2 instances.

Answer: C

Explanation:

To ensure that the EC2 instances are logged, the security engineer should do the following:

- Use AWS DNS resolvers for all EC2 instances. This allows the security engineer to use Amazon-provided DNS servers that resolve public DNS hostnames to private IP addresses within their VPC, and that log DNS queries in Amazon CloudWatch Logs.

NEW QUESTION 80

A company is planning to use Amazon Elastic File System (Amazon EFS) with its on-premises servers. The company has an existing IAM Direct Connect connection established between its on-premises data center and an IAM Region. A security policy states that the company's on-premises firewall should only have specific IP addresses added to the allow list and not a CIDR range. The company also wants to restrict access so that only certain data center-based servers have access to Amazon EFS.

How should a security engineer implement this solution?

- A. Add the file-system-id:efs IAM-region:amazoniam.com URL to the allow list for the data center firewall. Install the IAM CLI on the data center-based servers to mount the EFS file system. In the EFS security group, add the data center IP range to the allow list. Mount the EFS using the EFS file system name.
- B. Assign an Elastic IP address to Amazon EFS and add the Elastic IP address to the allow list for the data center firewall. Install the IAM CLI on the data center-based servers to mount the EFS file system. In the EFS security group, add the IP addresses of the data center servers to the allow list. Mount the EFS using the Elastic IP address.
- C. Add the EFS file system mount target IP addresses to the allow list for the data center firewall. In the EFS security group, add the data center server IP addresses to the allow list. Use the Linux terminal to mount the EFS file system using the IP address of one of the mount targets.
- D. Assign a static range of IP addresses for the EFS file system by contacting IAM Support. In the EFS security group, add the data center server IP addresses to the allow list. Use the Linux terminal to mount the EFS file system using one of the static IP addresses.

Answer: B

Explanation:

To implement the solution, the security engineer should do the following:

- Assign an Elastic IP address to Amazon EFS and add the Elastic IP address to the allow list for the data center firewall. This allows the security engineer to use a specific IP address for the EFS file system that can be added to the firewall rules, instead of a CIDR range or a URL.
- Install the AWS CLI on the data center-based servers to mount the EFS file system. This allows the security engineer to use the mount helper provided by AWS CLI to mount the EFS file system with encryption in transit.
- In the EFS security group, add the IP addresses of the data center servers to the allow list. This allows the security engineer to restrict access to the EFS file system to only certain data center-based servers.
- Mount the EFS using the Elastic IP address. This allows the security engineer to use the Elastic IP address as the DNS name for mounting the EFS file system.

NEW QUESTION 82

A company uses an external identity provider to allow federation into different IAM accounts. A security engineer for the company needs to identify the federated user that terminated a production Amazon EC2 instance a week ago.

What is the FASTEST way for the security engineer to identify the federated user?

- A. Review the IAM CloudTrail event history logs in an Amazon S3 bucket and look for the TerminateInstances event to identify the federated user from the role session name.
- B. Filter the IAM CloudTrail event history for the TerminateInstances event and identify the assumed IAM role.
- C. Review the AssumeRoleWithSAML event call in CloudTrail to identify the corresponding username.
- D. Search the IAM CloudTrail logs for the TerminateInstances event and note the event time.
- E. Review the IAM Access Advisor tab for all federated roles.
- F. The last accessed time should match the time when the instance was terminated.
- G. Use Amazon Athena to run a SQL query on the IAM CloudTrail logs stored in an Amazon S3 bucket and filter on the TerminateInstances event.
- H. Identify the corresponding role and run another query to filter the AssumeRoleWithWebIdentity event for the user name.

Answer: B

Explanation:

The fastest way to identify the federated user who terminated a production Amazon EC2 instance is to filter the IAM CloudTrail event history for the TerminateInstances event and identify the assumed IAM role. Then, review the AssumeRoleWithSAML event call in CloudTrail to identify the corresponding

username. This method does not require any additional tools or queries, and it directly links the IAM role with the federated user.

Option A is incorrect because the role session name may not be the same as the federated user name, and it may not be unique or descriptive enough to identify the user.

Option C is incorrect because the IAM Access Advisor tab only shows when a role was last accessed, not by whom or for what purpose. It also does not show the specific time of access, only the date.

Option D is incorrect because using Amazon Athena to run SQL queries on the IAM CloudTrail logs is not the fastest way to identify the federated user, as it requires creating a table schema and running multiple queries. It also assumes that the federation is done using web identity providers, not SAML providers, as indicated by the AssumeRoleWithWebIdentity event.

References:

- > AWS Identity and Access Management
- > Logging AWS STS API Calls with AWS CloudTrail
- > [Using Amazon Athena to Query S3 Data for CloudTrail Analysis]

NEW QUESTION 84

A security engineer is checking an AWS CloudFormation template for vulnerabilities. The security engineer finds a parameter that has a default value that exposes an application's API key in plaintext. The parameter is referenced several times throughout the template. The security engineer must replace the parameter while maintaining the ability to reference the value in the template. Which solution will meet these requirements in the MOST secure way? `{resolve:s3:MyBucketName:MyObjectName}}`.

- A. Store the API key value as a SecureString parameter in AWS Systems Manager Parameter Store
- B. In the template, replace all references to the value with `{{resolve:ssm:MySSMParameterName:}}`.
- C. Store the API key value in AWS Secrets Manager
- D. In the template, replace all references to the value with `{ {resolve:secretsmanager:MySecretId:SecretString}}`.
- E. Store the API key value in Amazon DynamoDB
- F. In the template, replace all references to the value with `{{resolve:dynamodb:MyTableName:MyPrimaryKey}}`.
- G. Store the API key value in a new Amazon S3 bucket
- H. In the template, replace all references to the value with `{`

Answer: B

Explanation:

The correct answer is B. Store the API key value in AWS Secrets Manager. In the template, replace all references to the value with `{{resolve:secretsmanager:MySecretId:SecretString}}`.

This answer is correct because AWS Secrets Manager is a service that helps you protect secrets that are needed to access your applications, services, and IT resources. You can store and manage secrets such as database credentials, API keys, and other sensitive data in Secrets Manager. You can also use Secrets Manager to rotate, manage, and retrieve your secrets throughout their lifecycle¹. Secrets Manager integrates with AWS CloudFormation, which allows you to reference secrets from your templates using the `{{resolve:secretsmanager:...}}` syntax². This way, you can avoid exposing your secrets in plaintext and still use them in your resources.

The other options are incorrect because:

- > A. Storing the API key value as a SecureString parameter in AWS Systems Manager Parameter Store is not a solution, because AWS CloudFormation does not support references to SecureString parameters. This means that you cannot use the `{{resolve:ssm:...}}` syntax to retrieve encrypted parameter values from Parameter Store³. You would have to use a custom resource or a Lambda function to decrypt the parameter value, which adds complexity and overhead to your template.
- > C. Storing the API key value in Amazon DynamoDB is not a solution, because AWS CloudFormation does not support references to DynamoDB items. This means that you cannot use the `{{resolve:dynamodb:...}}` syntax to retrieve item values from DynamoDB tables⁴. You would have to use a custom resource or a Lambda function to query the DynamoDB table, which adds complexity and overhead to your template.
- > D. Storing the API key value in a new Amazon S3 bucket is not a solution, because AWS CloudFormation does not support references to S3 objects. This means that you cannot use the `{{resolve:s3:...}}` syntax to retrieve object values from S3 buckets⁵. You would have to use a custom resource or a Lambda function to download the object from S3, which adds complexity and overhead to your template.

References:

1: What is AWS Secrets Manager? 2: Referencing AWS Secrets Manager secrets from Parameter Store parameters 3: Using dynamic references to specify template values 4: Amazon DynamoDB 5: Amazon Simple Storage Service (S3)

NEW QUESTION 87

A security engineer must use AWS Key Management Service (AWS KMS) to design a key management solution for a set of Amazon Elastic Block Store (Amazon EBS) volumes that contain sensitive data. The solution needs to ensure that the key material automatically expires in 90 days. Which solution meets these criteria?

- A. A customer managed CMK that uses customer provided key material
- B. A customer managed CMK that uses AWS provided key material
- C. An AWS managed CMK
- D. Operation system-native encryption that uses GnuPG

Answer: A

Explanation:

```
https://awscli.amazonaws.com/v2/documentation/api/latest/reference/kms/import-key-material.html aws kms import-key-material \
--key-id 1234abcd-12ab-34cd-56ef-1234567890ab \
--encrypted-key-material fileb://EncryptedKeyMaterial.bin \
--import-token fileb://ImportToken.bin \
--expiration-model KEY_MATERIAL_EXPIRES \
--valid-to 2021-09-21T19:00:00Z
```

The correct answer is A. A customer managed CMK that uses customer provided key material.

A customer managed CMK is a KMS key that you create, own, and manage in your AWS account. You have full control over the key configuration, permissions, rotation, and deletion. You can use a customer managed CMK to encrypt and decrypt data in AWS services that are integrated with AWS KMS, such as Amazon EBS¹.

A customer managed CMK can use either AWS provided key material or customer provided key material. AWS provided key material is generated by AWS KMS and never leaves the service unencrypted. Customer provided key material is generated outside of AWS KMS and imported into a customer managed CMK. You can specify an expiration date for the imported key material, after which the CMK becomes unusable until you reimport new key material².

To meet the criteria of automatically expiring the key material in 90 days, you need to use customer provided key material and set the expiration date accordingly. This way, you can ensure that the data encrypted with the CMK will not be accessible after 90 days unless you reimport new key material and re-encrypt the data. The other options are incorrect for the following reasons:

* B. A customer managed CMK that uses AWS provided key material does not expire automatically. You can enable automatic rotation of the key material every year, but this does not prevent access to the data encrypted with the previous key material. You would need to manually delete the CMK and its backing key material to make the data inaccessible³.

* C. An AWS managed CMK is a KMS key that is created, owned, and managed by an AWS service on your behalf. You have limited control over the key configuration, permissions, rotation, and deletion. You cannot use an AWS managed CMK to encrypt data in other AWS services or applications. You also cannot set an expiration date for the key material of an AWS managed CMK⁴.

* D. Operation system-native encryption that uses GnuPG is not a solution that uses AWS KMS. GnuPG is a command line tool that implements the OpenPGP standard for encrypting and signing data. It does not integrate with Amazon EBS or other AWS services. It also does not provide a way to automatically expire the key material used for encryption⁵.

References:

1: Customer Managed Keys - AWS Key Management Service 2: [Importing Key Material in AWS Key Management Service (AWS KMS) - AWS Key Management Service] 3: [Rotating Customer Master Keys - AWS Key Management Service] 4: [AWS Managed Keys - AWS Key Management Service] 5: The GNU Privacy Guard

NEW QUESTION 91

A Security Engineer is troubleshooting an issue with a company's custom logging application. The application logs are written to an Amazon S3 bucket with event notifications enabled to send events to an Amazon SNS topic. All logs are encrypted at rest using an IAM KMS CMK. The SNS topic is subscribed to an encrypted Amazon SQS queue. The logging application polls the queue for new messages that contain metadata about the S3 object. The application then reads the content of the object from the S3 bucket for indexing.

The Logging team reported that Amazon CloudWatch metrics for the number of messages sent or received is showing zero. No logs are being received.

What should the Security Engineer do to troubleshoot this issue?

A) Add the following statement to the IAM managed CMKs:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": ["sns.amazonaws.com", "sqs.amazonaws.com", "s3.amazonaws.com"]
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

B)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "sns.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

C)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "sqs.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

D)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "s3.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 95

A company is running an application in The eu-west-1 Region. The application uses an IAM Key Management Service (IAM KMS) CMK to encrypt sensitive data. The company plans to deploy the application in the eu-north-1 Region.

A security engineer needs to implement a key management solution for the application deployment in the new Region. The security engineer must minimize changes to the application code.

Which change should the security engineer make to the IAM KMS configuration to meet these requirements?

- A. Update the key policies in eu-west-1. Point the application in eu-north-1 to use the same CMK as the application in eu-west-1.
- B. Allocate a new CMK to eu-north-1 to be used by the application that is deployed in that Region.
- C. Allocate a new CMK to eu-north-1. Create the same alias name for both key
- D. Configure the application deployment to use the key alias.
- E. Allocate a new CMK to eu-north-1. Create an alias for eu-'-1. Change the application code to point to the alias for eu-'-1.

Answer: B

NEW QUESTION 100

A Security Engineer is building a Java application that is running on Amazon EC2. The application communicates with an Amazon RDS instance and authenticates with a user name and password.

Which combination of steps can the Engineer take to protect the credentials and minimize downtime when the credentials are rotated? (Choose two.)

- A. Have a Database Administrator encrypt the credentials and store the ciphertext in Amazon S3. Grant permission to the instance role associated with the EC2 instance to read the object and decrypt the ciphertext.
- B. Configure a scheduled job that updates the credential in AWS Systems Manager Parameter Store and notifies the Engineer that the application needs to be restarted.
- C. Configure automatic rotation of credentials in AWS Secrets Manager.
- D. Store the credential in an encrypted string parameter in AWS Systems Manager Parameter Store
- E. Grant permission to the instance role associated with the EC2 instance to access the parameter and the AWS KMS key that is used to encrypt it.
- F. Configure the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials when the password is rotate
- G. Grant permission to the instance role associated with the EC2 instance to access Secrets Manager.

Answer: CE

Explanation:

AWS Secrets Manager is a service that helps you manage, retrieve, and rotate secrets such as database credentials, API keys, and other sensitive information. By configuring automatic rotation of credentials in AWS Secrets Manager, you can ensure that your secrets are changed regularly and securely, without requiring manual intervention or application downtime. You can also specify the rotation frequency and the rotation function that performs the logic of changing the credentials on the database and updating the secret in Secrets Manager1.

* E. Configure the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials when the password is rotated. Grant permission to the instance role associated with the EC2 instance to access Secrets Manager.

By configuring the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials, you can avoid hard-coding the credentials in your application code or configuration files. This way, your application can dynamically obtain the latest credentials from Secrets Manager whenever the password is rotated, without needing to restart or redeploy the application. To enable this, you need to grant permission to the instance role associated with the EC2 instance to access Secrets Manager using IAM policies2. You can also use the AWS SDK for Java to integrate your application with Secrets Manager3.

NEW QUESTION 101

A company needs a security engineer to implement a scalable solution for multi-account authentication and authorization. The solution should not introduce additional user-managed architectural components. Native IAM features should be used as much as possible The security engineer has set up IAM Organizations w1th all features activated and IAM SSO enabled.

Which additional steps should the security engineer take to complete the task?

- A. Use AD Connector to create users and groups for all employees that require access to IAM accounts. Assign AD Connector groups to IAM accounts and link to the IAM roles in accordance with the employees' job functions and access requirements Instruct employees to access IAM accounts by using the IAM Directory Service user portal.
- B. Use an IAM SSO default directory to create users and groups for all employees that require access to IAM account
- C. Assign groups to IAM accounts and link to permission sets in accordance with the employees' job functions and access requirement

- D. Instruct employees to access IAM accounts by using the IAM SSO user portal.
- E. Use an IAM SSO default directory to create users and groups for all employees that require access to IAM account
- F. Link IAM SSO groups to the IAM users present in all accounts to inherit existing permission
- G. Instruct employees to access IAM accounts by using the IAM SSO user portal.
- H. Use IAM Directory Service for Microsoft Active Directory to create users and groups for all employees that require access to IAM accounts Enable IAM Management Console access in the created directory and specify IAM SSO as a source of information for integrated accounts and permission set
- I. Instruct employees to access IAM accounts by using the IAM Directory Service user portal.

Answer: B

NEW QUESTION 104

A security engineer receives a notice from the AWS Abuse team about suspicious activity from a Linux-based Amazon EC2 instance that uses Amazon Elastic Block Store (Amazon EBS)-based storage. The instance is making connections to known malicious addresses. The instance is in a development account within a VPC that is in the us-east-1 Region. The VPC contains an internet gateway and has a subnet in us-east-1a and us-east-1b. Each subnet is associated with a route table that uses the internet gateway as a default route. Each subnet also uses the default network ACL. The suspicious EC2 instance runs within the us-east-1b subnet. During an initial investigation, a security engineer discovers that the suspicious instance is the only instance that runs in the subnet. Which response will immediately mitigate the attack and help investigate the root cause?

- A. Log in to the suspicious instance and use the netstat command to identify remote connections. Use the IP addresses from these remote connections to create deny rules in the security group of the instance. Install diagnostic tools on the instance for investigation. Update the outbound network ACL for the subnet in us-east-1b to explicitly deny all connections as the first rule during the investigation of the instance.
- B. Update the outbound network ACL for the subnet in us-east-1b to explicitly deny all connections as the first rule. Replace the security group with a new security group that allows connections only from a diagnostics security group. Update the outbound network ACL for the us-east-1b subnet to remove the deny all rule. Launch a new EC2 instance that has diagnostic tools. Assign the new security group to the new EC2 instance. Use the new EC2 instance to investigate the suspicious instance.
- C. Ensure that the Amazon Elastic Block Store (Amazon EBS) volumes that are attached to the suspicious EC2 instance will not delete upon termination. Terminate the instance. Launch a new EC2 instance in us-east-1a that has diagnostic tools. Mount the EBS volumes from the terminated instance for investigation.
- D. Create an AWS WAF web ACL that denies traffic to and from the suspicious instance. Attach the AWS WAF web ACL to the instance to mitigate the attack. Log in to the instance and install diagnostic tools to investigate the instance.

Answer: B

Explanation:

This option suggests updating the outbound network ACL for the subnet in us-east-1b to explicitly deny all connections as the first rule, replacing the security group with a new one that only allows connections from a diagnostics security group, and launching a new EC2 instance with diagnostic tools to investigate the suspicious instance. This option will immediately mitigate the attack and provide the necessary tools for investigation.

NEW QUESTION 107

A company is undergoing a layer 3 and layer 4 DDoS attack on its web servers running on IAM. Which combination of IAM services and features will provide protection in this scenario? (Select THREE).

- A. Amazon Route 53
- B. IAM Certificate Manager (ACM)
- C. Amazon S3
- D. IAM Shield
- E. Elastic Load Balancer
- F. Amazon GuardDuty

Answer: DEF

NEW QUESTION 112

A company is building an application on IAM that will store sensitive information. The company has a support team with access to the IT infrastructure, including databases. The company's security engineer must introduce measures to protect the sensitive data against any data breach while minimizing management overhead. The credentials must be regularly rotated. What should the security engineer recommend?

- A. Enable Amazon RDS encryption to encrypt the database and snapshot
- B. Enable Amazon Elastic Block Store (Amazon EBS) encryption on Amazon EC2 instance
- C. Include the database credential in the EC2 user data field
- D. Use an IAM Lambda function to rotate database credential
- E. Set up TLS for the connection to the database.
- F. Install a database on an Amazon EC2 instance
- G. Enable third-party disk encryption to encrypt the Amazon Elastic Block Store (Amazon EBS) volume
- H. Store the database credentials in IAM CloudHSM with automatic rotation
- I. Set up TLS for the connection to the database.
- J. Enable Amazon RDS encryption to encrypt the database and snapshot
- K. Enable Amazon Elastic Block Store (Amazon EBS) encryption on Amazon EC2 instance
- L. Store the database credentials in IAM Secrets Manager with automatic rotation
- M. Set up TLS for the connection to the RDS hosted database.
- N. Set up an IAM CloudHSM cluster with IAM Key Management Service (IAM KMS) to store KMS keys. Set up Amazon RDS encryption using IAM KMS to encrypt the database
- O. Store database credentials in the IAM Systems Manager Parameter Store with automatic rotation
- P. Set up TLS for the connection to the RDS hosted database.

Answer: C

Explanation:

To protect the sensitive data against any data breach and minimize management overhead, the security engineer should recommend the following solution:

- Enable Amazon RDS encryption to encrypt the database and snapshots. This allows the security engineer to use AWS Key Management Service (AWS KMS) to encrypt data at rest for the database and any backups or replicas.
- Enable Amazon Elastic Block Store (Amazon EBS) encryption on Amazon EC2 instances. This allows the security engineer to use AWS KMS to encrypt data at rest for the EC2 instances and any snapshots or volumes.
- Store the database credentials in AWS Secrets Manager with automatic rotation. This allows the security engineer to encrypt and manage secrets centrally, and to configure automatic rotation schedules for them.
- Set up TLS for the connection to the RDS hosted database. This allows the security engineer to encrypt data in transit between the EC2 instances and the database.

NEW QUESTION 113

A company is using AWS Organizations to manage multiple accounts. The company needs to allow an IAM user to use a role to access resources that are in another organization's AWS account.

Which combination of steps must the company perform to meet this requirement? (Select TWO.)

- A. Create an identity policy that allows the sts: AssumeRole action in the AWS account that contains the resource
- B. Attach the identity policy to the IAM user.
- C. Ensure that the sts: AssumeRole action is allowed by the SCPs of the organization that owns the resources that the IAM user needs to access.
- D. Create a role in the AWS account that contains the resource
- E. Create an entry in the role's trust policy that allows the IAM user to assume the rol
- F. Attach the trust policy to the role.
- G. Establish a trust relationship between the IAM user and the AWS account that contains the resources.
- H. Create a role in the IAM user's AWS account
- I. Create an identity policy that allows the sts: AssumeRole action
- J. Attach the identity policy to the role.

Answer: BC

Explanation:

To allow cross-account access to resources using IAM roles, the following steps are required:

- Create a role in the AWS account that contains the resources (the trusting account) and specify the AWS account that contains the IAM user (the trusted account) as a trusted entity in the role's trust policy. This allows users from the trusted account to assume the role and access resources in the trusting account.
- Ensure that the IAM user has permission to assume the role in their own AWS account. This can be done by creating an identity policy that allows the sts:AssumeRole action and attaching it to the IAM user or their group.
- Ensure that there are no service control policies (SCPs) in the organization that owns the resources that deny or restrict access to the sts:AssumeRole action or the role itself. SCPs are applied to all accounts in an organization and can override any permissions granted by IAM policies.

Verified References:

- <https://repost.aws/knowledge-center/cross-account-access-iam>
- https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_accounts_access.html
- https://docs.aws.amazon.com/IAM/latest/UserGuide/tutorial_cross-account-with-roles.html

NEW QUESTION 116

The Security Engineer is managing a traditional three-tier web application that is running on Amazon EC2 instances. The application has become the target of increasing numbers of malicious attacks from the Internet.

What steps should the Security Engineer take to check for known vulnerabilities and limit the attack surface? (Choose two.)

- A. Use AWS Certificate Manager to encrypt all traffic between the client and application servers.
- B. Review the application security groups to ensure that only the necessary ports are open.
- C. Use Elastic Load Balancing to offload Secure Sockets Layer encryption.
- D. Use Amazon Inspector to periodically scan the backend instances.
- E. Use AWS Key Management Services to encrypt all the traffic between the client and application servers.

Answer: BD

Explanation:

The steps that the Security Engineer should take to check for known vulnerabilities and limit the attack surface are:

- B. Review the application security groups to ensure that only the necessary ports are open. This is a good practice to reduce the exposure of the EC2 instances to potential attacks from the Internet. Application security groups are a feature of Azure that allow you to group virtual machines and define network security policies based on those groups¹.
- D. Use Amazon Inspector to periodically scan the backend instances. This is a service that helps you to identify vulnerabilities and exposures in your EC2 instances and applications. Amazon Inspector can perform automated security assessments based on predefined or custom rules packages².

NEW QUESTION 117

A company needs to follow security best practices to deploy resources from an AWS CloudFormation template. The CloudFormation template must be able to configure sensitive database credentials.

The company already uses AWS Key Management Service (AWS KMS) and AWS Secrets Manager. Which solution will meet the requirements?

- A. Use a dynamic reference in the CloudFormation template to reference the database credentials in Secrets Manager.
- B. Use a parameter in the CloudFormation template to reference the database credential
- C. Encrypt the CloudFormation template by using AWS KMS.
- D. Use a SecureString parameter in the CloudFormation template to reference the database credentials in Secrets Manager.
- E. Use a SecureString parameter in the CloudFormation template to reference an encrypted value in AWS KMS

Answer: A

Explanation:

➤

Option A: This option meets the requirements of following security best practices and configuring sensitive database credentials in the CloudFormation template. A dynamic reference is a way to specify external values that are stored and managed in other services, such as Secrets Manager, in the stack templates¹. When using a dynamic reference, CloudFormation retrieves the value of the specified reference when necessary during stack and change set operations¹. Dynamic references can be used for certain resources that support them, such as AWS::RDS::DBInstance¹. By using a dynamic reference to reference the database credentials in Secrets Manager, the company can leverage the existing integration between these services and avoid hardcoding the secret information in the template. Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources². Secrets Manager enables you to rotate, manage, and retrieve database credentials, API keys, and other secrets throughout their lifecycle².

NEW QUESTION 120

A company's Security Team received an email notification from the Amazon EC2 Abuse team that one or more of the company's Amazon EC2 instances may have been compromised

Which combination of actions should the Security team take to respond to (be current modem? (Select TWO.)

- A. Open a support case with the IAM Security team and ask them to remove the malicious code from the affected instance
- B. Respond to the notification and list the actions that have been taken to address the incident
- C. Delete all IAM users and resources in the account
- D. Detach the internet gateway from the VPC remove aft rules that contain 0.0.0.0/0 from the security groups, and create a NACL rule to deny all traffic Inbound from the internet
- E. Delete the identified compromised instances and delete any associated resources that the Security team did not create.

Answer: DE

Explanation:

these are the recommended actions to take when you receive an abuse notice from AWS⁸. You should review the abuse notice to see what content or activity was reported and detach the internet gateway from the VPC to isolate the affected instances from the internet. You should also remove any rules that allow inbound traffic from 0.0.0.0/0 from the security groups and create a network access control list (NACL) rule to deny all traffic inbound from the internet. You should then delete the compromised instances and any associated resources that you did not create. The other options are either inappropriate or unnecessary for responding to the abuse notice.

NEW QUESTION 124

A company is using Amazon Route 53 Resolver for its hybrid DNS infrastructure. The company has set up Route 53 Resolver forwarding rules for authoritative domains that are hosted on on-premises DNS servers.

A new security mandate requires the company to implement a solution to log and query DNS traffic that goes to the on-premises DNS servers. The logs must show details of the source IP address of the instance from which the query originated. The logs also must show the DNS name that was requested in Route 53 Resolver. Which solution will meet these requirements?

- A. Use VPC Traffic Mirrorin
- B. Configure all relevant elastic network interfaces as the traffic source, include amazon-dns in the mirror filter, and set Amazon CloudWatch Logs as the mirror target
- C. Use CloudWatch Insights on the mirror session logs to run queries on the source IP address and DNS name.
- D. Configure VPC flow logs on all relevant VPC
- E. Send the logs to an Amazon S3 bucke
- F. Use Amazon Athena to run SQL queries on the source IP address and DNS name.
- G. Configure Route 53 Resolver query logging on all relevant VPC
- H. Send the logs to Amazon CloudWatch Log
- I. Use CloudWatch Insights to run queries on the source IP address and DNS name.
- J. Modify the Route 53 Resolver rules on the authoritative domains that forward to the on-premises DNS server
- K. Send the logs to an Amazon S3 bucke
- L. Use Amazon Athena to run SQL queries on the source IP address and DNS name.

Answer: C

Explanation:

The correct answer is C. Configure Route 53 Resolver query logging on all relevant VPCs. Send the logs to Amazon CloudWatch Logs. Use CloudWatch Insights to run queries on the source IP address and DNS name.

According to the AWS documentation¹, Route 53 Resolver query logging lets you log the DNS queries that Route 53 Resolver handles for your VPCs. You can send the logs to CloudWatch Logs, Amazon S3, or Kinesis Data Firehose. The logs include information such as the following:

- The AWS Region where the VPC was created
- The ID of the VPC that the query originated from
- The IP address of the instance that the query originated from
- The instance ID of the resource that the query originated from
- The date and time that the query was first made
- The DNS name requested (such as prod.example.com)
- The DNS record type (such as A or AAAA)
- The DNS response code, such as NoError or ServFail
- The DNS response data, such as the IP address that is returned in response to the DNS query

You can use CloudWatch Insights to run queries on your log data and analyze the results using graphs and statistics². You can filter and aggregate the log data based on any field, and use operators and functions to perform calculations and transformations. For example, you can use CloudWatch Insights to find out how many queries were made for a specific domain name, or which instances made the most queries.

Therefore, this solution meets the requirements of logging and querying DNS traffic that goes to the on-premises DNS servers, showing details of the source IP address of the instance from which the query originated, and the DNS name that was requested in Route 53 Resolver.

The other options are incorrect because:

- A. Using VPC Traffic Mirroring would not capture the DNS queries that go to the on-premises DNS servers, because Traffic Mirroring only copies network traffic from an elastic network interface of an EC2 instance to a target for analysis³. Traffic Mirroring does not include traffic that goes through a Route 53 Resolver outbound endpoint, which is used to forward queries to on-premises DNS servers⁴. Therefore, this solution would not meet the requirements.
- B. Configuring VPC flow logs on all relevant VPCs would not capture the DNS name that was requested in Route 53 Resolver, because flow logs only record

information about the IP traffic going to and from network interfaces in a VPC5. Flow logs do not include any information about the content or payload of a packet, such as a DNS query or response. Therefore, this solution would not meet the requirements.

➤ D. Modifying the Route 53 Resolver rules on the authoritative domains that forward to the on-premises DNS servers would not enable logging of DNS queries, because Resolver rules only specify how to forward queries for specified domain names to your network6. Resolver rules do not have any logging functionality by themselves. Therefore, this solution would not meet the requirements. References:

1: Resolver query logging - Amazon Route 53 2: Analyzing log data with CloudWatch Logs Insights - Amazon CloudWatch 3: What is Traffic Mirroring? - Amazon Virtual Private Cloud 4: Outbound Resolver endpoints - Amazon Route 53 5: Logging IP traffic using VPC Flow Logs - Amazon Virtual Private Cloud 6: Managing forwarding rules - Amazon Route 53

NEW QUESTION 126

A company needs a forensic-logging solution for hundreds of applications running in Docker on Amazon EC2 The solution must perform real-time analytics on the logs must support the replay of messages and must persist the logs.

Which IAM services should be used to meet these requirements? (Select TWO)

- A. Amazon Athena
- B. Amazon Kinesis
- C. Amazon SQS
- D. Amazon Elasticsearch
- E. Amazon EMR

Answer: BD

Explanation:

Amazon Kinesis and Amazon Elasticsearch are both suitable for forensic-logging solutions. Amazon Kinesis can collect, process, and analyze streaming data in real time3. Amazon Elasticsearch can store, search, and analyze log data using the popular open-source tool Elasticsearch. The other options are not designed for forensic-logging purposes. Amazon Athena is a query service that can analyze data in S3, Amazon SQS is a message queue service that can decouple and scale microservices, and Amazon EMR is a big data platform that can run Apache Spark and Hadoop clusters.

NEW QUESTION 127

A company has an AWS account that includes an Amazon S3 bucket. The S3 bucket uses server-side encryption with AWS KMS keys (SSE-KMS) to encrypt all the objects at rest by using a customer managed key. The S3 bucket does not have a bucket policy.

An IAM role in the same account has an IAM policy that allows s3 List* and s3 Get* permissions for the S3 bucket. When the IAM role attempts to access an object in the S3 bucket the role receives an access denied message.

Why does the IAM role not have access to the objects that are in the S3 bucket?

- A. The IAM role does not have permission to use the KMS CreateKey operation.
- B. The S3 bucket lacks a policy that allows access to the customer managed key that encrypts the objects.
- C. The IAM role does not have permission to use the customer managed key that encrypts the objects that are in the S3 bucket.
- D. The ACL of the S3 objects does not allow read access for the objects when the objects are encrypted at rest.

Answer: C

Explanation:

When using server-side encryption with AWS KMS keys (SSE-KMS), the requester must have both Amazon S3 permissions and AWS KMS permissions to access the objects. The Amazon S3 permissions are for the bucket and object operations, such as s3:ListBucket and s3:GetObject. The AWS KMS permissions are for the key operations, such as kms:GenerateDataKey and kms:Decrypt. In this case, the IAM role has the necessary Amazon S3 permissions, but not the AWS KMS permissions to use the customer managed key that encrypts the objects. Therefore, the IAM role receives an access denied message when trying to access the objects. Verified References:

- <https://docs.aws.amazon.com/AmazonS3/latest/userguide/troubleshoot-403-errors.html>
- <https://repost.aws/knowledge-center/s3-access-denied-error-kms>
- <https://repost.aws/knowledge-center/cross-account-access-denied-error-s3>

NEW QUESTION 132

A company is using AWS Organizations to manage multiple AWS accounts for its human resources, finance, software development, and production departments. All the company's developers are part of the software development AWS account.

The company discovers that developers have launched Amazon EC2 instances that were preconfigured with software that the company has not approved for use. The company wants to implement a solution to ensure that developers can launch EC2 instances with only approved software applications and only in the software development AWS account.

Which solution will meet these requirements?

- A. In the software development account, create AMIS of preconfigured instances that include only approved software
- B. Include the AMI IDs in the condition section of an AWS CloudFormation template to launch the appropriate AMI based on the AWS Region
- C. Provide the developers with the CloudFormation template to launch EC2 instances in the software development account.
- D. Create an Amazon EventBridge rule that runs when any EC2 RunInstances API event occurs in the software development account
- E. Specify AWS Systems Manager Run Command as a target of the rule
- F. Configure Run Command to run a script that will install all approved software onto the instances that the developers launch.
- G. Use an AWS Service Catalog portfolio that contains EC2 products with appropriate AMIS that include only approved software
- H. Grant the developers permission to portfolio access only the Service Catalog to launch a product in the software development account.
- I. In the management account, create AMIS of preconfigured instances that include only approved software
- J. Use AWS CloudFormation StackSets to launch the AMIS across any AWS account in the organization
- K. Grant the developers permission to launch the stack sets within the management account.

Answer: C

NEW QUESTION 134

An IAM user receives an Access Denied message when the user attempts to access objects in an Amazon S3 bucket. The user and the S3 bucket are in the same AWS account. The S3 bucket is configured to use server-side encryption with AWS KMS keys (SSE-KMS) to encrypt all of its objects at rest by using a customer

managed key from the same AWS account. The S3 bucket has no bucket policy defined. The IAM user has been granted permissions through an IAM policy that allows the kms:Decrypt permission to the customer managed key. The IAM policy also allows the s3:List* and s3:Get* permissions for the S3 bucket and its objects.

Which of the following is a possible reason that the IAM user cannot access the objects in the S3 bucket?

- A. The IAM policy needs to allow the kms:DescribeKey permission.
- B. The S3 bucket has been changed to use the AWS managed key to encrypt objects at rest.
- C. An S3 bucket policy needs to be added to allow the IAM user to access the objects.
- D. The KMS key policy has been edited to remove the ability for the AWS account to have full access to the key.

Answer: D

Explanation:

The possible reason that the IAM user cannot access the objects in the S3 bucket is D. The KMS key policy has been edited to remove the ability for the AWS account to have full access to the key.

This answer is correct because the KMS key policy is the primary way to control access to the KMS key, and it must explicitly allow the AWS account to have full access to the key. If the KMS key policy has been edited to remove this permission, then the IAM policy that grants kms:Decrypt permission to the IAM user has no effect, and the IAM user cannot decrypt the objects in the S3 bucket¹².

The other options are incorrect because:

- A. The IAM policy does not need to allow the kms:DescribeKey permission, because this permission is not required for decrypting objects in S3 using SSE-KMS. The kms:DescribeKey permission allows getting information about a KMS key, such as its creation date, description, and key state³.
- B. The S3 bucket has not been changed to use the AWS managed key to encrypt objects at rest, because this would not cause an Access Denied message for the IAM user. The AWS managed key is a default KMS key that is created and managed by AWS for each AWS account and Region. The IAM user does not need any permissions on this key to use it for SSE-KMS⁴.
- C. An S3 bucket policy does not need to be added to allow the IAM user to access the objects, because the IAM user already has s3:List* and s3:Get* permissions for the S3 bucket and its objects through an IAM policy. An S3 bucket policy is an optional way to grant cross-account access or public access to an S3 bucket⁵.

References:

1: Key policies in AWS KMS 2: Using server-side encryption with AWS KMS keys (SSE-KMS) 3: AWS KMS API Permissions Reference 4: Using server-side encryption with Amazon S3 managed keys (SSE-S3) 5: Bucket policy examples

NEW QUESTION 138

A developer at a company uses an SSH key to access multiple Amazon EC2 instances. The company discovers that the SSH key has been posted on a public GitHub repository. A security engineer verifies that the key has not been used recently.

How should the security engineer prevent unauthorized access to the EC2 instances?

- A. Delete the key pair from the EC2 console
- B. Create a new key pair.
- C. Use the ModifyInstanceAttribute API operation to change the key on any EC2 instance that is using the key.
- D. Restrict SSH access in the security group to only known corporate IP addresses.
- E. Update the key pair in any AMI that is used to launch the EC2 instance
- F. Restart the EC2 instances.

Answer: C

Explanation:

To prevent unauthorized access to the EC2 instances, the security engineer should do the following:

- Restrict SSH access in the security group to only known corporate IP addresses. This allows the security engineer to use a virtual firewall that controls inbound and outbound traffic for their EC2 instances, and limit SSH access to only trusted sources.

NEW QUESTION 140

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual SCS-C01 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the SCS-C01 Product From:

<https://www.2passeasy.com/dumps/SCS-C01/>

Money Back Guarantee

SCS-C01 Practice Exam Features:

- * SCS-C01 Questions and Answers Updated Frequently
- * SCS-C01 Practice Questions Verified by Expert Senior Certified Staff
- * SCS-C01 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * SCS-C01 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year