

Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam



NEW QUESTION 1

All IP addresses within a 10.0.0.0/16 VPC are fully utilized with application servers across two Availability Zones. The application servers need to send frequent UDP probes to a single central authentication server on the Internet to confirm that is running up-to-date packages. The network is designed for application servers to use a single NAT gateway for internal access. Testing reveals that a few of the servers are unable to communicate with the authentication server.

- A. The NAT gateway does not support UDP traffic.
- B. The authentication server is not accepting traffic.
- C. The NAT gateway cannot allocate more ports.
- D. The NAT gateway is launched in a private subnet.

Answer: C

Explanation:

Ref: <https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

"A NAT gateway can support up to 55,000 simultaneous connections to each unique destination. This limit also applies if you create approximately 900 connections per second to a single destination (about 55,000 connections per minute). If the destination IP address, the destination port, or the protocol (TCP/UDP/ICMP) changes, you can create an additional 55,000 connections. For more than 55,000 connections, there is an increased chance of connection errors due to port allocation errors. These errors can be monitored by viewing the ErrorPortAllocation CloudWatch metric for your NAT gateway. For more information, see Monitoring NAT Gateways Using Amazon CloudWatch."

NEW QUESTION 2

A company's network engineer is designing a hybrid DNS solution for an AWS Cloud workload. Individual teams want to manage their own DNS hostnames for their applications in their development environment. The solution must integrate the application-specific hostnames with the centrally managed DNS hostnames from the on-premises network and must provide bidirectional name resolution. The solution also must minimize management overhead.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Use an Amazon Route 53 Resolver inbound endpoint.
- B. Modify the DHCP options set by setting a custom DNS server value.
- C. Use an Amazon Route 53 Resolver outbound endpoint.
- D. Create DNS proxy servers.
- E. Create Amazon Route 53 private hosted zones.
- F. Set up a zone transfer between Amazon Route 53 and the on-premises DNS.

Answer: ABE

NEW QUESTION 3

A network engineer needs to set up an Amazon EC2 Auto Scaling group to run a Linux-based network appliance in a highly available architecture. The network engineer is configuring the new launch template for the Auto Scaling group.

In addition to the primary network interface the network appliance requires a second network interface that will be used exclusively by the application to exchange traffic with hosts over the internet. The company has set up a Bring Your Own IP (BYOIP) pool that includes an Elastic IP address that should be used as the public IP address for the second network interface.

How can the network engineer implement the required architecture?

- A. Configure the two network interfaces in the launch template.
- B. Define the primary network interface to be created in one of the private subnets.
- C. For the second network interface, select one of the public subnets.
- D. Choose the BYOIP pool ID as the source of public IP addresses.
- E. Configure the primary network interface in a private subnet in the launch template.
- F. Use the user data option to run a cloud-init script after boot to attach the second network interface from a subnet with auto-assign public IP addressing enabled.
- G. Create an AWS Lambda function to run as a lifecycle hook of the Auto Scaling group when an instance is launching.
- H. In the Lambda function, assign a network interface to an AWS Global Accelerator endpoint.
- I. During creation of the Auto Scaling group, select subnets for the primary network interface.
- J. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

Answer: D

Explanation:

During creation of the Auto Scaling group, select subnets for the primary network interface. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

This solution meets all of the requirements stated in the question. The primary network interface can be configured in a private subnet during creation of the Auto Scaling group. The user data option can be used to run a cloud-init script that will allocate a second network interface and associate an Elastic IP address from the BYOIP pool with it.

NEW QUESTION 4

Your organization has a newly installed 1-Gbps AWS Direct Connect connection. You order the cross-connect from the Direct Connect location provider to the port on your router in the same facility. To enable the use of your first virtual interface, your router must be configured appropriately.

What are the minimum requirements for your router?

- A. 1-Gbps Multi Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- B. 1-Gbps Single Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- C. IPsec Parameters, Pre-Shared key, Peer IP Address, BGP Session with MD5
- D. BGP Session with MD5, 802.1Q VLAN, Route-Map, Prefix List, IPsec encrypted GRE Tunnel

Answer: B

NEW QUESTION 5

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC

in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity
- O. Add a NAT gateway
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 6

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud.

Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connection
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connection
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connection
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connection
- H. Configure two AWS Site-to-Site VPN connections to the transit gateway
- I. Enable equal-cost multi-path (ECMP) routing.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

NEW QUESTION 7

An AWS CloudFormation template is being used to create a VPC peering connection between two existing operational VPCs, each belonging to a different AWS account. All necessary components in the 'Remote' (receiving) account are already in place.

The template below creates the VPC peering connection in the Originating account. It contains these components:

AWSTemplateFormatVersion: 2010-09-09 Parameters:

OriginatingVPCId: Type: String RemoteVPCId: Type: String

RemoteVPCAccountID: Type: String Resources:

newVPCPeeringConnection:

Type: 'AWS::EC2::VPCPeeringConnection'

Properties:

VpcId: !Ref OriginatingVPCId PeerVpcId: !Ref RemoteVPCId PeerOwnerId: !Ref RemoteVPCAccountID

Which additional AWS CloudFormation components are necessary in the Originating account to create an operational cross-account VPC peering connection with AWS CloudFormation? (Select two.)

- A. Resources:NewEC2SecurityGroup:Type: AWS::EC2::SecurityGroup
- B. Resources:NetworkInterfaceToRemoteVPC:Type: "AWS::EC2NetworkInterface"
- C. Resources:newEC2Route:Type: AWS::EC2::Route
- D. Resources:VPCGatewayToRemoteVPC:Type: "AWS::EC2::VPCGatewayAttachment"
- E. Resources:newVPCPeeringConnection:Type: 'AWS::EC2VPCPeeringConnection'PeerRoleArn: !Ref PeerRoleArn

Answer: CE

Explanation:

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/AWS_EC2.html

NEW QUESTION 8

A company is deploying an application. The application is implemented in a series of containers in an Amazon Elastic Container Service (Amazon ECS) cluster. The company will use the Fargate launch type for its tasks. The containers will run workloads that require connectivity initiated over an SSL connection. Traffic must be able to flow to the application from other AWS accounts over private connectivity. The application must scale in a manageable way as more consumers use the application.

Which solution will meet these requirements?

- A. Choose a Gateway Load Balancer (GLB) as the type of load balancer for the ECS service
- B. Create a lifecycle hook to add new tasks to the target group from Amazon ECS as required to handle scaling
- C. Specify the GLB in the service definition
- D. Create a VPC peer for external AWS account
- E. Update the route tables so that the AWS accounts can reach the GLB.
- F. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS service
- G. Create path-based routing rules to allow the application to target the containers that are registered in the target group
- H. Specify the ALB in the service definition
- I. Create a VPC endpoint service for the ALB. Share the VPC endpoint service with other AWS accounts.
- J. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS service
- K. Create path-based routing rules to allow the application to target the containers that are registered in the target group
- L. Specify the ALB in the service definition
- M. Create a VPC peer for the external AWS account
- N. Update the route tables so that the AWS accounts can reach the ALB.
- O. Choose a Network Load Balancer (NLB) as the type of load balancer for the ECS service
- P. Specify the NLB in the service definition
- Q. Create a VPC endpoint service for the NLB
- R. Share the VPC endpoint service with other AWS accounts.

Answer: D

NEW QUESTION 9

A company is using an AWS Site-to-Site VPN connection from the company's on-premises data center to a virtual private gateway in the AWS Cloud. Because of congestion, the company is experiencing availability and performance issues as traffic travels across the internet before the traffic reaches AWS. A network engineer must reduce these issues for the connection as quickly as possible with minimum administration effort.

Which solution will meet these requirements?

- A. Edit the existing Site-to-Site VPN connection by enabling acceleration
- B. Stop and start the VPN service on the customer gateway for the new setting to take effect.
- C. Configure a transit gateway in the same AWS Region as the existing virtual private gateway
- D. Create a new accelerated Site-to-Site VPN connection
- E. Connect the new connection to the transit gateway by using a VPN attachment
- F. Update the customer gateway device to use the new Site-to-Site VPN connection
- G. Delete the existing Site-to-Site VPN connection
- H. Create a new accelerated Site-to-Site VPN connection
- I. Connect the new Site-to-Site VPN connection to the existing virtual private gateway
- J. Update the customer gateway device to use the new Site-to-Site VPN connection
- K. Delete the existing Site-to-Site VPN connection.
- L. Create a new AWS Direct Connect connection with a private VIF between the on-premises data center and the AWS Cloud
- M. Update the customer gateway device to use the new Direct Connect connection
- N. Delete the existing Site-to-Site VPN connection.

Answer: B

NEW QUESTION 10

A company is hosting an application on Amazon EC2 instances behind an Application Load Balancer. The instances are in an Amazon EC2 Auto Scaling group. Because of a recent change to a security group, external users cannot access the application.

A network engineer needs to prevent this downtime from happening again. The network engineer must implement a solution that remediates noncompliant changes to security groups.

Which solution will meet these requirements?

- A. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- B. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.
- C. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- D. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- E. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- F. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- G. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- H. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.

Answer: D

Explanation:

Configuring an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration would enable evaluation of the compliance status of the security groups based on predefined or custom rules³. Creating an AWS Systems Manager Automation runbook to remediate noncompliant security groups would enable automation of the remediation process². Additionally, configuring AWS Config to trigger the runbook when a noncompliant change is detected would enable timely and consistent remediation of security group changes.

NEW QUESTION 10

A global company operates all its non-production environments out of three AWS Regions: eu-west-1, us-east-1, and us-west-1. The company hosts all its production workloads in two on-premises data centers. The company has 60 AWS accounts and each account has two VPCs in each Region. Each VPC has a virtual private gateway where two VPN connections terminate for resilient connectivity to the data centers. The company has 360 VPN tunnels to each data center, resulting in high management overhead. The total VPN throughput for each Region is 500 Mbps.

The company wants to migrate the production environments to AWS. The company needs a solution that will simplify the network architecture and allow for future growth. The production environments will generate an additional 2 Gbps of traffic per Region back to the data centers. This traffic will increase over time.

Which solution will meet these requirements?

- A. Set up an AWS Direct Connect connection from each data center to AWS in each Region

- B. Create and attach private VIFs to a single Direct Connect gateway
- C. Attach the Direct Connect gateway to all the VPC
- D. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- E. Create a single transit gateway with VPN connections from each data center
- F. Share the transit gateway with each account by using AWS Resource Access Manager (AWS RAM). Attach the transit gateway to each VPC
- G. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- H. Create a transit gateway in each Region with multiple newly commissioned VPN connections from each data center
- I. Share the transit gateways with each account by using AWS Resource Access Manager (AWS RAM). In each Region, attach the transit gateway to each VPC
- J. Peer all the VPCs in each Region to a new VPC in each Region that will function as a centralized transit VPC
- K. Create new VPN connections from each data center to the transit VPC
- L. Terminate the original VPN connections that are attached to all the original VPC
- M. Retain the new VPN connection to the new transit VPC in each Region.

Answer: C

NEW QUESTION 15

A company has a hybrid cloud environment. The company's data center is connected to the AWS Cloud by an AWS Direct Connect connection. The AWS environment includes VPCs that are connected together in a hub-and-spoke model by a transit gateway. The AWS environment has a transit VIF with a Direct Connect gateway for on-premises connectivity.

The company has a hybrid DNS model. The company has configured Amazon Route 53 Resolver endpoints in the hub VPC to allow bidirectional DNS traffic flow. The company is running a backend application in one of the VPCs.

The company uses a message-oriented architecture and employs Amazon Simple Queue Service (Amazon SQS) to receive messages from other applications over a private network. A network engineer wants to use an interface VPC endpoint for Amazon SQS for this architecture. Client services must be able to access the endpoint service from on premises and from multiple VPCs within the company's AWS infrastructure.

Which combination of steps should the network engineer take to ensure that the client applications can resolve DNS for the interface endpoint? (Choose three.)

- A. Create the interface endpoint for Amazon SQS with the option for private DNS names turned on.
- B. Create the interface endpoint for Amazon SQS with the option for private DNS names turned off.
- C. Manually create a private hosted zone for sqs.us-east-1.amazonaws.com
- D. Add necessary records that point to the interface endpoint
- E. Associate the private hosted zones with other VPCs.
- F. Use the automatically created private hosted zone for sqs.us-east-1.amazonaws.com with previously created necessary records that point to the interface endpoint
- G. Associate the private hosted zones with other VPCs.
- H. Access the SQS endpoint by using the public DNS name sqs.us-east-1.amazonaws.com in VPCs and on premises.
- I. Access the SQS endpoint by using the private DNS name of the interface endpoint sqs.us-east-1.vpc.amazonaws.com in VPCs and on premises.

Answer: ADF

NEW QUESTION 17

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this issue in the most operationally efficient manner.

What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 21

An organization launched an IPv6-only web portal to support IPv6-native mobile clients. Front-end instances launch in an Amazon VPC associated with an appropriate IPv6 CIDR. The VPC IPv4 CIDR is fully utilized. A single subnet exists in each of two Availability Zones with appropriately configured IPv6 CIDR associations. Auto Scaling is properly configured, and no Elastic Load Balancing is used.

Customers say the service is unavailable during peak load times. The network engineer attempts to launch an instance manually and receives the following message: "There are not enough free addresses in subnet 'subnet-12345677' to satisfy the requested number of instances."

What action will resolve the availability problem?

- A. Create a new subnet using a VPC secondary IPv6 CIDR, and associate an IPv6 CID
- B. Include the new subnet in the Auto Scaling group.
- C. Create a new subnet using a VPC secondary IPv4 CIDR, and associate an IPv6 CID
- D. Include the new subnet in the Auto Scaling group.
- E. Resize the IPv6 CIDR on each of the existing subnet
- F. Modify the Auto Scaling group maximum number of instances.
- G. Add a secondary IPv4 CIDR to the Amazon VPC
- H. Assign secondary IPv4 address space to each of the existing subnets.

Answer: B

NEW QUESTION 24

A company hosts a web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin in an Amazon CloudFront distribution. The company wants to implement a custom authentication system that will provide a token for its authenticated customers. The web application must ensure that the GET/POST requests come from authenticated customers before it delivers the content. A network engineer must design a solution that gives the web application the ability to identify authorized customers. What is the MOST operationally efficient solution that meets these requirements?

- A. Use the ALB to inspect the authorized token inside the GET/POST request payload
- B. Use an AWS Lambda function to insert a customized header to inform the web application of an authenticated customer request.
- C. Integrate AWS WAF with the ALB to inspect the authorized token inside the GET/POST request payload
- D. Configure the ALB listener to insert a customized header to inform the web application of an authenticated customer request.
- E. Use an AWS Lambda@Edge function to inspect the authorized token inside the GET/POST request payload
- F. Use the Lambda@Edge function also to insert a customized header to inform the web application of an authenticated customer request.
- G. Set up an EC2 instance that has a third-party packet inspection tool to inspect the authorized token inside the GET/POST request payload
- H. Configure the tool to insert a customized header to inform the web application of an authenticated customer request.

Answer: C

NEW QUESTION 27

A company has deployed a new web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances are in an Amazon EC2 Auto Scaling group. Enterprise customers from around the world will use the application. Employees of these enterprise customers will connect to the application over HTTPS from office locations. The company must configure firewalls to allow outbound traffic to only approved IP addresses. The employees of the enterprise customers must be able to access the application with the least amount of latency. Which change should a network engineer make in the infrastructure to meet these requirements?

- A. Create a new Network Load Balancer (NLB). Add the ALB as a target of the NLB.
- B. Create a new Amazon CloudFront distribution
- C. Set the ALB as the distribution's origin.
- D. Create a new accelerator in AWS Global Accelerator
- E. Add the ALB as an accelerator endpoint.
- F. Create a new Amazon Route 53 hosted zone
- G. Create a new record to route traffic to the ALB.

Answer: B

Explanation:

Amazon CloudFront is a content delivery network (CDN) that can speed up the delivery of static and dynamic web content, such as images, videos, and APIs. CloudFront can also provide end-to-end encryption for HTTPS traffic by using SSL certificates from AWS Certificate Manager (ACM) or other sources. CloudFront can also support session affinity (sticky sessions) with a load balancer-generated cookie or an application-based cookie policy.

NEW QUESTION 31

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting slowness when they access resources that are hosted on AWS. A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem. Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for `VirtualInterfaceBpsEgress` and `VirtualInterfaceBpsIngress` to determine which VIF is sending the highest throughput during the period in which slowness is observed
- B. Create a new 10 Gbps dedicated connection
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for `VirtualInterfaceBpsEgress` and `VirtualInterfaceBpsIngress` to determine which VIF is sending the highest throughput during the period in which slowness is observed
- E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.
- F. Review the Amazon CloudWatch metrics for `ConnectionBpsIngress` and `ConnectionBpsEgress` to determine which VIF is sending the highest throughput during the period in which slowness is observed
- G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.
- H. Review the Amazon CloudWatch metrics for `ConnectionBpsIngress` and `ConnectionBpsEgress` to determine which VIF is sending the highest throughput during the period in which slowness is observed. Create a new 10 Gbps dedicated connection
- I. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for `VirtualInterfaceBpsEgress` and `VirtualInterfaceBpsIngress` to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option A). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option E).

NEW QUESTION 36

A company has deployed an application in a VPC that uses a NAT gateway for outbound traffic to the internet. A network engineer notices a large quantity of suspicious network traffic that is traveling from the VPC over the internet to IP addresses that are included on a deny list. The network engineer must implement a solution to determine which AWS resources are generating the suspicious traffic. The solution must minimize cost and administrative overhead. Which solution will meet these requirements?

- A. Launch an Amazon EC2 instance in the VPC

- B. Use Traffic Mirroring by specifying the NAT gateway as the source and the EC2 instance as the destination.
- C. Analyze the captured traffic by using open-source tools to identify the AWS resources that are generating the suspicious traffic.
- D. Use VPC flow log
- E. Launch a security information and event management (SIEM) solution in the VPC
- F. Configure the SIEM solution to ingest the VPC flow log
- G. Run queries on the SIEM solution to identify the AWS resources that are generating the suspicious traffic.
- H. Use VPC flow log
- I. Publish the flow logs to a log group in Amazon CloudWatch Log
- J. Use CloudWatch Logs Insights to query the flow logs to identify the AWS resources that are generating the suspicious traffic.
- K. Configure the VPC to stream the network traffic directly to an Amazon Kinesis data stream
- L. Send the data from the Kinesis data stream to an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Use Amazon Athena to query the data to identify the AWS resources that are generating the suspicious traffic.

Answer: C

NEW QUESTION 41

A company wants to improve visibility into its AWS environment. The AWS environment consists of multiple VPCs that are connected to a transit gateway. The transit gateway connects to an on-premises data center through an AWS Direct Connect gateway and a pair of redundant Direct Connect connections that use transit VIFs. The company must receive notification each time a new route is advertised to AWS from on premises over Direct Connect. What should a network engineer do to meet these requirements?

- A. Enable Amazon CloudWatch metrics on Direct Connect to track the received route
- B. Configure a CloudWatch alarm to send notifications when routes change.
- C. Onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insight
- D. Use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change.
- E. Configure an AWS Lambda function to periodically check the routes on the Direct Connect gateway and to send notifications when routes change.
- F. Enable Amazon CloudWatch Logs on the transit VIFs to track the received route
- G. Create a metric filter Set an alarm on the filter to send notifications when routes change.

Answer: B

Explanation:

<https://docs.aws.amazon.com/network-manager/latest/cloudwan/cloudwan-cloudwatch-events.html>

To receive notification each time a new route is advertised to AWS from on premises over Direct Connect, a network engineer should onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insights and use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change (Option B). This solution allows for real-time monitoring of route changes and automatic notification when new routes are advertised.

NEW QUESTION 46

A company has multiple AWS accounts. Each account contains one or more VPCs. A new security guideline requires the inspection of all traffic between VPCs. The company has deployed a transit gateway that provides connectivity between all VPCs. The company also has deployed a shared services VPC with Amazon EC2 instances that include IDS services for stateful inspection. The EC2 instances are deployed across three Availability Zones. The company has set up VPC associations and routing on the transit gateway. The company has migrated a few test VPCs to the new solution for traffic inspection. Soon after the configuration of routing, the company receives reports of intermittent connections for traffic that crosses Availability Zones. What should a network engineer do to resolve this issue?

- A. Modify the transit gateway VPC attachment on the shared services VPC by enabling cross-Availability Zone load balancing.
- B. Modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support.
- C. Modify the transit gateway by selecting VPN equal-cost multi-path (ECMP) routing support.
- D. Modify the transit gateway by selecting multicast support.

Answer: B

Explanation:

To resolve the issue of intermittent connections for traffic that crosses Availability Zones after configuring routing for traffic inspection between VPCs using a transit gateway and EC2 instances with IDS services in a shared services VPC, a network engineer should modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support (Option B). This will ensure that traffic is routed to the same EC2 instance for stateful inspection and prevent intermittent connections.

NEW QUESTION 49

A company is deploying a new application on AWS. The application uses dynamic multicasting. The company has five VPCs that are all attached to a transit gateway. Amazon EC2 instances in each VPC need to be able to register dynamically to receive a multicast transmission. How should a network engineer configure the AWS resources to meet these requirements?

- A. Create a static source multicast domain within the transit gateway
- B. Associate the VPCs and applicable subnets with the multicast domain
- C. Register the multicast senders' network interface with the multicast domain
- D. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- E. Create a static source multicast domain within the transit gateway
- F. Associate the VPCs and applicable subnets with the multicast domain
- G. Register the multicast senders' network interface with the multicast domain
- H. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.
- I. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- J. Register the multicast senders' network interface with the multicast domain
- K. Adjust the network ACLs to allow UDP traffic from the source to all receivers and to allow UDP traffic that is sent to the multicast group address.
- L. Create an Internet Group Management Protocol (IGMP) multicast domain within the transit gateway. Associate the VPCs and applicable subnets with the multicast domain
- M. Register the multicast senders' network interface with the multicast domain
- N. Adjust the network ACLs to allow TCP traffic from the source to all receivers and to allow TCP traffic that is sent to the multicast group address.

Answer: C

NEW QUESTION 52

An organization is replacing a tape backup system with a storage gateway. There is currently no connectivity to AWS. Initial testing is needed. What connection option should the organization use to get up and running at minimal cost?

- A. Use an internet connection.
- B. Set up an AWS VPN connection.
- C. Provision an AWS Direct Connection private virtual interface.
- D. Provision a Direct Connect public virtual interface.

Answer: A

NEW QUESTION 57

A company delivers applications over the internet. An Amazon Route 53 public hosted zone is the authoritative DNS service for the company and its internet applications, all of which are offered from the same domain name.

A network engineer is working on a new version of one of the applications. All the application's components are hosted in the AWS Cloud. The application has a three-tier design. The front end is delivered through Amazon EC2 instances that are deployed in public subnets with Elastic IP addresses assigned. The backend components are deployed in private subnets from RFC1918.

Components of the application need to be able to access other components of the application within the application's VPC by using the same host names as the host names that are used over the public internet. The network engineer also needs to accommodate future DNS changes, such as the introduction of new host names or the retirement of DNS entries.

Which combination of steps will meet these requirements? (Choose three.)

- A. Add a geoproximity routing policy in Route 53.
- B. Create a Route 53 private hosted zone for the same domain name. Associate the application's VPC with the new private hosted zone.
- C. Enable DNS hostnames for the application's VPC.
- D. Create entries in the private hosted zone for each name in the public hosted zone by using the corresponding private IP addresses.
- E. Create an Amazon EventBridge (Amazon CloudWatch Events) rule that runs when AWS CloudTrail logs a Route 53 API call to the public hosted zone.
- F. Create an AWS Lambda function as the target of the rule.
- G. Configure the function to use the event information to update the private hosted zone.
- H. Add the private IP addresses in the existing Route 53 public hosted zone.

Answer: BCD

NEW QUESTION 58

A company is hosting an application on Amazon EC2 instances behind a Network Load Balancer (NLB). A solutions architect added EC2 instances in a second Availability Zone to improve the availability of the application. The solutions architect added the instances to the NLB target group.

The company's operations team notices that traffic is being routed only to the instances in the first Availability Zone.

What is the MOST operationally efficient solution to resolve this issue?

- A. Enable the new Availability Zone on the NLB
- B. Create a new NLB for the instances in the second Availability Zone
- C. Enable proxy protocol on the NLB
- D. Create a new target group with the instances in both Availability Zones

Answer: A

Explanation:

When adding instances in a new Availability Zone to an existing Network Load Balancer (NLB), it is important to ensure that the new Availability Zone is enabled on the NLB. This will allow traffic to be routed to instances in both Availability Zones. This can be done by editing the settings of the NLB and selecting the new Availability Zone from the list of available zones.

NEW QUESTION 59

A company uses AWS Direct Connect to connect its corporate network to multiple VPCs in the same AWS account and the same AWS Region. Each VPC uses its own private VIF and its own virtual LAN on the Direct Connect connection. The company has grown and will soon surpass the limit of VPCs and private VIFs for each connection.

What is the MOST scalable way to add VPCs with on-premises connectivity?

- A. Provision a new Direct Connect connection to handle the additional VPC
- B. Use the new connection to connect additional VPCs.
- C. Create virtual private gateways for each VPC that is over the service quota
- D. Use AWS Site-to-Site VPN to connect the virtual private gateways to the corporate network.
- E. Create a Direct Connect gateway, and add virtual private gateway associations to the VPC
- F. Configure a private VIF to connect to the corporate network.
- G. Create a transit gateway, and attach the VPC
- H. Create a Direct Connect gateway, and associate it with the transit gateway
- I. Create a transit VIF to the Direct Connect gateway.

Answer: D

Explanation:

When a company requires connectivity to multiple VPCs over AWS Direct Connect, a scalable solution is to use a transit gateway. A transit gateway is a hub that can interconnect multiple VPCs and VPN connections. The VPCs can communicate with each other over the transit gateway, and on-premises networks can communicate with the VPCs through the Direct Connect gateway. This solution provides a central point of management and simplifies the configuration of network routing. By associating the Direct Connect gateway with the transit gateway, traffic between the VPCs and the on-premises network can be routed through the Direct Connect connection.

NEW QUESTION 60

A network engineer has deployed an Amazon EC2 instance in a private subnet in a VPC. The VPC has no public subnet. The EC2 instance hosts application code that sends messages to an Amazon Simple Queue Service (Amazon SQS) queue. The subnet has the default network ACL with no modification applied. The EC2 instance has the default security group with no modification applied.

The SQS queue is not receiving messages.

Which of the following are possible causes of this problem? (Choose two.)

- A. The EC2 instance is not attached to an IAM role that allows write operations to Amazon SQS.
- B. The security group is blocking traffic to the IP address range used by Amazon SQS
- C. There is no interface VPC endpoint configured for Amazon SQS
- D. The network ACL is blocking return traffic from Amazon SQS
- E. There is no route configured in the subnet route table for the IP address range used by Amazon SQS

Answer: CE

NEW QUESTION 63

An ecommerce company is hosting a web application on Amazon EC2 instances to handle continuously changing customer demand. The EC2 instances are part of an Auto Scaling group. The company wants to implement a solution to distribute traffic from customers to the EC2 instances. The company must encrypt all traffic at all stages between the customers and the application servers. No decryption at intermediate points is allowed.

Which solution will meet these requirements?

- A. Create an Application Load Balancer (ALB). Add an HTTPS listener to the AL
- B. Configure the Auto Scaling group to register instances with the ALB's target group.
- C. Create an Amazon CloudFront distributio
- D. Configure the distribution with a custom SSL/TLS certificat
- E. Set the Auto Scaling group as the distribution's origin.
- F. Create a Network Load Balancer (NLB). Add a TCP listener to the NL
- G. Configure the Auto Scaling group to register instances with the NLB's target group.
- H. Create a Gateway Load Balancer (GLB). Configure the Auto Scaling group to register instances with the GLB's target group.

Answer: C

Explanation:

To distribute traffic from customers to EC2 instances in an Auto Scaling group and encrypt all traffic at all stages between the customers and the application servers without decryption at intermediate points, the company should create a Network Load Balancer (NLB) with a TCP listener and configure the Auto Scaling group to register instances with the NLB's target group (Option C). This solution allows for end-to-end encryption of traffic without decryption at intermediate points.

NEW QUESTION 68

A government contractor is designing a multi-account environment with multiple VPCs for a customer. A network security policy requires all traffic between any two VPCs to be transparently inspected by a third-party appliance.

The customer wants a solution that features AWS Transit Gateway. The setup must be highly available across multiple Availability Zones, and the solution needs to support automated failover. Furthermore, asymmetric routing is not supported by the inspection appliances.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy two clusters that consist of multiple appliances across multiple Availability Zones in a designated inspection VP
- B. Connect the inspection VPC to the transit gateway by using a VPCattachmen
- C. Create a target group, and register the appliances with the target grou
- D. Create a Network Load Balancer (NLB), and set it up to forward to the newly created target grou
- E. Configure a default route in the inspection VPCs transit gateway subnet toward the NLB.
- F. Deploy two clusters that consist of multiple appliances across multiple Availability Zones in a designated inspection VP
- G. Connect the inspection VPC to the transit gateway by using a VPC attachmen
- H. Create a target group, and register the appliances with the target grou
- I. Create a Gateway Load Balancer, and set it up to forward to the newly created target grou
- J. Configure a default route in the inspection VPC's transit gateway subnet toward the Gateway Load Balancer endpoint.
- K. Configure two route tables on the transit gatewa
- L. Associate one route table with all the attachments of the application VPC
- M. Associate the other route table with the inspection VPC's attachmen
- N. Propagate all VPC attachments into the inspection route tabl
- O. Define a static default route in the application route tabl
- P. Enable appliance mode on the attachment that connects the inspection VPC.
- Q. Configure two route tables on the transit gatewa
- R. Associate one route table with all the attachments of the application VPC
- S. Associate the other route table with the inspection VPCs attachmen
- T. Propagate all VPC attachments into the application route tabl
- . Define a static default route in the inspection route tabl
- . Enable appliance mode on the attachment that connects the inspection VPC.
- . Configure one route table on the transit gatewa
- . Associate the route table with all the VPC
- . Propagate all VPC attachments into the route tabl
- . Define a static default route in the route table.

Answer: BC

NEW QUESTION 69

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

ANS-C01 Practice Exam Features:

- * ANS-C01 Questions and Answers Updated Frequently
- * ANS-C01 Practice Questions Verified by Expert Senior Certified Staff
- * ANS-C01 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * ANS-C01 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The ANS-C01 Practice Test Here](#)