

Fortinet

Exam Questions NSE7_SDW-7.0

Fortinet NSE 7 - SD-WAN 7.0



NEW QUESTION 1

Refer to the exhibits.

Exhibit A

```
config duplication
edit 1
    set srcaddr "10.0.1.0/24"
    set dstaddr "10.1.0.0/24"
    set srcintf "port5"
    set dstintf "overlay"
    set service "ALL"
    set packet-duplication force
next
end

branch1_fgt # diagnose sys sdwan zone
Zone SASE index=2
    members(0):
Zone overlay index=4
    members(3): 19(T_INET_0_0) 20(T_INET_1_0) 21(T_MPLS_0)
Zone underlay index=3
    members(2): 3(port1) 4(port2)
Zone virtual-wan-link index=1
    members(0):

1.274665 port5 in 10.0.1.101 -> 10.1.0.7: icmp: echo request
1.275788 T_INET_0_0 out 10.0.1.101 -> 10.1.0.7: icmp: echo request
1.275790 T_INET_1_0 out 10.0.1.101 -> 10.1.0.7: icmp: echo request
1.275801 T_MPLS_0 out 10.0.1.101 -> 10.1.0.7: icmp: echo request
1.278365 T_INET_1_0 in 10.1.0.7 -> 10.0.1.101: icmp: echo reply
1.278553 port5 out 10.1.0.7 -> 10.0.1.101: icmp: echo reply
```

Exhibit B

```
3.874431 T_INET_1_0 in 10.0.1.101 -> 10.1.0.7: icmp: echo request
3.874630 port5 out 10.0.1.101 -> 10.1.0.7: icmp: echo request
3.874895 T_INET_0_0 in 10.0.1.101 -> 10.1.0.7: icmp: echo request
3.875125 T_MPLS_0 in 10.0.1.101 -> 10.1.0.7: icmp: echo request
3.875054 port5 in 10.1.0.7 -> 10.0.1.101: icmp: echo reply
3.875308 T_INET_1_0 out 10.1.0.7 -> 10.0.1.101: icmp: echo reply
```

Exhibit A shows the packet duplication rule configuration, the SD-WAN zone status output, and the sniffer output on FortiGate acting as the sender. Exhibit B shows the sniffer output on a FortiGate acting as the receiver.

The administrator configured packet duplication on both FortiGate devices. The sniffer output on the sender FortiGate shows that FortiGate forwards an ICMP echo request packet over three overlays, but it only receives one reply packet through T_INET_1_0.

Based on the output shown in the exhibits, which two reasons can cause the observed behavior? (Choose two.)

- A. On the receiver FortiGate, packet-de-duplication is enabled.
- B. The ICMP echo request packets sent over T_INET_0_0 and T_MPLS_0 were dropped along the way.
- C. The ICMP echo request packets received over T_INET_0_0 and T_MPLS_0 were offloaded to NPU.
- D. On the sender FortiGate, duplication-max-num is set to 3.

Answer: AD

NEW QUESTION 2

Which diagnostic command can you use to show the member utilization statistics measured by performance SLAs for the last 10 minutes?

- A. diagnose sys sdwan intf-sla-log
- B. diagnose sys sdwan health-check
- C. diagnose sys sdwan log
- D. diagnose sys sdwan sla-log

Answer: D

Explanation:

SD-WAN 7.2 Study Guide page 321 You can view the stored member metrics by running the diagnose sys sdwan sla-log command. Note that you must include the name of the performance SLA followed by the member configuration index number. To display the SLA logs per interface, you run the diagnose sys sdwan intf-sla-log command.

NEW QUESTION 3

In a hub-and-spoke topology, what are two advantages of enabling ADVPN on the IPsec overlays? (Choose two.)

- A. It provides the benefits of a full-mesh topology in a hub-and-spoke network.
- B. It provides direct connectivity between spokes by creating shortcuts.
- C. It enables spokes to bypass the hub during shortcut negotiation.
- D. It enables spokes to establish shortcuts to third-party gateways.

Answer: AB

NEW QUESTION 4

What is the route-tag setting in an SD-WAN rule used for?

- A. To indicate the routes for health check probes.
- B. To indicate the destination of a rule based on learned BGP prefixes.
- C. To indicate the routes that can be used for routing SD-WAN traffic.
- D. To indicate the members that can be used to route SD-WAN traffic.

Answer: B

NEW QUESTION 5

Refer to the exhibit.

```
ike 0:T_INET_0_0:214: received informational request
ike 0:T_INET_0_0:214: processing notify type SHORTCUT_QUERY
ike 0:T_INET_0_0: recv shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 32
nat 0 ver 2 mode 0
ike 0:T_INET_0: iif 20 10.0.1.101->10.0.2.101 route lookup oif 20 T_INET_0 gwy
10.201.1.1
ike 0:T_INET_0_1: forward shortcut-query 9065761962601467474
07409008f7fbd17e/0000000000000000 192.2.0.1 10.0.1.101->10.0.2.101 psk 64 ppk 0 ttl 31
ver 2 mode 0, ext-mapping 192.2.0.1:500
```

Which statement about the role of the ADVPN device in handling traffic is true?

- A. This is a spoke that has received a query from a remote hub and has forwarded the response to its hub.
- B. Two hubs, 10.0.1.101 and 10.0.2.101, are receiving and forwarding queries between each other.
- C. This is a hub that has received a query from a spoke and has forwarded it to another spoke.
- D. Two spokes, 192.2.0.1 and 10.0.2.101, forward their queries to their hubs.

Answer: C

NEW QUESTION 6

What does enabling the exchange-interface-ip setting enable FortiGate devices to exchange?

- A. The gateway address of their IPsec interfaces
- B. The tunnel ID of their IPsec interfaces
- C. The IP address of their IPsec interfaces
- D. The name of their IPsec interfaces

Answer: C

NEW QUESTION 7

What is a benefit of using application steering in SD-WAN?

- A. The traffic always skips the regular policy routes.
- B. You steer traffic based on the detected application.
- C. You do not need to enable SSL inspection.
- D. You do not need to configure firewall policies that accept the SD-WAN traffic.

Answer: B

NEW QUESTION 8

Which two statements about SLA targets and SD-WAN rules are true? (Choose two.)

- A. When configuring an SD-WAN rule, you can select multiple SLA targets of the same performance SLA.
- B. SD-WAN rules use SLA targets to check if the preferred members meet the SLA requirements.
- C. SLA targets are used only by SD-WAN rules that are configured with Lowest Cost (SLA) or Maximize Bandwidth (SLA) as strategy.
- D. Member metrics are measured only if an SLA target is configured.

Answer: BC

NEW QUESTION 9

Which are three key routing principles in SD-WAN? (Choose three.)

- A. FortiGate performs route lookups for new sessions only.
- B. Regular policy routes have precedence over SD-WAN rules.
- C. SD-WAN rules have precedence over ISDB routes.
- D. By default, SD-WAN members are skipped if they do not have a valid route to the destination.
- E. By default, SD-WAN rules are skipped if the best route to the destination is not an SD-WAN member.

Answer: BDE

NEW QUESTION 10

In the default SD-WAN minimum configuration, which two statements are correct when traffic matches the default implicit SD-WAN rule? (Choose two)

- A. Traffic has matched none of the FortiGate policy routes.
- B. Matched traffic failed RPF and was caught by the rule.
- C. The FIB lookup resolved interface was the SD-WAN interface.
- D. An absolute SD-WAN rule was defined and matched traffic.

Answer: AC

NEW QUESTION 10

Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 3

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
  Gen(2), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(priority), link-cost-factor(packet-loss), link-cost-threshold(0), health-check(VPN_PING)
  Members(3):
    1: Seq_num(3 T_INET_0_0), alive, packet loss: 2.000%, selected
    2: Seq_num(4 T_MPLS_0), alive, packet loss: 4.000%, selected
    3: Seq_num(5 T_INET_1_0), alive, packet loss: 12.000%, selected
  Src address(1):
    10.0.1.0-10.0.1.255

  Dst address(1):
    10.0.0.0-10.255.255.255

branch1_fgt (3) # show
config service
  edit 3
    set name "Corp"
    set mode priority
    set dst "Corp-net"
    set src "LAN-net"
    set health-check "VPN_PING"
    set link-cost-factor packet-loss
    set link-cost-threshold 0
    set priority-members 5 3 4
  next
end
```

The exhibit shows the SD-WAN rule status and configuration.

Based on the exhibit, which change in the measured packet loss will make T_INET_1_0 the new preferred member?

- A. When all three members have the same packet loss.
- B. When T_INET_0_0 has 4% packet loss.
- C. When T_INET_0_0 has 12% packet loss.
- D. When T_INET_1_0 has 4% packet loss.

Answer: A

NEW QUESTION 12

Refer to the exhibit.

```
session info: proto=6 proto_state=11 duration=242 expire=3349 timeout=3600
flags=00000000 socktype=0 sockport=0 av_idx=0 use=4
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=log dirty may_dirty ndr f00 app_valid
statistic(bytes/packets/allow_err): org=3421/20/1 reply=3777/17/1 tuples=3
tx speed(Bps/kbps): 0/0 rx speed(Bps/kbps): 0/0
origin->sink: org pre->post, reply pre->post dev=7->3/3->7 gwy=0.0.0.0/0.0.0.0
hook=post dir=org act=snat 10.0.1.101:34676->128.66.0.1:22(192.2.0.1:34676)
hook=pre dir=reply act=dnat 128.66.0.1:22->192.2.0.1:34676(10.0.1.101:34676)
hook=post dir=reply act=noop 128.66.0.1:22->10.0.1.101:34676(0.0.0.0:0)
pos/(before,after) 0/(0,0), 0/(0,0)
misc=0 policy_id=2 pol_uuid_idx=14721 auth_info=0 chk_client_info=0 vd=0
serial=000032d9 tos=ff/ff app_list=2000 app=16060 url_cat=0
sdwan_mbr_seq=1 sdwan_service_id=2
rpd_b_link_id=ff000002 rpd_b_svc_id=0 ngfwid=n/a
npu_state=0x001008
```

Which statement explains the output shown in the exhibit?

- A. FortiGate performed standard FIB routing on the session.
- B. FortiGate will not re-evaluate the session following a firewall policy change.
- C. FortiGate used 192.2.0.1 as the gateway for the original direction of the traffic.
- D. FortiGate must re-evaluate the session due to routing change.

Answer: D

NEW QUESTION 17

Which diagnostic command can you use to show the configured SD-WAN zones and their assigned members?

- A. diagnose sys sdwan zone
- B. diagnose sys sdwan service
- C. diagnose sys sdwan member
- D. diagnose sys sdwan interface

Answer: A

NEW QUESTION 20

Refer to the exhibit.

```
branch1_fgt # diagnose firewall proute list
list route policy info(vf=root):

id=1 dscp_tag=0xff 0xff flags=0x0 tos=0x00 tos_mask=0x00 protocol=17 sport=0-65535 iif=7
dport=53 path(1) oif=3(port1)
source wildcard(1): 0.0.0.0/0.0.0.0
destination wildcard(1): 4.2.2.1/255.255.255.255
hit_count=0 last_used=2022-03-25 10:53:26

id=2131165185(0x7f070001) vwl_service=1(Critical-DIA) vwl_mbr_seq=1 2 dscp_tag=0xff 0xff
flags=0x0 tos=0x00 tos_mask=0x00 protocol=0 sport=0-65535 iif=0 dport=1-65535 path(2)
oif=3(port1) oif=4(port2)
source(1): 10.0.1.0-10.0.1.255
destination wildcard(1): 0.0.0.0/0.0.0.0
internet service(3): GoToMeeting(4294836966,0,0,0, 16354)
Microsoft.Office.365.Portals(4294837474,0,0,0, 41468) Salesforce(4294837976,0,0,0, 16920)
hit_count=0 last_used=2022-03-24 12:18:16

id=2131165186(0x7f070002) vwl_service=2(Non-Critical-DIA) vwl_mbr_seq=2 dscp_tag=0xff
0xff flags=0x0 tos=0x00 tos_mask=0x00 protocol=0 sport=0-65535 iif=0 dport=1-65535
path(1) oif=4(port2)
source(1): 10.0.1.0-10.0.1.255
destination wildcard(1): 0.0.0.0/0.0.0.0
internet service(2): Facebook(4294836806,0,0,0, 15832) Twitter(4294838278,0,0,0, 16001)
hit_count=0 last_used=2022-03-24 12:18:16

id=2131165187(0x7f070003) vwl_service=3(all_rules) vwl_mbr_seq=1 dscp_tag=0xff 0xff
flags=0x0 tos=0x00 tos_mask=0x00 protocol=0 sport=0-65535 iif=0 dport=1-65535 path(1)
oif=3(port1)
source(1): 0.0.0.0-255.255.255.255
destination(1): 0.0.0.0-255.255.255.255
hit_count=0 last_used=2022-03-25 10:58:12
```

Based on the output, which two conclusions are true? (Choose two.)

- A. There is more than one SD-WAN rule configured.
- B. The SD-WAN rules take precedence over regular policy routes.
- C. The all_rules rule represents the implicit SD-WAN rule.
- D. Entry 1(id=1) is a regular policy route.

Answer: AD

NEW QUESTION 21

Refer to the exhibit.

```
config vpn ipsec phase1-interface
edit "T_INET_0_0"
set type dynamic
set interface "port1"
set keylife 28800
set peertype any
set net-device disable
set proposal aes128-sha256
set add-route enable
set psksecret ENC
Zv9n4Urfk0W4jj8vWI+KywxBG4ZDT7jWHKd8YaL8j4+pRpYOx/N7mSgc7VL0BW22HQUXWJ6zvFxNKktiPYntA8aP
i6ly7gDx2lP/OfKexTQQJzgCGRYzLM8eFTOnK7K6AuX0bFDCpBBhEIdf+03CYBMLwkFZmdU6RsT+qvybblVX+Ioy
HK5EXakpmz5RiltELgZ9Gg==
next
end
```

Which configuration change is required if the responder FortiGate uses a dynamic routing protocol to exchange routes over IPsec?

- A. type must be set to static.
- B. mode-cfg must be enabled.
- C. exchange-interface-ip must be enabled.
- D. add-route must be disabled.

Answer: D

Explanation:

for using "non ike" routes (for example BGP/static and so on) you must do disable the add-route that inject automatically kernel route based on p2 selectors from the remote site from the SD-WAN_7.2_Study_Guide page 236

NEW QUESTION 24

Refer to the exhibit.

```
config system sdwan
  set status enable
  set load-balance source-dest-ip-based
  config zone
    edit "virtual-wan-link"
    next
    edit "SASE"
    next
    edit "underlay"
    next
  end
  config members
    edit 1
      set interface "port1"
      set zone "underlay"
      set gateway 192.2.0.2
    next
    edit 2
      set interface "port2"
      set zone "underlay"
      set gateway 192.2.0.10
    next
  end
  ...
end
```

Which algorithm does SD-WAN use to distribute traffic that does not match any of the SD-WAN rules?

- A. All traffic from a source IP to a destination IP is sent to the same interface.
- B. All traffic from a source IP is sent to the same interface.
- C. All traffic from a source IP is sent to the most used interface.
- D. All traffic from a source IP to a destination IP is sent to the least used interface.

Answer: A

NEW QUESTION 29

Refer to the exhibit.

```
config system sdwan
  set fail-detect enable
  set fail-alert-interfaces "port5"
  config health-check
    edit "Level3_DNS"
      set update-cascade-interface enable
      set members 1 2
    next
    edit "HQ"
      set update-cascade-interface enable
      set members 3
    next
  end
end
```

Based on the exhibit, which action does FortiGate take?

- A. FortiGate bounces port5 after it detects all SD-WAN members as dead.
- B. FortiGate fails over to the secondary device after it detects all SD-WAN members as dead.

- C. FortiGate brings up port5 after it detects all SD-WAN members as alive.
- D. FortiGate brings down port5 after it detects all SD-WAN members as dead.

Answer: B

NEW QUESTION 33

Which CLI command do you use to perform real-time troubleshooting for ADVPN negotiation?

- A. get router info routing-table all
- B. diagnose debug application ike
- C. diagnose vpn tunnel list
- D. get ipsec tunnel list

Answer: B

Explanation:

IKE real-time debug - useful when debugging ADVPN shortcut messages and spoke-to-spoke negotiations.

- diagnose debug console timestamp enable
- diagnose vpn ike log filter clear
- diagnose vpn ike log filter mdst-addr4 <ip.of.hub> <ip.of.spoke>
- diagnose debug application ike -1
- diagnose debug enable

NEW QUESTION 35

Which two protocols in the IPsec suite are most used for authentication and encryption? (Choose two.)

- A. Encapsulating Security Payload (ESP)
- B. Secure Shell (SSH)
- C. Internet Key Exchange (IKE)
- D. Security Association (SA)

Answer: AC

NEW QUESTION 37

Which two tasks are part of using central VPN management? (Choose two.)

- A. You can configure full mesh, star, and dial-up VPN topologies.
- B. You must enable VPN zones for SD-WAN deployments.
- C. FortiManager installs VPN settings on both managed and external gateways.
- D. You configure VPN communities to define common IPsec settings shared by all VPN gateways.

Answer: AD

NEW QUESTION 40

Refer to the exhibit.

```
config firewall policy
  edit 1
    set anti-replay disable
  next
end
```

In a dual-hub hub-and-spoke SD-WAN deployment, which is a benefit of disabling the anti-replay setting on the hubs?

- A. It instructs the hub to disable the reordering of TCP packets on behalf of the receiver, to improve performance.
- B. It instructs the hub to disable TCP sequence number check, which is required for TCP sessions originated from spokes to fail over back and forth between the hubs.
- C. It instructs the hub to not check the ESP sequence numbers on IPsec traffic, to improve performance.
- D. It instructs the hub to skip content inspection on TCP traffic, to improve performance.

Answer: B

NEW QUESTION 45

Which statement is correct about SD-WAN and ADVPN?

- A. Routes for ADVPN shortcuts must be manually configured.
- B. SD-WAN can steer traffic to ADVPN shortcuts, established over IPsec overlays, configured as SD-WAN members.
- C. SD-WAN does not monitor the health and performance of ADVPN shortcuts.
- D. You must use IKEv2 on IPsec tunnels.

Answer: B

NEW QUESTION 46

Which three matching traffic criteria are available in SD-WAN rules? (Choose three.)

- A. Type of physical link connection

- B. Internet service database (ISDB) address object
- C. Source and destination IP address
- D. URL categories
- E. Application signatures

Answer: BCE

NEW QUESTION 50

Refer to the exhibit.

```
config system settings
    set firewall-session-dirty check-new
end
```

Based on the exhibit, which two actions does FortiGate perform on sessions after a firewall policy change? (Choose two.)

- A. FortiGate flushes all sessions.
- B. FortiGate terminates the old sessions.
- C. FortiGate does not change existing sessions.
- D. FortiGate evaluates new sessions.

Answer: CD

Explanation:

FortiGate not to flag existing impacted session as dirty by setting firewall-session-dirty to check new. The results is that FortiGate evaluates only new session against the new firewall policy.

NEW QUESTION 55

Refer to the exhibit.

```
# diagnose sys session list

session info: proto=6 proto_state=01 duration=39 expire=3593 timeout=3600 flags=00000000
socktype=0 sockport=0 av_idx=0 use=4
state=may_dirty npu
origin->sink: org pre->post, reply pre->post dev=7->5/5->7 gwy=10.10.10.1/10.9.31.160
hook=pre dir=org act=noop 10.9.31.160:7932->10.0.1.7:22(0.0.0.0:0)
hook=post dir=reply act=noop 10.0.1.7:22->10.9.31.160:7932(0.0.0.0:0)
pos/(before,after) 0/(0,0), 0/(0,0)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00045e02 tos=ff/ff app_list=0 app=0 url_cat=0
sdwan_mbr_seq=1 sdwan_service_id=1
rpd_b_link_id=80000000 rpd_b_svc_id=0 ngfwid=n/a
npu_state=0x4000c00
npu info: flag=0x81/0x81, offload=8/8, ips_offload=0/0, epid=64/76, ipid=76/64,
vlan=0x0000/0x0000
vlifid=76/64, vtag_in=0x0000/0x0000 in_npu=1/1, out_npu=1/1, fwd_en=0/0, qid=2/2
reflect info 0:
dev=7->6/6->7
npu_state=0x4000800
npu info: flag=0x00/0x81, offload=0/8, ips_offload=0/0, epid=0/76, ipid=0/65, vlan=0x0000/0x0000
vlifid=0/65, vtag_in=0x0000/0x0000 in_npu=0/1, out_npu=0/1, fwd_en=0/0, qid=0/2
total reflect session num: 1
total session 1

# diagnose netlink interface list

if=port1 family=00 type=1 index=5 mtu=1500 link=0 master=0
if=port2 family=00 type=1 index=6 mtu=1500 link=0 master=0
if=port3 family=00 type=1 index=7 mtu=1500 link=0 master=0
```

The exhibit shows the details of a session and the index numbers of some relevant interfaces on a FortiGate appliance that supports hardware offloading. Based on the information shown in the exhibits, which two statements about the session are true? (Choose two.)

- A. The reply direction of the asymmetric traffic flows from port2 to port3.
- B. The auxiliary session can be offloaded to hardware.
- C. The original direction of the symmetric traffic flows from port3 to port2.
- D. The main session cannot be offloaded to hardware.

Answer: AB

NEW QUESTION 56

Refer to the exhibit.


```
config system interface
  edit "port2"
    set vdom "root"
    set ip 192.2.0.9 255.255.255.248
    set allowaccess ping
    set type physical
    set role wan
    set snmp-index 2
    set preserve-session-route enable
  next
end
```

Based on the exhibit, which two actions does FortiGate perform on traffic passing through port2? (Choose two.)

- A. FortiGate does not change the routing information on existing sessions that use a valid gateway, after a route change.
- B. FortiGate performs routing lookups for new sessions only, after a route change.
- C. FortiGate always blocks all traffic, after a route change.
- D. FortiGate flushes all routing information from the session table, after a route change.

Answer: AB

NEW QUESTION 59

What are two benefits of using forward error correction (FEC) in IPsec VPNs? (Choose two.)

- A. FEC supports hardware offloading.
- B. FEC improves reliability of noisy links.
- C. FEC transmits parity packets that can be used to reconstruct packet loss.
- D. FEC can leverage multiple IPsec tunnels for parity packets transmission.

Answer: BC

NEW QUESTION 61

Which two statements about SD-WAN central management are true? (Choose two.)

- A. The objects are saved in the ADOM common object database.
- B. It does not support meta fields.
- C. It uses templates to configure SD-WAN on managed devices.
- D. It supports normalized interfaces for SD-WAN member configuration.

Answer: AC

Explanation:

Normalized interfaces are not supported for SD-WAN templates. You can create multiple SD-WAN zones and add interface members to the SD-WAN zones. You must bind the interface members by name to physical interfaces or VPN interfaces. <https://docs.fortinet.com/document/fortigate/7.0.0/sd-wan-new-features/794804/new-sd-wan-template>

NEW QUESTION 66

Refer to the exhibit.

```
id=20085 trace_id=847 func=print_pkt_detail line=5428 msg="vd-root:0 received a
packet(proto=6, 10.1.10.1:33920->74.125.195.93:443) from port3. flag [.], seq
2018554516, ack 4141536963, win 2238"
id=20085 trace_id=847 func=resolve_ip_tuple_fast line=5508 msg="Find an existing
session, id-000008c1, original direction"
id=20085 trace id=847 func=shaper handler line=821 msg="exceeded shaper limit, drop"
```

Which conclusion about the packet debug flow output is correct?

- A. The original traffic exceeded the maximum packets per second of the outgoing interface, and the packet was dropped.
- B. The reply traffic exceeded the maximum bandwidth configured in the traffic shaper, and the packet was dropped.
- C. The original traffic exceeded the maximum bandwidth of the outgoing interface, and the packet was dropped.
- D. The original traffic exceeded the maximum bandwidth configured in the traffic shaper, and the packet was dropped.

Answer: D

NEW QUESTION 67

Refer to the exhibits.
 Exhibit A

Edit Traffic Shaping Policy

IP Version: IPv4 IPv6

Name:

Status: Enable Disable

Comments:
0/255

If Traffic Matches:

Source Internet Service: ☐

Source Address: ×

Source User: +

Source User Group: +

Destination Internet Service: ☐

Destination Address: ×

Schedule: +

Service: ×

Application: ×

Application Category: +

Application Group: +

URL Category: +

Type Of Service:

Type Of Service Mask:

Then:

Action: Apply Shaper Assign Group

Outgoing Interface: ×

Shared Shaper: ×

Reverse Shaper: ×

Per-IP Shaper: +

Differentiated Services: ☐

Differentiated Services Reverse: ☐

Exhibit B

Edit Firewall Policy

ID: 1

Name:

ZTNA: Disable Full ZTNA IP/MAC filtering

Incoming Interface: ×

Outgoing Interface: ×

Source Internet Service: ☐

IPv4 Source Address: ×

IPv6 Source Address: +

Source User: +

Source User Group: +

FSSO Groups: +

Destination Internet Service: ☐

IPv4 Destination Address: ×

IPv6 Destination Address: +

Service: ×

Schedule: ×

Action: Deny Accept IPSEC

Inspection Mode: Flow-based Proxy-based

Firewall/Network Options

NAT: ☒ NAT NAT46 NAT64

IP Pool Configuration: Use Outgoing Interface Address Use Dynamic IP Pool

Preserve Source Port: ☐

Protocol Options: ×

Disclaimer Options

Display Disclaimer: ☐

Security Profiles

SSL/SSH Inspection: ×

Decrypted Traffic Mirror: +

Traffic Shaping Options

Shared Shaper: +

Reverse Shaper: +

Per-IP Shaper: +

Logging Options

Log Allowed Traffic: No Log Log Security Events Log All Sessions

☐ Capture Packets

☐ Generate Logs when Session Starts

Exhibit A shows the traffic shaping policy and exhibit B shows the firewall policy.

The administrator wants FortiGate to limit the bandwidth used by YouTube. When testing, the administrator determines that FortiGate does not apply traffic shaping on YouTube traffic.

Based on the policies shown in the exhibits, what configuration change must be made so FortiGate performs traffic shaping on YouTube traffic?

- A. Destination internet service must be enabled on the traffic shaping policy.
- B. Application control must be enabled on the firewall policy.
- C. Web filtering must be enabled on the firewall policy.
- D. Individual SD-WAN members must be selected as the outgoing interface on the traffic shaping policy.

Answer: B

NEW QUESTION 69

Which two statements are true about using SD-WAN to steer local-out traffic? (Choose two.)

- A. FortiGate does not consider the source address of the packet when matching an SD-WAN rule for local-out traffic.
- B. By default, local-out traffic does not use SD-WAN.
- C. By default, FortiGate does not check if the selected member has a valid route to the destination.
- D. You must configure each local-out feature individually, to use SD-WAN.

Answer: BD

NEW QUESTION 74

Which two interfaces are considered overlay links? (Choose two.)

- A. LAG
- B. IPsec
- C. Physical
- D. GRE

Answer: BD

NEW QUESTION 76

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

NSE7_SDW-7.0 Practice Exam Features:

- * NSE7_SDW-7.0 Questions and Answers Updated Frequently
- * NSE7_SDW-7.0 Practice Questions Verified by Expert Senior Certified Staff
- * NSE7_SDW-7.0 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * NSE7_SDW-7.0 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The NSE7_SDW-7.0 Practice Test Here](#)