



Amazon-Web-Services

Exam Questions SCS-C01

AWS Certified Security- Specialty

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A company manages three separate IAM accounts for its production, development, and test environments. Each Developer is assigned a unique IAM user under the development account. A new application hosted on an Amazon EC2 instance in the developer account requires read access to the archived documents stored in an Amazon S3 bucket in the production account.

How should access be granted?

- A. Create an IAM role in the production account and allow EC2 instances in the development account to assume that role using the trust policy.
- B. Provide read access for the required S3 bucket to this role.
- C. Use a custom identity broker to allow Developer IAM users to temporarily access the S3 bucket.
- D. Create a temporary IAM user for the application to use in the production account.
- E. Create a temporary IAM user in the production account and provide read access to Amazon S3. Generate the temporary IAM user's access key and secret key and store these on the EC2 instance used by the application in the development account.

Answer: A

Explanation:

<https://IAM.amazon.com/premiumsupport/knowledge-center/cross-account-access-s3/>

NEW QUESTION 2

A company's Chief Security Officer has requested that a Security Analyst review and improve the security posture of each company IAM account. The Security Analyst decides to do this by improving IAM account root user security.

Which actions should the Security Analyst take to meet these requirements? (Select THREE.)

- A. Delete the access keys for the account root user in every account.
- B. Create an admin IAM user with administrative privileges and delete the account root user in every account.
- C. Implement a strong password to help protect account-level access to the IAM Management Console by the account root user.
- D. Enable multi-factor authentication (MFA) on every account root user in all accounts.
- E. Create a custom IAM policy to limit permissions to required actions for the account root user and attach the policy to the account root user.
- F. Attach an IAM role to the account root user to make use of the automated credential rotation in IAM STS.

Answer: ADE

Explanation:

because these are the actions that can improve IAM account root user security. IAM account root user is a user that has complete access to all AWS resources and services in an account. IAM account root user security is a set of best practices that help protect the account root user from unauthorized or accidental use. Deleting the access keys for the account root user in every account can help prevent programmatic access by the account root user, which reduces the risk of compromise or misuse. Enabling MFA on every account root user in all accounts can help add an extra layer of security for console access by requiring a verification code in addition to a password. Creating a custom IAM policy to limit permissions to required actions for the account root user and attaching the policy to the account root user can help enforce the principle of least privilege and restrict the account root user from performing unnecessary or dangerous actions. The other options are either invalid or ineffective for improving IAM account root user security.

NEW QUESTION 3

A development team is attempting to encrypt and decode a secure string parameter from the IAM Systems Manager Parameter Store using an IAM Key Management Service (IAM KMS) CMK. However, each attempt results in an error message being sent to the development team.

Which CMK-related problems possibly account for the error? (Select two.)

- A. The CMK used in the attempt does not exist.
- B. The CMK used in the attempt needs to be rotated.
- C. The CMK used in the attempt is using the CMK's key ID instead of the CMK ARN.
- D. The CMK used in the attempt is not enabled.
- E. The CMK used in the attempt is using an alias.

Answer: AD

Explanation:

<https://docs.IAM.amazon.com/kms/latest/developerguide/services-parameter-store.html#parameter-store-cmk-fa>

NEW QUESTION 4

A company is designing a multi-account structure for its development teams. The company is using AWS Organizations and AWS Single Sign-On (AWS SSO). The company must implement a solution so that the development teams can use only specific AWS Regions and so that each AWS account allows access to only specific AWS services.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS SSO to set up service-linked roles with IAM policy statements that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.
- B. Deactivate AWS Security Token Service (AWS STS) in Regions that the developers are not allowed to use.
- C. Create SCPs that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.
- D. For each AWS account, create tailored identity-based policies for AWS SSO.
- E. Use statements that include the Condition, Resource, and NotAction elements to allow access to only the Regions and services that are needed.

Answer: C

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps_syntax.html#scp-element

NEW QUESTION 5

A company uses AWS Organizations to manage several AWS accounts. The company processes a large volume of sensitive data. The company uses a serverless

approach to microservices. The company stores all the data in either Amazon S3 or Amazon DynamoDB. The company reads the data by using either AWS lambda functions or container-based services that the company hosts on Amazon Elastic Kubernetes Service (Amazon EKS) on AWS Fargate. The company must implement a solution to encrypt all the data at rest and enforce least privilege data access controls. The company creates an AWS Key Management Service (AWS KMS) customer managed key. What should the company do next to meet these requirements?

- A. Create a key policy that allows the kms:Decrypt action only for Amazon S3 and DynamoD
- B. Create an SCP that denies the creation of S3 buckets and DynamoDB tables that are not encrypted with the key.
- C. Create an IAM policy that denies the kms:Decrypt action for the ke
- D. Create a Lambda function than runs on a schedule to attach the policy to any new role
- E. Create an AWS Config rule to send alerts for resources that are not encrypted with the key.
- F. Create a key policy that allows the kms:Decrypt action only for Amazon S3, DynamoDB, Lambda, and Amazon EK
- G. Create an SCP that denies the creation of S3 buckets and DynamoDB tables that are not encrypted with the key.
- H. Create a key policy that allows the kms:Decrypt action only for Amazon S3, DynamoDB, Lambda, and Amazon EK
- I. Create an AWS Config rule to send alerts for resources that are not encrypted with the key.

Answer: B

NEW QUESTION 6

A security engineer is using AWS Organizations and wants to optimize SCPs. The security engineer needs to ensure that the SCPs conform to best practices. Which approach should the security engineer take to meet this requirement?

- A. Use AWS IAM Access Analyzer to analyze the policie
- B. View the findings from policy validation checks.
- C. Review AWS Trusted Advisor checks for all accounts in the organization.
- D. Set up AWS Audit Manage
- E. Run an assessment for all AWS Regions for all accounts.
- F. Ensure that Amazon Inspector agents are installed on all Amazon EC2 in-stances in all accounts.

Answer: A

NEW QUESTION 7

A company that uses AWS Organizations wants to see AWS Security Hub findings for many AWS accounts and AWS Regions. Some of the accounts are in the company's organization, and some accounts are in organizations that the company manages for customers. Although the company can see findings in the Security Hub administrator account for accounts in the company's organization, there are no findings from accounts in other organizations. Which combination of steps should the company take to see findings from accounts that are outside the organization that includes the Security Hub administrator account? (Select TWO.)

- A. Use a designated administration account to automatically set up member accounts.
- B. Create the AWS Service Role ForSecurrty Hub service-linked rote for Security Hub.
- C. Send an administration request from the member accounts.
- D. Enable Security Hub for all member accounts.
- E. Send invitations to accounts that are outside the company's organization from the Security Hub administrator account.

Answer: CE

Explanation:

To see Security Hub findings for accounts that are outside the organization that includes the Security Hub administrator account, the following steps are required:

➤ Send invitations to accounts that are outside the company's organization from the Security Hub administrator account. This will allow the administrator account to view and manage findings from those accounts. The administrator account can send invitations by using the Security Hub console, API, or CLI. For more information, see [Sending invitations to member accounts](#).

➤ Send an administration request from the member accounts. This will allow the member accounts to accept the invitation from the administrator account and establish a relationship with it. The member accounts can send administration requests by using the Security Hub console, API, or CLI. For more information, see [Sending administration requests](#).

This solution will enable the company to see Security Hub findings for many AWS accounts and AWS Regions, including accounts that are outside its own organization.

The other options are incorrect because they either do not establish a relationship between the administrator and member accounts (A, B), do not enable Security Hub for all member accounts (D), or do not use a valid service for Security Hub (F).

Verified References:

➤ <https://docs.aws.amazon.com/securityhub/latest/userguide/securityhub-member-accounts.html>

NEW QUESTION 8

A security engineer is configuring a mechanism to send an alert when three or more failed sign-in attempts to the AWS Management Console occur during a 5-minute period. The security engineer creates a trail in AWS CloudTrail to assist in this work. Which solution will meet these requirements?

- A. In CloudTrail, turn on Insights events on the trai
- B. Configure an alarm on the insight with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Configure a threshold of 3 and a period of 5 minutes.
- C. Configure CloudTrail to send events to Amazon CloudWatch Log
- D. Create a metric filter for the relevant log grou
- E. Create a filter pattern with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Create a CloudWatch alarm with a threshold of 3 and a period of 5 minutes.
- F. Create an Amazon Athena table from the CloudTrail event
- G. Run a query for eventName matching ConsoleLogin and for errorMessage matching "Failed authentication". Create a notification action from the query to send an Amazon Simple Notification Service (Amazon SNS) notification when the count equals 3 within a period of 5 minutes.
- H. In AWS Identity and Access Management Access Analyzer, create a new analyze
- I. Configure the analyzer to send an Amazon Simple Notification Service (Amazon SNS) notification when a failed sign-in event occurs 3 times for any IAM user within a period of 5 minutes.

Answer: B

Explanation:

The correct answer is B. Configure CloudTrail to send events to Amazon CloudWatch Logs. Create a metric filter for the relevant log group. Create a filter pattern with eventName matching ConsoleLogin and errorMessage matching "Failed authentication". Create a CloudWatch alarm with a threshold of 3 and a period of 5 minutes.

This answer is correct because it meets the requirements of sending an alert when three or more failed sign-in attempts to the AWS Management Console occur during a 5-minute period. By configuring CloudTrail to send events to CloudWatch Logs, the security engineer can create a metric filter that matches the desired pattern of failed sign-in events. Then, by creating a CloudWatch alarm based on the metric filter, the security engineer can set a threshold of 3 and a period of 5 minutes, and choose an action such as sending an email or an Amazon Simple Notification Service (Amazon SNS) message when the alarm is triggered¹².

The other options are incorrect because:

- A. Turning on Insights events on the trail and configuring an alarm on the insight is not a solution, because Insights events are used to analyze unusual activity in management events, such as spikes in API call volume or error rates. Insights events do not capture failed sign-in attempts to the AWS Management Console³.
- C. Creating an Amazon Athena table from the CloudTrail events and running a query for failed sign-in events is not a solution, because it does not provide a mechanism to send an alert based on the query results. Amazon Athena is an interactive query service that allows analyzing data in Amazon S3 using standard SQL, but it does not support creating notifications or alarms from queries⁴.
- D. Creating an analyzer in AWS Identity and Access Management Access Analyzer and configuring it to send an Amazon SNS notification when a failed sign-in event occurs 3 times for any IAM user within a period of 5 minutes is not a solution, because IAM Access Analyzer is not a service that monitors sign-in events, but a service that helps identify resources that are shared with external entities. IAM Access Analyzer does not generate findings for failed sign-in attempts to the AWS Management Console⁵.

References:

1: Sending CloudTrail Events to CloudWatch Logs - AWS CloudTrail 2: Creating Alarms Based on Metric Filters - Amazon CloudWatch 3: Analyzing unusual activity in management events - AWS CloudTrail 4: What is Amazon Athena? - Amazon Athena 5: Using AWS Identity and Access Management Access Analyzer - AWS Identity and Access Management

NEW QUESTION 9

To meet regulatory requirements, a Security Engineer needs to implement an IAM policy that restricts the use of AWS services to the us-east-1 Region. What policy should the Engineer implement?

A.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

B. A computer code with black text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    }
  ]
}
```

C. A computer code with black text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

D. A computer code with text Description automatically generated

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "NotAction": "*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:RequestedRegion": "us-east-1"
        }
      }
    }
  ]
}
```

Answer: C

Explanation:

https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_examples_aws_deny-requested-region.h

NEW QUESTION 10

A company uses Amazon GuardDuty. The company's security team wants all High severity findings to automatically generate a ticket in a third-party ticketing system through email integration.

Which solution will meet this requirement?

- A. Create a verified identity for the third-party ticketing email system in Amazon Simple Email Service (Amazon SES). Create an Amazon EventBridge rule that includes an event pattern that matches High severity GuardDuty finding
- B. Specify the SES identity as the target for the EventBridge rule.
- C. Create an Amazon Simple Notification Service (Amazon SNS) topic
- D. Subscribe the third-party ticketing email system to the SNS topic
- E. Create an Amazon EventBridge rule that includes an event pattern that matches High severity GuardDuty finding
- F. Specify the SNS topic as the target for the EventBridge rule.
- G. Use the GuardDuty CreateFilter API operation to build a filter in GuardDuty to monitor for High severity finding
- H. Export the results of the filter to an Amazon Simple Notification Service (Amazon SNS) topic
- I. Subscribe the third-party ticketing email system to the SNS topic.
- J. Use the GuardDuty CreateFilter API operation to build a filter in GuardDuty to monitor for High severity finding
- K. Create an Amazon Simple Notification Service (Amazon SNS) topic
- L. Subscribe the third-party ticketing email system to the SNS topic
- M. Create an Amazon EventBridge rule that includes an event pattern that matches GuardDuty findings that are selected by the filter
- N. Specify the SNS topic as the target for the EventBridge rule.

Answer: B

Explanation:

The correct answer is B. Create an Amazon Simple Notification Service (Amazon SNS) topic. Subscribe the third-party ticketing email system to the SNS topic. Create an Amazon EventBridge rule that includes an event pattern that matches High severity GuardDuty findings. Specify the SNS topic as the target for the Event-Bridge rule.

According to the AWS documentation¹, you can use Amazon EventBridge to create rules that match events from GuardDuty and route them to targets such as Amazon SNS topics. You can use event patterns to filter events based on criteria such as severity, type, or resource. For example, you can create a rule that matches only High severity findings and sends them to an SNS topic that is subscribed by a third-party ticketing email system. This way, you can automate the creation of tickets for High severity findings and notify the security team.

NEW QUESTION 10

A security engineer is defining the controls required to protect the IAM account root user credentials in an IAM Organizations hierarchy. The controls should also limit the impact in case these credentials have been compromised.

Which combination of controls should the security engineer propose? (Select THREE.)

A)

Apply the following SCP:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "GRRESTRICTROOTUSER",
      "Effect": "Deny",
      "Action": "*",
      "Resource": [
        "*"
      ],
      "Condition": {
        "StringLike": {
          "aws:PrincipalArn": [
            "arn:aws:iam::*:root"
          ]
        }
      }
    }
  ]
}
```

B)

Apply the following SCP:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "GRRESTRICTROOTUSER",
      "Effect": "Deny",
      "Principal": "arn:aws:iam::*:root",
      "Action": "*",
      "Resource": [
        "*"
      ]
    }
  ]
}
```

C) Enable multi-factor authentication (MFA) for the root user.

D) Set a strong randomized password and store it in a secure location.

E) Create an access key ID and secret access key, and store them in a secure location.

F) Apply the following permissions boundary to the root user:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "GRRESTRICTROOTUSER",
      "Effect": "Deny",
      "Action": "*",
      "Resource": [
        "*"
      ],
      "Condition": {
        "StringLike": {
          "aws:PrincipalArn": [
            "arn:aws:iam::*:root"
          ]
        }
      }
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

- E. Option E
- F. Option F

Answer: ACE

NEW QUESTION 15

A Security Engineer is troubleshooting an issue with a company's custom logging application. The application logs are written to an Amazon S3 bucket with event notifications enabled to send events to an Amazon SNS topic. All logs are encrypted at rest using an IAM KMS CMK. The SNS topic is subscribed to an encrypted Amazon SQS queue. The logging application polls the queue for new messages that contain metadata about the S3 object. The application then reads the content of the object from the S3 bucket for indexing.

The Logging team reported that Amazon CloudWatch metrics for the number of messages sent or received is showing zero. No logs are being received.

What should the Security Engineer do to troubleshoot this issue?

A) Add the following statement to the IAM managed CMKs:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": ["sns.amazonaws.com", "sqs.amazonaws.com", "s3.amazonaws.com"]
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

B)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "sns.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

C)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "sqs.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

D)

Add the following statement to the CMK key policy:

```
{
  "Sid": "Allow Amazon SNS to use this key",
  "Effect": "Allow",
  "Principal": {
    "Service": "s3.amazonaws.com"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey*"
  ],
  "Resource": "*"
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 16

A Security Engineer is building a Java application that is running on Amazon EC2. The application communicates with an Amazon RDS instance and authenticates with a user name and password.

Which combination of steps can the Engineer take to protect the credentials and minimize downtime when the credentials are rotated? (Choose two.)

- A. Have a Database Administrator encrypt the credentials and store the ciphertext in Amazon S3. Grant permission to the instance role associated with the EC2 instance to read the object and decrypt the ciphertext.
- B. Configure a scheduled job that updates the credential in AWS Systems Manager Parameter Store and notifies the Engineer that the application needs to be restarted.
- C. Configure automatic rotation of credentials in AWS Secrets Manager.
- D. Store the credential in an encrypted string parameter in AWS Systems Manager Parameter Store.
- E. Grant permission to the instance role associated with the EC2 instance to access the parameter and the AWS KMS key that is used to encrypt it.
- F. Configure the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials when the password is rotated.
- G. Grant permission to the instance role associated with the EC2 instance to access Secrets Manager.

Answer: CE

Explanation:

AWS Secrets Manager is a service that helps you manage, retrieve, and rotate secrets such as database credentials, API keys, and other sensitive information. By configuring automatic rotation of credentials in AWS Secrets Manager, you can ensure that your secrets are changed regularly and securely, without requiring manual intervention or application downtime. You can also specify the rotation frequency and the rotation function that performs the logic of changing the credentials on the database and updating the secret in Secrets Manager¹.

* E. Configure the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials when the password is rotated. Grant permission to the instance role associated with the EC2 instance to access Secrets Manager.

By configuring the Java application to catch a connection failure and make a call to AWS Secrets Manager to retrieve updated credentials, you can avoid hard-coding the credentials in your application code or configuration files. This way, your application can dynamically obtain the latest credentials from Secrets Manager whenever the password is rotated, without needing to restart or redeploy the application. To enable this, you need to grant permission to the instance role associated with the EC2 instance to access Secrets Manager using IAM policies². You can also use the AWS SDK for Java to integrate your application with Secrets Manager³.

NEW QUESTION 20

A company needs a security engineer to implement a scalable solution for multi-account authentication and authorization. The solution should not introduce additional user-managed architectural components. Native IAM features should be used as much as possible. The security engineer has set up IAM Organizations with all features activated and IAM SSO enabled.

Which additional steps should the security engineer take to complete the task?

- A. Use AD Connector to create users and groups for all employees that require access to IAM accounts. Assign AD Connector groups to IAM accounts and link to the IAM roles in accordance with the employees' job functions and access requirements. Instruct employees to access IAM accounts by using the IAM Directory Service user portal.
- B. Use an IAM SSO default directory to create users and groups for all employees that require access to IAM accounts.
- C. Assign groups to IAM accounts and link to permission sets in accordance with the employees' job functions and access requirements.
- D. Instruct employees to access IAM accounts by using the IAM SSO user portal.
- E. Use an IAM SSO default directory to create users and groups for all employees that require access to IAM accounts.
- F. Link IAM SSO groups to the IAM users present in all accounts to inherit existing permissions.
- G. Instruct employees to access IAM accounts by using the IAM SSO user portal.
- H. Use IAM Directory Service for Microsoft Active Directory to create users and groups for all employees that require access to IAM accounts. Enable IAM Management Console access in the created directory and specify IAM SSO as a source of information for integrated accounts and permission sets.
- I. Instruct employees to access IAM accounts by using the IAM Directory Service user portal.

Answer: B

NEW QUESTION 21

A company purchased a subscription to a third-party cloud security scanning solution that integrates with AWS Security Hub. A security engineer needs to implement a solution that will remediate the findings

from the third-party scanning solution automatically. Which solution will meet this requirement?

- A. Set up an Amazon EventBridge rule that reacts to new Security Hub findings.
- B. Configure an AWS Lambda function as the target for the rule to remediate the findings.
- C. Set up a custom action in Security Hub.
- D. Configure the custom action to call AWS Systems Manager Automation runbooks to remediate the findings.
- E. Set up a custom action in Security Hub.
- F. Configure an AWS Lambda function as the target for the custom action to remediate the findings.
- G. Set up AWS Config rules to use AWS Systems Manager Automation runbooks to remediate the findings.

Answer: A

NEW QUESTION 22

A business requires a forensic logging solution for hundreds of Docker-based apps running on Amazon EC2. The solution must analyze logs in real time, provide message replay, and persist logs.

Which Amazon Web Services (AWS) services should be employed to satisfy these requirements? (Select two.)

- A. Amazon Athena
- B. Amazon Kinesis
- C. Amazon SQS
- D. Amazon Elasticsearch
- E. Amazon EMR

Answer: BD

NEW QUESTION 27

What are the MOST secure ways to protect the AWS account root user of a recently opened AWS account? (Select TWO.)

- A. Use the AWS account root user access keys instead of the AWS Management Console.
- B. Enable multi-factor authentication for the AWS IAM users with the Adminis-tratorAccess managed policy attached to them.
- C. Enable multi-factor authentication for the AWS account root user.
- D. Use AWS KMS to encrypt all AWS account root user and AWS IAM access keys and set automatic rotation to 30 days.
- E. Do not create access keys for the AWS account root user; instead, create AWS IAM users.

Answer: CE

NEW QUESTION 29

A company's public Application Load Balancer (ALB) recently experienced a DDoS attack. To mitigate this issue, the company deployed Amazon CloudFront in front of the ALB so that users would not directly access the Amazon EC2 instances behind the ALB.

The company discovers that some traffic is still coming directly into the ALB and is still being handled by the EC2 instances.

Which combination of steps should the company take to ensure that the EC2 instances will receive traffic only from CloudFront? (Choose two.)

- A. Configure CloudFront to add a cache key policy to allow a custom HTTP header that CloudFront sends to the ALB.
- B. Configure CloudFront to add a custom: HTTP header to requests that CloudFront sends to the ALB.
- C. Configure the ALB to forward only requests that contain the custom HTTP header.
- D. Configure the ALB and CloudFront to use the X-Forwarded-For header to check client IP addresses.
- E. Configure the ALB and CloudFront to use the same X.509 certificate that is generated by AWS Certificate Manager (ACM).

Answer: BC

Explanation:

To prevent users from directly accessing an Application Load Balancer and allow access only through CloudFront, complete these high-level steps: Configure CloudFront to add a custom HTTP header to requests that it sends to the Application Load Balancer. Configure the Application Load Balancer to only forward requests that contain the custom HTTP header. (Optional) Require HTTPS to improve the security of this solution.

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/restrict-access-to-load-balancer.html>

NEW QUESTION 32

A company accidentally deleted the private key for an Amazon Elastic Block Store (Amazon EBS)-backed Amazon EC2 instance. A security engineer needs to regain access to the instance.

Which combination of steps will meet this requirement? (Choose two.)

- A. Stop the instanc
- B. Detach the root volum
- C. Generate a new key pair.
- D. Keep the instance runnin
- E. Detach the root volum
- F. Generate a new key pair.
- G. When the volume is detached from the original instance, attach the volume to another instance as a data volum
- H. Modify the authorized_keys file with a new public ke
- I. Move the volume back to the original instanc
- J. Start the instance.
- K. When the volume is detached from the original instance, attach the volume to another instance as a data volum
- L. Modify the authorized_keys file with a new private ke
- M. Move the volume back to the original instanc
- N. Start the instance.
- O. When the volume is detached from the original instance, attach the volume to another instance as a data volum
- P. Modify the authorized_keys file with a new public ke
- Q. Move the volume back to the original instance that is running.

Answer: AC

Explanation:

If you lose the private key for an EBS-backed instance, you can regain access to your instance. You must stop the instance, detach its root volume and attach it to another instance as a data volume, modify the authorized_keys file with a new public key, move the volume back to the original instance, and restart the instance.

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/TroubleshootingInstancesConnecting.html#replacing>

NEW QUESTION 37

A company needs to follow security best practices to deploy resources from an AWS CloudFormation template. The CloudFormation template must be able to configure sensitive database credentials.

The company already uses AWS Key Management Service (AWS KMS) and AWS Secrets Manager. Which solution will meet the requirements?

- A. Use a dynamic reference in the CloudFormation template to reference the database credentials in Secrets Manager.
- B. Use a parameter in the CloudFormation template to reference the database credential
- C. Encrypt the CloudFormation template by using AWS KMS.
- D. Use a SecureString parameter in the CloudFormation template to reference the database credentials in Secrets Manager.
- E. Use a SecureString parameter in the CloudFormation template to reference an encrypted value in AWS KMS

Answer: A

Explanation:

➤ Option A: This option meets the requirements of following security best practices and configuring sensitive database credentials in the CloudFormation template. A dynamic reference is a way to specify external values that are stored and managed in other services, such as Secrets Manager, in the stack templates¹. When using a dynamic reference, CloudFormation retrieves the value of the specified reference when necessary during stack and change set operations¹. Dynamic references can be used for certain resources that support them, such as AWS::RDS::DBInstance¹. By using a dynamic reference to

reference the database credentials in Secrets Manager, the company can leverage the existing integration between these services and avoid hardcoding the secret information in the template. Secrets Manager is a service that helps you protect secrets needed to access your applications, services, and IT resources². Secrets Manager enables you to rotate, manage, and retrieve database credentials, API keys, and other secrets throughout their lifecycle².

NEW QUESTION 39

A company has hundreds of AWS accounts in an organization in AWS Organizations. The company operates out of a single AWS Region. The company has a dedicated security tooling AWS account in the organization. The security tooling account is configured as the organization's delegated administrator for Amazon GuardDuty and AWS Security Hub. The company has configured the environment to automatically enable GuardDuty and Security Hub for existing AWS accounts and new AWS accounts.

The company is performing control tests on specific GuardDuty findings to make sure that the company's security team can detect and respond to security events. The security team launched an Amazon EC2 instance and attempted to run DNS requests against a test domain, example.com, to generate a DNS finding.

However, the GuardDuty finding was never created in the Security Hub delegated administrator account.

Why was the finding was not created in the Security Hub delegated administrator account?

- A. VPC flow logs were not turned on for the VPC where the EC2 instance was launched.
- B. The VPC where the EC2 instance was launched had the DHCP option configured for a custom OpenDNS resolver.
- C. The GuardDuty integration with Security Hub was never activated in the AWS account where the finding was generated.
- D. Cross-Region aggregation in Security Hub was not configured.

Answer: C

Explanation:

The correct answer is C. The GuardDuty integration with Security Hub was never activated in the AWS account where the finding was generated.

According to the AWS documentation¹, GuardDuty findings are automatically sent to Security Hub only if the GuardDuty integration with Security Hub is enabled in the same account and Region. This means that the security tooling account, which is the delegated administrator for both GuardDuty and Security Hub, must enable the GuardDuty integration with Security Hub in each member account and Region where GuardDuty is enabled. Otherwise, the findings from GuardDuty will not be visible in Security Hub.

The other options are incorrect because:

- VPC flow logs are not required for GuardDuty to generate DNS findings. GuardDuty uses VPC DNS logs, which are automatically enabled for all VPCs, to detect malicious or unauthorized DNS activity.
- The DHCP option configured for a custom OpenDNS resolver does not affect GuardDuty's ability to generate DNS findings. GuardDuty uses its own threat intelligence sources to identify malicious domains, regardless of the DNS resolver used by the EC2 instance.
- Cross-Region aggregation in Security Hub is not relevant for this scenario, because the company operates out of a single AWS Region. Cross-Region aggregation allows Security Hub to aggregate findings from multiple Regions into a single Region.

References:

1: Managing GuardDuty accounts with AWS Organizations : Amazon GuardDuty Findings : How Amazon GuardDuty Works : Cross-Region aggregation in AWS Security Hub

NEW QUESTION 44

A company is using Amazon Elastic Container Service (Amazon ECS) to deploy an application that deals with sensitive data. During a recent security audit, the company identified a security issue in which Amazon RDS credentials were stored with the application code in the company's source code repository.

A security engineer needs to develop a solution to ensure that database credentials are stored securely and rotated periodically. The credentials should be accessible to the application only. The engineer also needs to prevent database administrators from sharing database credentials as plaintext with other teammates. The solution must also minimize administrative overhead.

Which solution meets these requirements?

- A. Use the IAM Systems Manager Parameter Store to generate database credential.
- B. Use an IAM profile for ECS tasks to restrict access to database credentials to specific containers only.
- C. Use IAM Secrets Manager to store database credential.
- D. Use an IAM inline policy for ECS tasks to restrict access to database credentials to specific containers only.
- E. Use the IAM Systems Manager Parameter Store to store database credential.
- F. Use IAM roles for ECS tasks to restrict access to database credentials to specific containers only.
- G. Use IAM Secrets Manager to store database credential.
- H. Use IAM roles for ECS tasks to restrict access to database credentials to specific containers only.

Answer: D

Explanation:

To ensure that database credentials are stored securely and rotated periodically, the security engineer should do the following:

- Use AWS Secrets Manager to store database credentials. This allows the security engineer to encrypt and manage secrets centrally, and to configure automatic rotation schedules for them.
- Use IAM roles for ECS tasks to restrict access to database credentials to specific containers only. This allows the security engineer to grant fine-grained permissions to ECS tasks based on their roles, and to avoid sharing credentials as plaintext with other teammates.

NEW QUESTION 45

A security engineer is designing an IAM policy for a script that will use the AWS CLI. The script currently assumes an IAM role that is attached to three AWS managed IAM policies: AmazonEC2FullAccess, AmazonDynamoDBFullAccess, and AmazonVPCFullAccess.

The security engineer needs to construct a least privilege IAM policy that will replace the AWS managed IAM policies that are attached to this role.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. In AWS CloudTrail, create a trail for management event.
- B. Run the script with the existing AWS managed IAM policies.
- C. Use IAM Access Analyzer to generate a new IAM policy that is based on access activity in the trail.
- D. Replace the existing AWS managed IAM policies with the generated IAM policy for the role.
- E. Remove the existing AWS managed IAM policies from the role.
- F. Attach the IAM Access Analyzer Role Policy Generator to the role.
- G. Run the script.
- H. Return to IAM Access Analyzer and generate a least privilege IAM policy.

- I. Attach the new IAM policy to the role.
- J. Create an account analyzer in IAM Access Analyze
- K. Create an archive rule that has a filter that checks whether the PrincipalArn value matches the ARN of the rol
- L. Run the scrip
- M. Remove the existing AWS managed IAM poli-cies from the role.
- N. In AWS CloudTrail, create a trail for management event
- O. Remove the exist-ing AWS managed IAM policies from the rol
- P. Run the scrip
- Q. Find the au-thorization failure in the trail event that is associated with the scrip
- R. Create a new IAM policy that includes the action and resource that caused the authorization failur
- S. Repeat the process until the script succeed
- T. Attach the new IAM policy to the role.

Answer: A

NEW QUESTION 46

A security engineer needs to configure an Amazon S3 bucket policy to restrict access to an S3 bucket that is named DOC-EXAMPLE-BUCKET. The policy must allow access to only DOC-EXAMPLE-BUCKET from only the following endpoint: vpce-1a2b3c4d. The policy must deny all access to DOC-EXAMPLE-BUCKET if the specified endpoint is not used.

Which bucket policy statement meets these requirements?

A. A computer code with black text Description automatically generated

```
"Statement": [
  {
    "Sid": "Access-to-specific-VPCE-only",
    "Principal": "*",
    "Action": "s3:*",
    "Effect": "Allow",
    "Resource": ["arn:aws:s3:::DOC-EXAMPLE-BUCKET",
                "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"],
    "Condition": {
      "StringNotEquals": {
        "aws:sourceVpce": "vpce-1a2b3c4d"
      }
    }
  }
]
```

B. A computer code with black text Description automatically generated

```
"Statement": [
  {
    "Sid": "Access-to-specific-VPCE-only",
    "Principal": "*",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": ["arn:aws:s3:::DOC-EXAMPLE-BUCKET",
                "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"],
    "Condition": {
      "StringNotEquals": {
        "aws:sourceVpce": "vpce-1a2b3c4d"
      }
    }
  }
]
```

C. A computer code with black text Description automatically generated

```
"Statement": [
  {
    "Sid": "Access-to-specific-VPCE-only",
    "Principal": "*",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": ["arn:aws:s3:::DOC-EXAMPLE-BUCKET",
                "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"],
    "Condition": {
      "StringEquals": {
        "aws:sourceVpce": "vpce-1a2b3c4d"
      }
    }
  }
]
```

D. A computer code with black text Description automatically generated

```

"Statement": [
  {
    "Sid": "Access-to-specific-VPCE-only",
    "Principal": "*",
    "Action": "s3:*",
    "Effect": "Allow",
    "Resource": ["arn:aws:s3::DOC-EXAMPLE-BUCKET",
      "arn:aws:s3::DOC-EXAMPLE-BUCKET/*"],
    "Condition": {
      "StringEquals": {
        "aws:sourceVpce": "vpce-la2b3c4d"
      }
    }
  }
]

```

Answer: B

Explanation:

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/example-bucket-policies-vpc-endpoint.html>

NEW QUESTION 47

A company uses Amazon API Gateway to present REST APIs to users. An API developer wants to analyze API access patterns without the need to parse the log files.

Which combination of steps will meet these requirements with the LEAST effort? (Select TWO.)

- A. Configure access logging for the required API stage.
- B. Configure an AWS CloudTrail trail destination for API Gateway event
- C. Configure filters on the userIdentity, userAgent, and sourceIPAddress fields.
- D. Configure an Amazon S3 destination for API Gateway log
- E. Run Amazon Athena queries to analyze API access information.
- F. Use Amazon CloudWatch Logs Insights to analyze API access information.
- G. Select the Enable Detailed CloudWatch Metrics option on the required API stage.

Answer: CD

NEW QUESTION 49

A company has launched an Amazon EC2 instance with an Amazon Elastic Block Store (Amazon EBS) volume in the us-east-1 Region. The volume is encrypted with an AWS Key Management Service (AWS KMS) customer managed key that the company's security team created. The security team has created an IAM key policy and has assigned the policy to the key. The security team has also created an IAM instance profile and has assigned the profile to the instance. The EC2 instance will not start and transitions from the pending state to the shutting-down state to the terminated state.

Which combination of steps should a security engineer take to troubleshoot this issue? (Select TWO.)

- A. Verify that the KMS key policy specifies a deny statement that prevents access to the key by using the aws:SourceIP condition key. Check that the range includes the EC2 instance IP address that is associated with the EBS volume.
- B. Verify that the KMS key that is associated with the EBS volume is set to the Symmetric key type.
- C. Verify that the KMS key that is associated with the EBS volume is in the Enabled state.
- D. Verify that the EC2 role that is associated with the instance profile has the correct IAM instance policy to launch an EC2 instance with the EBS volume.
- E. Verify that the key that is associated with the EBS volume has not expired and needs to be rotated.

Answer: CD

Explanation:

To troubleshoot the issue of an EC2 instance failing to start and transitioning to a terminated state when it has an EBS volume encrypted with an AWS KMS customer managed key, a security engineer should take the following steps:

* C. Verify that the KMS key that is associated with the EBS volume is in the Enabled state. If the key is not enabled, it will not function properly and could cause the EC2 instance to fail.

* D. Verify that the EC2 role that is associated with the instance profile has the correct IAM instance policy to launch an EC2 instance with the EBS volume. If the instance does not have the necessary permissions, it may not be able to mount the volume and could cause the instance to fail.

Therefore, options C and D are the correct answers.

NEW QUESTION 54

A company maintains an open-source application that is hosted on a public GitHub repository. While creating a new commit to the repository, an engineer uploaded their IAM access key and secret access key. The engineer reported the mistake to a manager, and the manager immediately disabled the access key. The company needs to assess the impact of the exposed access key. A security engineer must recommend a solution that requires the least possible managerial overhead.

Which solution meets these requirements?

- A. Analyze an IAM Identity and Access Management (IAM) use report from IAM Trusted Advisor to see when the access key was last used.
- B. Analyze Amazon CloudWatch Logs for activity by searching for the access key.
- C. Analyze VPC flow logs for activity by searching for the access key.
- D. Analyze a credential report in IAM Identity and Access Management (IAM) to see when the access key was last used.

Answer: A

Explanation:

To assess the impact of the exposed access key, the security engineer should recommend the following solution:

- Analyze an IAM use report from AWS Trusted Advisor to see when the access key was last used. This allows the security engineer to use a tool that provides

information about IAM entities and credentials in their account, and check if there was any unauthorized activity with the exposed access key.

NEW QUESTION 56

A security engineer needs to run an AWS CloudFormation script. The CloudFormation script builds AWS infrastructure to support a stack that includes web servers and a MySQL database. The stack has been deployed in pre-production environments and is ready for production.

The production script must comply with the principle of least privilege. Additionally, separation of duties must exist between the security engineer's IAM account and CloudFormation.

Which solution will meet these requirements?

- A. Use IAM Access Analyzer policy generation to generate a policy that allows the CloudFormation script to run and manage the stack.
- B. Attach the policy to a new IAM role.
- C. Modify the security engineer's IAM permissions to be able to pass the new role to CloudFormation.
- D. Create an IAM policy that allows `ec2:*` and `rds:*` permission.
- E. Attach the policy to a new IAM role. Modify the security engineer's IAM permissions to be able to assume the new role.
- F. Use IAM Access Analyzer policy generation to generate a policy that allows the CloudFormation script to run and manage the stack.
- G. Modify the security engineer's IAM permissions to be able to run the CloudFormation script.
- H. Create an IAM policy that allows `ec2:*` and `rds:*` permission.
- I. Attach the policy to a new IAM role.
- J. Use the IAM policy simulator to confirm that the policy allows the AWS API calls that are necessary to build the stack.
- K. Modify the security engineer's IAM permissions to be able to pass the new role to CloudFormation.

Answer: A

Explanation:

The correct answer is A. Use IAM Access Analyzer policy generation to generate a policy that allows the CloudFormation script to run and manage the stack. Attach the policy to a new IAM role. Modify the security engineer's IAM permissions to be able to pass the new role to CloudFormation.

According to the AWS documentation, IAM Access Analyzer is a service that helps you identify the resources in your organization and accounts, such as Amazon S3 buckets or IAM roles, that are shared with an external entity. You can also use IAM Access Analyzer to generate fine-grained policies that grant least privilege access based on access activity and access attempts.

To use IAM Access Analyzer policy generation, you need to enable IAM Access Analyzer in your account or organization. You can then use the IAM console or the AWS CLI to generate a policy for a resource based on its access activity or access attempts. You can review and edit the generated policy before applying it to the resource.

To use IAM Access Analyzer policy generation with CloudFormation, you can follow these steps:

- > Run the CloudFormation script in a pre-production environment and monitor its access activity or access attempts using IAM Access Analyzer.
- > Use IAM Access Analyzer policy generation to generate a policy that allows the CloudFormation script to run and manage the stack. The policy will include only the permissions that are necessary for the script to function.
- > Attach the policy to a new IAM role that has a trust relationship with CloudFormation. This will allow CloudFormation to assume the role and execute the script.
- > Modify the security engineer's IAM permissions to be able to pass the new role to CloudFormation.

This will allow the security engineer to launch the stack using the role.

- > Run the CloudFormation script in the production environment using the new role.

This solution will meet the requirements of least privilege and separation of duties, as it will limit the permissions of both CloudFormation and the security engineer to only what is needed for running and managing the stack.

Option B is incorrect because creating an IAM policy that allows `ec2:*` and `rds:*` permissions is not following the principle of least privilege, as it will grant more permissions than necessary for running and managing the stack. Moreover, modifying the security engineer's IAM permissions to be able to assume the new role is not ensuring separation of duties, as it will allow the security engineer to bypass CloudFormation and directly access the resources.

Option C is incorrect because modifying the security engineer's IAM permissions to be able to run the CloudFormation script is not ensuring separation of duties, as it will allow the security engineer to execute the script without using CloudFormation.

Option D is incorrect because creating an IAM policy that allows `ec2:*` and `rds:*` permissions is not following the principle of least privilege, as it will grant more permissions than necessary for running and managing the stack. Using the IAM policy simulator to confirm that the policy allows the AWS API calls that are necessary to build the stack is not sufficient, as it will not generate a fine-grained policy based on access activity or access attempts.

NEW QUESTION 57

A developer is building a serverless application hosted on IAM that uses Amazon Redshift in a data store. The application has separate modules for read/write and read-only functionality. The modules need their own database users for compliance reasons.

Which combination of steps should a security engineer implement to grant appropriate access? (Select TWO)

- A. Configure cluster security groups for each application module to control access to database users that are required for read-only and read/write.
- B. Configure a VPC endpoint for Amazon Redshift. Configure an endpoint policy that maps database users to each application module, and allow access to the tables that are required for read-only and read/write.
- C. Configure an IAM policy for each module. Specify the ARN of an Amazon Redshift database user that allows the `GetClusterCredentials` API call.
- D. Create local database users for each module.
- E. Configure an IAM policy for each module. Specify the ARN of an IAM user that allows the `GetClusterCredentials` API call.

Answer: CD

Explanation:

To grant appropriate access to the application modules, the security engineer should do the following:

- > Configure an IAM policy for each module. Specify the ARN of an Amazon Redshift database user that allows the `GetClusterCredentials` API call. This allows the application modules to use temporary credentials to access the database with the permissions of the specified user.
- > Create local database users for each module. This allows the security engineer to create separate users for read/write and read-only functionality, and to assign them different privileges on the database tables.

NEW QUESTION 61

A company has a guideline that mandates the encryption of all Amazon S3 bucket data in transit. A security engineer must implement an S3 bucket policy that denies any S3 operations if data is not encrypted.

Which S3 bucket policy will meet this requirement?

```
A. {
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowSSLRequestOnly",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": [
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET",
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    ],
    "Condition": {
      "Bool": {
        "aws:SecureTransport": "true"
      }
    },
    "Principal": "*"
  }]
}
```

```
B. {
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowSSLRequestOnly",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": [
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET",
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    ],
    "Condition": {
      "Bool": {
        "aws:SecureTransport": "false"
      }
    },
    "Principal": "*"
  }]
}
```

```
C. {
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowSSLRequestOnly",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": [
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET",
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    ],
    "Condition": {
      "StringNotEquals": {
        "s3:x-amz-server-side-encryption": "AES256"
      }
    },
    "Principal": "*"
  }]
}
```

D. A screenshot of a computer code Description automatically generated {

```

  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowSSLRequestOnly",
    "Action": "s3:*",
    "Effect": "Deny",
    "Resource": [
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET",
      "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    ],
    "Condition": {
      "StringNotEquals": {
        "s3:x-amz-server-side-encryption": true
      }
    },
    "Principal": "*"
  }]
}
```

Answer: B

Explanation:

<https://aws.amazon.com/blogs/security/how-to-use-bucket-policies-and-apply-defense-in-depth-to-help-secure-y>

NEW QUESTION 66

A company's security engineer is designing an isolation procedure for Amazon EC2 instances as part of an incident response plan. The security engineer needs to isolate a target instance to block any traffic to and from the target instance, except for traffic from the company's forensics team. Each of the company's EC2 instances has its own dedicated security group. The EC2 instances are deployed in subnets of a VPC. A subnet can contain multiple instances. The security engineer is testing the procedure for EC2 isolation and opens an SSH session to the target instance. The procedure starts to simulate access to the target instance by an attacker. The security engineer removes the existing security group rules and adds security group rules to give the forensics team access to the target instance on port 22.

After these changes, the security engineer notices that the SSH connection is still active and usable. When the security engineer runs a ping command to the public IP address of the target instance, the ping command is blocked.

What should the security engineer do to isolate the target instance?

- A. Add an inbound rule to the security group to allow traffic from 0.0.0.0/0 for all port
- B. Add an outbound rule to the security group to allow traffic to 0.0.0.0/0 for all port
- C. Then immediately delete these rules.
- D. Remove the port 22 security group rule
- E. Attach an instance role policy that allows AWS Systems Manager Session Manager connections so that the forensics team can access the target instance.
- F. Create a network ACL that is associated with the target instance's subnet
- G. Add a rule at the top of the inbound rule set to deny all traffic from 0.0.0.0/0. Add a rule at the top of the outbound rule set to deny all traffic to 0.0.0.0/0.
- H. Create an AWS Systems Manager document that adds a host-level firewall rule to block all inbound traffic and outbound traffic
- I. Run the document on the target instance.

Answer: C

NEW QUESTION 67

A company has implemented IAM WAF and Amazon CloudFront for an application. The application runs on Amazon EC2 instances that are part of an Auto Scaling group. The Auto Scaling group is behind an Application Load Balancer (ALB).

The IAM WAF web ACL uses an IAM Managed Rules rule group and is associated with the CloudFront distribution. CloudFront receives the request from IAM WAF and then uses the ALB as the distribution's origin.

During a security review, a security engineer discovers that the infrastructure is susceptible to a large, layer 7 DDoS attack.

How can the security engineer improve the security at the edge of the solution to defend against this type of attack?

- A. Configure the CloudFront distribution to use the Lambda@Edge feature
- B. Create an IAM Lambda function that imposes a rate limit on CloudFront viewer request
- C. Block the request if the rate limit is exceeded.
- D. Configure the IAM WAF web ACL so that the web ACL has more capacity units to process all IAM WAF rules faster.
- E. Configure IAM WAF with a rate-based rule that imposes a rate limit that automatically blocks requests when the rate limit is exceeded.
- F. Configure the CloudFront distribution to use IAM WAF as its origin instead of the ALB.

Answer: C

Explanation:

To improve the security at the edge of the solution to defend against a large, layer 7 DDoS attack, the security engineer should do the following:

- Configure AWS WAF with a rate-based rule that imposes a rate limit that automatically blocks requests when the rate limit is exceeded. This allows the security engineer to use a rule that tracks the number of requests from a single IP address and blocks subsequent requests if they exceed a specified threshold within a specified time period.

NEW QUESTION 70

A company became aware that one of its access keys was exposed on a code sharing website 11 days ago. A Security Engineer must review all use of the exposed access keys to determine the extent of the exposure. The company enabled IAM CloudTrail in all regions when it opened the account

Which of the following will allow the Security Engineer to complete the task?

- A. Filter the event history on the exposed access key in the CloudTrail console. Examine the data from the past 11 days.
- B. Use the IAM CLI to generate an IAM credential report. Extract all the data from the past 11 days.
- C. Use Amazon Athena to query the CloudTrail logs from Amazon S3. Retrieve the rows for the exposed access key for the past 11 days.
- D. Use the Access Advisor tab in the IAM console to view all of the access key activity for the past 11 days.

Answer: C

Explanation:

Amazon Athena is a service that enables you to analyze data in Amazon S3 using standard SQL. You can use Athena to query the CloudTrail logs that are stored in S3 and filter them by the exposed access key and the date range. The other options are not effective ways to review the use of the exposed access key.

NEW QUESTION 75

A company is evaluating the use of AWS Systems Manager Session Manager to grant access to the company's Amazon EC2 instances. However, until the company implements the change, the company must protect the key file for the EC2 instances from read and write operations by any other users.

When a security administrator tries to connect to a critical EC2 Linux instance during an emergency, the security administrator receives the following error. "Error: Unprotected private key file - Permissions for 'ssh/my_private_key.pem' are too open".

Which command should the security administrator use to modify the private key file permissions to resolve this error?

- A. `chmod 0040 ssh/my_private_key.pem`
- B. `chmod 0400 ssh/my_private_key.pem`
- C. `chmod 0004 ssh/my_private_key.pem`
- D. `chmod 0777 ssh/my_private_key.pem`

Answer: B

Explanation:

The error message indicates that the private key file permissions are too open, meaning that other users can read or write to the file. This is a security risk, as the

private key should be accessible only by the owner of the file. To fix this error, the security administrator should use the chmod command to change the permissions of the private key file to 0400, which means that only the owner can read the file and no one else can read or write to it.

The chmod command takes a numeric argument that represents the permissions for the owner, group, and others in octal notation. Each digit corresponds to a set of permissions: read (4), write (2), and execute (1). The digits are added together to get the final permissions for each category. For example, 0400 means that the owner has read permission (4) and no other permissions (0), and the group and others have no permissions at all (0).

The other options are incorrect because they either do not change the permissions at all (D), or they give too much or too little permissions to the owner, group, or others (A, C).

Verified References:

- <https://superuser.com/questions/215504/permissions-on-private-key-in-ssh-folder>
- <https://www.baeldung.com/linux/ssh-key-permissions>

NEW QUESTION 77

You have an S3 bucket defined in IAM. You want to ensure that you encrypt the data before sending it across the wire. What is the best way to achieve this. Please select:

- A. Enable server side encryption for the S3 bucket
- B. This request will ensure that the data is encrypted first.
- C. Use the IAM Encryption CLI to encrypt the data first
- D. Use a Lambda function to encrypt the data before sending it to the S3 bucket.
- E. Enable client encryption for the bucket

Answer: B

Explanation:

One can use the IAM Encryption CLI to encrypt the data before sending it across to the S3 bucket. Options A and C are invalid because this would still mean that data is transferred in plain text. Option D is invalid because you cannot just enable client side encryption for the S3 bucket. For more information on Encrypting and Decrypting data, please visit the below URL:

<https://IAM.amazonaws.com/blogs/security/how-to-encrypt-and-decrypt-your-data-with-the-IAM-encryption-cli> The correct answer is: Use the IAM Encryption CLI to encrypt the data first. Submit your Feedback/Queries to our Experts

NEW QUESTION 78

A company needs to retain log data archives for several years to be compliant with regulations. The log data is no longer used but it must be retained. What is the MOST secure and cost-effective solution to meet these requirements?

- A. Archive the data to Amazon S3 and apply a restrictive bucket policy to deny the s3 DeleteObject API
- B. Archive the data to Amazon S3 Glacier and apply a Vault Lock policy
- C. Archive the data to Amazon S3 and replicate it to a second bucket in a second IAM Region. Choose the S3 Standard-Infrequent Access (S3 Standard-1A) storage class and apply a restrictive bucket policy to deny the s3 DeleteObject API
- D. Migrate the log data to a 16 TB Amazon Elastic Block Store (Amazon EBS) volume. Create a snapshot of the EBS volume

Answer: B

Explanation:

To securely and cost-effectively retain log data archives for several years, the company should do the following:

- Archive the data to Amazon S3 Glacier and apply a Vault Lock policy. This allows the company to use a low-cost storage class that is designed for long-term archival of data that is rarely accessed. It also allows the company to enforce compliance controls on their S3 Glacier vault by locking a vault access policy that cannot be changed.

NEW QUESTION 83

A company is operating a website using Amazon CloudFront. CloudFront servers some content from Amazon S3 and other from web servers running EC2 instances behind an Application Load Balancer (ALB). Amazon DynamoDB is used as the data store. The company already uses IAM Certificate Manager (ACM) to store a public TLS certificate that can optionally secure connections between the website users and CloudFront. The company has a new requirement to enforce end-to-end encryption in transit.

Which combination of steps should the company take to meet this requirement? (Select THREE.)

- A. Update the CloudFront distribution
- B. configuring it to optionally use HTTPS when connecting to origins on Amazon S3
- C. Update the web application configuration on the web servers to use HTTPS instead of HTTP when connecting to DynamoDB
- D. Update the CloudFront distribution to redirect HTTP requests to HTTPS
- E. Configure the web servers on the EC2 instances to listen using HTTPS using the public ACM TLS certificate. Update the ALB to connect to the target group using HTTPS
- F. Update the ALB to listen using HTTPS using the public ACM TLS certificate
- G. Update the CloudFront distribution to connect to the HTTPS listener.
- H. Create a TLS certificate. Configure the web servers on the EC2 instances to use HTTPS only with that certificate
- I. Update the ALB to connect to the target group using HTTPS.

Answer: BCE

Explanation:

To enforce end-to-end encryption in transit, the company should do the following:

- Update the web application configuration on the web servers to use HTTPS instead of HTTP when connecting to DynamoDB. This ensures that the data is encrypted when it travels from the web servers to the data store.
- Update the CloudFront distribution to redirect HTTP requests to HTTPS. This ensures that the viewers always use HTTPS when they access the website through CloudFront.
- Update the ALB to listen using HTTPS using the public ACM TLS certificate. Update the CloudFront distribution to connect to the HTTPS listener. This ensures that the data is encrypted when it travels from CloudFront to the ALB and from the ALB to the web servers.

NEW QUESTION 88

A company is hosting multiple applications within a single VPC in its IAM account. The applications are running behind an Application Load Balancer that is associated with an IAM WAF web ACL. The company's security team has identified that multiple port scans are originating from a specific range of IP addresses on the internet.

A security engineer needs to deny access from the offending IP addresses. Which solution will meet these requirements?

- A. Modify the IAM WAF web ACL with an IP set match rule statement to deny incoming requests from the IP address range.
- B. Add a rule to all security groups to deny the incoming requests from the IP address range.
- C. Modify the IAM WAF web ACL with a rate-based rule statement to deny the incoming requests from the IP address range.
- D. Configure the IAM WAF web ACL with regex match condition
- E. Specify a pattern set to deny the incoming requests based on the match condition

Answer: A

Explanation:

Note that the IP is known and the question wants us to deny access from that particular address and so we can use IP set match policy of WAF to block access.

NEW QUESTION 92

A company that uses AWS Organizations is migrating workloads to AWS. The company's application team determines that the workloads will use Amazon EC2 instances, Amazon S3 buckets, Amazon DynamoDB tables, and Application Load Balancers. For each resource type, the company mandates that deployments must comply with the following requirements:

- All EC2 instances must be launched from approved AWS accounts.
- All DynamoDB tables must be provisioned with a standardized naming convention.
- All infrastructure that is provisioned in any accounts in the organization must be deployed by AWS CloudFormation templates.

Which combination of steps should the application team take to meet these requirements? (Select TWO.)

- A. Create CloudFormation templates in an administrator AWS account
- B. Share the stack sets with an application AWS account
- C. Restrict the template to be used specifically by the application AWS account.
- D. Create CloudFormation templates in an application AWS account
- E. Share the output with an administrator AWS account to review compliant resource
- F. Restrict output to only the administrator AWS account.
- G. Use permissions boundaries to prevent the application AWS account from provisioning specific resources unless conditions for the internal compliance requirements are met.
- H. Use SCPs to prevent the application AWS account from provisioning specific resources unless conditions for the internal compliance requirements are met.
- I. Activate AWS Config managed rules for each service in the application AWS account.

Answer: AD

NEW QUESTION 93

A company's Security Engineer has been tasked with restricting a contractor's IAM account access to the company's Amazon EC2 console without providing access to any other AWS services. The contractor's IAM account must not be able to gain access to any other AWS service, even if the IAM account is assigned additional permissions based on IAM group membership.

What should the Security Engineer do to meet these requirements?

- A. Create an Inline IAM user policy that allows for Amazon EC2 access for the contractor's IAM user.
- B. Create an IAM permissions boundary policy that allows Amazon EC2 access
- C. Associate the contractor's IAM account with the IAM permissions boundary policy.
- D. Create an IAM group with an attached policy that allows for Amazon EC2 access
- E. Associate the contractor's IAM account with the IAM group.
- F. Create an IAM role that allows for EC2 and explicitly denies all other service
- G. Instruct the contractor to always assume this role.

Answer: B

NEW QUESTION 96

A website currently runs on Amazon EC2, with mostly static content on the site. Recently the site was subjected to a DDoS attack a security engineer was asked to redesign the edge security to help

Mitigate this risk in the future.

What are some ways the engineer could achieve this (Select THREE)?

- A. Use IAM X-Ray to inspect the traffic going to the EC2 instances.
- B. Move the static content to Amazon S3, and front this with an Amazon CloudFront distribution.
- C. Change the security group configuration to block the source of the attack traffic
- D. Use IAM WAF security rules to inspect the inbound traffic.
- E. Use Amazon Inspector assessment templates to inspect the inbound traffic.
- F. Use Amazon Route 53 to distribute traffic.

Answer: BDF

Explanation:

To redesign the edge security to help mitigate the DDoS attack risk in the future, the engineer could do the following:

- Move the static content to Amazon S3, and front this with an Amazon CloudFront distribution. This allows the engineer to use a global content delivery network that can cache static content at edge locations and reduce the load on the origin servers.
- Use AWS WAF security rules to inspect the inbound traffic. This allows the engineer to use web application firewall rules that can filter malicious requests based on IP addresses, headers, body, or URI strings, and block them before they reach the web servers.
- Use Amazon Route 53 to distribute traffic. This allows the engineer to use a scalable and highly available DNS service that can route traffic based on different policies, such as latency, geolocation, or health checks.

NEW QUESTION 99

A company receives a notification from the AWS Abuse team about an AWS account. The notification indicates that a resource in the account is compromised. The company determines that the compromised resource is an Amazon EC2 instance that hosts a web application. The compromised EC2 instance is part of an EC2 Auto Scaling group.

The EC2 instance accesses Amazon S3 and Amazon DynamoDB resources by using an IAM access key and secret key. The IAM access key and secret key are stored inside the AMI that is specified in the Auto Scaling group's launch configuration. The company is concerned that the credentials that are stored in the AMI might also have been exposed.

The company must implement a solution that remediates the security concerns without causing downtime for the application. The solution must comply with security best practices. Which solution will meet these requirements?

- A. Rotate the potentially compromised access key that the EC2 instance uses. Create a new AMI without the potentially compromised credentials. Perform an EC2 Auto Scaling instance refresh.
- B. Delete or deactivate the potentially compromised access key. Create an EC2 Auto Scaling linked IAM role that includes a custom policy that matches the potentially compromised access key permission. Associate the new IAM role with the Auto Scaling group. Perform an EC2 Auto Scaling instance refresh.
- C. Delete or deactivate the potentially compromised access key. Create a new AMI without the potentially compromised credentials. Create an IAM role that includes the correct permissions. Create a launch template for the Auto Scaling group to reference the new AMI and IAM role. Perform an EC2 Auto Scaling instance refresh.
- D. Rotate the potentially compromised access key. Create a new AMI without the potentially compromised access key. Use a user data script to supply the new access key as environmental variables in the Auto Scaling group's launch configuration. Perform an EC2 Auto Scaling instance refresh.

Answer: C

Explanation:

The AWS documentation states that you can create a new AMI without the potentially compromised credentials and create an IAM role that includes the correct permissions. You can then create a launch template for the Auto Scaling group to reference the new AMI and IAM role. This method is the most secure way to remediate the security concerns without causing downtime for the application.

References: : AWS Security Best Practices

NEW QUESTION 104

A company is testing its incident response plan for compromised credentials. The company runs a database on an Amazon EC2 instance and stores the sensitive data-base credentials as a secret in AWS Secrets Manager. The secret has rotation configured with an AWS Lambda function that uses the generic rotation function template. The EC2 instance and the Lambda function are deployed in the same private subnet. The VPC has a Secrets Manager VPC endpoint.

A security engineer discovers that the secret cannot rotate. The security engineer determines that the VPC endpoint is working as intended. The Amazon CloudWatch logs contain the following error:

"setSecret: Unable to log into database". Which solution will resolve this error?

- A. Use the AWS Management Console to edit the JSON structure of the secret in Secrets Manager so that the secret automatically conforms with the structure that the database requires.
- B. Ensure that the security group that is attached to the Lambda function allows outbound connections to the EC2 instance.
- C. Ensure that the security group that is attached to the EC2 instance allows inbound connections from the security group that is attached to the Lambda function.
- D. Use the Secrets Manager list-secrets command in the AWS CLI to list the secrets.
- E. Identify the database credential.
- F. Use the Secrets Manager rotate-secret command in the AWS CLI to force the immediate rotation of the secret.
- G. Add an internet gateway to the VPC.
- H. Create a NAT gateway in a public subnet.
- I. Update the VPC route tables so that traffic from the Lambda function and traffic from the EC2 instance can reach the Secrets Manager public endpoint.

Answer: B

Explanation:

This answer is correct because ensuring that the security groups allow bidirectional communication between the Lambda function and the EC2 instance will resolve the error. The error indicates that the Lambda function cannot connect to the database, which might be due to firewall rules blocking the traffic. By allowing outbound connections from the Lambda function and inbound connections to the EC2 instance, the security engineer can enable the rotation function to access and update the database credentials.

NEW QUESTION 108

A company has contracted with a third party to audit several AWS accounts. To enable the audit, cross-account IAM roles have been created in each account targeted for audit. The Auditor is having trouble accessing some of the accounts.

Which of the following may be causing this problem? (Choose three.)

- A. The external ID used by the Auditor is missing or incorrect.
- B. The Auditor is using the incorrect password.
- C. The Auditor has not been granted sts:AssumeRole for the role in the destination account.
- D. The Amazon EC2 role used by the Auditor must be set to the destination account role.
- E. The secret key used by the Auditor is missing or incorrect.
- F. The role ARN used by the Auditor is missing or incorrect.

Answer: ACF

Explanation:

The following may be causing the problem for the Auditor:

- A. The external ID used by the Auditor is missing or incorrect. This is a possible cause, because the external ID is a unique identifier that is used to establish a trust relationship between the accounts. The external ID must match the one that is specified in the role's trust policy in the destination account1.
- C. The Auditor has not been granted sts:AssumeRole for the role in the destination account. This is a possible cause, because sts:AssumeRole is the API action that allows the Auditor to assume the cross-account role and obtain temporary credentials. The Auditor must have an IAM policy that allows them to call sts:AssumeRole for the role ARN in the destination account2.
- F. The role ARN used by the Auditor is missing or incorrect. This is a possible cause, because the role ARN is the Amazon Resource Name of the cross-account role that the Auditor wants to assume. The role ARN must be valid and exist in the destination account3.

NEW QUESTION 110

Example.com is hosted on Amazon EC2 instances behind an Application Load Balancer (ALB). Third-party host intrusion detection system (HIDS) agents that capture the traffic of the EC2 instance are running on each host. The company must ensure they are using privacy enhancing technologies for users, without losing the assurance the third-party solution offers.

What is the MOST secure way to meet these requirements?

- A. Enable TLS pass through on the ALB, and handle decryption at the server using Elliptic Curve Diffie-Hellman (ECDHE) cipher suites.
- B. Create a listener on the ALB that uses encrypted connections with Elliptic Curve Diffie-Hellman (ECDHE) cipher suites, and pass the traffic in the clear to the server.
- C. Create a listener on the ALB that uses encrypted connections with Elliptic Curve Diffie-Hellman (ECDHE) cipher suites, and use encrypted connections to the servers that do not enable Perfect Forward Secrecy (PFS).
- D. Create a listener on the ALB that does not enable Perfect Forward Secrecy (PFS) cipher suites, and use encrypted connections to the servers using Elliptic Curve Diffie-Hellman (ECDHE) cipher suites.

Answer: D

Explanation:

the most secure way to meet the requirements. TLS is a protocol that provides encryption and authentication for data in transit. ALB is a service that distributes incoming traffic across multiple EC2 instances. HIDS is a system that monitors and detects malicious activity on a host. ECDHE is a type of cipher suite that supports perfect forward secrecy, which is a property that ensures that past and current TLS traffic stays secure even if the certificate private key is leaked. By creating a listener on the ALB that does not enable PFS cipher suites, and using encrypted connections to the servers using ECDHE cipher suites, you can ensure that the HIDS agents can capture the traffic of the EC2 instance without compromising the privacy of the users. The other options are either less secure or less compatible with the third-party solution.

NEW QUESTION 115

A company uses AWS Signer with all of the company's AWS Lambda functions. A developer recently stopped working for the company. The company wants to ensure that all the code that the developer wrote can no longer be deployed to the Lambda functions.

Which solution will meet this requirement?

- A. Revoke all versions of the signing profile assigned to the developer.
- B. Examine the developer's IAM role
- C. Remove all permissions that grant access to Signer.
- D. Re-encrypt all source code with a new AWS Key Management Service (AWS KMS) key.
- E. Use Amazon CodeGuru to profile all the code that the Lambda functions use.

Answer: A

Explanation:

The correct answer is A. Revoke all versions of the signing profile assigned to the developer.

According to the AWS documentation¹, AWS Signer is a fully managed code-signing service that helps you ensure the trust and integrity of your code. You can use Signer to sign code artifacts, such as Lambda deployment packages, with code-signing certificates that you control and manage.

A signing profile is a collection of settings that Signer uses to sign your code artifacts. A signing profile includes information such as the following:

- The type of signature that you want to create (for example, a code-signing signature).
- The signing algorithm that you want Signer to use to sign your code.
- The code-signing certificate and its private key that you want Signer to use to sign your code.

You can create multiple versions of a signing profile, each with a different code-signing certificate. You can also revoke a version of a signing profile if you no longer want to use it for signing code artifacts.

In this case, the company wants to ensure that all the code that the developer wrote can no longer be deployed to the Lambda functions. One way to achieve this is to revoke all versions of the signing profile that was assigned to the developer. This will prevent Signer from using that signing profile to sign any new code artifacts, and also invalidate any existing signatures that were created with that signing profile. This way, the company can ensure that only trusted and authorized code can be deployed to the Lambda functions.

The other options are incorrect because:

- B. Examining the developer's IAM roles and removing all permissions that grant access to Signer may not be sufficient to prevent the deployment of the developer's code. The developer may have already signed some code artifacts with a valid signing profile before leaving the company, and those signatures may still be accepted by Lambda unless the signing profile is revoked.
- C. Re-encrypting all source code with a new AWS Key Management Service (AWS KMS) key may not be effective or practical. AWS KMS is a service that lets you create and manage encryption keys for your data. However, Lambda does not require encryption keys for deploying code artifacts, only valid signatures from Signer. Therefore, re-encrypting the source code may not prevent the deployment of the developer's code if it has already been signed with a valid signing profile. Moreover, re-encrypting all source code may be time-consuming and disruptive for other developers who are working on the same code base.
- D. Using Amazon CodeGuru to profile all the code that the Lambda functions use may not help with preventing the deployment of the developer's code. Amazon CodeGuru is a service that provides intelligent recommendations to improve your code quality and identify an application's most expensive lines of code. However, CodeGuru does not perform any security checks or validations on your code artifacts, nor does it interact with Signer or Lambda in any way. Therefore, using CodeGuru may not prevent unauthorized or untrusted code from being deployed to the Lambda functions.

References:

1: What is AWS Signer? - AWS Signer

NEW QUESTION 118

A company's application team needs to host a MySQL database on IAM. According to the company's security policy, all data that is stored on IAM must be encrypted at rest. In addition, all cryptographic material must be compliant with FIPS 140-2 Level 3 validation.

The application team needs a solution that satisfies the company's security requirements and minimizes operational overhead.

Which solution will meet these requirements?

- A. Host the database on Amazon RD
- B. Use Amazon Elastic Block Store (Amazon EBS) for encryption. Use an IAM Key Management Service (IAM KMS) custom key store that is backed by IAM CloudHSM for key management.
- C. Host the database on Amazon RD
- D. Use Amazon Elastic Block Store (Amazon EBS) for encryption. Use an IAM managed CMK in IAM Key Management Service (IAM KMS) for key management.
- E. Host the database on an Amazon EC2 instanc

- F. Use Amazon Elastic Block Store (Amazon EBS) for encryption
- G. Use a customer managed CMK in IAM Key Management Service (IAM KMS) for key management.
- H. Host the database on an Amazon EC2 instance
- I. Use Transparent Data Encryption (TDE) for encryption and key management.

Answer: B

NEW QUESTION 120

Your company uses IAM to host its resources. They have the following requirements

- 1) Record all API calls and Transitions
 - 2) Help in understanding what resources are there in the account
 - 3) Facility to allow auditing credentials and logins
- Which services would suffice the above requirements Please select:

- A. IAM Inspector, CloudTrail, IAM Credential Reports
- B. CloudTrail
- C. IAM Credential Reports, IAM SNS
- D. CloudTrail, IAM Config, IAM Credential Reports
- E. IAM SQS, IAM Credential Reports, CloudTrail

Answer: C

Explanation:

You can use IAM CloudTrail to get a history of IAM API calls and related events for your account. This history includes calls made with the IAM Management Console, IAM Command Line Interface, IAM SDKs, and other IAM services.

Options A,B and D are invalid because you need to ensure that you use the services of CloudTrail, IAM Config, IAM Credential Reports

For more information on Cloudtrail, please visit the below URL:

<http://docs.IAM.amazon.com/IAMcloudtrail/latest/userguide/cloudtrail-user-guide.html>

IAM Config is a service that enables you to assess, audit and evaluate the configurations of your IAM resources. Config continuously monitors and records your IAM resource configurations and allows you to automate the evaluation of recorded configurations against desired configurations. With Config, you can review changes in configurations and relationships between IAM resources, dive into detailed resource configuration histories, and determine your overall compliance against the configurations specified in your internal guidelines. This enables you to simplify compliance auditing, security analysis, change management and operational troubleshooting.

For more information on the config service, please visit the below URL <https://IAM.amazon.com/config/>

You can generate and download a credential report that lists all users in your account and the status of their various credentials, including passwords, access keys, and MFA devices. You can get a credential report from the IAM Management Console, the IAM SDKs and Command Line Tools, or the IAM API.

For more information on Credentials Report, please visit the below URL: http://docs.IAM.amazon.com/IAM/latest/UserGuide/id_credentials_getting-report.html

The correct answer is: CloudTrail, IAM Config, IAM Credential Reports Submit your Feedback/Queries to our Experts

NEW QUESTION 122

An ecommerce company has a web application architecture that runs primarily on containers. The application containers are deployed on Amazon Elastic Container Service (Amazon ECS). The container images for the application are stored in Amazon Elastic Container Registry (Amazon ECR).

The company's security team is performing an audit of components of the application architecture. The security team identifies issues with some container images that are stored in the container repositories.

The security team wants to address these issues by implementing continual scanning and on-push scanning of the container images. The security team needs to implement a solution that makes any findings from these scans visible in a centralized dashboard. The security team plans to use the dashboard to view these findings along with other security-related findings that they intend to generate in the future.

There are specific repositories that the security team needs to exclude from the scanning process. Which solution will meet these requirements?

- A. Use Amazon Inspector
- B. Create inclusion rules in Amazon ECR to match repositories that need to be scanned
- C. Push Amazon Inspector findings to AWS Security Hub.
- D. Use ECR basic scanning of container image
- E. Create inclusion rules in Amazon ECR to match repositories that need to be scanned
- F. Push findings to AWS Security Hub.
- G. Use ECR basic scanning of container image
- H. Create inclusion rules in Amazon ECR to match repositories that need to be scanned
- I. Push findings to Amazon Inspector.
- J. Use Amazon Inspector
- K. Create inclusion rules in Amazon Inspector to match repositories that need to be scanned
- L. Push Amazon Inspector findings to AWS Config.

Answer: A

NEW QUESTION 123

A company manages multiple IAM accounts using IAM Organizations. The company's security team notices that some member accounts are not sending IAM CloudTrail logs to a centralized Amazon S3 logging bucket. The security team wants to ensure there is at least one trail configured (or all existing accounts and for any account that is created in the future).

Which set of actions should the security team implement to accomplish this?

- A. Create a new trail and configure it to send CloudTrail logs to Amazon S3. Use Amazon EventBridge (Amazon CloudWatch Events) to send notification if a trail is deleted or stopped.
- B. Deploy an IAM Lambda function in every account to check if there is an existing trail and create a new trail, if needed.
- C. Edit the existing trail in the Organizations master account and apply it to the organization.
- D. Create an SCP to deny the cloudtrail:Delete and cloudtrail:Stop action
- E. Apply the SCP to all accounts.

Answer: C

Explanation:

Users in member accounts will not have sufficient permissions to delete the organization trail, turn logging on or off, change what types of events are logged, or otherwise alter the organization trail in any way. <https://docs.aws.amazon.com/awsccloudtrail/latest/userguide/creating-trail-organization.html>

NEW QUESTION 126

You work at a company that makes use of IAM resources. One of the key security policies is to ensure that all data is encrypted both at rest and in transit. Which of the following is one of the right ways to implement this.

Please select:

- A. Use S3 SSE and use SSL for data in transit
- B. SSL termination on the ELB
- C. Enabling Proxy Protocol
- D. Enabling sticky sessions on your load balancer

Answer: A

Explanation:

By disabling SSL termination, you are leaving an unsecure connection from the ELB to the back end instances. Hence this means that part of the data transit is not being encrypted.

Option B is incorrect because this would not guarantee complete encryption of data in transit Option C and D are incorrect because these would not guarantee encryption

For more information on SSL Listeners for your load balancer, please visit the below URL: <http://docs.IAM.amazon.com/elasticloadbalancing/latest/classic/elb-https-load-balancers.html> The correct answer is: Use S3 SSE and use SSL for data in transit

Submit your Feedback/Queries to our Experts

NEW QUESTION 128

A company has an AWS account that hosts a production application. The company receives an email notification that Amazon GuardDuty has detected an Impact:IAMUser/AnomalousBehavior finding in the account. A security engineer needs to run the investigation playbook for this security incident and must collect and analyze the information without affecting the application.

Which solution will meet these requirements MOST quickly?

- A. Log in to the AWS account by using read-only credential
- B. Review the GuardDuty finding for details about the IAM credentials that were used
- C. Use the IAM console to add a DenyAll policy to the IAM principal.
- D. Log in to the AWS account by using read-only credential
- E. Review the GuardDuty finding to determine which API calls initiated the finding
- F. Use Amazon Detective to review the API calls in context.
- G. Log in to the AWS account by using administrator credential
- H. Review the GuardDuty finding for details about the IAM credentials that were used
- I. Use the IAM console to add a DenyAll policy to the IAM principal.
- J. Log in to the AWS account by using read-only credential
- K. Review the GuardDuty finding to determine which API calls initiated the finding
- L. Use AWS CloudTrail Insights and AWS CloudTrail Lake to review the API calls in context.

Answer: B

Explanation:

This answer is correct because logging in with read-only credentials minimizes the risk of accidental or malicious changes to the AWS account. Reviewing the GuardDuty finding can help identify which API calls initiated the finding and which IAM principal was involved. Using Amazon Detective can help analyze and visualize the API calls in context, such as which resources were affected, which IP addresses were used, and how the activity deviated from normal patterns. Amazon Detective can also help identify related findings from other sources, such as AWS Config or AWS Audit Manager.

NEW QUESTION 129

A company has recently recovered from a security incident that required the restoration of Amazon EC2 instances from snapshots. The company uses an AWS Key

Management Service (AWS KMS) customer managed key to encrypt all Amazon Elastic Block Store (Amazon EBS) snapshots.

The company performs a gap analysis of its disaster recovery procedures and backup strategies. A security engineer needs to implement a solution so that the company can recover the EC2 instances if the AWS account is compromised and the EBS snapshots are deleted.

Which solution will meet this requirement?

- A. Create a new Amazon S3 bucket
- B. Use EBS lifecycle policies to move EBS snapshots to the new S3 bucket
- C. Use lifecycle policies to move snapshots to the S3 Glacier Instant Retrieval storage class
- D. Use S3 Object Lock to prevent deletion of the snapshots.
- E. Use AWS Systems Manager to distribute a configuration that backs up all attached disks to Amazon S3.
- F. Create a new AWS account that has limited privilege
- G. Allow the new account to access the KMS key that encrypts the EBS snapshot
- H. Copy the encrypted snapshots to the new account on a recurring basis.
- I. Use AWS Backup to copy EBS snapshots to Amazon S3. Use S3 Object Lock to prevent deletion of the snapshots.

Answer: C

Explanation:

This solution meets the requirement of recovering the EC2 instances if the AWS account is compromised and the EBS snapshots are deleted. By creating a new AWS account with limited privileges, the company can isolate the backup snapshots from the main account and reduce the risk of accidental or malicious deletion. By allowing the new account to access the KMS key that encrypts the EBS snapshots, the company can ensure that the snapshots are copied in an encrypted form and can be decrypted when needed. By copying the encrypted snapshots to the new account on a recurring basis, the company can maintain a consistent backup schedule and minimize data loss.

NEW QUESTION 132

A company is using AWS Organizations to create OUs for its accounts. The company has more than 20 accounts that are all part of the OUs. A security engineer must implement a solution to ensure that no account can stop file delivery to AWS CloudTrail. Which solution will meet this requirement?

- A. Use the --is-multi-region-trail option while running the create-trail command to ensure that logs are configured across all AWS Regions.
- B. Create an SCP that includes a Deny rule for the cloudtrail
- C. StopLogging action Apply the SCP to all accounts in the OUs.
- D. Create an SCP that includes an Allow rule for the cloudtrail
- E. StopLogging action Apply the SCP to all accounts in the OUs.
- F. Use AWS Systems Manager to ensure that CloudTrail is always turned on.

Answer: B

Explanation:

This SCP prevents users or roles in any affected account from disabling a CloudTrail log, either directly as a command or through the console.
https://asecure.cloud/a/scp_cloudtrail/

NEW QUESTION 137

A company has an organization in AWS Organizations. The company wants to use AWS CloudFormation StackSets in the organization to deploy various AWS design patterns into environments. These patterns consist of Amazon EC2 instances, Elastic Load Balancing (ELB) load balancers, Amazon RDS databases, and Amazon Elastic Kubernetes Service (Amazon EKS) clusters or Amazon Elastic Container Service (Amazon ECS) clusters. Currently, the company's developers can create their own CloudFormation stacks to increase the overall speed of delivery. A centralized CI/CD pipeline in a shared services AWS account deploys each CloudFormation stack. The company's security team has already provided requirements for each service in accordance with internal standards. If there are any resources that do not comply with the internal standards, the security team must receive notification to take appropriate action. The security team must implement a notification solution that gives developers the ability to maintain the same overall delivery speed that they currently have. Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an Amazon Simple Notification Service (Amazon SNS) topic
- B. Subscribe the security team's email addresses to the SNS topic
- C. Create a custom AWS Lambda function that will run the aws cloudformation validate-template AWS CLI command on all CloudFormation templates before the build stage in the CI/CD pipeline
- D. Configure the CI/CD pipeline to publish a notification to the SNS topic if any issues are found.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic
- F. Subscribe the security team's email addresses to the SNS topic
- G. Create custom rules in CloudFormation Guard for each resource configuration
- H. In the CI/CD pipeline, before the build stage, configure a Docker image to run the cfn-guard command on the CloudFormation template
- I. Configure the CI/CD pipeline to publish a notification to the SNS topic if any issues are found.
- J. Create an Amazon Simple Notification Service (Amazon SNS) topic and an Amazon Simple Queue Service (Amazon SQS) queue
- K. Subscribe the security team's email addresses to the SNS topic
- L. Create an Amazon S3 bucket in the shared services AWS account
- M. Include an event notification to publish to the SQS queue when new objects are added to the S3 bucket
- N. Require the developers to put their CloudFormation templates in the S3 bucket
- O. Launch EC2 instances that automatically scale based on the SQS queue depth
- P. Configure the EC2 instances to use CloudFormation Guard to scan the templates and deploy the templates if there are no issues
- Q. Configure the CI/CD pipeline to publish a notification to the SNS topic if any issues are found.
- R. Create a centralized CloudFormation stack set that includes a standard set of resources that the developers can deploy in each AWS account
- S. Configure each CloudFormation template to meet the security requirement
- T. For any new resources or configurations, update the CloudFormation template and send the template to the security team for review. When the review is completed, add the new CloudFormation stack to the repository for the developers to use.

Answer: B

NEW QUESTION 138

A company is hosting a static website on Amazon S3. The company has configured an Amazon CloudFront distribution to serve the website contents. The company has associated an IAM WAF web ACL with the CloudFront distribution. The web ACL ensures that requests originate from the United States to address compliance restrictions. The company is worried that the S3 URL might still be accessible directly and that requests can bypass the CloudFront distribution. Which combination of steps should the company take to remove direct access to the S3 URL? (Select TWO.)

- A. Select "Restrict Bucket Access" in the origin settings of the CloudFront distribution
- B. Create an origin access identity (OAI) for the S3 origin
- C. Update the S3 bucket policy to allow s3 GetObject with a condition that the IAM Referer key matches the secret value. Deny all other requests
- D. Configure the S3 bucket policy so that only the origin access identity (OAI) has read permission for objects in the bucket
- E. Add an origin custom header that has the name Referer to the CloudFront distribution. Give the header a secret value.

Answer: AD

NEW QUESTION 143

A company wants to establish separate IAM Key Management Service (IAM KMS) keys to use for different IAM services. The company's security engineer created the following key policy to allow the infrastructure deployment team to create encrypted Amazon Elastic Block Store (Amazon EBS) volumes by assuming the InfrastructureDeployment IAM role:

```
{
  "Version": "2012-10-17",
  "Id": "key-policy-eps",
  "Statement": [
    {
      "Sid": "Enable IAM User Permissions",
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::123456789012:root"
      },
      "Action": "kms:*",
      "Resource": "*"
    },
    {
      "Sid": "Allow use of the key",
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::123456789012:role/aws-reserved/sso.amazonaws.com/InfrastructureDeployment"
      },
      "Action": [
        "kms:Encrypt",
        "kms:Decrypt",
        "kms:ReEncrypt*",
        "kms:GenerateDataKey*",
        "kms:DescribeKey",
        "kms:CreateGrant",
        "kms:ListGrants",
        "kms:RevokeGrant"
      ],
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "kms:ViaService": "ec2.us-west-2.amazonaws.com"
        }
      }
    }
  ]
}
```

The security engineer recently discovered that IAM roles other than the InfrastructureDeployment role used this key (or other services). Which change to the policy should the security engineer make to resolve these issues?

- A. In the statement block that contains the Sid "Allow use of the key", under the "Condition" block, change StringEquals to StringLike.
- B. In the policy document, remove the statement block that contains the Sid "Enable IAM User Permissions". Add key management policies to the KMS policy.
- C. In the statement block that contains the Sid "Allow use of the Key", under the "Condition" block, change the Kms:ViaService value to ec2.us-east-1.amazonaws.com.
- D. In the policy document, add a new statement block that grants the kms:Disable' permission to the security engineer's IAM role.

Answer: C

Explanation:

To resolve the issues, the security engineer should make the following change to the policy:

- In the statement block that contains the Sid "Allow use of the key", under the "Condition" block, change the Kms:ViaService value to ec2.us-east-1.amazonaws.com. This allows the security engineer to restrict the use of the key to only EC2 service in the us-east-1 region, and prevent other services from using the key.

NEW QUESTION 145

An Application team has requested a new IAM KMS master key for use with Amazon S3, but the organizational security policy requires separate master keys for different IAM services to limit blast radius.

How can an IAM KMS customer master key (CMK) be constrained to work with only Amazon S3?

- A. Configure the CMK key policy to allow only the Amazon S3 service to use the kms Encrypt action
- B. Configure the CMK key policy to allow IAM KMS actions only when the kms ViaService condition matches the Amazon S3 service name.
- C. Configure the IAM user's policy to allow KMS to pass a role to Amazon S3
- D. Configure the IAM user's policy to allow only Amazon S3 operations when they are combined with the CMK

Answer: B

Explanation:

the kms:ViaService condition key can be used to restrict a CMK to work with only a specific AWS service. By configuring the CMK key policy to allow KMS actions only when the kms:ViaService condition matches the Amazon S3 service name, you can ensure that only Amazon S3 can use the CMK. The other options are either incorrect or insufficient for constraining a CMK to work with only Amazon S3.

NEW QUESTION 148

A company has a batch-processing system that uses Amazon S3, Amazon EC2, and AWS Key Management Service (AWS KMS). The system uses two AWS accounts: Account A and Account B.

Account A hosts an S3 bucket that stores the objects that will be processed. The S3 bucket also stores the results of the processing. All the S3 bucket objects are encrypted by a KMS key that is managed in Account A.

Account B hosts a VPC that has a fleet of EC2 instances that access the S3 bucket in Account A by using statements in the bucket policy. The VPC was created with DNS hostnames enabled and DNS resolution enabled.

A security engineer needs to update the design of the system without changing any of the system's code. No AWS API calls from the batch-processing EC2 instances can travel over the internet.

Which combination of steps will meet these requirements? (Select TWO.)

- A. In the Account B VPC, create a gateway VPC endpoint for Amazon S3. For the gateway VPC endpoint, create a resource policy that allows the s3:GetObject, s3:ListBucket, s3:PutObject, and s3:PutObjectAcl actions for the S3 bucket.
- B. In the Account B VPC, create an interface VPC endpoint for Amazon S3. For the interface VPC endpoint, create a resource policy that allows the s3:GetObject, s3:ListBucket, s3:PutObject, and s3:PutObjectAcl actions for the S3 bucket.
- C. In the Account B VPC, create an interface VPC endpoint for AWS KM
- D. For the interface VPC endpoint, create a resource policy that allows the kms:Encrypt, kms:Decrypt, and kms:GenerateDataKey actions for the KMS ke
- E. Ensure that private DNS is turned on for the endpoint.
- F. In the Account B VPC, create an interface VPC endpoint for AWS KM
- G. For the interface VPC endpoint, create a resource policy that allows the kms:Encrypt, kms:Decrypt, and kms:GenerateDataKey actions for the KMS ke
- H. Ensure that private DNS is turned off for the endpoint.
- I. In the Account B VPC, verify that the S3 bucket policy allows the s3:PutObjectAcl action for cross-account us
- J. In the Account B VPC, create a gateway VPC endpoint for Amazon S3. For the gateway VPC endpoint, create a resource policy that allows the s3:GetObject, s3:ListBucket, and s3:PutObject actions for the S3 bucket.

Answer: BC

NEW QUESTION 149

A company has an AWS Lambda function that creates image thumbnails from larger images. The Lambda function needs read and write access to an Amazon S3 bucket in the same AWS account.

Which solutions will provide the Lambda function this access? (Select TWO.)

- A. Create an IAM user that has only programmatic acces
- B. Create a new access key pai
- C. Add environmental variables to the Lambda function with the ac-cess key ID and secret access ke
- D. Modify the Lambda function to use the environmental variables at run time during communication with Amazon S3.
- E. Generate an Amazon EC2 key pai
- F. Store the private key in AWS Secrets Man-age
- G. Modify the Lambda function to retrieve the private key from Secrets Manager and to use the private key during communication with Amazon S3.
- H. Create an IAM role for the Lambda functio
- I. Attach an IAM policy that al-lows access to the S3 bucket.
- J. Create an IAM role for the Lambda functio
- K. Attach a bucket policy to the S3 bucket to allow access. Specify the function's IAM role as the princi-pal.
- L. Create a security grou
- M. Attach the security group to the Lambda functio
- N. Attach a bucket policy that allows access to the S3 bucket through the se-curity group ID.

Answer: CD

NEW QUESTION 153

A company has an organization in AWS Organizations that includes dedicated accounts for each of its business units. The company is collecting all AWS CloudTrail logs from the accounts in a single Amazon S3 bucket in the top-level account. The company's IT governance team has access to the top-level account. A security engineer needs to allow each business unit to access its own CloudTrail logs.

The security engineer creates an IAM role in the top-level account for each of the other accounts. For each role the security engineer creates an IAM policy to allow read-only permissions to objects in the S3 bucket with the prefix of the respective logs.

Which action must the security engineer take in each business unit account to allow an IAM user in that account to read the logs?

- A. Attach a policy to the IAM user to allow the user to assume the role that was created in the top-level accoun
- B. Specify the role's ARN in the policy.
- C. Create an SCP that grants permissions to the top-level account.
- D. Use the root account of the business unit account to assume the role that was created in the top-level accoun
- E. Specify the role's ARN in the policy.
- F. Forward the credentials of the IAM role in the top-level account to the IAM user in the business unit account.

Answer: A

Explanation:

To allow an IAM user in one AWS account to access resources in another AWS account using IAM roles, the following steps are required:

- Create a role in the AWS account that contains the resources (the trusting account) and specify the AWS account that contains the IAM user (the trusted account) as a trusted entity in the role's trust policy. This allows users from the trusted account to assume the role and access resources in the trusting account.
- Attach a policy to the IAM user in the trusted account that allows the user to assume the role in the trusting account. The policy must specify the ARN of the role that was created in the trusting account.
- The IAM user can then switch roles or use temporary credentials to access the resources in the trusting account.

Verified References:

- <https://repost.aws/knowledge-center/cross-account-access-iam>
- https://docs.aws.amazon.com/IAM/latest/UserGuide/tutorial_cross-account-with-roles.html

NEW QUESTION 155

There are currently multiple applications hosted in a VPC. During monitoring it has been noticed that multiple port scans are coming in from a specific IP Address block. The internal security team has requested that all offending IP Addresses be denied for the next 24 hours. Which of the following is the best method to quickly and temporarily deny access from the specified IP Address's.

Please select:

- A. Create an AD policy to modify the Windows Firewall settings on all hosts in the VPC to deny access from the IP Address block.
- B. Modify the Network ACLs associated with all public subnets in the VPC to deny access from the IP Address block.
- C. Add a rule to all of the VPC Security Groups to deny access from the IP Address block.
- D. Modify the Windows Firewall settings on all AMI'S that your organization uses in that VPC to deny access from the IP address block.

Answer: B

Explanation:

NACL acts as a firewall at the subnet level of the VPC and we can deny the offending IP address block at the subnet level using NACL rules to block the incoming traffic to the VPC instances. Since NACL rules are applied as per the Rule numbers make sure that this rule number should take precedence over other rule numbers if there are any such rules that will allow traffic from these IP ranges. The lowest rule number has more precedence over a rule that has a higher number. The IAM Documentation mentions the following as a best practices for IAM users

For extra security, enable multi-factor authentication (MFA) for privileged IAM users (users who are allowed access to sensitive resources or APIs). With MFA, users have a device that generates a unique authentication code (a one-time password, or OTP). Users must provide both their normal credentials (like their user name and password) and the OTP. The MFA device can either be a special piece of hardware, or it can be a virtual device (for example, it can run in an app on a smartphone).

Options C is invalid because these options are not available Option D is invalid because there is not root access for users

For more information on IAM best practices, please visit the below URL: <https://docs.IAM.amazon.com/IAM/latest/UserGuide/best-practices.html>

The correct answer is: Modify the Network ACLs associated with all public subnets in the VPC to deny access from the IP Address block.

omit your Feedback/Queries to our Experts

NEW QUESTION 156

A company is building a data processing application that uses AWS Lambda functions. The application's Lambda functions need to communicate with an Amazon RDS DB instance that is deployed within a VPC in the same AWS account

Which solution meets these requirements in the MOST secure way?

- A. Configure the DB instance to allow public access Update the DB instance security group to allow access from the Lambda public address space for the AWS Region
- B. Deploy the Lambda functions inside the VPC Attach a network ACL to the Lambda subnet Provide outbound rule access to the VPC CIDR range only Update the DB instance security group to allow traffic from 0.0.0.0/0
- C. Deploy the Lambda functions inside the VPC Attach a security group to the Lambda functions Provide outbound rule access to the VPC CIDR range only Update the DB instance security group to allow traffic from the Lambda security group
- D. Peer the Lambda default VPC with the VPC that hosts the DB instance to allow direct network access without the need for security groups

Answer: C

Explanation:

This solution ensures that the Lambda functions are deployed inside the VPC and can communicate with the Amazon RDS DB instance securely. The security group attached to the Lambda functions only allows

outbound traffic to the VPC CIDR range, and the DB instance security group only allows traffic from the Lambda security group. This solution ensures that the Lambda functions can communicate with the DB instance securely and that the DB instance is not exposed to the public internet.

NEW QUESTION 158

A company in France uses Amazon Cognito with the Cognito Hosted UI as an identity broker for sign-in and sign-up processes. The company is marketing an application and expects that all the application's users will come from France.

When the company launches the application the company's security team observes fraudulent sign-ups for the application. Most of the fraudulent registrations are from users outside of France.

The security team needs a solution to perform custom validation at sign-up Based on the results of the validation the solution must accept or deny the registration request.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Create a pre sign-up AWS Lambda trigger
- B. Associate the Amazon Cognito function with the Amazon Cognito user pool.
- C. Use a geographic match rule statement to configure an AWS WAF web ACL
- D. Associate the web ACL with the Amazon Cognito user pool.
- E. Configure an app client for the application's Amazon Cognito user pool
- F. Use the app client ID to validate the requests in the hosted UI.
- G. Update the application's Amazon Cognito user pool to configure a geographic restriction setting.
- H. Use Amazon Cognito to configure a social identity provider (IdP) to validate the requests on the hosted UI.

Answer: B

Explanation:

<https://docs.aws.amazon.com/cognito/latest/developerguide/user-pool-lambda-post-authentication.html>

NEW QUESTION 160

A company stores sensitive documents in Amazon S3 by using server-side encryption with an IAM Key Management Service (IAM KMS) CMK. A new requirement mandates that the CMK that is used for these documents can be used only for S3 actions.

Which statement should the company add to the key policy to meet this requirement?

A)

```
{
  "Effect": "Deny",
  "Principal": "*",
  "Action": "kms:*",
  "Resource": "*",
  "Condition": {
    "StringNotEquals": {
      "kms:CallerAccount": "s3.amazonaws.com"
    }
  }
}
```

B)

```
{
  "Effect": "Deny",
  "Principal": "*",
  "Action": "s3:*",
  "Resource": "*",
  "Condition": {
    "StringNotEquals": {
      "kms:ViaService": "kms.*amazonaws.com"
    }
  }
}
```

- A. Option A
- B. Option B

Answer: A

NEW QUESTION 163

A company's security team is building a solution for logging and visualization. The solution will assist the company with the large variety and velocity of data that it receives from IAM across multiple accounts. The security team has enabled IAM CloudTrail and VPC Flow Logs in all of its accounts. In addition, the company has an organization in IAM Organizations and has an IAM Security Hub master account.

The security team wants to use Amazon Detective. However, the security team cannot enable Detective and is unsure why. What must the security team do to enable Detective?

- A. Enable Amazon Macie so that Security Hub will allow Detective to process findings from Macie.
- B. Disable IAM Key Management Service (IAM KMS) encryption on CloudTrail logs in every member account of the organization.
- C. Enable Amazon GuardDuty on all member accounts. Try to enable Detective in 48 hours.
- D. Ensure that the principal that launches Detective has the organizations ListAccounts permission.

Answer: D

NEW QUESTION 164

Your company has just set up a new central server in a VPC. There is a requirement for other teams who have their servers located in different VPC's in the same region to connect to the central server. Which of the below options is best suited to achieve this requirement?

Please select:

- A. Set up VPC peering between the central server VPC and each of the teams VPCs.
- B. Set up IAM DirectConnect between the central server VPC and each of the teams VPCs.
- C. Set up an IPSec Tunnel between the central server VPC and each of the teams VPCs.
- D. None of the above options will work.

Answer: A

Explanation:

A VPC peering connection is a networking connection between two VPCs that enables you to route traffic between them using private IPv4 addresses or IPv6 addresses. Instances in either VPC can communicate with each other as if they are within the same network. You can create a VPC peering connection between your own VPCs, or with a VPC in another IAM account within a single region.

Options B and C are invalid because you need to use VPC Peering. Option D is invalid because VPC Peering is available.

For more information on VPC Peering, please see the below link:

<http://docs.IAM.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.html>

The correct answer is: Set up VPC peering between the central server VPC and each of the teams VPCs. Submit your Feedback/Queries to our Experts

NEW QUESTION 166

A company has developed a new Amazon RDS database application. The company must secure the RDS database credentials for encryption in transit and encryption at rest. The company also must rotate the credentials automatically on a regular basis.

Which solution meets these requirements?

- A. Use IAM Systems Manager Parameter Store to store the database credentials.
- B. Configure automatic rotation of the credentials.
- C. Use IAM Secrets Manager to store the database credentials.
- D. Configure automatic rotation of the credentials.
- E. Store the database credentials in an Amazon S3 bucket that is configured with server-side encryption with S3 managed encryption keys (SSE-S3). Rotate the credentials with IAM database authentication.
- F. Store the database credentials in Amazon S3 Glacier, and use S3 Glacier Vault Lock. Configure an IAM Lambda function to rotate the credentials on a scheduled basis.

Answer: A

NEW QUESTION 170

.....

Relate Links

100% Pass Your SCS-C01 Exam with Exambible Prep Materials

<https://www.exambible.com/SCS-C01-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>