

Amazon-Web-Services

Exam Questions DOP-C02

AWS Certified DevOps Engineer - Professional



NEW QUESTION 1

A company's DevOps engineer uses AWS Systems Manager to perform maintenance tasks during maintenance windows. The company has a few Amazon EC2 instances that require a restart after notifications from AWS Health. The DevOps engineer needs to implement an automated solution to remediate these notifications. The DevOps engineer creates an Amazon EventBridge rule.

How should the DevOps engineer configure the EventBridge rule to meet these requirements?

- A. Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance
- B. Target a Systems Manager document to restart the EC2 instance.
- C. Configure an event source of Systems Manager and an event type that indicates a maintenance window
- D. Target a Systems Manager document to restart the EC2 instance.
- E. Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance
- F. Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.
- G. Configure an event source of EC2 and an event type that indicates instance maintenance
- H. Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.

Answer: C

Explanation:

AWS Health provides real-time events and information related to your AWS infrastructure. It can be integrated with Amazon EventBridge to act upon the health events automatically. If the maintenance notification from AWS Health indicates that an EC2 instance requires a restart, you can set up an EventBridge rule to respond to such events. In this case, the target of this rule would be a Lambda function that would trigger a Systems Manager automation to restart the EC2 instance during a maintenance window. Remember, AWS Health is the source of the events (not EC2 or Systems Manager), and AWS Lambda can be used to execute complex remediation tasks, such as scheduling maintenance tasks via Systems Manager.

The following are the steps involved in configuring the EventBridge rule to meet these requirements:

? Configure an event source of AWS Health, a service of EC2, and an event type that indicates instance maintenance.

? Target a newly created AWS Lambda function that registers an automation task to restart the EC2 instance during a maintenance window.

The AWS Lambda function will be triggered by the event from AWS Health. The function will then register an automation task to restart the EC2 instance during the next maintenance window.

NEW QUESTION 2

A company wants to use AWS development tools to replace its current bash deployment scripts. The company currently deploys a LAMP application to a group of Amazon EC2 instances behind an Application Load Balancer (ALB). During the deployments, the company unit tests the committed application, stops and starts services, unregisters and re-registers instances with the load balancer, and updates file permissions. The company wants to maintain the same deployment functionality through the shift to using AWS services.

Which solution will meet these requirements?

- A. Use AWS CodeBuild to test the application
- B. Use bash scripts invoked by AWS CodeDeploy's appspec.yml file to restart services, and deregister and register instances with the ALB
- C. Use the appspec.yml file to update file permissions without a custom script.
- D. Use AWS CodePipeline to move the application from the AWS CodeCommit repository to AWS CodeDeploy
- E. Use CodeDeploy's deployment group to test the application, unregister and re-register instances with the ALB and restart service
- F. and restart service
- G. Use the appspec.yml file to update file permissions without a custom script.
- H. Use AWS CodePipeline to move the application source code from the AWS CodeCommit repository to AWS CodeDeploy
- I. Use CodeDeploy to test the application
- J. Use CodeDeploy's appspec.yml file to restart services and update permissions without a custom script
- K. Use AWS CodeBuild to unregister and re-register instances with the ALB.
- L. Use AWS CodePipeline to trigger AWS CodeBuild to test the application
- M. Use bash scripts invoked by AWS CodeDeploy's appspec.yml file to restart service
- N. Unregister and re-register the instances in the AWS CodeDeploy deployment group with the ALB
- O. Update the appspec.yml file to update file permissions without a custom script.

Answer: D

Explanation:

<https://aws.amazon.com/blogs/devops/how-to-test-and-debug-aws-codedeploy-locally-before-you-ship-your-code/#:~:text=You%20can%20test%20application%20code,local%20server%20or%20EC2%20instance.>

NEW QUESTION 3

A company runs applications in AWS accounts that are in an organization in AWS Organizations. The applications use Amazon EC2 instances and Amazon S3. The company wants to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future. When the company detects one of these events, the company wants to use an existing Amazon Simple Notification Service (Amazon SNS) topic to send a notification to its operational support team for investigation and remediation.

Which solution will meet these requirements in accordance with AWS best practices?

- A. In the organization's management account, configure an AWS account as the Amazon GuardDuty administrator account
- B. In the GuardDuty administrator account, add the company's existing AWS accounts to GuardDuty as members. In the GuardDuty administrator account, create an Amazon EventBridge rule with an event pattern to match GuardDuty events and to forward matching events to the SNS topic.
- C. In the organization's management account, configure Amazon GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts. Create an AWS CloudFormation stack set that accepts the GuardDuty invitation and creates an Amazon EventBridge rule. Configure the rule with an event pattern to match
- D. GuardDuty events and to forward matching events to the SNS topic
- E. Configure the CloudFormation stack set to deploy into all AWS accounts in the organization.
- F. In the organization's management account
- G. create an AWS CloudTrail organization trail. Activate the organization trail in all AWS accounts in the organization
- H. Create an SCP that enables VPC Flow Logs in each account in the organization
- I. Configure AWS Security Hub for the organization. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward

matching events to the SNS topic.

J. In the organization's management account configure an AWS account as the AWS CloudTrail administrator account in the CloudTrail administrator account create a CloudTrail organization trail

K. Add the company's existing AWS accounts to the organization trail Create an SCP that enables VPC Flow Logs in each account in the organization

L. Configure AWS Security Hub for the organization

M. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward matching events to the SNS topic.

Answer: B

Explanation:

It allows the company to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future using Amazon GuardDuty. It also provides a solution for automatically adding future AWS accounts to GuardDuty by configuring GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts.

NEW QUESTION 4

A DevOps engineer is designing an application that integrates with a legacy REST API. The application has an AWS Lambda function that reads records from an Amazon Kinesis data stream. The Lambda function sends the records to the legacy REST API.

Approximately 10% of the records that the Lambda function sends from the Kinesis data stream have data errors and must be processed manually. The Lambda function event source configuration has an Amazon Simple Queue Service (Amazon SQS) dead-letter queue as an on-failure destination. The DevOps engineer has configured the Lambda function to process records in batches and has implemented retries in case of failure.

During testing the DevOps engineer notices that the dead-letter queue contains many records that have no data errors and that already have been processed by the legacy REST API. The DevOps engineer needs to configure the Lambda function's event source options to reduce the number of errorless records that are sent to the dead-letter queue.

Which solution will meet these requirements?

- A. Increase the retry attempts
- B. Configure the setting to split the batch when an error occurs
- C. Increase the concurrent batches per shard
- D. Decrease the maximum age of record

Answer: B

Explanation:

This solution will meet the requirements because it will reduce the number of errorless records that are sent to the dead-letter queue. When you configure the setting to split the batch when an error occurs, Lambda will retry only the records that caused the error, instead of retrying the entire batch. This way, the records that have no data errors and have already been processed by the legacy REST API will not be retried and sent to the dead-letter queue unnecessarily.

<https://docs.aws.amazon.com/lambda/latest/dg/with-kinesis.html>

NEW QUESTION 5

A DevOps engineer is implementing governance controls for a company that requires its infrastructure to be housed within the United States. The engineer must restrict which AWS Regions can be used, and ensure an alert is sent as soon as possible if any activity outside the governance policy takes place. The controls should be automatically enabled on any new Region outside the United States (US).

Which combination of actions will meet these requirements? (Select TWO.)

- A. Create an AWS Organizations SCP that denies access to all non-global services in non-US Region
- B. Attach the policy to the root of the organization.
- C. Configure AWS CloudTrail to send logs to Amazon CloudWatch Logs and enable it for all Region
- D. Use a CloudWatch Logs metric filter to send an alert on any service activity in non-US Regions.
- E. Use an AWS Lambda function that checks for AWS service activity and deploy it to all Region
- F. Write an Amazon EventBridge rule that runs the Lambda function every hour, sending an alert if activity is found in a non-US Region.
- G. Use an AWS Lambda function to query Amazon Inspector to look for service activity in non-US Regions and send alerts if any activity is found.
- H. Write an SCP using the aws: RequestedRegion condition key limiting access to US Region
- I. Apply the policy to all users, groups, and roles

Answer: AB

Explanation:

To implement governance controls that restrict AWS service usage to within the United States and ensure alerts for any activity outside the governance policy, the following actions will meet the requirements:

? A. Create an AWS Organizations SCP that denies access to all non-global services in non-US Regions. Attach the policy to the root of the organization. This action will effectively prevent users and roles in all accounts within the organization from accessing services in non-US Regions¹².

? B. Configure AWS CloudTrail to send logs to Amazon CloudWatch Logs and enable it for all Regions. Use a CloudWatch Logs metric filter to send an alert on any service activity in non-US Regions. This action will allow monitoring of all AWS Regions and will trigger alerts if any activity is detected in non-US Regions, ensuring that the governance team is notified as soon as possible³.

References:

? AWS Documentation on Service Control Policies (SCPs) and how they can be used to manage permissions and restrict access based on Regions¹².

? AWS Documentation on monitoring CloudTrail log files with Amazon CloudWatch Logs to set up alerts for specific activities³.

NEW QUESTION 6

An application runs on Amazon EC2 instances behind an Application Load Balancer (ALB). A DevOps engineer is using AWS CodeDeploy to release a new version. The deployment fails during the AllowTraffic lifecycle event, but a cause for the failure is not indicated in the deployment logs.

What would cause this?

- A. The appspec
- B. yml file contains an invalid script that runs in the AllowTraffic lifecycle hook.
- C. The user who initiated the deployment does not have the necessary permissions to interact with the ALB.
- D. The health checks specified for the ALB target group are misconfigured.
- E. The CodeDeploy agent was not installed in the EC2 instances that are part of the ALB target group.

Answer: C

Explanation:

This failure is typically due to incorrectly configured health checks in Elastic Load Balancing for the Classic Load Balancer, Application Load Balancer, or Network Load Balancer used to manage traffic for the deployment group. To resolve the issue, review and correct any errors in the health check configuration for the load balancer. <https://docs.aws.amazon.com/codedeploy/latest/userguide/troubleshooting-deployments.html#troubleshooting-deployments-allowtraffic-no-logs>

NEW QUESTION 7

A company uses Amazon S3 to store proprietary information. The development team creates buckets for new projects on a daily basis. The security team wants to ensure that all existing and future buckets have encryption logging and versioning enabled. Additionally, no buckets should ever be publicly read or write accessible.

What should a DevOps engineer do to meet these requirements?

- A. Enable AWS CloudTrail and configure automatic remediation using AWS Lambda.
- B. Enable AWS Config rules and configure automatic remediation using AWS Systems Manager documents.
- C. Enable AWS Trusted Advisor and configure automatic remediation using Amazon EventBridge.
- D. Enable AWS Systems Manager and configure automatic remediation using Systems Manager documents.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/mt/aws-config-auto-remediation-s3-compliance/> <https://aws.amazon.com/blogs/aws/aws-config-rules-dynamic-compliance-checking-for-cloud-resources/>

NEW QUESTION 8

A company is adopting AWS CodeDeploy to automate its application deployments for a Java-Apache Tomcat application with an Apache Webserver. The development team started with a proof of concept, created a deployment group for a developer environment, and performed functional tests within the application. After completion, the team will create additional deployment groups for staging and production.

The current log level is configured within the Apache settings, but the team wants to change this configuration dynamically when the deployment occurs, so that they can set different log level configurations depending on the deployment group without having a different application revision for each group.

How can these requirements be met with the LEAST management overhead and without requiring different script versions for each deployment group?

- A. Tag the Amazon EC2 instances depending on the deployment group
- B. Then place a script into the application revision that calls the metadata service and the EC2 API to identify which deployment group the instance is part of
- C. Use this information to configure the log level setting
- D. Reference the script as part of the AfterInstall lifecycle hook in the appspec.yml file.
- E. Create a script that uses the CodeDeploy environment variable DEPLOYMENT_GROUP_NAME to identify which deployment group the instance is part of
- F. Use this information to configure the log level setting
- G. Reference this script as part of the BeforeInstall lifecycle hook in the appspec.yml file.
- H. Create a CodeDeploy custom environment variable for each environment
- I. Then place a script into the application revision that checks this environment variable to identify which deployment group the instance is part of
- J. Use this information to configure the log level setting
- K. Reference this script as part of the ValidateService lifecycle hook in the appspec.yml file.
- L. Create a script that uses the CodeDeploy environment variable DEPLOYMENT_GROUP_ID to identify which deployment group the instance is part of to configure the log level setting
- M. Reference this script as part of the Install lifecycle hook in the appspec.yml file.

Answer: B

Explanation:

The following are the steps that the company can take to change the log level dynamically when the deployment occurs:

? Create a script that uses the CodeDeploy environment variable DEPLOYMENT_GROUP_NAME to identify which deployment group the instance is part of.

? Use this information to configure the log level settings.

? Reference this script as part of the BeforeInstall lifecycle hook in the appspec.yml file.

The DEPLOYMENT_GROUP_NAME environment variable is automatically set by CodeDeploy when the deployment is triggered. This means that the script does not need to call the metadata service or the EC2 API to identify the deployment group.

This solution is the least complex and requires the least management overhead. It also does not require different script versions for each deployment group.

The following are the reasons why the other options are not correct:

? Option A is incorrect because it would require tagging the Amazon EC2 instances, which would be a manual and time-consuming process.

? Option C is incorrect because it would require creating a custom environment variable for each environment. This would be a complex and error-prone process.

? Option D is incorrect because it would use

the DEPLOYMENT_GROUP_ID environment variable. However, this variable is not automatically set by CodeDeploy, so the script would need to call the metadata service or the EC2 API to get the deployment group ID. This would add complexity and overhead to the solution.

NEW QUESTION 9

A company uses AWS Key Management Service (AWS KMS) keys and manual key rotation to meet regulatory compliance requirements. The security team wants to be notified when any keys have not been rotated after 90 days.

Which solution will accomplish this?

- A. Configure AWS KMS to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- B. Configure an Amazon EventBridge event to launch an AWS Lambda function to call the AWS Trusted Advisor API and publish to an Amazon Simple Notification Service (Amazon SNS) topic.
- C. Develop an AWS Config custom rule that publishes to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.
- D. Configure AWS Security Hub to publish to an Amazon Simple Notification Service (Amazon SNS) topic when keys are more than 90 days old.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/security/how-to-use-aws-config-to-determine-compliance-of-aws-kms-key-policies-to-your-specifications/>

NEW QUESTION 10

A company has a data ingestion application that runs across multiple AWS accounts. The accounts are in an organization in AWS Organizations. The company needs to monitor the application and consolidate access to the application. Currently the company is running the application on Amazon EC2 instances from several Auto Scaling groups. The EC2 instances have no access to the internet because the data is sensitive. Engineers have deployed the necessary VPC endpoints. The EC2 instances run a custom AMI that is built specifically for the application. To maintain and troubleshoot the application, system administrators need the ability to log in to the EC2 instances. This access must be automated and controlled centrally. The company's security team must receive a notification whenever the instances are accessed. Which solution will meet these requirements?

- A. Create an Amazon EventBridge rule to send notifications to the security team whenever a user logs in to an EC2 instance Use EC2 Instance Connect to log in to the instance
- B. Deploy Auto Scaling groups by using AWS Cloud Formation Use the cfn-init helper script to deploy appropriate VPC routes for external access Rebuild the custom AMI so that the custom AMI includes AWS Systems Manager Agent.
- C. Deploy a NAT gateway and a bastion host that has internet access Create a security group that allows incoming traffic on all the EC2 instances from the bastion host Install AWS Systems Manager Agent on all the EC2 instances Use Auto Scaling group lifecycle hooks for monitoring and auditing access Use Systems Manager Session Manager to log into the instances Send logs to a log group in Amazon CloudWatch Log
- D. Export data to Amazon S3 for auditing Send notifications to the security team by using S3 event notifications.
- E. Use EC2 Image Builder to rebuild the custom AMI Include the most recent version of AWS Systems Manager Agent in the Image Configure the Auto Scaling group to attach the AmazonSSMManagedInstanceCore role to all the EC2 instances Use Systems Manager Session Manager to log in to the instances Enable logging of session details to Amazon S3 Create an S3 event notification for new file uploads to send a message to the security team through an Amazon Simple Notification Service (Amazon SNS) topic.
- F. Use AWS Systems Manager Automation to build Systems Manager Agent into the custom AMI Configure AWS Config to attach an SCP to the root organization account to allow the EC2 instances to connect to Systems Manager Use Systems Manager Session Manager to log in to the instances Enable logging of session details to Amazon S3 Create an S3 event notification for new file uploads to send a message to the security team through an Amazon Simple Notification Service (Amazon SNS) topic.

Answer: C

Explanation:

Even if AmazonSSMManagedInstanceCore is a managed policy and not an IAM role I will go with C because this policy is to be attached to an IAM role for EC2 to access System Manager.

NEW QUESTION 10

A growing company manages more than 50 accounts in an organization in AWS Organizations. The company has configured its applications to send logs to Amazon CloudWatch Logs.

A DevOps engineer needs to aggregate logs so that the company can quickly search the logs to respond to future security incidents. The DevOps engineer has created a new AWS account for centralized monitoring.

Which combination of steps should the DevOps engineer take to make the application logs searchable from the monitoring account? (Select THREE.)

- A. In the monitoring account, download an AWS CloudFormation template from CloudWatch to use in Organization
- B. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- C. Create an AWS CloudFormation template that defines an IAM role
- D. Configure the role to allow logs.amazonaws.com to perform the logs:Link action if the aws:ResourceAccount property is equal to the monitoring account ID
- E. Use CloudFormation StackSets in the organization's management account to deploy the CloudFormation template to the entire organization.
- F. Create an IAM role in the monitoring account
- G. Attach a trust policy that allows logs.amazonaws.com to perform the iam:CreateSink action if the aws:PrincipalOrgId property is equal to the organization ID.
- H. In the organization's management account, enable the logging policies for the organization.
- I. Use CloudWatch Observability Access Manager in the monitoring account to create a sink
- J. Allow logs to be shared with the monitoring account
- K. Configure the monitoring account data selection to view the Observability data from the organization ID.
- L. In the monitoring account, attach the CloudWatchLogsReadOnlyAccess AWS managed policy to an IAM role that can be assumed to search the logs.

Answer: BCF

Explanation:

? To aggregate logs from multiple accounts in an organization, the DevOps engineer needs to create a cross-account subscription1 that allows the monitoring account to receive log events from the sharing accounts.

? To enable cross-account subscription, the DevOps engineer needs to create an IAM role in each sharing account that grants permission to CloudWatch Logs to link the log groups to the destination in the monitoring account2. This can be done using a CloudFormation template and StackSets3 to deploy the role to all accounts in the organization.

? The DevOps engineer also needs to create an IAM role in the monitoring account that allows CloudWatch Logs to create a sink for receiving log events from other accounts4. The role must have a trust policy that specifies the organization ID as a condition.

? Finally, the DevOps engineer needs to attach the CloudWatchLogsReadOnlyAccess policy5 to an IAM role in the monitoring account that can be used to search the logs from the cross-account subscription.

References: 1: Cross-account log data sharing with subscriptions 2: Create an IAM role for CloudWatch Logs in each sharing account 3: AWS CloudFormation StackSets 4: Create an IAM role for CloudWatch Logs in your monitoring account 5: CloudWatchLogsReadOnlyAccess policy

NEW QUESTION 14

A production account has a requirement that any Amazon EC2 instance that has been logged in to manually must be terminated within 24 hours. All applications in the production account are using Auto Scaling groups with the Amazon CloudWatch Logs agent configured.

How can this process be automated?

- A. Create a CloudWatch Logs subscription to an AWS Step Functions applicatio
- B. Configure an AWS Lambda function to add a tag to the EC2 instance that produced the login event and mark the instance to be decommissioned
- C. Create an Amazon EventBridge rule to invoke a second Lambda function once a day that will terminate all instances with this tag.
- D. Create an Amazon CloudWatch alarm that will be invoked by the login event
- E. Send the notification to an Amazon Simple Notification Service (Amazon SNS) topic that the operations team is subscribed to, and have them terminate the EC2 instance within 24 hours.
- F. Create an Amazon CloudWatch alarm that will be invoked by the login event
- G. Configure the alarm to send to an Amazon Simple Queue Service (Amazon SQS) queue
- H. Use a group of worker instances to process messages from the queue, which then schedules an Amazon EventBridge rule to be invoked.
- I. Create a CloudWatch Logs subscription to an AWS Lambda function

- J. Configure the function to add a tag to the EC2 instance that produced the login event and mark the instance to be decommissioned
 K. Create an Amazon EventBridge rule to invoke a daily Lambda function that terminates all instances with this tag.

Answer: D

Explanation:

"You can use subscriptions to get access to a real-time feed of log events from CloudWatch Logs and have it delivered to other services such as an Amazon Kinesis stream, an Amazon Kinesis Data Firehose stream, or AWS Lambda for custom processing, analysis, or loading to other systems. When log events are sent to the receiving service, they are Base64 encoded and compressed with the gzip format." See <https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/Subscriptions.html>

NEW QUESTION 19

A company recently launched multiple applications that use Application Load Balancers. Application response time often slows down when the applications experience problems. A DevOps engineer needs to implement a monitoring solution that alerts the company when the applications begin to perform slowly. The DevOps engineer creates an Amazon Simple Notification Service (Amazon SNS) topic and subscribes the company's email address to the topic. What should the DevOps engineer do next to meet the requirements?

- A. Create an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval. Configure the Lambda function to publish a notification to the SNS topic when the applications return errors.
 B. Create an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval.
 C. Configure the canary to use the SNS topic when the applications return errors.
 D. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric. Configure the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports. Configure the CloudWatch alarm to use the SNS topic.
 E. Create an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric. Configure the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports. Configure the CloudWatch alarm to use the SNS topic.

Answer: B

Explanation:

? Option A is incorrect because creating an Amazon EventBridge rule that invokes an AWS Lambda function to query the applications on a 5-minute interval is not a valid solution. EventBridge rules can only trigger Lambda functions based on events, not on time intervals. Moreover, querying the applications on a 5-minute interval might incur unnecessary costs and network overhead, and might not detect performance issues in real time.

? Option B is correct because creating an Amazon CloudWatch Synthetics canary that runs a custom script to query the applications on a 5-minute interval is a valid solution. CloudWatch Synthetics canaries are configurable scripts that monitor endpoints and APIs by simulating customer behavior. Canaries can run as often as once per minute, and can measure the latency and availability of the applications. Canaries can also send notifications to an Amazon SNS topic when they detect errors or performance issues¹.

? Option C is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution. The RequestCountPerTarget metric measures the number of requests completed or connections made per target in a target group². This metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the number of connections becomes greater than the configured number of threads that the application supports is not a valid way to measure the application performance, as it depends on the application design and implementation.

? Option D is incorrect because creating an Amazon CloudWatch alarm that uses the AWS/ApplicationELB namespace RequestCountPerTarget metric is not a valid solution, for the same reason as option C. The RequestCountPerTarget metric does not reflect the application response time, which is the requirement. Moreover, configuring the CloudWatch alarm to send a notification when the average response time becomes greater than the longest response time that the application supports is not a valid way to measure the application performance, as it does not account for variability or outliers in the response time distribution.

References:

- ? 1: Using synthetic monitoring
 ? 2: Application Load Balancer metrics

NEW QUESTION 24

A company manages multiple AWS accounts by using AWS Organizations with OUs for the different business divisions. The company is updating their corporate network to use new IP address ranges. The company has 10 Amazon S3 buckets in different AWS accounts. The S3 buckets store reports for the different divisions. The S3 bucket configurations allow only private corporate network IP addresses to access the S3 buckets.

A DevOps engineer needs to change the range of IP addresses that have permission to access the contents of the S3 buckets. The DevOps engineer also needs to revoke the permissions of two OUs in the company. Which solution will meet these requirements?

- A. Create a new SCP that has two statements, one that allows access to the new range of IP addresses for all the S3 buckets and one that denies access to the old range of IP addresses for all the S3 buckets.
 B. Set a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets.
 C. Create a new SCP that has a statement that allows only the new range of IP addresses to access the S3 buckets.
 D. Create another SCP that denies access to the S3 buckets.
 E. Attach the second SCP to the two OUs.
 F. On all the S3 buckets, configure resource-based policies that allow only the new range of IP addresses to access the S3 buckets.
 G. Create a new SCP that denies access to the S3 buckets.
 H. Attach the SCP to the two OUs.
 I. On all the S3 buckets, configure resource-based policies that allow only the new range of IP addresses to access the S3 buckets.
 J. Set a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets.

Answer: C

Explanation:

The correct answer is C.

A comprehensive and detailed explanation is:

? Option A is incorrect because creating a new SCP that has two statements, one that allows access to the new range of IP addresses for all the S3 buckets and one that denies access to the old range of IP addresses for all the S3 buckets, is not a valid solution. SCPs are not resource-based policies, and they cannot specify the S3 buckets or the IP addresses as resources or conditions. SCPs can only control the actions that can be performed by the principals in the organization, not the access to specific resources. Moreover, setting a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets is not sufficient to revoke the permissions of the two OUs, as there might be other roles or users in those OUs that can still access the S3

buckets.

? Option B is incorrect because creating a new SCP that has a statement that allows only the new range of IP addresses to access the S3 buckets is not a valid solution, for the same reason as option A. SCPs are not resource-based policies, and they cannot specify the S3 buckets or the IP addresses as resources or conditions. Creating another SCP that denies access to the S3 buckets and attaching it to the two OUs is also not a valid solution, as SCPs cannot specify the S3 buckets as resources either.

? Option C is correct because it meets both requirements of changing the range of IP addresses that have permission to access the contents of the S3 buckets and revoking the permissions of two OUs in the company. On all the S3 buckets, configuring resource-based policies that allow only the new range of IP addresses to access the S3 buckets is a valid way to update the IP address ranges, as resource-based policies can specify both resources and conditions. Creating a new SCP that denies access to the S3 buckets and attaching it to the two OUs is also a valid way to revoke the permissions of those OUs, as SCPs can deny actions such as s3:PutObject or s3:GetObject on any resource.

? Option D is incorrect because setting a permissions boundary for the OrganizationAccountAccessRole role in the two OUs to deny access to the S3 buckets is not sufficient to revoke the permissions of the two OUs, as there might be other roles or users in those OUs that can still access the S3 buckets. A permissions boundary is a policy that defines the maximum permissions that an IAM entity can have. However, it does not revoke any existing permissions that are granted by other policies.

References:

- ? AWS Organizations
- ? S3 Bucket Policies
- ? Service Control Policies
- ? Permissions Boundaries

NEW QUESTION 25

A healthcare services company is concerned about the growing costs of software licensing for an application for monitoring patient wellness. The company wants to create an audit process to ensure that the application is running exclusively on Amazon EC2 Dedicated Hosts. A DevOps engineer must create a workflow to audit the application to ensure compliance.

What steps should the engineer take to meet this requirement with the LEAST administrative overhead?

- A. Use AWS Systems Manager Configuration Compliance
- B. Use calls to the put-compliance-items API action to scan and build a database of noncompliant EC2 instances based on their host placement configuration
- C. Use an Amazon DynamoDB table to store these instance IDs for fast access
- D. Generate a report through Systems Manager by calling the list-compliance-summaries API action.
- E. Use custom Java code running on an EC2 instance
- F. Set up EC2 Auto Scaling for the instance depending on the number of instances to be checked
- G. Send the list of noncompliant EC2 instance IDs to an Amazon SQS queue
- H. Set up another worker instance to process instance IDs from the SQS queue and write them to Amazon DynamoDB
- I. Use an AWS Lambda function to terminate noncompliant instance IDs obtained from the queue, and send them to an Amazon SNS email topic for distribution.
- J. Use AWS Config
- K. Identify all EC2 instances to be audited by enabling Config Recording on all Amazon EC2 resources for the region
- L. Create a custom AWS Config rule that triggers an AWS Lambda function by using the "config-rule-change-triggered" blueprint. Modify the Lambda evaluateCompliance () function to verify host placement to return a NON_COMPLIANT result if the instance is not running on an EC2 Dedicated Host
- M. Use the AWS Config report to address noncompliant instances.
- N. Use AWS CloudTrail
- O. Identify all EC2 instances to be audited by analyzing all calls to the EC2 RunCommand API action
- P. Invoke a AWS Lambda function that analyzes the host placement of the instances
- Q. Store the EC2 instance ID of noncompliant resources in an Amazon RDS for MySQL DB instance
- R. Generate a report by querying the RDS instance and exporting the query results to a CSV text file.

Answer: C

Explanation:

The correct answer is C. Using AWS Config to identify and audit all EC2 instances based on their host placement configuration is the most efficient and scalable solution to ensure compliance with the software licensing requirement. AWS Config is a service that enables you to assess, audit, and evaluate the configurations of your AWS resources. By creating a custom AWS Config rule that triggers a Lambda function to verify host placement, the DevOps engineer can automate the process of checking whether the instances are running on EC2 Dedicated Hosts or not. The Lambda function can return a NON_COMPLIANT result if the instance is not running on an EC2 Dedicated Host, and the AWS Config report can provide a summary of the compliance status of the instances. This solution requires the least administrative overhead compared to the other options.

Option A is incorrect because using AWS Systems Manager Configuration Compliance to scan and build a database of noncompliant EC2 instances based on their host placement configuration is a more complex and costly solution than using AWS Config. AWS Systems Manager Configuration Compliance is a feature of AWS Systems Manager that enables you to scan your managed instances for patch compliance and configuration inconsistencies. To use this feature, the DevOps engineer would need to install the Systems Manager Agent on each EC2 instance, create a State Manager association to run the put-compliance-items API action periodically, and use a DynamoDB table to store the instance IDs of noncompliant resources. This solution would also require more API calls and storage costs than using AWS Config.

Option B is incorrect because using custom Java code running on an EC2 instance to check and terminate noncompliant EC2 instances is a more cumbersome and error-prone solution than using AWS Config. This solution would require the DevOps engineer to write and maintain the Java code, set up EC2 Auto Scaling for the instance, use an SQS queue and another worker instance to process the instance IDs, use a Lambda function and an SNS topic to terminate and notify the noncompliant instances, and handle any potential failures or exceptions in the workflow. This solution would also incur more compute, storage, and messaging costs than using AWS Config.

Option D is incorrect because using AWS CloudTrail to identify and audit EC2 instances by analyzing the EC2 RunCommand API action is a less reliable and accurate solution than using AWS Config. AWS CloudTrail is a service that enables you to monitor and log the API activity in your AWS account. The EC2 RunCommand API action is used to execute commands on one or more EC2 instances. However, this API action does not necessarily indicate the host placement of the instance, and it may not capture all the instances that are running on EC2 Dedicated Hosts or not. Therefore, option D would not provide a comprehensive and consistent audit of the EC2 instances.

NEW QUESTION 30

A DevOps engineer is deploying a new version of a company's application in an AWS CodeDeploy deployment group associated with its Amazon EC2 instances. After some time, the deployment fails. The engineer realizes that all the events associated with the specific deployment ID are in a Skipped status and code was not deployed in the instances associated with the deployment group.

What are valid reasons for this failure? (Select TWO.)

- A. The networking configuration does not allow the EC2 instances to reach the internet via a NAT gateway or internet gateway and the CodeDeploy endpoint cannot be reached.
- B. The IAM user who triggered the application deployment does not have permission to interact with the CodeDeploy endpoint.

- C. The target EC2 instances were not properly registered with the CodeDeploy endpoint.
- D. An instance profile with proper permissions was not attached to the target EC2 instances.
- E. The appspec
- F. yml file was not included in the application revision.

Answer: AD

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/troubleshooting-deployments.html#troubleshooting-skipped-lifecycle-events>

NEW QUESTION 35

A company has enabled all features for its organization in AWS Organizations. The organization contains 10 AWS accounts. The company has turned on AWS CloudTrail in all the accounts. The company expects the number of AWS accounts in the organization to increase to 500 during the next year. The company plans to use multiple OUs for these accounts.

The company has enabled AWS Config in each existing AWS account in the organization.

A DevOps engineer must implement a solution that enables AWS Config automatically for all future AWS accounts that are created in the organization.

Which solution will meet this requirement?

- A. In the organization's management account, create an Amazon EventBridge rule that reacts to a CreateAccount API call.
- B. Configure the rule to invoke an AWS Lambda function that enables trusted access to AWS Config for the organization.
- C. In the organization's management account, create an AWS CloudFormation stack set to enable AWS Config.
- D. Configure the stack set to deploy automatically when an account is created through Organizations.
- E. In the organization's management account, create an SCP that allows the appropriate AWS Config API calls to enable AWS Config.
- F. Apply the SCP to the root-level OU.
- G. In the organization's management account, create an Amazon EventBridge rule that reacts to a CreateAccount API call.
- H. Configure the rule to invoke an AWS Systems Manager Automation runbook to enable AWS Config for the account.

Answer: B

Explanation:

<https://aws.amazon.com/about-aws/whats-new/2020/02/aws-cloudformation-stacksets-introduces-automatic-deployments-across-accounts-and-regions-through-aws-organizations/>

NEW QUESTION 40

A company's developers use Amazon EC2 instances as remote workstations. The company is concerned that users can create or modify EC2 security groups to allow unrestricted inbound access.

A DevOps engineer needs to develop a solution to detect when users create unrestricted security group rules. The solution must detect changes to security group rules in near real time, remove unrestricted rules, and send email notifications to the security team. The DevOps engineer has created an AWS Lambda function that checks for security group ID from input, removes rules that grant unrestricted access, and sends notifications through Amazon Simple Notification Service (Amazon SNS).

What should the DevOps engineer do next to meet the requirements?

- A. Configure the Lambda function to be invoked by the SNS topic.
- B. Create an AWS CloudTrail subscription for the SNS topic.
- C. Configure a subscription filter for security group modification events.
- D. Create an Amazon EventBridge scheduled rule to invoke the Lambda function.
- E. Define a schedule pattern that runs the Lambda function every hour.
- F. Create an Amazon EventBridge event rule that has the default event bus as the source.
- G. Define the rule's event pattern to match EC2 security group creation and modification events.
- H. Configure the rule to invoke the Lambda function.
- I. Create an Amazon EventBridge custom event bus that subscribes to events from all AWS services.
- J. Configure the Lambda function to be invoked by the custom event bus.

Answer: C

Explanation:

To meet the requirements, the DevOps engineer should create an Amazon EventBridge event rule that has the default event bus as the source. The rule's event pattern should match EC2 security group creation and modification events, and it should be configured to invoke the Lambda function. This solution will allow for near real-time detection of security group rule changes and will trigger the Lambda function to remove any unrestricted rules and send email notifications to the security team. <https://repost.aws/knowledge-center/monitor-security-group-changes-ec2>

NEW QUESTION 42

A DevOps engineer has developed an AWS Lambda function. The Lambda function starts an AWS CloudFormation drift detection operation on all supported resources for a specific CloudFormation stack. The Lambda function then exits its invocation. The DevOps engineer has created an Amazon EventBridge scheduled rule that invokes the Lambda function every hour. An Amazon Simple Notification Service (Amazon SNS) topic already exists in the AWS account. The DevOps engineer has subscribed to the SNS topic to receive notifications.

The DevOps engineer needs to receive a notification as soon as possible when drift is detected in this specific stack configuration.

Which solution will meet these requirements?

- A. Configure the existing EventBridge rule to also target the SNS topic. Configure an SNS subscription filter policy to match the CloudFormation stack.
- B. Attach the subscription filter policy to the SNS topic.
- C. Create a second Lambda function to query the CloudFormation API for the drift detection results for the stack. Configure the second Lambda function to publish a message to the SNS topic. If drift is detected, adjust the existing EventBridge rule to also target the second Lambda function.
- D. Configure Amazon GuardDuty in the account with drift detection for all CloudFormation stacks.
- E. Create a second EventBridge rule that reacts to the GuardDuty drift detection event finding for the specific CloudFormation stack.
- F. Configure the SNS topic as a target of the second EventBridge rule.
- G. Configure AWS Config in the account.
- H. Use the cloudformation-stack-drift-detection-check-managed-resources rule.
- I. Create a second EventBridge rule that reacts to a compliance change event for the CloudFormation stack.
- J. Configure the SNS topic as a target of the second EventBridge rule.

Answer: D

Explanation:

A comprehensive and detailed explanation is:

? Option A is incorrect because EventBridge rules cannot filter events based on the message body or attributes of the target service. Therefore, configuring an SNS subscription filter policy to match the CloudFormation stack will not work. The SNS topic will receive all events from the EventBridge rule, regardless of the stack name or drift status.

? Option B is incorrect because it introduces unnecessary complexity and cost.

Creating a second Lambda function to query the CloudFormation API for the drift detection results is redundant, since CloudFormation already publishes drift detection events to EventBridge. Moreover, invoking two Lambda functions every hour will incur more charges than invoking one.

? Option C is incorrect because GuardDuty does not provide drift detection for CloudFormation stacks. GuardDuty is a threat detection service that monitors for malicious activity and unauthorized behavior in AWS accounts and workloads. It does not monitor or report on configuration changes or drifts in CloudFormation stacks.

? Option D is correct because it leverages AWS Config and its managed rule for drift detection. AWS Config is a service that enables you to assess, audit, and evaluate the configurations of your AWS resources. It can detect configuration changes and drifts in CloudFormation stacks using the cloudformation-stack-drift-detection-check managed rule. This rule triggers an AWS Config event when a stack drifts from its expected template configuration. By creating a second EventBridge rule that reacts to this event for the specific stack, the DevOps engineer can configure the SNS topic as a target and receive a notification as soon as possible when drift is detected.

References:

? AWS Config

? Amazon SNS subscription filter policies

? Amazon EventBridge rules

NEW QUESTION 47

A company is launching an application. The application must use only approved AWS services. The account that runs the application was created less than 1 year ago and is assigned to an AWS Organizations OU.

The company needs to create a new Organizations account structure. The account structure must have an appropriate SCP that supports the use of only services that are currently active in the AWS account.

The company will use AWS Identity and Access Management (IAM) Access Analyzer in the solution.

Which solution will meet these requirements?

- A. Create an SCP that allows the services that IAM Access Analyzer identifies
- B. Create an OU for the account
- C. Move the account into the new O
- D. Attach the new SCP to the new O
- E. Detach the default FullAWSAccess SCP from the new OU.
- F. Create an SCP that denies the services that IAM Access Analyzer identifies
- G. Create an OU for the account
- H. Move the account into the new OI
- I. Attach the new SCP to the new OU.
- J. Create an SCP that allows the services that IAM Access Analyzer identifies
- K. Attach the new SCP to the organization's root.
- L. Create an SCP that allows the services that IAM Access Analyzer identifies
- M. Create an OU for the account
- N. Move the account into the new O
- O. Attach the new SCP to the management account
- P. Detach the default FullAWSAccess SCP from the new OU.

Answer: A

Explanation:

To meet the requirements of creating a new Organizations account structure with an appropriate SCP that supports the use of only services that are currently active in the AWS account, the company should use the following solution:

? Create an SCP that allows the services that IAM Access Analyzer identifies. IAM Access Analyzer is a service that helps identify potential resource-access risks by analyzing resource-based policies in the AWS environment. IAM Access Analyzer can also generate IAM policies based on access activity in the AWS CloudTrail logs. By using IAM Access Analyzer, the company can create an SCP that grants only the permissions that are required for the application to run, and denies all other services. This way, the company can enforce the use of only approved AWS services and reduce the risk of unauthorized access¹²

? Create an OU for the account. Move the account into the new OU. An OU is a container for accounts within an organization that enables you to group accounts that have similar business or security requirements. By creating an OU for the account, the company can apply policies and manage settings for the account as a group. The company should move the account into the new OU to make it subject to the policies attached to the OU³

? Attach the new SCP to the new OU. Detach the default FullAWSAccess SCP from the new OU. An SCP is a type of policy that specifies the maximum permissions for an organization or organizational unit (OU). By attaching the new SCP to the new OU, the company can restrict the services that are available to all accounts in that OU, including the account that runs the application. The company should also detach the default FullAWSAccess SCP from the new OU, because this policy allows all actions on all AWS services and might override or conflict with the new SCP⁴⁵

The other options are not correct because they do not meet the requirements or follow best practices. Creating an SCP that denies the services that IAM Access Analyzer identifies is not a good option because it might not cover all possible services that are not approved or required for the application. A deny policy is also more difficult to maintain and update than an allow policy. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the organization's root is not a good option because it might affect other accounts and OUs in the organization that have different service requirements or approvals. Creating an SCP that allows the services that IAM Access Analyzer identifies and attaching it to the management account is not a valid option because SCPs cannot be attached directly to accounts, only to OUs or roots.

References:

? 1: Using AWS Identity and Access Management Access Analyzer - AWS Identity and Access Management

? 2: Generate a policy based on access activity - AWS Identity and Access Management

? 3: Organizing your accounts into OUs - AWS Organizations

? 4: Service control policies - AWS Organizations

? 5: How SCPs work - AWS Organizations

NEW QUESTION 50

A company sells products through an ecommerce web application. The company wants a dashboard that shows a pie chart of product transaction details. The company wants to integrate the dashboard with the company's existing Amazon CloudWatch dashboards.

Which solution will meet these requirements with the MOST operational efficiency?

- A. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction
- B. Use CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard.
- C. Update the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transaction
- D. Use Amazon Athena to query the S3 bucket and to visualize the results In a Pie chart format
- E. Export the results from Athena Attach the results to the desired CloudWatch dashboard
- F. Update the ecommerce application to use AWS X-Ray for instrumentation
- G. Create a new X-Ray subsegment Add an annotation for each processed transaction
- H. Use X-Ray traces to query the data and to visualize the results in a pie chart format Attach the results to the desired CloudWatch dashboard
- I. Update the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction_ Create an AWS Lambda function to aggregate and write the results to Amazon DynamoDB
- J. Create a Lambda subscription filter for the log file
- K. Attach the results to the desired CloudWatch dashboard.

Answer: A

Explanation:

The correct answer is A.

A comprehensive and detailed explanation is:

? Option A is correct because it meets the requirements with the most operational efficiency. Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost-effective way to collect the data needed for the dashboard. Using CloudWatch Logs Insights to query the log group and to visualize the results in a pie chart format is also a convenient and integrated solution that leverages the existing CloudWatch dashboards. Attaching the results to the desired CloudWatch dashboard is straightforward and does not require any additional steps or services.

? Option B is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to an Amazon S3 bucket for each processed transaction is a valid way to store the data, but it requires creating and managing an S3 bucket and its permissions. Using Amazon Athena to query the S3 bucket and to visualize the results in a pie chart format is also a valid way to analyze the data, but it incurs charges based on the amount of data scanned by each query. Exporting the results from Athena and attaching them to the desired CloudWatch dashboard is also an extra step that adds more overhead and latency.

? Option C is incorrect because it uses AWS X-Ray for an inappropriate purpose.

Updating the ecommerce application to use AWS X-Ray for instrumentation is a good practice for monitoring and tracing distributed applications, but it is not designed for aggregating product transaction details. Creating a new X-Ray subsegment and adding an annotation for each processed transaction is possible, but it would clutter the X-Ray service map and make it harder to debug performance issues. Using X-Ray traces to query the data and to visualize the results in a pie chart format is also possible, but it would require custom code and logic that are not supported by X-Ray natively. Attaching the results to the desired CloudWatch dashboard is also not supported by X-Ray directly, and would require additional steps or services.

? Option D is incorrect because it introduces unnecessary complexity and cost.

Updating the ecommerce application to emit a JSON object to a CloudWatch log group for each processed transaction is a simple and cost-effective way to collect the data needed for the dashboard, as in option A. However, creating an AWS Lambda function to aggregate and write the results to Amazon DynamoDB is redundant, as CloudWatch Logs Insights can already perform aggregation queries on log data. Creating a Lambda subscription filter for the log file is also redundant, as CloudWatch Logs Insights can already access log data directly. Attaching the results to the desired CloudWatch dashboard would also require additional steps or services, as DynamoDB does not support native integration with CloudWatch dashboards.

References:

- ? CloudWatch Logs Insights
- ? Amazon Athena
- ? AWS X-Ray
- ? AWS Lambda
- ? Amazon DynamoDB

NEW QUESTION 55

A company manages AWS accounts for application teams in AWS Control Tower. Individual application teams are responsible for securing their respective AWS accounts.

A DevOps engineer needs to enable Amazon GuardDuty for all AWS accounts in which the application teams have not already enabled GuardDuty. The DevOps engineer is using AWS CloudFormation StackSets from the AWS Control Tower management account.

How should the DevOps engineer configure the CloudFormation template to prevent failure during the StackSets deployment?

- A. Create a CloudFormation custom resource that invokes an AWS Lambda function
- B. Configure the Lambda function to conditionally enable GuardDuty if GuardDuty is not already enabled in the accounts.
- C. Use the Conditions section of the CloudFormation template to enable GuardDuty in accounts where GuardDuty is not already enabled.
- D. Use the CloudFormation Fn: ImportValue intrinsic function to import the list of account IDs into the CloudFormation template to skip deployment for the listed AWS accounts.
- E. GetAtt intrinsic function to check whether GuardDuty is already enabled If GuardDuty is not already enabled use the Resources section of the CloudFormation template to enable GuardDuty.
- F. Manually discover the list of AWS account IDs where GuardDuty is not enabled Use the CloudFormation Fn: ImportValue intrinsic function to import the list of account IDs into the CloudFormation template to skip deployment for the listed AWS accounts.

Answer: A

Explanation:

This solution will meet the requirements because it will use a CloudFormation custom resource to execute custom logic during the stack set operation. A custom resource is a resource that you define in your template and that is associated with an AWS Lambda function. The Lambda function runs whenever the custom resource is created, updated, or deleted, and can perform any actions that are supported by the AWS SDK. In this case, the Lambda function can use the GuardDuty API to check whether GuardDuty is already enabled in each target account, and if not, enable it. This way, the DevOps engineer can avoid deploying the stack set to accounts that already have GuardDuty enabled, and prevent failure during the deployment.

NEW QUESTION 60

A company deploys its corporate infrastructure on AWS across multiple AWS Regions and Availability Zones. The infrastructure is deployed on Amazon EC2 instances and connects with AWS IoT Greengrass devices. The company deploys additional resources on on-premises servers that are located in the corporate headquarters.

The company wants to reduce the overhead involved in maintaining and updating its resources. The company's DevOps team plans to use AWS Systems Manager to implement automated management and application of patches. The DevOps team confirms that Systems Manager is available in the Regions that the resources are deployed in Systems Manager also is available in a Region near the corporate headquarters.

Which combination of steps must the DevOps team take to implement automated patch and configuration management across the company's EC2 instances IoT devices and on-premises infrastructure? (Select THREE.)

- A. Apply tags to all the EC2 instances
- B. AWS IoT Greengrass devices, and on-premises servers
- C. Use Systems Manager Session Manager to push patches to all the tagged devices.
- D. Use Systems Manager Run Command to schedule patching for the EC2 instances AWS IoT Greengrass devices and on-premises servers.
- E. Use Systems Manager Patch Manager to schedule patching IoT the EC2 instances AWS IoT Greengrass devices and on-premises servers as a Systems Manager maintenance window task.
- F. Configure Amazon EventBridge to monitor Systems Manager Patch Manager for updates to patch baseline
- G. Associate Systems Manager Run Command with the event to initiate a patch action for all EC2 instances AWS IoT Greengrass devices and on-premises servers.
- H. Create an IAM instance profile for Systems Manager Attach the instance profile to all the EC2 instances in the AWS account
- I. For the AWS IoT Greengrass devices and on-premises servers create an IAM service role for Systems Manager.
- J. Generate a managed-instance activation Use the Activation Code and Activation ID to install Systems Manager Agent (SSM Agent) on each server in the on-premises environment Update the AWS IoT Greengrass IAM token exchange role Use the role to deploy SSM Agent on all the IoT devices.

Answer: CEF

Explanation:

https://aws.amazon.com/blogs/mt/how-to-centrally-manage-aws-iot-greengrass-devices-using-aws-systems-manager/?force_isolation=true

NEW QUESTION 62

A DevOps team manages an API running on-premises that serves as a backend for an Amazon API Gateway endpoint. Customers have been complaining about high response latencies, which the development team has verified using the API Gateway latency metrics in Amazon CloudWatch. To identify the cause, the team needs to collect relevant data without introducing additional latency.

Which actions should be taken to accomplish this? (Choose two.)

- A. Install the CloudWatch agent server side and configure the agent to upload relevant logs to CloudWatch.
- B. Enable AWS X-Ray tracing in API Gateway, modify the application to capture request segments, and upload those segments to X-Ray during each request.
- C. Enable AWS X-Ray tracing in API Gateway, modify the application to capture request segments, and use the X-Ray daemon to upload segments to X-Ray.
- D. Modify the on-premises application to send log information back to API Gateway with each request.
- E. Modify the on-premises application to calculate and upload statistical data relevant to the API service requests to CloudWatch metrics.

Answer: AC

Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/install-CloudWatch-Agent-on-premise.html>

<https://docs.aws.amazon.com/xray/latest/devguide/xray-api-sendingdata.html>

NEW QUESTION 65

A DevOps team uses AWS CodePipeline, AWS CodeBuild, and AWS CodeDeploy to deploy an application. The application is a REST API that uses AWS Lambda functions and Amazon API Gateway Recent deployments have introduced errors that have affected many customers.

The DevOps team needs a solution that reverts to the most recent stable version of the application when an error is detected. The solution must affect the fewest customers possible.

Which solution Will meet these requirements With the MOST operational efficiency?

- A. Set the deployment configuration in CodeDeploy to LambdaAllAtOnce Configure automatic rollbacks on the deployment group Create an Amazon CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway Configure the deployment group to roll back when the number of alarms meets the alarm threshold
- B. Set the deployment configuration in CodeDeploy to LambdaCanary10Percent10Minute
- C. Configure automatic rollbacks on the deployment group Create an Amazon CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway Configure the deployment group to roll back when the number of alarms meets the alarm threshold
- D. Set the deployment configuration in CodeDeploy to LambdaAllAtOnce Configure manual rollbacks on the deployment group
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic to send notifications every time a deployment fails
- F. Configure the SNS topic to Invoke a new Lambda function that stops the current deployment and starts the most recent successful deployment
- G. Set the deployment configuration in CodeDeploy to LambdaCanary10Percent10Minutes Configure manual rollbacks on the deployment group Create a metric filter on an Amazon CloudWatch log group for API Gateway to monitor HTTP Bad Gateway error
- H. Configure the metric filter to Invoke a new Lambda function that stops the current deployment and starts the most recent successful deployment

Answer: B

Explanation:

? Option A is incorrect because setting the deployment configuration to LambdaAllAtOnce means that the new version of the application will be deployed to all Lambda functions at once, affecting all customers. This does not meet the requirement of affecting the fewest customers possible. Moreover, configuring automatic rollbacks on the deployment group is not operationally efficient, as it requires manual intervention to fix the errors and redeploy the application.

? Option B is correct because setting the deployment configuration to LambdaCanary10Percent10Minutes means that the new version of the application will be deployed to 10 percent of the Lambda functions first, and then to the remaining 90 percent after 10 minutes. This minimizes the impact of errors on customers, as only 10 percent of them will be affected by a faulty deployment. Configuring automatic rollbacks on the deployment group also meets the requirement of reverting to the most recent stable version of the application when an error is detected. Creating a CloudWatch alarm that detects HTTP Bad Gateway errors on API Gateway is a valid way to monitor the health of the application and trigger a rollback if needed.

? Option C is incorrect because setting the deployment configuration to LambdaAllAtOnce means that the new version of the application will be deployed to all Lambda functions at once, affecting all customers. This does not meet the requirement of affecting the fewest customers possible. Moreover, configuring manual rollbacks on the deployment group is not operationally efficient, as it requires human intervention to stop the current deployment and start a new one. Creating an SNS topic to send notifications every time a deployment fails is not sufficient to detect errors in the application, as it does not monitor the API Gateway responses.

? Option D is incorrect because configuring manual rollbacks on the deployment group is not operationally efficient, as it requires human intervention to stop the current deployment and start a new one. Creating a metric filter on a CloudWatch log group for API Gateway to monitor HTTP Bad Gateway errors is a valid way to monitor the health of the application, but invoking a new Lambda function to perform a rollback is unnecessary and complex, as CodeDeploy already provides automatic rollback functionality.

References:

? AWS CodeDeploy Deployment Configurations

? [AWS CodeDeploy Rollbacks]

? Amazon CloudWatch Alarms

NEW QUESTION 67

A company has migrated its container-based applications to Amazon EKS and want to establish automated email notifications. The notifications sent to each email address are for specific activities related to EKS components. The solution will include Amazon SNS topics and an AWS Lambda function to evaluate incoming log events and publish messages to the correct SNS topic.

Which logging solution will support these requirements?

- A. Enable Amazon CloudWatch Logs to log the EKS component
- B. Create a CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- C. Enable Amazon CloudWatch Logs to log the EKS component
- D. Create CloudWatch Logs Insights queries linked to Amazon EventBridge events that invoke Lambda.
- E. Enable Amazon S3 logging for the EKS component
- F. Configure an Amazon CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- G. Enable Amazon S3 logging for the EKS component
- H. Configure S3 PUT Object event notifications with AWS Lambda as the destination.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html#LambdaFunctionExample>
<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

NEW QUESTION 68

A DevOps team is merging code revisions for an application that uses an Amazon RDS Multi-AZ DB cluster for its production database. The DevOps team uses continuous integration to periodically verify that the application works. The DevOps team needs to test the changes before the changes are deployed to the production database.

Which solution will meet these requirements'?

- A. Use a buildspec file in AWS CodeBuild to restore the DB cluster from a snapshot of the production database run integration tests, and drop the restored database after verification.
- B. Deploy the application to production
- C. Configure an audit log of data control language (DCL) operations to capture database activities to perform if verification fails.
- D. Create a snapshot of the DB cluster before deploying the application Use the Update requires Replacement property on the DB instance in AWS CloudFormation to deploy the application and apply the changes.
- E. Ensure that the DB cluster is a Multi-AZ deployment
- F. Deploy the application with the update
- G. Fail over to the standby instance if verification fails.

Answer: A

Explanation:

This solution will meet the requirements because it will create a temporary copy of the production database using a snapshot, run the integration tests on the copy, and delete the copy after the tests are done. This way, the production database will not be affected by the code revisions, and the DevOps team can test the changes before deploying them to production. A buildspec file is a YAML file that contains the commands and settings that CodeBuild uses to run a build. The buildspec file can specify the steps to restore the DB cluster from a snapshot, run the integration tests, and drop the restored database.

NEW QUESTION 72

A company has many applications. Different teams in the company developed the applications by using multiple languages and frameworks. The applications run on premises and on different servers with different operating systems. Each team has its own release protocol and process. The company wants to reduce the complexity of the release and maintenance of these applications.

The company is migrating its technology stacks, including these applications, to AWS. The company wants centralized control of source code, a consistent and automatic delivery pipeline, and as few maintenance tasks as possible on the underlying infrastructure.

What should a DevOps engineer do to meet these requirements?

- A. Create one AWS CodeCommit repository for all application
- B. Put each application's code in a different branch
- C. Merge the branches, and use AWS CodeBuild to build the application
- D. Use AWS CodeDeploy to deploy the applications to one centralized application server.
- E. Create one AWS CodeCommit repository for each of the application
- F. Use AWS CodeBuild to build the applications one at a time
- G. Use AWS CodeDeploy to deploy the applications to one centralized application server.
- H. Create one AWS CodeCommit repository for each of the application
- I. Use AWS CodeBuild to build the applications one at a time and to create one AMI for each server
- J. Use AWS CloudFormation StackSets to automatically provision and decommission Amazon EC2 fleets by using these AMIs.
- K. Create one AWS CodeCommit repository for each of the application
- L. Use AWS CodeBuild to build one Docker image for each application in Amazon Elastic Container Registry (Amazon ECR). Use AWS CodeDeploy to deploy the applications to Amazon Elastic Container Service (Amazon ECS) on infrastructure that AWS Fargate manages.

Answer: D

Explanation:

because of "as few maintenance tasks as possible on the underlying infrastructure". Fargate does that better than "one centralized application server"

NEW QUESTION 73

A company provides an application to customers. The application has an Amazon API Gateway REST API that invokes an AWS Lambda function. On initialization, the Lambda function loads a large amount of data from an Amazon DynamoDB table. The data load process results in long cold-start times of 8-10 seconds. The DynamoDB table has DynamoDB Accelerator (DAX) configured.

Customers report that the application intermittently takes a long time to respond to requests. The application receives thousands of requests throughout the day. In the middle of the day, the application experiences 10 times more requests than at any other time of the day. Near the end of the day, the application's request volume decreases to 10% of its normal total.

A DevOps engineer needs to reduce the latency of the Lambda function at all times of the day. Which solution will meet these requirements?

- A. Configure provisioned concurrency on the Lambda function with a concurrency value of 1. Delete the DAX cluster for the DynamoDB table.
- B. Configure reserved concurrency on the Lambda function with a concurrency value of 0.
- C. Configure provisioned concurrency on the Lambda function.
- D. Configure AWS Application Auto Scaling on the Lambda function with provisioned concurrency values set to a minimum of 1 and a maximum of 100.
- E. Configure reserved concurrency on the Lambda function.
- F. Configure AWS Application Auto Scaling on the API Gateway API with a reserved concurrency maximum value of 100.

Answer: C

Explanation:

The following are the steps that the DevOps engineer should take to reduce the latency of the Lambda function at all times of the day:

? Configure provisioned concurrency on the Lambda function.

? Configure AWS Application Auto Scaling on the Lambda function with provisioned concurrency values set to a minimum of 1 and a maximum of 100.

The provisioned concurrency setting ensures that there is always a minimum number of Lambda function instances available to handle requests. The Application Auto Scaling setting will automatically scale the number of Lambda function instances up or down based on the demand for the application.

This solution will ensure that the Lambda function is able to handle the increased load during the middle of the day, while also keeping the cold-start latency low.

The following are the reasons why the other options are not correct:

? Option A is incorrect because it will not reduce the cold-start latency of the Lambda function.

? Option B is incorrect because it will not scale the number of Lambda function instances up or down based on demand.

? Option D is incorrect because it will only configure reserved concurrency on the API Gateway API, which will not affect the Lambda function.

NEW QUESTION 74

A company requires its developers to tag all Amazon Elastic Block Store (Amazon EBS) volumes in an account to indicate a desired backup frequency. This requirement includes EBS volumes that do not require backups. The company uses custom tags named Backup_Frequency that have values of none, daily, or weekly that correspond to the desired backup frequency. An audit finds that developers are occasionally not tagging the EBS volumes.

A DevOps engineer needs to ensure that all EBS volumes always have the Backup_Frequency tag so that the company can perform backups at least weekly unless a different value is specified.

Which solution will meet these requirements?

- A. Set up AWS Config in the account.
- B. Create a custom rule that returns a compliance failure for all Amazon EC2 resources that do not have a Backup Frequency tag applied. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- C. Set up AWS Config in the account.
- D. Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied.
- E. Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- F. Turn on AWS CloudTrail in the account.
- G. Create an Amazon EventBridge rule that reacts to EBS CreateVolume event.
- H. Configure a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- I. Specify the runbook as the target of the rule.
- J. Turn on AWS CloudTrail in the account.
- K. Create an Amazon EventBridge rule that reacts to EBS CreateVolume events or EBS ModifyVolume event.
- L. Configure a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.
- M. Specify the runbook as the target of the rule.

Answer: B

Explanation:

The following are the steps that the DevOps engineer should take to ensure that all EBS volumes always have the Backup_Frequency tag so that the company can perform backups at least weekly unless a different value is specified:

? Set up AWS Config in the account.

? Use a managed rule that returns a compliance failure for EC2::Volume resources that do not have a Backup Frequency tag applied.

? Configure a remediation action that uses a custom AWS Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly.

The managed rule AWS::Config::EBSVolumesWithoutBackupTag will return a compliance failure for any EBS volume that does not have the Backup_Frequency tag applied. The remediation action will then use the Systems Manager Automation runbook to apply the Backup_Frequency tag with a value of weekly to the EBS volume.

NEW QUESTION 76

An ecommerce company is receiving reports that its order history page is experiencing delays in reflecting the processing status of orders. The order processing system consists of an AWS Lambda function that uses reserved concurrency. The Lambda function processes order messages from an Amazon Simple Queue Service (Amazon SQS) queue and inserts processed orders into an Amazon DynamoDB table. The DynamoDB table has auto scaling enabled for read and write capacity.

Which actions should a DevOps engineer take to resolve this delay? (Choose two.)

- A. Check the ApproximateAgeOfOldestMessage metric for the SQS queue.
- B. Increase the Lambda function concurrency limit.
- C. Check the ApproximateAgeOfOldestMessage metric for the SQS queue. Configure a redrive policy on the SQS queue.
- D. Check the NumberOfMessagesSent metric for the SQS queue.
- E. Increase the SQS queue visibility timeout.
- F. Check the WriteThrottleEvents metric for the DynamoDB table.
- G. Increase the maximum write capacity units (WCUs) for the table's scaling policy.
- H. Check the Throttles metric for the Lambda function.
- I. Increase the Lambda function timeout.

Answer: AD

Explanation:

A: If the ApproximateAgeOfOldestMessages indicate that orders are remaining in the SQS queue for longer than expected, the reserved concurrency limit may be set too small to keep up with the number of orders entering the queue and is being throttled. D: The DynamoDB table is using Auto Scaling. With Auto Scaling, you

create a scaling policy that specifies whether you want to scale read capacity or write capacity (or both), and the minimum and maximum provisioned capacity unit settings for the table. The ThrottledWriteRequests metric will indicate if there is a throttling issue on the DynamoDB table, which can be resolved by increasing the maximum write capacity units for the table's Auto Scaling policy. <https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/AutoScaling.html>

NEW QUESTION 80

A DevOps engineer needs to configure a blue green deployment for an existing three-tier application. The application runs on Amazon EC2 instances and uses an Amazon RDS database. The EC2 instances run behind an Application Load Balancer (ALB) and are in an Auto Scaling group.

The DevOps engineer has created a launch template and an Auto Scaling group for the blue environment. The DevOps engineer also has created a launch template and an Auto Scaling group for the green environment. Each Auto Scaling group deploys to a matching blue or green target group. The target group also specifies which software blue or green gets loaded on the EC2 instances. The ALB can be configured to send traffic to the blue environment's target group or the green environment's target group. An Amazon Route 53 record for `www.example.com` points to the ALB.

The deployment must move traffic all at once between the software on the blue environment's EC2 instances to the newly deployed software on the green environment's EC2 instances.

What should the DevOps engineer do to meet these requirements?

- A. Start a rolling restart to the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances. When the rolling restart is complete, use an AWS CLI command to update the ALB to send traffic to the green environment's target group.
- B. Use an AWS CLI command to update the ALB to send traffic to the green environment's target group.
- C. Then start a rolling restart of the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances.
- D. Update the launch template to deploy the green environment's software on the blue environment's EC2 instances. Keep the target groups and Auto Scaling groups unchanged in both environments. Perform a rolling restart of the blue environment's EC2 instances.
- E. Start a rolling restart of the Auto Scaling group for the green environment to deploy the new software on the green environment's EC2 instances. When the rolling restart is complete, update the Route 53 DNS to point to the green environment's endpoint on the ALB.

Answer: A

Explanation:

This solution will meet the requirements because it will use a rolling restart to gradually replace the EC2 instances in the green environment with new instances that have the new software version installed. A rolling restart is a process that terminates and launches instances in batches, ensuring that there is always a minimum number of healthy instances in service. This way, the green environment can be updated without affecting the availability or performance of the application. When the rolling restart is complete, the DevOps engineer can use an AWS CLI command to modify the listener rules of the ALB and change the default action to forward traffic to the green environment's target group. This will switch the traffic from the blue environment to the green environment all at once, as required by the question.

NEW QUESTION 84

A DevOps engineer is working on a project that is hosted on Amazon Linux and has failed a security review. The DevOps manager has been asked to review the company `buildspec.yaml` file for an AWS CodeBuild project and provide recommendations. The `buildspec.yaml` file is configured as follows:

```
env:
  variables:
    AWS_ACCESS_KEY_ID: AKIAJF7BRFWJBA4GHXNA
    AWS_SECRET_ACCESS_KEY: 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
    AWS_DEFAULT_REGION: us-east-1
    DB_PASSWORD: cuj5RptFa3va
  phases:
    build:
      commands:
        - aws s3 cp s3://db-deploy-bucket/my.cnf.template /tmp/my.cnf
        - sed -i '' s/DB_PW/${DB_PASSWORD}/ /tmp/my.cnf
        - aws s3 cp s3://db-deploy-bucket/instance.key /tmp/instance.key
        - chmod 600 /tmp/instance.key
        - scp -i /tmp/instance.key /tmp/my.cnf root@10.25.15.23:/etc/my.cnf
        - ssh -i /tmp/instance.key root@10.25.15.23 /etc/init.d/mysqld restart
```

What changes should be recommended to comply with AWS security best practices? (Select THREE.)

- A. Add a post-build command to remove the temporary files from the container before termination to ensure they cannot be seen by other CodeBuild users.
- B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable.
- C. Store the `db_password` as a SecureString value in AWS Systems Manager Parameter Store and then remove the `db_password` from the environment variables.
- D. Move the environment variables to the 'db-deploy-bucket' Amazon S3 bucket, add a prebuild stage to download then export the variables.
- E. Use AWS Systems Manager `run` command versus `scp` and `ssh` commands directly to the instance.

Answer: BCE

Explanation:

B. Update the CodeBuild project role with the necessary permissions and then remove the AWS credentials from the environment variable. C. Store the `DB_PASSWORD` as a SecureString value in AWS Systems Manager Parameter Store and then remove the `DB_PASSWORD` from the environment variables. E. Use AWS Systems Manager `run` command versus `scp` and `ssh` commands directly to the instance.

NEW QUESTION 86

A company runs its container workloads in AWS App Runner. A DevOps engineer manages the company's container repository in Amazon Elastic Container Registry (Amazon ECR).

The DevOps engineer must implement a solution that continuously monitors the container repository. The solution must create a new container image when the solution detects an operating system vulnerability or language package vulnerability.

Which solution will meet these requirements?

- A. Use EC2 Image Builder to create a container image pipeline.
- B. Use Amazon ECR as the target repository.
- C. Turn on enhanced scanning on the ECR repository.
- D. Create an Amazon EventBridge rule to capture an Inspector2 finding even

- E. Use the event to invoke the image pipeline
- F. Re-upload the container to the repository.
- G. Use EC2 Image Builder to create a container image pipeline
- H. Use Amazon ECR as the target repository
- I. Enable Amazon GuardDuty Malware Protection on the container workload
- J. Create an Amazon EventBridge rule to capture a GuardDuty finding event
- K. Use the event to invoke the image pipeline.
- L. Create an AWS CodeBuild project to create a container image
- M. Use Amazon ECR as the target repository
- N. Turn on basic scanning on the repository
- O. Create an Amazon EventBridge rule to capture an ECR image action event
- P. Use the event to invoke the CodeBuild project
- Q. Re-upload the container to the repository.
- R. Create an AWS CodeBuild project to create a container image
- S. Use Amazon ECR as the target repository
- T. Configure AWS Systems Manager Compliance to scan all managed nodes
- . Create an Amazon EventBridge rule to capture a configuration compliance state change event
- . Use the event to invoke the CodeBuild project.

Answer: A

Explanation:

The solution that meets the requirements is to use EC2 Image Builder to create a container image pipeline, use Amazon ECR as the target repository, turn on enhanced scanning on the ECR repository, create an Amazon EventBridge rule to capture an Inspector2 finding event, and use the event to invoke the image pipeline. Re-upload the container to the repository.

This solution will continuously monitor the container repository for vulnerabilities using enhanced scanning, which is a feature of Amazon ECR that provides detailed information and guidance on how to fix security issues found in your container images. Enhanced scanning uses Inspector2, a security assessment service that integrates with Amazon ECR and generates findings for any vulnerabilities detected in your images. You can use Amazon EventBridge to create a rule that triggers an action when an Inspector2 finding event occurs. The action can be to invoke an EC2 Image Builder pipeline, which is a service that automates the creation of container images. The pipeline can use the latest patches and updates to build a new container image and upload it to the same ECR repository, replacing the vulnerable image.

The other options are not correct because they do not meet all the requirements or use services that are not relevant for the scenario.

Option B is not correct because it uses Amazon GuardDuty Malware Protection, which is a feature of GuardDuty that detects malicious activity and unauthorized behavior on your AWS accounts and resources. GuardDuty does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

Option C is not correct because it uses basic scanning on the ECR repository, which only provides a summary of the vulnerabilities found in your container images. Basic scanning does not use Inspector2 or generate findings that can be captured by Amazon EventBridge. Moreover, basic scanning does not provide guidance on how to fix the vulnerabilities.

Option D is not correct because it uses AWS Systems Manager Compliance, which is a feature of Systems Manager that helps you monitor and manage the compliance status of your AWS resources based on AWS Config rules and AWS Security Hub standards. Systems Manager Compliance does not scan container images for vulnerabilities, nor does it integrate with Amazon ECR or EC2 Image Builder.

NEW QUESTION 87

A company hosts applications in its AWS account. Each application logs to an individual Amazon CloudWatch log group. The company's CloudWatch costs for ingestion are increasing.

A DevOps engineer needs to identify which applications are the source of the increased logging costs.

Which solution will meet these requirements?

- A. Use CloudWatch metrics to create a custom expression that identifies the CloudWatch log groups that have the most data being written to them.
- B. Use CloudWatch Logs Insights to create a set of queries for the application log groups to identify the number of logs written for a period of time.
- C. Use AWS Cost Explorer to generate a cost report that details the cost for CloudWatch usage.
- D. Use AWS CloudTrail to filter for CreateLogStream events for each application.

Answer: C

Explanation:

The correct answer is C.

A comprehensive and detailed explanation is:

? Option A is incorrect because using CloudWatch metrics to create a custom expression that identifies the CloudWatch log groups that have the most data being written to them is not a valid solution. CloudWatch metrics do not provide information about the size or volume of data being ingested by CloudWatch logs. CloudWatch metrics only provide information about the number of events, bytes, and errors that occur within a log group or stream. Moreover, creating a custom expression with CloudWatch metrics would require using the search_web tool, which is not necessary for this use case.

? Option B is incorrect because using CloudWatch Logs Insights to create a set of queries for the application log groups to identify the number of logs written for a period of time is not a valid solution. CloudWatch Logs Insights can help analyze and filter log events based on patterns and expressions, but it does not provide information about the cost or billing of CloudWatch logs. CloudWatch Logs Insights also charges based on the amount of data scanned by each query, which could increase the logging costs further.

? Option C is correct because using AWS Cost Explorer to generate a cost report that details the cost for CloudWatch usage is a valid solution. AWS Cost Explorer is a tool that helps visualize, understand, and manage AWS costs and usage over time. AWS Cost Explorer can generate custom reports that show the breakdown of costs by service, region, account, tag, or any other dimension. AWS Cost Explorer can also filter and group costs by usage type, which can help identify the specific CloudWatch log groups that are the source of the increased logging costs.

? Option D is incorrect because using AWS CloudTrail to filter for CreateLogStream events for each application is not a valid solution. AWS CloudTrail is a service that records API calls and account activity for AWS services, including CloudWatch logs. However, AWS CloudTrail does not provide information about the cost or billing of CloudWatch logs. Filtering for CreateLogStream events would only show when a new log stream was created within a log group, but not how much data was ingested or stored by that log stream.

References:

- ? CloudWatch Metrics
- ? CloudWatch Logs Insights
- ? AWS Cost Explorer
- ? AWS CloudTrail

NEW QUESTION 91

A company has an application that is using a MySQL-compatible Amazon Aurora Multi-AZ DB cluster as the database. A cross-Region read replica has been created for disaster recovery purposes. A DevOps engineer wants to automate the promotion of the replica so it becomes the primary database instance in the event of a failure.

Which solution will accomplish this?

- A. Configure a latency-based Amazon Route 53 CNAME with health checks so it points to both the primary and replica endpoint
- B. Subscribe an Amazon SNS topic to Amazon RDS failure notifications from AWS CloudTrail and use that topic to invoke an AWS Lambda function that will promote the replica instance as the primary.
- C. Create an Aurora custom endpoint to point to the primary database instance
- D. Configure the application to use this endpoint
- E. Configure AWS CloudTrail to run an AWS Lambda function to promote the replica instance and modify the custom endpoint to point to the newly promoted instance.
- F. Create an AWS Lambda function to modify the application's AWS CloudFormation template to promote the replica, apply the template to update the stack, and point the application to the newly promoted instance
- G. Create an Amazon CloudWatch alarm to invoke this Lambda function after the failure event occurs.
- H. Store the Aurora endpoint in AWS Systems Manager Parameter Store
- I. Create an Amazon EventBridge event that detects the database failure and runs an AWS Lambda function to promote the replica instance and update the endpoint URL stored in AWS Systems Manager Parameter Store
- J. Code the application to reload the endpoint from Parameter Store if a database connection fails.

Answer: D

Explanation:

EventBridge is needed to detect the database failure. Lambda is needed to promote the replica as it's in another Region (manual promotion, otherwise). Storing and updating the endpoint in Parameter store is important in updating the application. Look at High Availability section of Aurora FAQ: <https://aws.amazon.com/rds/aurora/faqs/>

NEW QUESTION 94

A company needs to ensure that flow logs remain configured for all existing and new VPCs in its AWS account. The company uses an AWS CloudFormation stack to manage its VPCs. The company needs a solution that will work for any VPCs that any IAM user creates.

Which solution will meet these requirements?

- A. Add the resource to the CloudFormation stack that creates the VPCs.
- B. Create an organization in AWS Organization
- C. Add the company's AWS account to the organization
- D. Create an SCP to prevent users from modifying VPC flow logs.
- E. Turn on AWS Config
- F. Create an AWS Config rule to check whether VPC flow logs are turned on
- G. Configure automatic remediation to turn on VPC flow logs.
- H. Create an IAM policy to deny the use of API calls for VPC flow log
- I. Attach the IAM policy to all IAM users.

Answer: C

Explanation:

To meet the requirements of ensuring that flow logs remain configured for all existing and new VPCs in the AWS account, the company should use AWS Config and automatic remediation. AWS Config is a service that enables customers to assess, audit, and evaluate the configurations of their AWS resources. AWS Config continuously monitors and records the configuration changes of the AWS resources and evaluates them against desired configurations. Customers can use AWS Config rules to define the desired configuration state of their AWS resources and trigger actions when a resource configuration violates a rule. One of the AWS Config rules that customers can use is `vpc-flow-logs-enabled`, which checks whether VPC flow logs are enabled for all VPCs in an AWS account. Customers can also configure automatic remediation for this rule, which means that AWS Config will automatically enable VPC flow logs for any VPCs that do not have them enabled. Customers can specify the destination (CloudWatch Logs or S3) and the traffic type (all, accept, or reject) for the flow logs as remediation parameters. By using AWS Config and automatic remediation, the company can ensure that flow logs remain configured for all existing and new VPCs in its AWS account, regardless of who creates them or how they are created.

The other options are not correct because they do not meet the requirements or follow best practices. Adding the resource to the CloudFormation stack that creates the VPCs is not a sufficient solution because it will only work for VPCs that are created by using the CloudFormation stack. It will not work for VPCs that are created by using other methods, such as the console or the API. Creating an organization in AWS Organizations and creating an SCP to prevent users from modifying VPC flow logs is not a good solution because it will not ensure that flow logs are enabled for all VPCs in the first place. It will only prevent users from disabling or changing flow logs after they are enabled. Creating an IAM policy to deny the use of API calls for VPC flow logs and attaching it to all IAM users is not a valid solution because it will prevent users from enabling or disabling flow logs at all.

It will also not work for VPCs that are created by using other methods, such as the console or CloudFormation.

References:

- ? 1: `AWS::EC2::FlowLog` - AWS CloudFormation
- ? 2: Amazon VPC Flow Logs extends CloudFormation Support to custom format subscriptions, 1-minute aggregation intervals and tagging
- ? 3: Logging IP traffic using VPC Flow Logs - Amazon Virtual Private Cloud
- ? : About AWS Config - AWS Config
- ? : `vpc-flow-logs-enabled` - AWS Config
- ? : Remediate Noncompliant Resources with AWS Config Rules - AWS Config

NEW QUESTION 95

A company has a guideline that every Amazon EC2 instance must be launched from an AMI that the company's security team produces. Every month the security team sends an email message with the latest approved AMIs to all the development teams.

The development teams use AWS CloudFormation to deploy their applications. When developers launch a new service they have to search their email for the latest AMIs that the security department sent. A DevOps engineer wants to automate the process that the security team uses to provide the AMI IDs to the development teams.

What is the MOST scalable solution that meets these requirements?

- A. Direct the security team to use CloudFormation to create new versions of the AMIs and to list the AMI ARNs in an encrypted Amazon S3 object as part of the stack's Outputs Section. Instruct the developers to use a cross-stack reference to load the encrypted S3 object and obtain the most recent AMI ARNs.
- B. Direct the security team to use a CloudFormation stack to create an AWS CodePipeline pipeline that builds new AMIs and places the latest AMI ARNs in an encrypted Amazon S3 object as part of the pipeline output. Instruct the developers to use a cross-stack reference within their own CloudFormation template to

obtain the S3 object location and the most recent AMI ARNs.

- C. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to place the AMI ARNs as parameters in AWS Systems Manager Parameter Store. Instruct the developers to specify a parameter of type SSM in their CloudFormation stack to obtain the most recent AMI ARNs from Parameter Store.
- D. Direct the security team to use Amazon EC2 Image Builder to create new AMIs and to create an Amazon Simple Notification Service (Amazon SNS) topic so that every development team can receive notification
- E. When the development teams receive a notification instruct them to write an AWS Lambda function that will update their CloudFormation stack with the most recent AMI ARNs.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/dynamic-references.html>

NEW QUESTION 98

A company hosts a security auditing application in an AWS account. The auditing application uses an IAM role to access other AWS accounts. All the accounts are in the same organization in AWS Organizations.

A recent security audit revealed that users in the audited AWS accounts could modify or delete the auditing application's IAM role. The company needs to prevent any modification to the auditing application's IAM role by any entity other than a trusted administrator IAM role.

Which solution will meet these requirements?

- A. Create an SCP that includes a Deny statement for changes to the auditing application's IAM role
- B. Include a condition that allows the trusted administrator IAM role to make change
- C. Attach the SCP to the root of the organization.
- D. Create an SCP that includes an Allow statement for changes to the auditing application's IAM role by the trusted administrator IAM role
- E. Include a Deny statement for changes by all other IAM principal
- F. Attach the SCP to the IAM service in each AWS account where the auditing application has an IAM role.
- G. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role
- H. Include a condition that allows the trusted administrator IAM role to make change
- I. Attach the permissions boundary to the audited AWS accounts.
- J. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role
- K. Include a condition that allows the trusted administrator IAM role to make change
- L. Attach the permissions boundary to the auditing application's IAM role in the AWS accounts.

Answer: A

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html?icmpid=docs_orgs_console

SCPs (Service Control Policies) are the best way to restrict permissions at the organizational level, which in this case would be used to restrict modifications to the IAM role used by the auditing application, while still allowing trusted administrators to make changes to it. Options C and D are not as effective because IAM permission boundaries are applied to IAM entities (users, groups, and roles), not the account itself, and must be applied to all IAM entities in the account.

NEW QUESTION 102

A company is hosting a web application in an AWS Region. For disaster recovery purposes, a second region is being used as a standby. Disaster recovery requirements state that session data must be replicated between regions in near-real time and 1% of requests should route to the secondary region to continuously verify system functionality. Additionally, if there is a disruption in service in the main region, traffic should be automatically routed to the secondary region, and the secondary region must be able to scale up to handle all traffic.

How should a DevOps engineer meet these requirements?

- A. In both regions, deploy the application on AWS Elastic Beanstalk and use Amazon DynamoDB global tables for session data
- B. Use an Amazon Route 53 weighted routing policy with health checks to distribute the traffic across the regions.
- C. In both regions, launch the application in Auto Scaling groups and use DynamoDB for session data
- D. Use a Route 53 failover routing policy with health checks to distribute the traffic across the regions.
- E. In both regions, deploy the application in AWS Lambda, exposed by Amazon API Gateway, and use Amazon RDS for PostgreSQL with cross-region replication for session data
- F. Deploy the web application with client-side logic to call the API Gateway directly.
- G. In both regions, launch the application in Auto Scaling groups and use DynamoDB global tables for session data
- H. Enable an Amazon CloudFront weighted distribution across region
- I. Point the Amazon Route 53 DNS record at the CloudFront distribution.

Answer: D

NEW QUESTION 104

A company manages multiple AWS accounts in AWS Organizations. The company's security policy states that AWS account root user credentials for member accounts must not be used. The company monitors access to the root user credentials.

A recent alert shows that the root user in a member account launched an Amazon EC2 instance. A DevOps engineer must create an SCP at the organization's root level that will prevent the root user in member accounts from making any AWS service API calls.

Which SCP will meet these requirements?

A)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringNotLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

B)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Principal": { "AWS": "arn:aws:iam::*:root" }
    }
  ]
}
```

C)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "*",
      "Resource": "*",
      "Condition": {
        "StringLike": { "aws:PrincipalArn": "arn:aws:iam::*:root" }
      }
    }
  ]
}
```

D)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*",
      "Principal": "root"
    }
  ]
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 108

A company wants to use a grid system for a proprietary enterprise m-memory data store on top of AWS. This system can run in multiple server nodes in any Linux-based distribution. The system must be able to reconfigure the entire cluster every time a node is added or removed. When adding or removing nodes an `/etc./cluster/nodes` config file must be updated listing the IP addresses of the current node members of that cluster.

The company wants to automate the task of adding new nodes to a cluster. What can a DevOps engineer do to meet these requirements?

- A. Use AWS OpsWorks Stacks to layer the server nodes of that cluste
- B. Create a Chef recipe that populates the content of the `/etc./cluster/nodes` config file and restarts the service by using the current members of the laye
- C. Assign that recipe to the Configure lifecycle event.
- D. Put the file nodes config in version contro
- E. Create an AWS CodeDeploy deployment configuration and deployment group based on an Amazon EC2 tag value for thecluster node
- F. When adding a new node to the cluster update the file with all tagged instances and make a commit in version contro
- G. Deploy the new file and restart the services.
- H. Create an Amazon S3 bucket and upload a version of the `/etc./cluster/nodes` config file Create a crontab script that will poll for that S3 file and download it frequentl
- I. Use a process manager such as Monit or system, to restart the cluster services when it detects that the new file was modifie
- J. When adding a node to the cluster edit the file's most recent members Upload the new file to the S3 bucket.
- K. Create a user data script that lists all members of the current security group of the cluster and automatically updates the `/etc/cluster/.` nodes confi
- L. Tile whenever a new instance is added to the cluster.

Answer: A

Explanation:

You can run custom recipes manually, but the best approach is usually to have AWS OpsWorks Stacks run them automatically. Every layer has a set of built-in recipes assigned each of five lifecycle events—Setup, Configure, Deploy, Undeploy, and Shutdown. Each time an event occurs for an instance, AWS OpsWorks Stacks runs the associated recipes for each of the instance's layers, which handle the corresponding tasks. For example, when an instance finishes booting, AWS OpsWorks Stacks triggers a Setup event. This event runs the associated layer's Setup recipes, which typically handle tasks such as installing and configuring packages

NEW QUESTION 110

A development team wants to use AWS CloudFormation stacks to deploy an application. However, the developer IAM role does not have the required permissions to provision the resources that are specified in the AWS CloudFormation template. A DevOps engineer needs to implement a solution that allows the developers to deploy the stacks. The solution must follow the principle of least privilege.

Which solution will meet these requirements?

- A. Create an IAM policy that allows the developers to provision the required resource
- B. Attach the policy to the developer IAM role.
- C. Create an IAM policy that allows full access to AWS CloudFormatio
- D. Attach the policy to the developer IAM role.
- E. Create an AWS CloudFormation service role that has the required permission
- F. Grant the developer IAM role a `cloudformation:* actio`
- G. Use the new service role during stack deployments.
- H. Create an AWS CloudFormation service role that has the required permission
- I. Grant the developer IAM role the `iam:PassRole` permissio
- J. Use the new service role during stack deployments.

Answer: D

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-iam-servicerole.html>

NEW QUESTION 114

A DevOps engineer is architecting a continuous development strategy for a company's software as a service (SaaS) web application running on AWS. For application and security reasons users subscribing to this application are distributed across multiple. Application Load Balancers (ALBs) each of which has a dedicated Auto Scaling group and fleet of Amazon EC2 instances The application does not require a build stage and when it is committed to AWS CodeCommit, the application must trigger a simultaneous deployment to all ALBs Auto Scaling groups and EC2 fleets.

Which architecture will meet these requirements with the LEAST amount of configuration?

- A. Create a single AWS CodePipeline pipeline that deploys the application in parallel using unique AWS CodeDeploy applications and deployment groups created for each ALB-Auto Scaling group pair.
- B. Create a single AWS CodePipeline pipeline that deploys the application using a single AWS CodeDeploy application and single deployment group.
- C. Create a single AWS CodePipeline pipeline that deploys the application in parallel using a single AWS CodeDeploy application and unique deployment group for each ALB-Auto Scaling group pair.
- D. Create an AWS CodePipeline pipeline for each ALB-Auto Scaling group pair that deploys the application using an AWS CodeDeploy application and deployment group created for the same ALB-Auto Scaling group pair.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/deployment-groups.html>

NEW QUESTION 118

A company uses AWS Secrets Manager to store a set of sensitive API keys that an AWS Lambda function uses. When the Lambda function is invoked, the Lambda function retrieves the API keys and makes an API call to an external service. The Secrets Manager secret is encrypted with the default AWS Key Management Service (AWS KMS) key.

A DevOps engineer needs to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege.

Which combination of steps will meet these requirements? (Select TWO.)

- A. Update the default KMS key for Secrets Manager to allow only the Lambda function's execution role to decrypt.

- B. Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt
- C. Update Secrets Manager to use the new customer managed key.
- D. Create a KMS customer managed key that trusts Secrets Manager and allows the account's :root principal to decrypt
- E. Update Secrets Manager to use the new customer managed key.
- F. Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level
- G. Configure the permissions so that the KMS key can encrypt the Secrets Manager secret.
- H. Remove all KMS permissions from the Lambda function's execution role.

Answer: BD

Explanation:

The requirement is to update the infrastructure to ensure that only the Lambda function's execution role can access the values in Secrets Manager. The solution must apply the principle of least privilege, which means granting the minimum permissions necessary to perform a task.

To do this, the DevOps engineer needs to use the following steps:

? Create a KMS customer managed key that trusts Secrets Manager and allows the Lambda function's execution role to decrypt. A customer managed key is a symmetric encryption key that is fully managed by the customer. The customer can define the key policy, which specifies who can use and manage the key. By creating a customer managed key, the DevOps engineer can restrict the decryption permission to only the Lambda function's execution role, and prevent other principals from accessing the secret values. The customer managed key also needs to trust Secrets Manager, which means allowing Secrets Manager to use the key to encrypt and decrypt secrets on behalf of the customer.

? Update Secrets Manager to use the new customer managed key. Secrets Manager allows customers to choose which KMS key to use for encrypting each secret. By default, Secrets Manager uses the default KMS key for Secrets Manager, which is a service-managed key that is shared by all customers in the same AWS Region. By updating Secrets Manager to use the new customer managed key, the DevOps engineer can ensure that only the Lambda function's execution role can decrypt the secret values using that key.

? Ensure that the Lambda function's execution role has the KMS permissions scoped on the resource level. The Lambda function's execution role is an IAM role that grants permissions to the Lambda function to access AWS services and resources. The role needs to have KMS permissions to use the customer managed key for decryption. However, to apply the principle of least privilege, the role should have the permissions scoped on the resource level, which means specifying the ARN of the customer managed key as a condition in the IAM policy statement. This way, the role can only use that specific key and not any other KMS keys in the account.

NEW QUESTION 120

A developer is maintaining a fleet of 50 Amazon EC2 Linux servers. The servers are part of an Amazon EC2 Auto Scaling group, and also use Elastic Load Balancing for load balancing.

Occasionally, some application servers are being terminated after failing ELB HTTP health checks. The developer would like to perform a root cause analysis on the issue, but before being able to access application logs, the server is terminated.

How can log collection be automated?

- A. Use Auto Scaling lifecycle hooks to put instances in a Pending:Wait stat
- B. Create an Amazon CloudWatch alarm for EC2 Instance Terminate Successful and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- C. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- D. Create an AWS Config rule for EC2 Instance-terminate Lifecycle Action and trigger a step function that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- E. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- F. Create an Amazon CloudWatch subscription filter for EC2 Instance Terminate Successful and trigger a CloudWatch agent that invokes a script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.
- G. Use Auto Scaling lifecycle hooks to put instances in a Terminating:Wait stat
- H. Create an Amazon EventBridge rule for EC2 Instance-terminate Lifecycle Action and trigger an AWS Lambda function that invokes an SSM Run Command script to collect logs, push them to Amazon S3, and complete the lifecycle action once logs are collected.

Answer: D

Explanation:

<https://blog.fourninecloud.com/auto-scaling-lifecycle-hooks-to-export-server-logs-when-instance-terminating-58e06d7c0d6a>

NEW QUESTION 123

A company has an application that includes AWS Lambda functions. The Lambda functions run Python code that is stored in an AWS CodeCommit repository. The company has recently experienced failures in the production environment because of an error in the Python code. An engineer has written unit tests for the Lambda functions to help avoid releasing any future defects into the production environment.

The company's DevOps team needs to implement a solution to integrate the unit tests into an existing AWS CodePipeline pipeline. The solution must produce reports about the unit tests for the company to view.

Which solution will meet these requirements?

- A. Associate the CodeCommit repository with Amazon CodeGuru Review
- B. Create a new AWS CodeBuild projec
- C. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild projec
- D. Create a buildspec.yml file in the CodeCommit repositor
- E. In the buildspec.yml file, define the actions to run a CodeGuru review.
- F. Create a new AWS CodeBuild projec
- G. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild projec
- H. Create a CodeBuild report grou
- I. Create a buildspec.yml file in the CodeCommit repositor
- J. In the buildspec.yml file, define the actions to run the unit tests with an output of JUNITXML in the build phase section. Configure the test reports to be uploaded to the new CodeBuild report group.
- K. Create a new AWS CodeArtifact repositor
- L. Create a new AWS CodeBuild projec
- M. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild projec
- N. Create an appspec.yml file in the original CodeCommit repositor
- O. In the appspec.yml file, define the actions to run the unit tests with an output of CUCUMBERJSON in the build phase sectio
- P. Configure the tests reports to be sent to the new CodeArtifact repository.
- Q. Create a new AWS CodeBuild projec
- R. In the CodePipeline pipeline, configure a test stage that uses the new CodeBuild projec

- S. Create a new Amazon S3 bucket
- T. Create a buildspec.yml file in the CodeCommit repository
- . In the buildspec.yml file, define the actions to run the unit tests with an output of HTML in the phases section
- . In the reports section, upload the test reports to the S3 bucket.

Answer: B

Explanation:

The correct answer is B. Creating a new AWS CodeBuild project and configuring a test stage in the AWS CodePipeline pipeline that uses the new CodeBuild project is the best way to integrate the unit tests into the existing pipeline. Creating a CodeBuild report group and uploading the test reports to the new CodeBuild report group will produce reports about the unit tests for the company to view. Using JUNITXML as the output format for the unit tests is supported by CodeBuild and will generate a valid report. Option A is incorrect because Amazon CodeGuru Reviewer is a service that provides automated code reviews and recommendations for improving code quality and performance. It is not a tool for running unit tests or producing test reports. Therefore, option A will not meet the requirements.

Option C is incorrect because AWS CodeArtifact is a service that provides secure, scalable, and cost-effective artifact management for software development. It is not a tool for running unit tests or producing test reports. Moreover, option C uses CUCUMBERJSON as the output format for the unit tests, which is not supported by CodeBuild and will not generate a valid report.

Option D is incorrect because uploading the test reports to an Amazon S3 bucket is not the best way to produce reports about the unit tests for the company to view. CodeBuild has a built-in feature to create and manage test reports, which is more convenient and efficient than using S3. Furthermore, option D uses HTML as the output format for the unit tests, which is not supported by CodeBuild and will not generate a valid report.

NEW QUESTION 127

A business has an application that consists of five independent AWS Lambda functions.

The DevOps engineer has built a CI/CD pipeline using AWS CodePipeline and AWS CodeBuild that builds test packages and deploys each Lambda function in sequence. The pipeline uses an Amazon EventBridge rule to ensure the pipeline starts as quickly as possible after a change is made to the application source code.

After working with the pipeline for a few months the DevOps engineer has noticed the pipeline takes too long to complete.

What should the DevOps engineer implement to BEST improve the speed of the pipeline?

- A. Modify the CodeBuild projects within the pipeline to use a compute type with more available network throughput.
- B. Create a custom CodeBuild execution environment that includes a symmetric multiprocessing configuration to run the builds in parallel.
- C. Modify the CodePipeline configuration to run actions for each Lambda function in parallel by specifying the same runorder.
- D. Modify each CodeBuild project to run within a VPC and use dedicated instances to increase throughput.

Answer: C

Explanation:

<https://docs.aws.amazon.com/codepipeline/latest/userguide/reference-pipeline-structure.html>

AWS doc: "To specify parallel actions, use the same integer for each action you want to run in parallel. For example, if you want three actions to run in sequence in a stage, you would give the first action the runOrder value of 1, the second action the runOrder value of 2, and the third the runOrder value of 3. However, if you want the second and third actions to run in parallel, you would give the first action the runOrder value of 1 and both the second and third actions the runOrder value of 2."

NEW QUESTION 131

A company is divided into teams. Each team has an AWS account and all the accounts are in an organization in AWS Organizations. Each team must retain full administrative rights to its AWS account. Each team also must be allowed to access only AWS services that the company approves for use. AWS services must gain approval through a request and approval process.

How should a DevOps engineer configure the accounts to meet these requirements?

- A. Use AWS CloudFormation StackSets to provision IAM policies in each account to deny access to restricted AWS services
- B. In each account configure AWS Config rules that ensure that the policies are attached to IAM principals in the account.
- C. Use AWS Control Tower to provision the accounts into OUs within the organization. Configure AWS Control Tower to enable AWS IAM Identity Center (AWS Single Sign-On). Configure IAM Identity Center to provide administrative access. Include deny policies on user roles for restricted AWS services.
- D. Place all the accounts under a new top-level OU within the organization. Create an SCP that denies access to restricted AWS services. Attach the SCP to the OU.
- E. Create an SCP that allows access to only approved AWS services
- F. Attach the SCP to the root OU of the organization
- G. Remove the FullAWSAccess SCP from the root OU of the organization.

Answer: C

Explanation:

<https://docs.aws.amazon.com/vpc/latest/userguide/managed-prefix-lists.html> A managed prefix list is a set of one or more CIDR blocks. You can use prefix lists to make it easier to configure and maintain your security groups and route tables. <https://docs.aws.amazon.com/vpc/latest/userguide/sharing-managed-prefix-lists.html> With AWS Resource Access Manager (AWS RAM), the owner of a prefix list can share a prefix list with the following: Specific AWS accounts inside or outside of its organization in AWS Organizations An organizational unit inside its organization in AWS Organizations An entire organization in AWS Organizations

NEW QUESTION 133

A company manages a web application that runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The EC2 instances run in an Auto Scaling group across multiple Availability Zones. The application uses an Amazon RDS for MySQL DB instance to store the data. The company has configured Amazon Route 53 with an alias record that points to the ALB.

A new company guideline requires a geographically isolated disaster recovery (DR) site with an RTO of 4 hours and an RPO of 15 minutes.

Which DR strategy will meet these requirements with the LEAST change to the application stack?

- A. Launch a replica environment of everything except Amazon RDS in a different Availability Zone. Create an RDS read replica in the new Availability Zone and configure the new stack to point to the local RDS DB instance.
- B. Add the new stack to the Route 53 record set by using a health check to configure a failover routing policy.
- C. Launch a replica environment of everything except Amazon RDS in a different AWS Region.
- D. Create an RDS read replica in the new Region and configure the new stack to point to the local RDS DB instance.
- E. Add the new stack to the Route 53 record set by using a health check to configure a latency routing policy.

- F. Launch a replica environment of everything except Amazon RDS in a different AWS Region
- G. In the event of an outage copy and restore the latest RDS snapshot from the primary Region to the DR Region
- H. Adjust the Route 53 record set to point to the ALB in the DR Region.
- I. Launch a replica environment of everything except Amazon RDS in a different AWS Region
- J. Create an RDS read replica in the new Region and configure the new environment to point to the local RDS DB instance
- K. Add the new stack to the Route 53 record set by using a health check to configure a failover routing policy
- L. In the event of an outage promote the read replica to primary.

Answer: D

NEW QUESTION 135

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

DOP-C02 Practice Exam Features:

- * DOP-C02 Questions and Answers Updated Frequently
- * DOP-C02 Practice Questions Verified by Expert Senior Certified Staff
- * DOP-C02 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * DOP-C02 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The DOP-C02 Practice Test Here](#)