

Amazon

Exam Questions AWS-Certified-Advanced-Networking-Specialty

Amazon AWS Certified Advanced Networking - Specialty



NEW QUESTION 1

A network engineer has deployed an Amazon EC2 instance in a private subnet in a VPC. The VPC has no public subnet. The EC2 instance hosts application code that sends messages to an Amazon Simple Queue Service (Amazon SQS) queue. The subnet has the default network ACL with no modification applied. The EC2 instance has the default security group with no modification applied.

The SQS queue is not receiving messages.

Which of the following are possible causes of this problem? (Choose two.)

- A. The EC2 instance is not attached to an IAM role that allows write operations to Amazon SQS.
- B. The security group is blocking traffic to the IP address range used by Amazon SQS
- C. There is no interface VPC endpoint configured for Amazon SQS
- D. The network ACL is blocking return traffic from Amazon SQS
- E. There is no route configured in the subnet route table for the IP address range used by Amazon SQS

Answer: CE

NEW QUESTION 2

A company is running multiple workloads on Amazon EC2 instances in public subnets. In a recent incident, an attacker exploited an application vulnerability on one of the EC2 instances to gain access to the instance. The company fixed the application and launched a replacement EC2 instance that contains the updated application.

The attacker used the compromised application to spread malware over the internet. The company became aware of the compromise through a notification from AWS. The company needs the ability to identify when an application that is deployed on an EC2 instance is spreading malware.

Which solution will meet this requirement with the LEAST operational effort?

- A. Use Amazon GuardDuty to analyze traffic patterns by inspecting DNS requests and VPC flow logs.
- B. Use Amazon GuardDuty to deploy AWS managed decoy systems that are equipped with the most recent malware signatures.
- C. Set up a Gateway Load Balance
- D. Run an intrusion detection system (IDS) appliance from AWS Marketplace on Amazon EC2 for traffic inspection.
- E. Configure Amazon Inspector to perform deep packet inspection of outgoing traffic.

Answer: A

Explanation:

This solution involves using Amazon GuardDuty to monitor network traffic and analyze DNS requests and VPC flow logs for suspicious activity. This will allow the company to identify when an application is spreading malware by monitoring the network traffic patterns associated with the instance. GuardDuty is a fully managed threat detection service that continuously monitors for malicious activity and unauthorized behavior in your AWS accounts and workloads. It requires minimal setup and configuration and can be integrated with other AWS services for automated remediation. This solution requires the least operational effort compared to the other options

NEW QUESTION 3

A network engineer must develop an AWS CloudFormation template that can create a virtual private gateway, a customer gateway, a VPN connection, and static routes in a route table. During testing of the template, the network engineer notes that the CloudFormation template has encountered an error and is rolling back. What should the network engineer do to resolve the error?

- A. Change the order of resource creation in the CloudFormation template.
- B. Add the DependsOn attribute to the resource declaration for the virtual private gateway
- C. Specify the route table entry resource.
- D. Add a wait condition in the template to wait for the creation of the virtual private gateway.
- E. Add the DependsOn attribute to the resource declaration for the route table entry
- F. Specify the virtual private gateway resource.

Answer: D

NEW QUESTION 4

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity

- O. Add a NAT gatewa
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 5

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud.

Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connectio
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connectio
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connectio
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connectio
- H. Configure two AWS Site-to-Site VPN connections to the transit gatewa
- I. Enable equal-cost multi-path (ECMP) routing.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

NEW QUESTION 6

An AWS CloudFormation template is being used to create a VPC peering connection between two existing operational VPCs, each belonging to a different AWS account. All necessary components in the 'Remote' (receiving) account are already in place.

The template below creates the VPC peering connection in the Originating account. It contains these components:

AWSTemplateFormation Version: 2010-09-09 Parameters:

Originating VPCId: Type: String RemoteVPCId: Type: String

RemoteVPCAccountId: Type: String Resources:

newVPCPeeringConnection:

Type: 'AWS::EC2::VPCPeeringConnection'

Properties:

VpcdId: !Ref OriginatingVPCId PeerVpcId: !Ref RemoteVPCId PeerOwnerId: !Ref RemoteVPCAccountId

Which additional AWS CloudFormation components are necessary in the Originating account to create an operational cross-account VPC peering connection with AWS CloudFormation? (Select two.)

- A. Resources:NewEC2SecurityGroup:Type: AWS::EC2::SecurityGroup
- B. Resources:NetworkInterfaceToRemoteVPC:Type: "AWS::EC2NetworkInterface"
- C. Resources:newEC2Route:Type: AWS::EC2::Route
- D. Resources:VPCGatewayToRemoteVPC:Type: "AWS::EC2::VPCGatewayAttachment"
- E. Resources:newVPCPeeringConnection:Type: 'AWS::EC2VPCPeeringConnection'PeerRoleArn: !Ref PeerRoleArn

Answer: CE

Explanation:

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/AWS_EC2.html

NEW QUESTION 7

A company is using Amazon Route 53 Resolver DNS Firewall in a VPC to block all domains except domains that are on an approved list. The company is concerned that if DNS Firewall is unresponsive, resources in the VPC might be affected if the network cannot resolve any DNS queries. To maintain application service level agreements, the company needs DNS queries to continue to resolve even if Route 53 Resolver does not receive a response from DNS Firewall.

Which change should a network engineer implement to meet these requirements?

- A. Update the DNS Firewall VPC configuration to disable fail open for the VPC.
- B. Update the DNS Firewall VPC configuration to enable fail open for the VPC.
- C. Create a new DHCP options set with parameter dns_firewall_fail_open=fals
- D. Associate the new DHCP options set with the VPC.
- E. Create a new DHCP options set with parameter dns_firewall_fail_open=tru
- F. Associate the new DHCP options set with the VPC.

Answer: B

NEW QUESTION 8

A company plans to deploy a two-tier web application to a new VPC in a single AWS Region. The company has configured the VPC with an internet gateway and four subnets. Two of the subnets are public and have default routes that point to the internet gateway. Two of the subnets are private and share a route table that does not have a default route.

The application will run on a set of Amazon EC2 instances that will be deployed behind an external Application Load Balancer. The EC2 instances must not be directly accessible from the internet. The application will use an Amazon S3 bucket in the same Region to store data. The application will invoke S3 GET API operations and S3 PUT API operations from the EC2 instances. A network engineer must design a VPC architecture that minimizes data transfer cost.

Which solution will meet these requirements?

- A. Deploy the EC2 instances in the public subnet
- B. Create an S3 interface endpoint in the VP
- C. Modify the application configuration to use the S3 endpoint-specific DNS hostname.
- D. Deploy the EC2 instances in the private subnet

- E. Create a NAT gateway in the VP
- F. Create default routes in the private subnets to the NAT gateway
- G. Connect to Amazon S3 by using the NAT gateway.
- H. Deploy the EC2 instances in the private subnet
- I. Create an S3 gateway endpoint in the VPC specify the route table of the private subnets during endpoint creation to create routes to Amazon S3.
- J. Deploy the EC2 instances in the private subnet
- K. Create an S3 interface endpoint in the VP
- L. Modify the application configuration to use the S3 endpoint-specific DNS hostname.

Answer: C

Explanation:

Option C is the optimal solution as it involves deploying the EC2 instances in the private subnets, which provides additional security benefits. Additionally, creating an S3 gateway endpoint in the VPC will enable the EC2 instances to communicate with Amazon S3 directly, without incurring data transfer costs. This is because the S3 gateway endpoint uses Amazon's private network to transfer data between the VPC and S3, which is not charged for data transfer. Furthermore, specifying the route table of the private subnets during endpoint creation will create routes to Amazon S3, which is required for the EC2 instances to communicate with S3.

NEW QUESTION 9

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VPC
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VPC
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- F. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- G. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disabled
- H. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

Answer: A

NEW QUESTION 10

A company is hosting an application on Amazon EC2 instances behind an Application Load Balancer. The instances are in an Amazon EC2 Auto Scaling group. Because of a recent change to a security group, external users cannot access the application.

A network engineer needs to prevent this downtime from happening again. The network engineer must implement a solution that remediates noncompliant changes to security groups.

Which solution will meet these requirements?

- A. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- B. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.
- C. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- D. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- E. Configure Amazon GuardDuty to detect inconsistencies between the desired security group configuration and the current security group configuration
- F. Configure AWS OpsWorks for Chef to remediate noncompliant security groups.
- G. Configure an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration
- H. Create an AWS Systems Manager Automation runbook to remediate noncompliant security groups.

Answer: D

Explanation:

Configuring an AWS Config rule to detect inconsistencies between the desired security group configuration and the current security group configuration would enable evaluation of the compliance status of the security groups based on predefined or custom rules³. Creating an AWS Systems Manager Automation runbook to remediate noncompliant security groups would enable automation of the remediation process². Additionally, configuring AWS Config to trigger the runbook when a noncompliant change is detected would enable timely and consistent remediation of security group changes.

NEW QUESTION 10

A company is using an AWS Site-to-Site VPN connection from the company's on-premises data center to a virtual private gateway in the AWS Cloud. Because of congestion, the company is experiencing availability and performance issues as traffic travels across the internet before the traffic reaches AWS. A network engineer must reduce these issues for the connection as quickly as possible with minimum administration effort.

Which solution will meet these requirements?

- A. Edit the existing Site-to-Site VPN connection by enabling acceleration
- B. Stop and start the VPN service on the customer gateway for the new setting to take effect.
- C. Configure a transit gateway in the same AWS Region as the existing virtual private gateway
- D. Create a new accelerated Site-to-Site VPN connection
- E. Connect the new connection to the transit gateway by using a VPN attachment
- F. Update the customer gateway device to use the new Site-to-Site VPN connection
- G. Delete the existing Site-to-Site VPN connection
- H. Create a new accelerated Site-to-Site VPN connection
- I. Connect the new Site-to-Site VPN connection to the existing virtual private gateway
- J. Update the customer gateway device to use the new Site-to-Site VPN connection
- K. Delete the existing Site-to-Site VPN connection.
- L. Create a new AWS Direct Connect connection with a private VIF between the on-premises data center and the AWS Cloud
- M. Update the customer gateway device to use the new Direct Connect connection
- N. Delete the existing Site-to-Site VPN connection.

Answer: B

NEW QUESTION 15

A company has deployed an AWS Network Firewall firewall into a VPC. A network engineer needs to implement a solution to deliver Network Firewall flow logs to the company's Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster in the shortest possible time.

Which solution will meet these requirements?

- A. Create an Amazon S3 bucket
- B. Create an AWS Lambda function to load logs into the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster
- C. Enable Amazon Simple Notification Service (Amazon SNS) notifications on the S3 bucket to invoke the Lambda function
- D. Configure flow logs for the firewall
- E. Set the S3 bucket as the destination.
- F. Create an Amazon Kinesis Data Firehose delivery stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination
- G. Configure flow logs for the firewall Set the Kinesis Data Firehose delivery stream as the destination for the Network Firewall flow logs.
- H. Configure flow logs for the firewall
- I. Set the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination for the Network Firewall flow logs.
- J. Create an Amazon Kinesis data stream that includes the Amazon OpenSearch Service (Amazon Elasticsearch Service) cluster as the destination
- K. Configure flow logs for the firewall
- L. Set the Kinesis data stream as the destination for the Network Firewall flow logs.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/how-to-analyze-aws-network-firewall-logs-using-aws-lambda/>

NEW QUESTION 19

A global company operates all its non-production environments out of three AWS Regions: eu-west-1, us-east-1, and us-west-1. The company hosts all its production workloads in two on-premises data centers. The company has 60 AWS accounts and each account has two VPCs in each Region. Each VPC has a virtual private gateway where two VPN connections terminate for resilient connectivity to the data centers. The company has 360 VPN tunnels to each data center, resulting in high management overhead. The total VPN throughput for each Region is 500 Mbps. The company wants to migrate the production environments to AWS. The company needs a solution that will simplify the network architecture and allow for future growth. The production environments will generate an additional 2 Gbps of traffic per Region back to the data centers. This traffic will increase over time. Which solution will meet these requirements?

- A. Set up an AWS Direct Connect connection from each data center to AWS in each Region
- B. Create and attach private VIFs to a single Direct Connect gateway
- C. Attach the Direct Connect gateway to all the VPCs
- D. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- E. Create a single transit gateway with VPN connections from each data center
- F. Share the transit gateway with each account by using AWS Resource Access Manager (AWS RAM). Attach the transit gateway to each VPC
- G. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- H. Create a transit gateway in each Region with multiple newly commissioned VPN connections from each data center
- I. Share the transit gateways with each account by using AWS Resource Access Manager (AWS RAM). In each Region, attach the transit gateway to each VPC
- J. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- K. Peer all the VPCs in each Region to a new VPC in each Region that will function as a centralized transit VPC
- L. Create new VPN connections from each data center to the transit VPC
- M. Terminate the original VPN connections that are attached to all the original VPCs
- N. Retain the new VPN connection to the new transit VPC in each Region.

Answer: C

NEW QUESTION 20

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this issue in the most operationally efficient manner.

What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 23

A company has deployed a critical application on a fleet of Amazon EC2 instances behind an Application Load Balancer. The application must always be reachable on port 443 from the public internet. The application recently had an outage that resulted from an incorrect change to the EC2 security group. A network engineer needs to automate a way to verify the network connectivity between the public internet and the EC2 instances whenever a change is made to the security group. The solution also must notify the network engineer when the change affects the connection. Which solution will meet these requirements?

- A. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture REJECT traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log
- B. Create a CloudWatch Logs metric filter for the log group for rejected traffi
- C. Create an alarm to notify the network engineer.
- D. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture all traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log
- E. Create a CloudWatch Logs metric filter for the log group for all traffi
- F. Create an alarm to notify the network engineer
- G. Create a VPC Reachability Analyzer path on port 443. Specify the security group as the sourc
- H. Specify the EC2 instances as the destinatio
- I. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connectio
- J. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fail Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security groupoccurs.
- K. Create a VPC Reachability Analyzer path on port 443. Specify the internet gateway of the VPC as the sourc
- L. Specify the EC2 instances as the destinatio
- M. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connectio
- N. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fai
- O. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security group occurs.

Answer: C

NEW QUESTION 24

A software company offers a software-as-a-service (SaaS) accounting application that is hosted in the AWS Cloud The application requires connectivity to the company's on-premises network. The company has two redundant 10 GB AWS Direct Connect connections between AWS and its on-premises network to accommodate the growing demand for the application.

The company already has encryption between its on-premises network and the colocation. The company needs to encrypt traffic between AWS and the edge routers in the colocation within the next few months. The company must maintain its current bandwidth.

What should a network engineer do to meet these requirements with the LEAST operational overhead?

- A. Deploy a new public VIF with encryption on the existing Direct Connect connection
- B. Reroute traffic through the new public VIF.
- C. Create a virtual private gateway Deploy new AWS Site-to-Site VPN connections from on premises to the virtual private gateway Reroute traffic from the Direct Connect private VIF to the new VPNs.
- D. Deploy a new pair of 10 GB Direct Connect connections with MACse
- E. Configure MACsec on the edge router
- F. Reroute traffic to the new Direct Connect connection
- G. Decommission the original Direct Connect connections
- H. Deploy a new pair of 10 GB Direct Connect connections with MACse
- I. Deploy a new public VIF on the new Direct Connect connection
- J. Deploy two AWS Site-to-Site VPN connections on top of the new public VI
- K. Reroute traffic from the existing private VIF to the new Site-to-Site connection
- L. Decommission the original Direct Connect connections.

Answer: C

NEW QUESTION 28

An organization is using a VPC endpoint for Amazon S3. When the security group rules for a set of instances were initially configured, access was restricted to allow traffic only to the IP addresses of the Amazon S3 API endpoints in the region from the published JSON file. The application was working properly, but now is logging a growing number of timeouts when connecting with Amazon S3. No internet gateway is configured for the VPC.

Which solution will fix the connectivity failures with the LEAST amount of effort?

- A. Create a Lambda function to update the security group based on AmazonIPSpaceChanged notifications.
- B. Update the VPC routing to direct Amazon S3 prefix-list traffic to the VPC endpoint using the route table APIs.
- C. Update the application server's outbound security group to use the prefix-list for Amazon S3 in the same region.
- D. Create an additional VPC endpoint for Amazon S3 in the same route table to scale the concurrent connections to Amazon.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/aws/subscribe-to-aws-public-ip-address-changes-via-amazon-sns/>

NEW QUESTION 31

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

- A. Create an internet gateway and a NAT gateway in the VP
- B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.
- C. Create an internet gateway and a NAT instance in the VP
- D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.
- E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables topoint IPv6 traffic to the egress-only internet gateway.
- F. Create an egress-only internet gateway in the VP
- G. Configure a security group that denies all inbound traffi
- H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 35

A company is planning to deploy many software-defined WAN (SD-WAN) sites. The company is using AWS Transit Gateway and has deployed a transit gateway in the required AWS Region. A network engineer needs to deploy the SD-WAN hub virtual appliance into a VPC that is connected to the transit gateway. The solution must support at least 5 Gbps of throughput from the SD-WAN hub virtual appliance to other VPCs that are attached to the transit gateway. Which solution will meet these requirements?

- A. Create a new VPC for the SD-WAN hub virtual appliance
- B. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- C. Configure BGP over the IPsec VPN connections
- D. Assign a new CIDR block to the transit gateway
- E. Create a new VPC for the SD-WAN hub virtual appliance
- F. Attach the new VPC to the transit gateway with a VPC attachment
- G. Add a transit gateway Connect attachment
- H. Create a Connect peer and specify the GRE and BGP parameter
- I. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.
- J. Create a new VPC for the SD-WAN hub virtual appliance
- K. Attach the new VPC to the transit gateway with a VPC attachment
- L. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- M. Configure BGP over the IPsec VPN connections.
- N. Assign a new CIDR block to the transit gateway
- O. Create a new VPC for the SD-WAN hub virtual appliance
- P. Attach the new VPC to the transit gateway with a VPC attachment
- Q. Add a transit gateway Connect attachment
- R. Create a Connect peer and specify the VXLAN and BGP parameter
- S. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.

Answer: D

NEW QUESTION 40

A company's network engineer is designing an active-passive connection to AWS from two on-premises data centers. The company has set up AWS Direct Connect connections between the on-premises data centers and AWS. From each location, the company is using a transit VIF that connects to a Direct Connect gateway that is associated with a transit gateway.

The network engineer must ensure that traffic from AWS to the data centers is routed first to the primary data center. The traffic should be routed to the failover data center only in the case of an outage.

Which solution will meet these requirements?

- A. Set the BGP community tag for all prefixes from the primary data center to 7224:7100. Set the BGP community tag for all prefixes from the failover data center to 7224:7300
- B. Set the BGP community tag for all prefixes from the primary data center to 7224:7300. Set the BGP community tag for all prefixes from the failover data center to 7224:7100
- C. Set the BGP community tag for all prefixes from the primary data center to 7224:9300. Set the BGP community tag for all prefixes from the failover data center to 7224:9100
- D. Set the BGP community tag for all prefixes from the primary data center to 7224:9100. Set the BGP community tag for all prefixes from the failover data center to 7224:9300

Answer: B

NEW QUESTION 41

An international company provides early warning about tsunamis. The company plans to use IoT devices to monitor sea waves around the world. The data that is collected by the IoT devices must reach the company's infrastructure on AWS as quickly as possible. The company is using three operation centers around the world. Each operation center is connected to AWS through its own AWS Direct Connect connection. Each operation center is connected to the internet through at least two upstream internet service providers.

The company has its own provider-independent (PI) address space. The IoT devices use TCP protocols for reliable transmission of the data they collect. The IoT devices have both landline and mobile internet connectivity. The infrastructure and the solution will be deployed in multiple AWS Regions. The company will use Amazon Route 53 for DNS services.

A network engineer needs to design connectivity between the IoT devices and the services that run in the AWS Cloud.

Which solution will meet these requirements with the HIGHEST availability?

- A. Set up an Amazon CloudFront distribution with origin failover
- B. Create an origin group for each Region where the solution is deployed.
- C. Set up Route 53 latency-based routing
- D. Add latency alias record
- E. For the latency alias records, set the value of Evaluate Target Health to Yes.
- F. Set up an accelerator in AWS Global Accelerator
- G. Configure Regional endpoint groups and health checks.
- H. Set up Bring Your Own IP (BYOIP) addresses
- I. Use the same PI addresses for each Region where the solution is deployed.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/iot/automate-global-device-provisioning-with-aws-iot-core-and-amazon-route-53>

NEW QUESTION 46

A company hosts a web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin in an Amazon CloudFront distribution. The company wants to implement a custom authentication system that will provide a token for its authenticated customers.

The web application must ensure that the GET/POST requests come from authenticated customers before it delivers the content. A network engineer must design a solution that gives the web application the ability to identify authorized customers.

What is the MOST operationally efficient solution that meets these requirements?

- A. Use the ALB to inspect the authorized token inside the GET/POST request payload
- B. Use an AWS Lambda function to insert a customized header to inform the web application of an authenticated customer request.
- C. Integrate AWS WAF with the ALB to inspect the authorized token inside the GET/POST request payload
- D. Configure the ALB listener to insert a customized header to inform the web application of an authenticated customer request.
- E. Use an AWS Lambda@Edge function to inspect the authorized token inside the GET/POST request payload
- F. Use the Lambda@Edge function also to insert a customized header to inform the web application of an authenticated customer request.
- G. Set up an EC2 instance that has a third-party packet inspection tool to inspect the authorized token inside the GET/POST request payload
- H. Configure the tool to insert a customized header to inform the web application of an authenticated customer request.

Answer: C

NEW QUESTION 47

A company operates its IT services through a multi-site hybrid infrastructure. The company deploys resources on AWS in the us-east-1 Region and in the eu-west-2 Region. The company also deploys resources in its own data centers that are located in the United States (US) and in the United Kingdom (UK). In both AWS Regions, the company uses a transit gateway to connect 15 VPCs to each other. The company has created a transit gateway peering connection between the two transit gateways. The VPC CIDR blocks do not overlap with each other or with IP addresses used within the data centers. The VPC CIDR prefixes can also be aggregated either on a Regional level or for the company's entire AWS environment.

The data centers are connected to each other by a private WAN connection. IP routing information is exchanged dynamically through Interior BGP (iBGP) sessions. The data centers maintain connectivity to AWS through one AWS Direct Connect connection in the US and one Direct Connect connection in the UK. Each Direct Connect connection is terminated on a Direct Connect gateway and is associated with a local transit gateway through a transit VIF.

Traffic follows the shortest geographical path from source to destination. For example, packets from the UK data center that are targeted to resources in eu-west-2 travel across the local Direct Connect connection. In cases of cross-Region data transfers, such as from the UK data center to VPCs in us-east-1, the private WAN connection must be used to minimize costs on AWS. A network engineer has configured each transit gateway association on the Direct Connect gateway to advertise VPC-specific CIDR IP prefixes only from the local Region. The routes toward the other Region must be learned through BGP from the routers in the other data center in the original, non-aggregated form.

The company recently experienced a problem with cross-Region data transfers because of issues with its private WAN connection. The network engineer needs to modify the routing setup to prevent similar interruptions in the future. The solution cannot modify the original traffic routing goal when the network is operating normally.

Which modifications will meet these requirements? (Choose two.)

- A. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- B. Add the company's entire AWS environment aggregate route to the list of subnets advertised through the local Direct Connect connection.
- C. Add the CIDR prefixes from the other Region VPCs and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection
- D. Configure data center routers to make routing decisions based on the BGP communities received.
- E. Add the aggregate IP prefix for the other Region and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- F. Add the aggregate IP prefix for the company's entire AWS environment and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- G. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- H. Add both Regional aggregate IP prefixes to the list of subnets advertised through the Direct Connect connection on both sides of the network
- I. Configure data center routers to make routing decisions based on the BGP communities received.

Answer: AD

NEW QUESTION 51

A Network Engineer is provisioning a subnet for a load balancer that will sit in front of a fleet of application servers in a private subnet. There is limited IP space left in the VPC CIDR. The application has few users now but is expected to grow quickly to millions of users.

What design will use the LEAST amount of IP space, while allowing for this growth?

- A. Use two /29 subnets for an Application Load Balancer in different Availability Zones.
- B. Use one /29 subnet for the Network Load Balance
- C. Add another VPC CIDR to the VPC to allow for future growth.
- D. Use two /28 subnets for a Network Load Balancer in different Availability Zones.
- E. Use one /28 subnet for an Application Load Balance
- F. Add another VPC CIDR to the VPC to allow for future growth.

Answer: C

NEW QUESTION 53

A company has deployed an application in a VPC that uses a NAT gateway for outbound traffic to the internet. A network engineer notices a large quantity of suspicious network traffic that is traveling from the VPC over the internet to IP addresses that are included on a deny list. The network engineer must implement a solution to determine which AWS resources are generating the suspicious traffic. The solution must minimize cost and administrative overhead.

Which solution will meet these requirements?

- A. Launch an Amazon EC2 instance in the VPC
- B. Use Traffic Mirroring by specifying the NAT gateway as the source and the EC2 instance as the destination
- C. Analyze the captured traffic by using open-source tools to identify the AWS resources that are generating the suspicious traffic.
- D. Use VPC flow log
- E. Launch a security information and event management (SIEM) solution in the VPC
- F. Configure the SIEM solution to ingest the VPC flow log
- G. Run queries on the SIEM solution to identify the AWS resources that are generating the suspicious traffic.
- H. Use VPC flow log
- I. Publish the flow logs to a log group in Amazon CloudWatch Log
- J. Use CloudWatch Logs Insights to query the flow logs to identify the AWS resources that are generating the suspicious traffic.
- K. Configure the VPC to stream the network traffic directly to an Amazon Kinesis data stream
- L. Send the data from the Kinesis data stream to an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Use Amazon Athena to query the data to identify the AWS resources that are generating the suspicious traffic.

Answer: C

NEW QUESTION 58

A bank built a new version of its banking application in AWS using containers that connect to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded. What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

- A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.
- B. Use a Classic Load Balancer for the new application
- C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer
- D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.
- E. Use an Application Load Balancer for the new application
- F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.
- G. Use an Application Load Balancer for the new application
- H. Register both the new and earlier application backends as separate target groups
- I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 63

A company is developing an application in which IoT devices will report measurements to the AWS Cloud. The application will have millions of end users. The company observes that the IoT devices cannot support DNS resolution. The company needs to implement an Amazon EC2 Auto Scaling solution so that the IoT devices can connect to an application endpoint without using DNS. Which solution will meet these requirements MOST cost-effectively?

- A. Use an Application Load Balancer (ALB)-type target group for a Network Load Balancer (NLB). Create an EC2 Auto Scaling group
- B. Attach the Auto Scaling group to the ALB
- C. Set up the IoT devices to connect to the IP addresses of the NLB.
- D. Use an AWS Global Accelerator accelerator with an Application Load Balancer (ALB) endpoint
- E. Create an EC2 Auto Scaling group
- F. Attach the Auto Scaling group to the ALB
- G. Use a Network Load Balancer (NLB). Create an EC2 Auto Scaling group
- H. Attach the Auto Scaling group to the NLB
- I. Set up the IoT devices to connect to the IP addresses of the NLB.
- J. Use an AWS Global Accelerator accelerator with a Network Load Balancer (NLB) endpoint
- K. Create an EC2 Auto Scaling group
- L. Attach the Auto Scaling group to the NLB
- M. Set up the IoT devices to connect to the IP addresses of the accelerator.

Answer: D

Explanation:

AWS Global Accelerator can provide static IP addresses that the IoT devices can connect to without using DNS². It can also route traffic over the AWS global network and improve performance and availability for the IoT devices². An NLB can provide end-to-end encryption for HTTPS traffic by using TLS as a target group protocol and terminating SSL connections at the load balancer level¹. An NLB can also support session affinity (sticky sessions) with TCP connections¹.

NEW QUESTION 64

A company wants to improve visibility into its AWS environment. The AWS environment consists of multiple VPCs that are connected to a transit gateway. The transit gateway connects to an on-premises data center through an AWS Direct Connect gateway and a pair of redundant Direct Connect connections that use transit VIFs. The company must receive notification each time a new route is advertised to AWS from on premises over Direct Connect. What should a network engineer do to meet these requirements?

- A. Enable Amazon CloudWatch metrics on Direct Connect to track the received route
- B. Configure a CloudWatch alarm to send notifications when routes change.
- C. Onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insight
- D. Use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change.
- E. Configure an AWS Lambda function to periodically check the routes on the Direct Connect gateway and to send notifications when routes change.
- F. Enable Amazon CloudWatch Logs on the transit VIFs to track the received route
- G. Create a metric filter. Set an alarm on the filter to send notifications when routes change.

Answer: B

Explanation:

<https://docs.aws.amazon.com/network-manager/latest/cloudwan/cloudwan-cloudwatch-events.html>

To receive notification each time a new route is advertised to AWS from on premises over Direct Connect, a network engineer should onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insights and use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change (Option B). This solution allows for real-time monitoring of route changes and automatic notification when new routes are advertised.

NEW QUESTION 65

A company's AWS architecture consists of several VPCs. The VPCs include a shared services VPC and several application VPCs. The company has established network connectivity from all VPCs to the on-premises DNS servers. Applications that are deployed in the application VPCs must be able to resolve DNS for internally hosted domains on premises. The applications also must be able to resolve local VPC domain names and domains that are hosted in Amazon Route 53 private hosted zones. What should a network engineer do to meet these requirements?

- A. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- B. Create forwarding rules for the on-premises hosted domain
- C. Associate the rules with the new Resolver endpoint and each application VPC
- D. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.

- E. Create a new Route 53 Resolver outbound endpoint in the shared services VPC
- F. Create forwarding rules for the on-premises hosted domain
- G. Associate the rules with the new Resolver endpoint and each application VPC.
- H. Create a new Route 53 Resolver outbound endpoint in the shared services VPC
- I. Create forwarding rules for the on-premises hosted domain
- J. Associate the rules with the new Resolver endpoint and each application VPC
- K. Update each application VPC's DHCP configuration to point DNS resolution to the new Resolver endpoint.
- L. Create a new Route 53 Resolver inbound endpoint in the shared services VPC
- M. Create forwarding rules for the on-premises hosted domain
- N. Associate the rules with the new Resolver endpoint and each application VPC.

Answer: B

Explanation:

Creating a new Route 53 Resolver outbound endpoint in the shared services VPC would enable forwarding of DNS queries from the VPC to on-premises1.
Creating forwarding rules for the on-premises hosted domains would enable specifying which domain names are forwarded to the on-premises DNS servers2.
Associating the rules with the new Resolver endpoint and each application VPC would enable applying the rules to the VPCs2. This solution would not affect the default DNS resolution behavior of Route 53 Resolver for local VPC domain names and domains that are hosted in Route 53 private hosted zones3.

NEW QUESTION 66

A media company is implementing a news website for a global audience. The website uses Amazon CloudFront as its content delivery network. The backend runs on Amazon EC2 Windows instances behind an Application Load Balancer (ALB). The instances are part of an Auto Scaling group. The company's customers access the website by using service.example.com as the CloudFront custom domain name. The CloudFront origin points to an ALB that uses service-alb.example.com as the domain name.

The company's security policy requires the traffic to be encrypted in transit at all times between the users and the backend.

Which combination of changes must the company make to meet this security requirement? (Choose three.)

- A. Create a self-signed certificate for service.example.co
- B. Import the certificate into AWS Certificate Manager (ACM). Configure CloudFront to use this imported SSL/TLS certificat
- C. Change the default behavior to redirect HTTP to HTTPS.
- D. Create a certificate for service.example.com by using AWS Certificate Manager (ACM). Configure CloudFront to use this custom SSL/TLS certificat
- E. Change the default behavior to redirect HTTP to HTTPS.
- F. Create a certificate with any domain name by using AWS Certificate Manager (ACM) for the EC2 instance
- G. Configure the backend to use this certificate for its HTTPS listene
- H. Specify the instance target type during the creation of a new target group that uses the HTTPS protocol for its target
- I. Attach the existing Auto Scaling group to this new target group.
- J. Create a public certificate from a third-party certificate provider with any domain name for the EC2 instance
- K. Configure the backend to use this certificate for its HTTPS listene
- L. Specify the instance target type during the creation of a new target group that uses the HTTPS protocol for its target
- M. Attach the existing Auto Scaling group to this new target group.
- N. Create a certificate for service-alb.example.com by using AWS Certificate Manager (ACM). On the ALB add a new HTTPS listener that uses the new target group and the service-alb.example.com ACM certificat
- O. Modify the CloudFront origin to use the HTTPS protocol onl
- P. Delete the HTTP listener on the ALB.
- Q. Create a self-signed certificate for service-alb.example.co
- R. Import the certificate into AWS Certificate Manager (ACM). On the ALB add a new HTTPS listener that uses the new target group and the imported service-alb.example.com ACM certificat
- S. Modify the CloudFront origin to use the HTTPS protocol onl
- T. Delete the HTTP listener on the ALB.

Answer: BDE

NEW QUESTION 70

A company has several production applications across different accounts in the AWS Cloud. The company operates from the us-east-1 Region only. Only certain partner companies can access the applications. The applications are running on Amazon EC2 instances that are in an Auto Scaling group behind an Application Load Balancer (ALB). The EC2 instances are in private subnets and allow traffic only from the ALB. The ALB is in a public subnet and allows inbound traffic only from partner network IP address ranges over port 80.

When the company adds a new partner, the company must allow the IP address range of the partner network in the security group that is associated with the ALB in each account. A network engineer must implement a solution to centrally manage the partner network IP address ranges.

Which solution will meet these requirements in the MOST operationally efficient manner?

- A. Create an Amazon DynamoDB table to maintain all IP address ranges and security groups that need to be update
- B. Update the DynamoDB table with the new IP address range when the company adds a new partne
- C. Invoke an AWS Lambda function to read new IP address ranges and security groups from the DynamoDB table to update the security group
- D. Deploy this solution in all accounts.
- E. Create a new prefix lis
- F. Add all allowed IP address ranges to the prefix lis
- G. Use Amazon EventBridge (Amazon CloudWatch Events) rules to invoke an AWS Lambda function to update security groups whenever a new IP address range is added to the prefix lis
- H. Deploy this solution in all accounts.
- I. Create a new prefix lis
- J. Add all allowed IP address ranges to the prefix lis
- K. Share the prefix list across different accounts by using AWS Resource Access Manager (AWS RAM). Update security groups to use the prefix list instead of the partner IP address rang
- L. Update the prefix list with the new IP address range when the company adds a new partner.
- M. Create an Amazon S3 bucket to maintain all IP address ranges and security groups that need to be update
- N. Update the S3 bucket with the new IP address range when the company adds a new partne
- O. Invoke an AWS Lambda function to read new IP address ranges and security groups from the S3 bucket to update the security group
- P. Deploy this solution in all accounts.

Answer: C

Explanation:

Creating a new prefix list and adding all allowed IP address ranges to the prefix list would enable grouping of CIDR blocks that can be referenced in security group rules3. Sharing the prefix list across different accounts by using AWS Resource Access Manager (AWS RAM)would enable central management of the partner network IP address ranges5. Updating security groups to use the prefix list instead of the partner IP address range would enable simplification of security group rules3. Updating the prefix list with the new IP address range when the company adds a new partner would enable automatic propagation of the changes to all security groups that use the prefix list3.

NEW QUESTION 75

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Advanced-Networking-Specialty Practice Exam Features:

- * AWS-Certified-Advanced-Networking-Specialty Questions and Answers Updated Frequently
- * AWS-Certified-Advanced-Networking-Specialty Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Advanced-Networking-Specialty Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Advanced-Networking-Specialty Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Advanced-Networking-Specialty Practice Test Here](#)