

Databricks

Exam Questions Databricks-Certified-Data-Engineer-Associate

Databricks Certified Data Engineer Associate Exam



NEW QUESTION 1

Which of the following approaches should be used to send the Databricks Job owner an email in the case that the Job fails?

- A. Manually programming in an alert system in each cell of the Notebook
- B. Setting up an Alert in the Job page
- C. Setting up an Alert in the Notebook
- D. There is no way to notify the Job owner in the case of Job failure
- E. MLflow Model Registry Webhooks

Answer: B

Explanation:

<https://docs.databricks.com/en/workflows/jobs/job-notifications.html>

NEW QUESTION 2

A data engineer is working with two tables. Each of these tables is displayed below in its entirety.

sales

customer_id	spend	units
a1	28.94	7
a3	874.12	23
a4	8.99	1

favorite_stores

customer_id	store_id
a1	s1
a2	s1
a4	s2

The data engineer runs the following query to join these tables together:

```
SELECT
    sales.customer_id,
    sales.spend,
    favorite_stores.store_id
FROM sales
LEFT JOIN favorite_stores
ON sales.customer_id = favorite_stores.customer_id;
```

Which of the following will be returned by the above query?

A.

customer_id	spend	store_id
a1	28.94	s1
a4	8.99	s2

B.

customer_id	spend	units	store_id
a1	28.94	7	s1
a4	8.99	1	s2

C.

customer_id	spend	store_id
a1	28.94	s1
a3	874.12	NULL
a4	8.99	s2

D.

customer_id	spend	store_id
a1	28.94	s1
a2	NULL	s1
a3	874.12	NULL
a4	8.99	s2

E.

customer_id	spend	store_id
a1	28.94	s1
a2	NULL	s1
a4	8.99	s2

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: C

NEW QUESTION 3

A new data engineering team has been assigned to work on a project. The team will need access to database customers in order to see what tables already exist. The team has its own group team.

Which of the following commands can be used to grant the necessary permission on the entire database to the new team?

- A. GRANT VIEW ON CATALOG customers TO team;
- B. GRANT CREATE ON DATABASE customers TO team;
- C. GRANT USAGE ON CATALOG team TO customers;
- D. GRANT CREATE ON DATABASE team TO customers;
- E. GRANT USAGE ON DATABASE customers TO team;

Answer: E

Explanation:

The GRANT statement is used to grant privileges on a database, table, or view to a user or role. The ALL PRIVILEGES option grants all possible privileges on the specified object, such as CREATE, SELECT, MODIFY, and USAGE. The syntax of the GRANT statement is:

GRANT privilege_type ON object TO user_or_role;

Therefore, to grant full permissions on the database customers to the new data engineering team, the command should be:

GRANT ALL PRIVILEGES ON DATABASE customers TO team;

NEW QUESTION 4

A data engineer is using the following code block as part of a batch ingestion pipeline to read from a composable table:

```
transactions_df = (spark.read
    .schema(schema)
    .format("delta")
    .table("transactions")
)
```

Which of the following changes needs to be made so this code block will work when the transactions table is a stream source?

- A. Replace predict with a stream-friendly prediction function
- B. Replace schema(schema) with option ("maxFilesPerTrigger", 1)
- C. Replace "transactions" with the path to the location of the Delta table
- D. Replace format("delta") with format("stream")
- E. Replace spark.read with spark.readStream

Answer: E

Explanation:

<https://docs.databricks.com/en/structured-streaming/delta-lake.html>

NEW QUESTION 5

In order for Structured Streaming to reliably track the exact progress of the processing so that it can handle any kind of failure by restarting and/or reprocessing, which of the following two approaches is used by Spark to record the offset range of the data being processed in each trigger?

- A. Checkpointing and Write-ahead Logs
- B. Structured Streaming cannot record the offset range of the data being processed in each trigger.
- C. Replayable Sources and Idempotent Sinks
- D. Write-ahead Logs and Idempotent Sinks
- E. Checkpointing and Idempotent Sinks

Answer: A

Explanation:

The engine uses checkpointing and write-ahead logs to record the offset range of the data being processed in each trigger. -- in the link search for "The engine uses " you'll find the answer. <https://spark.apache.org/docs/latest/structured-streaming-programming-guide.html#:~:text=The%20engine%20uses%20checkpointing%20and,being%20processe d%20in%20each%20trigger.>

NEW QUESTION 6

Which of the following is hosted completely in the control plane of the classic Databricks architecture?

- A. Worker node
- B. JDBC data source

- C. Databricks web application
- D. Databricks Filesystem
- E. Driver node

Answer: C

Explanation:

In the classic Databricks architecture, the control plane includes components like the Databricks web application, the Databricks REST API, and the Databricks Workspace. These components are responsible for managing and controlling the Databricks environment, including cluster provisioning, notebook management, access control, and job scheduling. The other options, such as worker nodes, JDBC data sources, Databricks Filesystem (DBFS), and driver nodes, are typically part of the data plane or the execution environment, which is separate from the control plane. Worker nodes are responsible for executing tasks and computations, JDBC data sources are used to connect to external databases, DBFS is a distributed file system for data storage, and driver nodes are responsible for coordinating the execution of Spark jobs.

NEW QUESTION 7

A new data engineering team has been assigned to an ELT project. The new data engineering team will need full privileges on the database customers to fully manage the project.

Which of the following commands can be used to grant full permissions on the database to the new data engineering team?

- A. GRANT USAGE ON DATABASE customers TO team;
- B. GRANT ALL PRIVILEGES ON DATABASE team TO customers;
- C. GRANT SELECT PRIVILEGES ON DATABASE customers TO teams;
- D. GRANT SELECT CREATE MODIFY USAGE PRIVILEGES ON DATABASE customers TO team;
- E. GRANT ALL PRIVILEGES ON DATABASE customers TO team;

Answer: E

Explanation:

To grant full privileges on the database "customers" to the new data engineering team, you can use the GRANT ALL PRIVILEGES command as shown in option E. This command provides the team with all possible privileges on the specified database, allowing them to fully manage it.

NEW QUESTION 8

A data engineer has three tables in a Delta Live Tables (DLT) pipeline. They have configured the pipeline to drop invalid records at each table. They notice that some data is being dropped due to quality concerns at some point in the DLT pipeline. They would like to determine at which table in their pipeline the data is being dropped.

Which of the following approaches can the data engineer take to identify the table that is dropping the records?

- A. They can set up separate expectations for each table when developing their DLT pipeline.
- B. They cannot determine which table is dropping the records.
- C. They can set up DLT to notify them via email when records are dropped.
- D. They can navigate to the DLT pipeline page, click on each table, and view the data quality statistics.
- E. They can navigate to the DLT pipeline page, click on the "Error" button, and review the present errors.

Answer: D

Explanation:

To identify the table in a Delta Live Tables (DLT) pipeline where data is being dropped due to quality concerns, the data engineer can navigate to the DLT pipeline page, click on each table in the pipeline, and view the data quality statistics. These statistics often include information about records dropped, violations of expectations, and other data quality metrics. By examining the data quality statistics for each table in the pipeline, the data engineer can determine at which table the data is being dropped.

NEW QUESTION 9

A data engineer needs to use a Delta table as part of a data pipeline, but they do not know if they have the appropriate permissions.

In which of the following locations can the data engineer review their permissions on the table?

- A. Databricks Filesystem
- B. Jobs
- C. Dashboards
- D. Repos
- E. Data Explorer

Answer: E

NEW QUESTION 10

A dataset has been defined using Delta Live Tables and includes an expectations clause:

CONSTRAINT valid_timestamp EXPECT (timestamp > '2020-01-01') ON VIOLATION DROP ROW

What is the expected behavior when a batch of data containing data that violates these constraints is processed?

- A. Records that violate the expectation are dropped from the target dataset and loaded into a quarantine table.
- B. Records that violate the expectation are added to the target dataset and flagged as invalid in a field added to the target dataset.
- C. Records that violate the expectation are dropped from the target dataset and recorded as invalid in the event log.
- D. Records that violate the expectation are added to the target dataset and recorded as invalid in the event log.
- E. Records that violate the expectation cause the job to fail.

Answer: C

Explanation:

With the defined constraint and expectation clause, when a batch of data is processed, any records that violate the expectation (in this case, where the timestamp is not greater than '2020-01-01') will be dropped from the target dataset. These dropped records will also be recorded as invalid in the event log, allowing for

auditing and tracking of the data quality issues without causing the entire job to fail. <https://docs.databricks.com/en/delta-live-tables/expectations.html>

NEW QUESTION 10

A data engineer needs to apply custom logic to identify employees with more than 5 years of experience in array column employees in table stores. The custom logic should create a new column exp_employees that is an array of all of the employees with more than 5 years of experience for each row. In order to apply this custom logic at scale, the data engineer wants to use the FILTER higher-order function.

Which of the following code blocks successfully completes this task?

```
SELECT
    store_id,
    employees,
    FILTER (employees, i -> i.years_exp > 5) AS exp_employees
FROM stores;

SELECT
    store_id,
    employees,
    FILTER (exp_employees, years_exp > 5) AS exp_employees
FROM stores;

SELECT
    store_id,
    employees,
    FILTER (employees, years_exp > 5) AS exp_employees
FROM stores;

SELECT
    store_id,
    employees,
    CASE WHEN employees.years_exp > 5 THEN employees
    ELSE NULL
    END AS exp_employees
FROM stores;

SELECT
    store_id,
    employees,
    FILTER (exp_employees, i -> i.years_exp > 5) AS exp_employees
FROM stores;
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: A

NEW QUESTION 12

A data engineer wants to schedule their Databricks SQL dashboard to refresh once per day, but they only want the associated SQL endpoint to be running when it is necessary.

Which of the following approaches can the data engineer use to minimize the total running time of the SQL endpoint used in the refresh schedule of their dashboard?

- A. They can ensure the dashboard's SQL endpoint matches each of the queries' SQL endpoints.
- B. They can set up the dashboard's SQL endpoint to be serverless.
- C. They can turn on the Auto Stop feature for the SQL endpoint.
- D. They can reduce the cluster size of the SQL endpoint.
- E. They can ensure the dashboard's SQL endpoint is not one of the included query's SQL endpoint.

Answer: C

NEW QUESTION 15

Which of the following describes the relationship between Gold tables and Silver tables?

- A. Gold tables are more likely to contain aggregations than Silver tables.
- B. Gold tables are more likely to contain valuable data than Silver tables.
- C. Gold tables are more likely to contain a less refined view of data than Silver tables.
- D. Gold tables are more likely to contain more data than Silver tables.
- E. Gold tables are more likely to contain truthful data than Silver tables.

Answer: A

Explanation:

In some data processing pipelines, especially those following a typical "Bronze-Silver-Gold" data lakehouse architecture, Silver tables are often considered a more refined version of the raw or Bronze data. Silver tables may include data cleansing, schema enforcement, and some initial transformations. Gold tables, on the other hand, typically represent a stage where data is further enriched, aggregated, and processed to provide valuable insights for analytical purposes. This could indeed involve more aggregations compared to Silver tables.

NEW QUESTION 16

A data engineer has a Python notebook in Databricks, but they need to use SQL to accomplish a specific task within a cell. They still want all of the other cells to use Python without making any changes to those cells.

Which of the following describes how the data engineer can use SQL within a cell of their Python notebook?

- A. It is not possible to use SQL in a Python notebook
- B. They can attach the cell to a SQL endpoint rather than a Databricks cluster
- C. They can simply write SQL syntax in the cell
- D. They can add %sql to the first line of the cell
- E. They can change the default language of the notebook to SQL

Answer: D

NEW QUESTION 18

A data engineer has realized that they made a mistake when making a daily update to a table. They need to use Delta time travel to restore the table to a version that is 3 days old. However, when the data engineer attempts to time travel to the older version, they are unable to restore the data because the data files have been deleted.

Which of the following explains why the data files are no longer present?

- A. The VACUUM command was run on the table
- B. The TIME TRAVEL command was run on the table
- C. The DELETE HISTORY command was run on the table
- D. The OPTIMIZE command was run on the table
- E. The HISTORY command was run on the table

Answer: A

Explanation:

The VACUUM command in Delta Lake is used to clean up and remove unnecessary data files that are no longer needed for time travel or query purposes. When you run VACUUM with certain retention settings, it can delete older data files, which might include versions of data that are older than the specified retention period. If the data engineer is unable to restore the table to a version that is 3 days old because the data files have been deleted, it's likely because the VACUUM command was run on the table, removing the older data files as part of data cleanup.

NEW QUESTION 21

A Delta Live Table pipeline includes two datasets defined using STREAMING LIVE TABLE. Three datasets are defined against Delta Lake table sources using LIVE TABLE.

The table is configured to run in Production mode using the Continuous Pipeline Mode. Assuming previously unprocessed data exists and all definitions are valid, what is the expected outcome after clicking Start to update the pipeline?

- A. All datasets will be updated at set intervals until the pipeline is shut down
- B. The compute resources will persist to allow for additional testing.
- C. All datasets will be updated once and the pipeline will persist without any processing
- D. The compute resources will persist but go unused.
- E. All datasets will be updated at set intervals until the pipeline is shut down
- F. The compute resources will be deployed for the update and terminated when the pipeline is stopped.
- G. All datasets will be updated once and the pipeline will shut down
- H. The compute resources will be terminated.
- I. All datasets will be updated once and the pipeline will shut down
- J. The compute resources will persist to allow for additional testing.

Answer: C

Explanation:

In a Delta Live Table pipeline running in Continuous Pipeline Mode, when you click Start to update the pipeline, the following outcome is expected: All datasets defined using STREAMING LIVE TABLE and LIVE TABLE against Delta Lake table sources will be updated at set intervals. The compute resources will be deployed for the update process and will be active during the execution of the pipeline. The compute resources will be terminated when the pipeline is stopped or shut down. This mode allows for continuous and periodic updates to the datasets as new data arrives or changes in the underlying Delta Lake tables occur. The compute resources are provisioned and utilized during the update intervals to process the data and perform the necessary operations.

NEW QUESTION 25

A Delta Live Table pipeline includes two datasets defined using STREAMING LIVE TABLE. Three datasets are defined against Delta Lake table sources using LIVE TABLE.

The table is configured to run in Development mode using the Continuous Pipeline Mode.

Assuming previously unprocessed data exists and all definitions are valid, what is the expected outcome after clicking Start to update the pipeline?

- A. All datasets will be updated once and the pipeline will shut down
- B. The compute resources will be terminated.
- C. All datasets will be updated at set intervals until the pipeline is shut down
- D. The compute resources will persist until the pipeline is shut down.
- E. All datasets will be updated once and the pipeline will persist without any processing
- F. The compute resources will persist but go unused.
- G. All datasets will be updated once and the pipeline will shut down
- H. The compute resources will persist to allow for additional testing.
- I. All datasets will be updated at set intervals until the pipeline is shut down
- J. The compute resources will persist to allow for additional testing.

Answer: E

Explanation:

You can optimize pipeline execution by switching between development and production modes. Use the Delta Live Tables Environment Toggle Icon buttons in the Pipelines UI to switch between these two modes. By default, pipelines run in development mode.

When you run your pipeline in development mode, the Delta Live Tables system does the following:

Reuses a cluster to avoid the overhead of restarts. By default, clusters run for two hours when development mode is enabled. You can change this with the `pipelines.clusterShutdown.delay` setting in the Configure your compute settings.

Disables pipeline retries so you can immediately detect and fix errors. In production mode, the Delta Live Tables system does the following:

Restarts the cluster for specific recoverable errors, including memory leaks and stale credentials.

Retries execution in the event of specific errors, for example, a failure to start a cluster. <https://docs.databricks.com/en/delta-live-tables/updates.html#optimize-execution>

NEW QUESTION 27

A data engineer has a Job with multiple tasks that runs nightly. Each of the tasks runs slowly because the clusters take a long time to start.

Which of the following actions can the data engineer perform to improve the start up time for the clusters used for the Job?

- A. They can use endpoints available in Databricks SQL
- B. They can use jobs clusters instead of all-purpose clusters
- C. They can configure the clusters to be single-node
- D. They can use clusters that are from a cluster pool
- E. They can configure the clusters to autoscale for larger data sizes

Answer: D

Explanation:

Cluster pools are a way to pre-provision clusters that are ready to use. This can reduce the start up time for clusters, as they do not have to be created from scratch. All-purpose clusters are not pre-provisioned, so they will take longer to start up. Jobs clusters are a type of cluster pool, but they are not the best option for this use case. Jobs clusters are designed for long-running jobs, and they can be more expensive than other types of cluster pools. Single-node clusters are the smallest type of cluster, and they will start up the fastest. However, they may not be powerful enough to run the Job's tasks. Autoscaling clusters can scale up or down based on demand. This can help to improve the start up time for clusters, as they will only be created when they are needed. However, autoscaling clusters can also be more expensive than other types of cluster pool <https://docs.databricks.com/en/clusters/pool-best-practices.html>

NEW QUESTION 31

A data engineer needs access to a table `new_table`, but they do not have the correct permissions. They can ask the table owner for permission, but they do not know who the table owner is.

Which of the following approaches can be used to identify the owner of `new_table`?

- A. Review the Permissions tab in the table's page in Data Explorer
- B. All of these options can be used to identify the owner of the table
- C. Review the Owner field in the table's page in Data Explorer
- D. Review the Owner field in the table's page in the cloud storage solution
- E. There is no way to identify the owner of the table

Answer: C

NEW QUESTION 34

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

Databricks-Certified-Data-Engineer-Associate Practice Exam Features:

- * Databricks-Certified-Data-Engineer-Associate Questions and Answers Updated Frequently
- * Databricks-Certified-Data-Engineer-Associate Practice Questions Verified by Expert Senior Certified Staff
- * Databricks-Certified-Data-Engineer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * Databricks-Certified-Data-Engineer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The Databricks-Certified-Data-Engineer-Associate Practice Test Here](#)