

Exam Questions 300-435

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

<https://www.2passeasy.com/dumps/300-435/>



NEW QUESTION 1

Which two features are foundations of a software-defined network instead of a traditional network? (Choose two.)

- A. control plane and data plane are tightly coupled
- B. build upon a robust software stack
- C. requires device by device-level configurations
- D. automated through expressed intent to a software controller
- E. requires significant physical hardware resources

Answer: BD

NEW QUESTION 2

```
module: ietf-ip
augment /if:interfaces/if:interface:
+--rw ipv4!
|   +--rw enabled?      boolean
|   +--rw forwarding?   boolean
|   +--rw mtu?           uint16
|   +--rw address* [ip]
|       |   +--rw ip                inet:ipv4-address-no-zone
|       |   +--rw (subnet)
|       |       |   +--: (prefix-length)
|       |       |   |   +--rw prefix-length?      uint8
|       |       |   |   +--: {netmask}
|       |       |       +--rw netmask?            yang:dotted-guad (ipv4-non-contiguous-netmasks)?
|       |       +--ro origin?                    ip-address-origin
|   +--rw neighbor* [ip]
|       +--rw ip                inet:ipv4-address-no-zone
|       +--rw link-layer-address yang:phys-address
```

Refer to the exhibit. Which NETCONF statement type is represented by +--rw address* [ip]?

- A. list
- B. leaf-list
- C. container
- D. submodule

Answer: A

NEW QUESTION 3

The automation engineer must replace device configuration using RESTCONF. How is this configured using the Python library Requests?

- A. delete()
- B. post()
- C. put()
- D. patch()

Answer: C

NEW QUESTION 4

```
<rpc message-id="101" xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <establish-subscription
    xmlns="urn:ietf:params:xml:ns:yang:ietf-event-notifications"
    xmlns:yp="urn:ietf:params:xml:ns:yang:ietf-yang-push">
    <stream>yp:yang-push</stream>
    <yp:xpath-filter>/mdt-oper:mdt-oper-data/mdt-subscriptions</yp:xpath-filter>
    <yp: <input type="text" value="period" /> >1000</yp: <input type="text" value="period" /> >
  </establish-subscription>
</rpc>
```

Refer to the exhibit. Which XML tag completes this NETCONF telemetry subscription with a Cisco IOS XE device?

- A. crontab
- B. cadence
- C. frequency
- D. period

Answer: D

NEW QUESTION 5

Which two statements are benefits of YANG-push telemetry data over traditional data collection methods? (Choose two.)

- A. The subscription requests use less bandwidth than SNMP polls.
- B. It uses UDP rather than TCP.
- C. You can precisely define data subscriptions.
- D. It scales better than SNMP.
- E. It is supported on more devices than SNMP.

Answer: BC

NEW QUESTION 6

```
from device_info import ios_xel
from ncclient import manager
import xmltodict

netconf_filter = open('filter-ietf-interfaces.xml').read()

if __name__ == '__main__':
    with manager.connect(host=ios_xel["address"],
                        port=ios_xel["port"],
                        username=ios_xel["username"],
                        password=ios_xel["password"],
                        hostkey_verify=False) as m:

        netconf_reply = m.get(netcong_filter)

        intf_details = xmltodict.parse(netconf_reply.xml) ["rpc-reply"] ["data"]
        intf_config = intf_details["interfaces"] ["interface"]
        intf_info = intf_details["interfaces-state"] ["interface"]

        print("")
        print("Interface Details:")
        print(" Name: {}".format(  ["name"]))
        print(" Description: {}".format(intf_config["description"]))
        print(" Type: {}".format(intf_config["type"] ["#text"]))
        print(" MAC Address: {}".format(intf_info["phys-address"]))
        print(" Packet Input: {}".format(intf_info["statistics"] ["in-unicast-pkts"]))
        print(" Packet Output: {}".format(intf_info["statistics"] ["out-unicast-pkts"]))
```

```
<filter>
  <interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces">
    <interface>
      <name>GigabitEthernet2</name>
    </interface>
  </interfaces>
  <interfaces-state xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces">
    <interface>
      <name>GigabitEthernet2</name>
    </interface>
  </interfaces-state>
</filter>
```

Refer to the exhibits. An engineer creates a Python scripts using ncclient to display interface information. The code must be completed so that it can be tested. Which expression completes the highlighted section in the format call?

- A. intf_info
- B. intf_config
- C. intf_get
- D. intf_config[0]

Answer: A

NEW QUESTION 7


```
from ncclient import manager
with manager.connect(
    host='10.0.0.1',
    port=12022,
    username='cisco',
    password='cisco',
    hostkey_verify=False,
    allow_agent=False,
    look_for_keys=False,
    device_params={'name': 'iosxe'},
) as m:
```

Refer to the exhibit. What is the correct ncclient method to use to collect the running configuration of a Cisco IOS XE device that uses NETCONF?

- A. config=m.copy_config(source='running')
- B. config=m.get(source='running')
- C. config=m.collect_config(source='running')
- D. config=m.get_config(source='running')

Answer: A

NEW QUESTION 8

What does the command boot ipxe forever switch 1 perform when executed on a Cisco IOS XE device?

- A. It continuously sends DHCP requests for iPXE until the device boots with an image.
- B. It continuously sends DNS requests for iPXE until the device restarts.
- C. It continuously sends DNS requests for iPXE until the device boots with an image.
- D. It continuously sends DHCP requests for iPXE until the device restarts.

Answer: A

NEW QUESTION 9

Webhook that are generated by Cisco DNA Center are REST calls with which properties?

- A. JSON payload delivered via PUT
- B. XML payload delivered via POST
- C. JSON payload delivered via POST
- D. XML payload delivered via PUT

Answer: A

NEW QUESTION 10

Which two API calls are used to trigger a device configuration sync in Cisco DNA Center? (Choose two.)

- A. PUT /dna/intent/api/v1/network-device
- B. PUT /dna/intent/api/v1/network-device/sync-all
- C. PUT /dna/intent/api/v1/network-device/{networkDeviceId}/sync
- D. PUT /dna/intent/api/v1/network-device/sync
- E. POST /dna/intent/api/v1/network-device/{networkDeviceId}/sync

Answer: CE

NEW QUESTION 10

A network administrator must troubleshoot a network issue using Cisco DNA Center. Which API request helps to determine issue details, impacted hosts, or suggested actions for the resolution?

- A. /dna/intent/v1/issues
- B. /dna/intent/api/v1/issues
- C. /dna/intent/v1/issue-enrichment-details
- D. /dna/api/v1/client-health/issues

Answer: B

NEW QUESTION 14

Which two features are characteristics of software-defined networks when compared to traditional infrastructure? (Choose two.)

- A. configured box-by-box
- B. changed manually
- C. use overlay networks
- D. designed to change
- E. require software development experience to manage

Answer: CD

NEW QUESTION 17

FILL BLANK

`https://vmanage-ip-address:8443/dataservice/device/action/reboot` `260faff9-2d31-4312-cf96-143b46db0211`

Information about a rebooted device needs to be displayed with an ID of 260faff9-2d31-4312-cf96-143b46db0211 using the Cisco SD-WAN vManage Administration APIs. The API documentation states that deviceid is a required request parameter. Fill in the blank to create the REST call.

- A. Mastered
- B. Not Mastered

Answer: A**Explanation:**
“deviceid”:**NEW QUESTION 18**

FILL BLANK

Fill in the blank to complete the URL for an API call to Cisco SD-WAN to display the history of the Bidirectional Forwarding Detection sessions that run on a vEdge router.

`https://<vmanage-ip-address>/dataservice/device/` `deviceid=<deviceid>`

- A. Mastered
- B. Not Mastered

Answer: A**Explanation:**
bfd/synced/sessions?**NEW QUESTION 21**

Which Python snippet receives a Meraki webhook request?

A.

```
@app.route('/mynet/webhook', methods=['PUT'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

A.

```
@app.route('/mynet/webhook', methods=['GET'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

B.

```
@app.route('/mynet/webhook', methods=['PATCH'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

C.

```
@app.route('/mynet/webhook', methods=['POST'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

Answer: D**NEW QUESTION 23**

Which two types of solution are built with the Meraki Location Scanning API? (Choose two.)

- A. networking automation
- B. mapping
- C. guest Wi-Fi
- D. Sense
- E. wayfinder

Answer: BE**NEW QUESTION 26**

With the MV Sense API, which REST endpoint provides LUX level?

- A. /merakimv/XXXX-XXXX-XXXX/light
- B. /merakimv/XXXX-XXXX-XXXX/raw_detections
- C. /merakimv/XXXX-XXXX-XXXX/0
- D. /merakimv/XXXX-XXXX-XXXX/zones

Answer: A

NEW QUESTION 30

Which REST endpoint is used to create a Cisco Meraki network?

- A. POST /organizations/{organizationId}/networks
- B. PATCH /networks{networkId}
- C. PUT /organizations/{organizationId}/networks
- D. POST /networks{networkId}

Answer: A

NEW QUESTION 32

```
{
  "id": "L_123456",
  "organizationId": 1357924,
  "name": "Long Island Office",
  "timeZone": "America/Los_Angeles",
  "tags": "tag1 tag2",
  "type": "combined",
  "disableMyMerakiCom": false
}
```

Refer to the exhibit. Which two parameters are mandatory when the Cisco Meraki API is used to create a network? (Choose two.)

- A. timezone
- B. disableMyMerakiCom
- C. type
- D. tags
- E. organizationId

Answer: AE

NEW QUESTION 36

Which HTTP request is valid to create a new wireless network called "Demo Wireless Network" in the organization "QASD- EROA-MKAW"?

- A. **POST /organizations/networks**
 Host: **https://api.meraki.com/api/v0**

```
{
  "name": "Demo Wireless Network",
  "organizationId": "QASD-EROA-MKAW",
  "type": "wireless"
}
```
- B. **POST /organizations/QASD-EROA-MKAW/networks**
 Host: **https://api.meraki.com/api/v0**

```
{
  "name": "Demo Wireless Network",
  "type": "combined"
}
```
- C. **POST /organizations/QASD-EROA-MKAW/networks**
 Host: **https://api.meraki.com/api/v0**

```
{
  "name": "Demo Wireless Network",
  "organizationId": "QASD-EROA-MKAW",
  "type": "wireless"
}
```

Answer: A

NEW QUESTION 40

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 300-435 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 300-435 Product From:

<https://www.2passeasy.com/dumps/300-435/>

Money Back Guarantee

300-435 Practice Exam Features:

- * 300-435 Questions and Answers Updated Frequently
- * 300-435 Practice Questions Verified by Expert Senior Certified Staff
- * 300-435 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-435 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year