

Exam Questions AWS-Certified-Data-Engineer-Associate

AWS Certified Data Engineer - Associate (DEA-C01)

<https://www.2passeasy.com/dumps/AWS-Certified-Data-Engineer-Associate/>



NEW QUESTION 1

A data engineer needs to join data from multiple sources to perform a one-time analysis job. The data is stored in Amazon DynamoDB, Amazon RDS, Amazon Redshift, and Amazon S3.

Which solution will meet this requirement MOST cost-effectively?

- A. Use an Amazon EMR provisioned cluster to read from all source
- B. Use Apache Spark to join the data and perform the analysis.
- C. Copy the data from DynamoDB, Amazon RDS, and Amazon Redshift into Amazon S3. Run Amazon Athena queries directly on the S3 files.
- D. Use Amazon Athena Federated Query to join the data from all data sources.
- E. Use Redshift Spectrum to query data from DynamoDB, Amazon RDS, and Amazon S3 directly from Redshift.

Answer: C

Explanation:

Amazon Athena Federated Query is a feature that allows you to query data from multiple sources using standard SQL. You can use Athena Federated Query to join data from Amazon DynamoDB, Amazon RDS, Amazon Redshift, and Amazon S3, as well as other data sources such as MongoDB, Apache HBase, and Apache Kafka¹. Athena Federated Query is a serverless and interactive service, meaning you do not need to provision or manage any infrastructure, and you only pay for the amount of data scanned by your queries. Athena Federated Query is the most cost-effective solution for performing a one-time analysis job on data from multiple sources, as it eliminates the need to copy or move data, and allows you to query data directly from the source.

The other options are not as cost-effective as Athena Federated Query, as they involve additional steps or costs. Option A requires you to provision and pay for an Amazon EMR cluster, which can be expensive and time-consuming for a one-time job. Option B requires you to copy or move data from DynamoDB, RDS, and Redshift to S3, which can incur additional costs for data transfer and storage, and also introduce latency and complexity. Option D requires you to have an existing Redshift cluster, which can be costly and may not be necessary for a one-time job. Option E also does not support querying data from RDS directly, so you would need to use Redshift Federated Query to access RDS data, which adds another layer of complexity². References:

- ? Amazon Athena Federated Query
- ? Redshift Spectrum vs Federated Query

NEW QUESTION 2

A media company uses software as a service (SaaS) applications to gather data by using third-party tools. The company needs to store the data in an Amazon S3 bucket. The company will use Amazon Redshift to perform analytics based on the data.

Which AWS service or feature will meet these requirements with the LEAST operational overhead?

- A. Amazon Managed Streaming for Apache Kafka (Amazon MSK)
- B. Amazon AppFlow
- C. AWS Glue Data Catalog
- D. Amazon Kinesis

Answer: B

Explanation:

Amazon AppFlow is a fully managed integration service that enables you to securely transfer data between SaaS applications and AWS services like Amazon S3 and Amazon Redshift. Amazon AppFlow supports many SaaS applications as data sources and targets, and allows you to configure data flows with a few clicks. Amazon AppFlow also provides features such as data transformation, filtering, validation, and encryption to prepare and protect your data. Amazon AppFlow meets the requirements of the media company with the least operational overhead, as it eliminates the need to write code, manage infrastructure, or monitor data pipelines. References:

- ? Amazon AppFlow
- ? Amazon AppFlow | SaaS Integrations List
- ? Get started with data integration from Amazon S3 to Amazon Redshift using AWS Glue interactive sessions

NEW QUESTION 3

A company stores datasets in JSON format and .csv format in an Amazon S3 bucket. The company has Amazon RDS for Microsoft SQL Server databases, Amazon DynamoDB tables that are in provisioned capacity mode, and an Amazon Redshift cluster. A data engineering team must develop a solution that will give data scientists the ability to query all data sources by using syntax similar to SQL.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use AWS Glue to crawl the data source
- B. Store metadata in the AWS Glue Data Catalog
- C. Use Amazon Athena to query the data
- D. Use SQL for structured data source
- E. Use PartiQL for data that is stored in JSON format.
- F. Use AWS Glue to crawl the data source
- G. Store metadata in the AWS Glue Data Catalog
- H. Use Redshift Spectrum to query the data
- I. Use SQL for structured data source
- J. Use PartiQL for data that is stored in JSON format.
- K. Use AWS Glue to crawl the data source
- L. Store metadata in the AWS Glue Data Catalog
- M. Use AWS Glue jobs to transform data that is in JSON format to Apache Parquet or .csv format
- N. Store the transformed data in an S3 bucket
- O. Use Amazon Athena to query the original and transformed data from the S3 bucket.
- P. Use AWS Lake Formation to create a data lake
- Q. Use Lake Formation jobs to transform the data from all data sources to Apache Parquet format
- R. Store the transformed data in an S3 bucket
- S. Use Amazon Athena or Redshift Spectrum to query the data.

Answer: A

Explanation:

The best solution to meet the requirements of giving data scientists the ability to query all data sources by using syntax similar to SQL with the least operational

overhead is to use AWS Glue to crawl the data sources, store metadata in the AWS Glue Data Catalog, use Amazon Athena to query the data, use SQL for structured data sources, and use PartiQL for data that is stored in JSON format.

AWS Glue is a serverless data integration service that makes it easy to prepare, clean, enrich, and move data between data stores¹. AWS Glue crawlers are processes that connect to a data store, progress through a prioritized list of classifiers to determine the schema for your data, and then create metadata tables in the Data Catalog². The Data Catalog is a persistent metadata store that contains table definitions, job definitions, and other control information to help you manage your AWS Glue components³. You can use AWS Glue to crawl the data sources, such as Amazon S3, Amazon RDS for Microsoft SQL Server, and Amazon DynamoDB, and store the metadata in the Data Catalog.

Amazon Athena is a serverless, interactive query service that makes it easy to analyze data directly in Amazon S3 using standard SQL or Python⁴. Amazon Athena also supports PartiQL, a SQL-compatible query language that lets you query, insert, update, and delete data from semi-structured and nested data, such as JSON. You can use Amazon Athena to query the data from the Data Catalog using SQL for structured data sources, such as .csv files and relational databases, and PartiQL for data that is stored in JSON format. You can also use Athena to query data from other data sources, such as Amazon Redshift, using federated queries.

Using AWS Glue and Amazon Athena to query all data sources by using syntax similar to SQL is the least operational overhead solution, as you do not need to provision, manage, or scale any infrastructure, and you pay only for the resources you use. AWS Glue charges you based on the compute time and the data processed by your crawlers and ETL jobs¹. Amazon Athena charges you based on the amount of data scanned by your queries. You can also reduce the cost and improve the performance of your queries by using compression, partitioning, and columnar formats for your data in Amazon S3.

Option B is not the best solution, as using AWS Glue to crawl the data sources, store metadata in the AWS Glue Data Catalog, and use Redshift Spectrum to query the data, would incur more costs and complexity than using Amazon Athena. Redshift Spectrum is a feature of Amazon Redshift, a fully managed data warehouse service, that allows you to query and join data across your data warehouse and your data lake using standard SQL. While Redshift Spectrum is powerful and useful for many data warehousing scenarios, it is not necessary or cost-effective for querying all data sources by using syntax similar to SQL. Redshift Spectrum charges you based on the amount of data scanned by your queries, which is similar to Amazon Athena, but it also requires you to have an Amazon Redshift cluster, which charges you based on the node type, the number of nodes, and the duration of the cluster⁵. These costs can add up quickly, especially if you have large volumes of data and complex queries. Moreover, using Redshift Spectrum would introduce additional latency and complexity, as you would have to provision and manage the cluster, and create an external schema and database for the data in the Data Catalog, instead of querying it directly from Amazon Athena.

Option C is not the best solution, as using AWS Glue to crawl the data sources, store metadata in the AWS Glue Data Catalog, use AWS Glue jobs to transform data that is in JSON format to Apache Parquet or .csv format, store the transformed data in an S3 bucket, and use Amazon Athena to query the original and transformed data from the S3 bucket, would incur more costs and complexity than using Amazon Athena with PartiQL. AWS Glue jobs are ETL scripts that you can write in Python or Scala to transform your data and load it to your target data store. Apache Parquet is a columnar storage format that can improve the performance of analytical queries by reducing the amount of data that needs to be scanned and providing efficient compression and encoding schemes⁶. While using AWS Glue jobs and Parquet can improve the performance and reduce the cost of your queries, they would also increase the complexity and the operational overhead of the data pipeline, as you would have to write, run, and monitor the ETL jobs, and store the transformed data in a separate location in Amazon S3. Moreover, using AWS Glue jobs and Parquet would introduce additional latency, as you would have to wait for the ETL jobs to finish before querying the transformed data.

Option D is not the best solution, as using AWS Lake Formation to create a data lake, use Lake Formation jobs to transform the data from all data sources to Apache Parquet format, store the transformed data in an S3 bucket, and use Amazon Athena or Redshift Spectrum to query the data, would incur more costs and complexity than using Amazon Athena with PartiQL. AWS Lake Formation is a service that helps you centrally govern, secure, and globally share data for analytics and machine learning⁷. Lake Formation jobs are ETL jobs that you can create and run using the Lake Formation console or API. While using Lake Formation and Parquet can improve the performance and reduce the cost of your queries, they would also increase the complexity and the operational overhead of the data pipeline, as you would have to create, run, and monitor the Lake Formation jobs, and store the transformed data in a separate location in Amazon S3. Moreover, using Lake Formation and Parquet would introduce additional latency, as you would have to wait for the Lake Formation jobs to finish before querying the transformed data. Furthermore, using Redshift Spectrum to query the data would also incur the same costs and complexity as mentioned in option B. References:

- ? What is Amazon Athena?
- ? Data Catalog and crawlers in AWS Glue
- ? AWS Glue Data Catalog
- ? Columnar Storage Formats
- ? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide
- ? AWS Glue Schema Registry
- ? What is AWS Glue?
- ? Amazon Redshift Serverless
- ? Amazon Redshift provisioned clusters
- ? [Querying external data using Amazon Redshift Spectrum]
- ? [Using stored procedures in Amazon Redshift]
- ? [What is AWS Lambda?]
- ? [PartiQL for Amazon Athena]
- ? [Federated queries in Amazon Athena]
- ? [Amazon Athena pricing]
- ? [Top 10 performance tuning tips for Amazon Athena]
- ? [AWS Glue ETL jobs]
- ? [AWS Lake Formation jobs]

NEW QUESTION 4

A company uses AWS Step Functions to orchestrate a data pipeline. The pipeline consists of Amazon EMR jobs that ingest data from data sources and store the data in an Amazon S3 bucket. The pipeline also includes EMR jobs that load the data to Amazon Redshift.

The company's cloud infrastructure team manually built a Step Functions state machine. The cloud infrastructure team launched an EMR cluster into a VPC to support the EMR jobs. However, the deployed Step Functions state machine is not able to run the EMR jobs.

Which combination of steps should the company take to identify the reason the Step Functions state machine is not able to run the EMR jobs? (Choose two.)

- A. Use AWS CloudFormation to automate the Step Functions state machine deployment
- B. Create a step to pause the state machine during the EMR jobs that fail
- C. Configure the step to wait for a human user to send approval through an email message
- D. Include details of the EMR task in the email message for further analysis.
- E. Verify that the Step Functions state machine code has all IAM permissions that are necessary to create and run the EMR job
- F. Verify that the Step Functions state machine code also includes IAM permissions to access the Amazon S3 buckets that the EMR jobs use
- G. Use Access Analyzer for S3 to check the S3 access properties.
- H. Check for entries in Amazon CloudWatch for the newly created EMR cluster
- I. Change the AWS Step Functions state machine code to use Amazon EMR on EKS
- J. Change the IAM access policies and the security group configuration for the Step Functions state machine code to reflect inclusion of Amazon Elastic Kubernetes Service (Amazon EKS).
- K. Query the flow logs for the VPC
- L. Determine whether the traffic that originates from the EMR cluster can successfully reach the data provider
- M. Determine whether any security group that might be attached to the Amazon EMR cluster allows connections to the data source servers on the informed ports.

- N. Check the retry scenarios that the company configured for the EMR job
- O. Increase the number of seconds in the interval between each EMR task
- P. Validate that each fallback state has the appropriate catch for each decision state
- Q. Configure an Amazon Simple Notification Service (Amazon SNS) topic to store the error messages.

Answer: BD

Explanation:

To identify the reason why the Step Functions state machine is not able to run the EMR jobs, the company should take the following steps:

? Verify that the Step Functions state machine code has all IAM permissions that are necessary to create and run the EMR jobs. The state machine code should have an IAM role that allows it to invoke the EMR APIs, such as RunJobFlow, AddJobFlowSteps, and DescribeStep. The state machine code should also have IAM permissions to access the Amazon S3 buckets that the EMR jobs use as input and output locations. The company can use Access Analyzer for S3 to check the access policies and permissions of the S3 buckets¹². Therefore, option B is correct.

? Query the flow logs for the VPC. The flow logs can provide information about the network traffic to and from the EMR cluster that is launched in the VPC. The company can use the flow logs to determine whether the traffic that originates from the EMR cluster can successfully reach the data providers, such as Amazon RDS, Amazon Redshift, or other external sources. The company can also determine whether any security group that might be attached to the EMR cluster allows connections to the data source servers on the informed ports. The company can use Amazon VPC Flow Logs or Amazon CloudWatch Logs Insights to query the flow logs³. Therefore, option D is correct.

Option A is incorrect because it suggests using AWS CloudFormation to automate the Step Functions state machine deployment. While this is a good practice to ensure consistency and repeatability of the deployment, it does not help to identify the reason why the state machine is not able to run the EMR jobs. Moreover, creating a step to pause the state machine during the EMR jobs that fail and wait for a human user to send approval through an email message is not a reliable way to troubleshoot the issue. The company should use the Step Functions console or API to monitor the execution history and status of the state machine, and use Amazon CloudWatch to view the logs and metrics of the EMR jobs. Option C is incorrect because it suggests changing the AWS Step Functions state machine code to use Amazon EMR on EKS. Amazon EMR on EKS is a service that allows you to run EMR jobs on Amazon Elastic Kubernetes Service (Amazon EKS) clusters. While this service has some benefits, such as lower cost and faster execution time, it does not support all the features and integrations that EMR on EC2 does, such as EMR Notebooks, EMR Studio, and EMRFS. Therefore, changing the state machine code to use EMR on EKS may not be compatible with the existing data pipeline and may introduce new issues. Option E is incorrect because it suggests checking the retry scenarios that the company configured for the EMR jobs. While this is a good practice to handle transient failures and errors, it does not help to identify the root cause of why the state machine is not able to run the EMR jobs. Moreover, increasing the number of seconds in the interval between each EMR task may not improve the success rate of the jobs, and may increase the execution time and cost of the state machine. Configuring an Amazon SNS topic to store the error messages may help to notify the company of any failures, but it does not provide enough information to troubleshoot the issue.

References:

- ? 1: Manage an Amazon EMR Job - AWS Step Functions
- ? 2: Access Analyzer for S3 - Amazon Simple Storage Service
- ? 3: Working with Amazon EMR and VPC Flow Logs - Amazon EMR
- ? [4]: Analyzing VPC Flow Logs with Amazon CloudWatch Logs Insights - Amazon Virtual Private Cloud
- ? [5]: Monitor AWS Step Functions - AWS Step Functions
- ? [6]: Monitor Amazon EMR clusters - Amazon EMR
- ? [7]: Amazon EMR on Amazon EKS - Amazon EMR

NEW QUESTION 5

A company receives .csv files that contain physical address data. The data is in columns that have the following names: Door_No, Street_Name, City, and Zip_Code. The company wants to create a single column to store these values in the following format:

```
{
  "Door_No": "24",
  "Street_Name": "AAA street",
  "City": "BBB",
  "Zip_Code": "111111"
}
```

Which solution will meet this requirement with the LEAST coding effort?

- A. Use AWS Glue DataBrew to read the file
- B. Use the NEST TO ARRAY transformation to create the new column.
- C. Use AWS Glue DataBrew to read the file
- D. Use the NEST TO MAP transformation to create the new column.
- E. Use AWS Glue DataBrew to read the file
- F. Use the PIVOT transformation to create the new column.
- G. Write a Lambda function in Python to read the file
- H. Use the Python data dictionary type to create the new column.

Answer: B

Explanation:

The NEST TO MAP transformation allows you to combine multiple columns into a single column that contains a JSON object with key-value pairs. This is the easiest way to achieve the desired format for the physical address data, as you can simply select the columns to nest and specify the keys for each column. The NEST TO ARRAY transformation creates a single column that contains an array of values, which is not the same as the JSON object format. The PIVOT transformation reshapes the data by creating new columns from unique values in a selected column, which is not applicable for this use case. Writing a Lambda function in Python requires more coding effort than using AWS Glue DataBrew, which provides a visual and interactive interface for data transformations.

References:

- ? 7 most common data preparation transformations in AWS Glue DataBrew (Section: Nesting and unnesting columns)
- ? NEST TO MAP - AWS Glue DataBrew (Section: Syntax)

NEW QUESTION 6

A data engineer is building a data pipeline on AWS by using AWS Glue extract, transform, and load (ETL) jobs. The data engineer needs to process data from Amazon RDS and MongoDB, perform transformations, and load the transformed data into Amazon Redshift for analytics. The data updates must occur every hour.

Which combination of tasks will meet these requirements with the LEAST operational overhead? (Choose two.)

- A. Configure AWS Glue triggers to run the ETL jobs even/ hour.
- B. Use AWS Glue DataBrew to clean and prepare the data for analytics.
- C. Use AWS Lambda functions to schedule and run the ETL jobs even/ hour.
- D. Use AWS Glue connections to establish connectivity between the data sources and Amazon Redshift.
- E. Use the Redshift Data API to load transformed data into Amazon Redshift.

Answer: AD

Explanation:

The correct answer is to configure AWS Glue triggers to run the ETL jobs every hour and use AWS Glue connections to establish connectivity between the data sources and Amazon Redshift. AWS Glue triggers are a way to schedule and orchestrate ETL jobs with the least operational overhead. AWS Glue connections are a way to securely connect to data sources and targets using JDBC or MongoDB drivers. AWS Glue DataBrew is a visual data preparation tool that does not support MongoDB as a data source. AWS Lambda functions are a serverless option to schedule and run ETL jobs, but they have a limit of 15 minutes for execution time, which may not be enough for complex transformations. The Redshift Data API is a way to run SQL commands on Amazon Redshift clusters without needing a persistent connection, but it does not support loading data from AWS Glue ETL jobs. References:

? AWS Glue triggers

? AWS Glue connections

? AWS Glue DataBrew

? [AWS Lambda functions]

? [Redshift Data API]

NEW QUESTION 7

A company uses Amazon Athena to run SQL queries for extract, transform, and load (ETL) tasks by using Create Table As Select (CTAS). The company must use Apache Spark instead of SQL to generate analytics.

Which solution will give the company the ability to use Spark to access Athena?

- A. Athena query settings
- B. Athena workgroup
- C. Athena data source
- D. Athena query editor

Answer: C

Explanation:

Athena data source is a solution that allows you to use Spark to access Athena by using the Athena JDBC driver and the Spark SQL interface. You can use the Athena data source to create Spark DataFrames from Athena tables, run SQL queries on the DataFrames, and write the results back to Athena. The Athena data source supports various data formats, such as CSV, JSON, ORC, and Parquet, and also supports partitioned and bucketed tables. The Athena data source is a cost-effective and scalable way to use Spark to access Athena, as it does not require any additional infrastructure or services, and you only pay for the data scanned by Athena.

The other options are not solutions that give the company the ability to use Spark to access Athena. Option A, Athena query settings, is a feature that allows you to configure various parameters for your Athena queries, such as the output location, the encryption settings, the query timeout, and the workgroup. Option B, Athena workgroup, is a feature that allows you to isolate and manage your Athena queries and resources, such as the query history, the query notifications, the query concurrency, and the query cost. Option D, Athena query editor, is a feature that allows you to write and run SQL queries on Athena using the web console or the API. None of these options enable you to use Spark instead of SQL to generate analytics on Athena. References:

? Using Apache Spark in Amazon Athena

? Athena JDBC Driver

? Spark SQL

? Athena query settings

? [Athena workgroups]

? [Athena query editor]

NEW QUESTION 8

A data engineer must orchestrate a data pipeline that consists of one AWS Lambda function and one AWS Glue job. The solution must integrate with AWS services.

Which solution will meet these requirements with the LEAST management overhead?

- A. Use an AWS Step Functions workflow that includes a state machine
- B. Configure the state machine to run the Lambda function and then the AWS Glue job.
- C. Use an Apache Airflow workflow that is deployed on an Amazon EC2 instance
- D. Define a directed acyclic graph (DAG) in which the first task is to call the Lambda function and the second task is to call the AWS Glue job.
- E. Use an AWS Glue workflow to run the Lambda function and then the AWS Glue job.
- F. Use an Apache Airflow workflow that is deployed on Amazon Elastic Kubernetes Service (Amazon EKS). Define a directed acyclic graph (DAG) in which the first task is to call the Lambda function and the second task is to call the AWS Glue job.

Answer: A

Explanation:

AWS Step Functions is a service that allows you to coordinate multiple AWS services into serverless workflows. You can use Step Functions to create state machines that define the sequence and logic of the tasks in your workflow. Step Functions supports various types of tasks, such as Lambda functions, AWS Glue jobs, Amazon EMR clusters, Amazon ECS tasks, etc. You can use Step Functions to monitor and troubleshoot your workflows, as well as to handle errors and retries.

Using an AWS Step Functions workflow that includes a state machine to run the Lambda function and then the AWS Glue job will meet the requirements with the least management overhead, as it leverages the serverless and managed capabilities of Step Functions. You do not need to write any code to orchestrate the tasks in your workflow, as you can use the Step Functions console or the AWS Serverless Application Model (AWS SAM) to define and deploy your state machine. You also do not need to provision or manage any servers or clusters, as Step Functions scales automatically based on the demand.

The other options are not as efficient as using an AWS Step Functions workflow. Using an Apache Airflow workflow that is deployed on an Amazon EC2 instance or on Amazon Elastic Kubernetes Service (Amazon EKS) will require more management overhead, as you will need to provision, configure, and maintain the EC2 instance or the EKS cluster, as well as the Airflow components. You will also need to write and maintain the Airflow DAGs to orchestrate the tasks in your workflow. Using an AWS Glue workflow to run the Lambda function and then the AWS Glue job will not work, as AWS Glue workflows only support AWS Glue jobs

and crawlers as tasks, not Lambda functions. References:

? AWS Step Functions

? AWS Glue

? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide, Chapter 6: Data Integration and Transformation, Section 6.3: AWS Step Functions

NEW QUESTION 9

A company needs to partition the Amazon S3 storage that the company uses for a data lake. The partitioning will use a path of the S3 object keys in the following format: s3://bucket/prefix/year=2023/month=01/day=01.

A data engineer must ensure that the AWS Glue Data Catalog synchronizes with the S3 storage when the company adds new partitions to the bucket.

Which solution will meet these requirements with the LEAST latency?

- A. Schedule an AWS Glue crawler to run every morning.
- B. Manually run the AWS Glue CreatePartition API twice each day.
- C. Use code that writes data to Amazon S3 to invoke the Boto3 AWS Glue create partition API call.
- D. Run the MSCK REPAIR TABLE command from the AWS Glue console.

Answer: C

Explanation:

The best solution to ensure that the AWS Glue Data Catalog synchronizes with the S3 storage when the company adds new partitions to the bucket with the least latency is to use code that writes data to Amazon S3 to invoke the Boto3 AWS Glue create partition API call. This way, the Data Catalog is updated as soon as new data is written to S3, and the partition information is immediately available for querying by other services. The Boto3 AWS Glue create partition API call allows you to create a new partition in the Data Catalog by specifying the table name, the database name, and the partition values¹. You can use this API call in your code that writes data to S3, such as a Python script or an AWS Glue ETL job, to create a partition for each new S3 object key that matches the partitioning scheme.

Option A is not the best solution, as scheduling an AWS Glue crawler to run every morning would introduce a significant latency between the time new data is written to S3 and the time the Data Catalog is updated. AWS Glue crawlers are processes that connect to a data store, progress through a prioritized list of classifiers to determine the schema for your data, and then create metadata tables in the Data Catalog². Crawlers can be scheduled to run periodically, such as daily or hourly, but they cannot run continuously or in real-time. Therefore, using a crawler to synchronize the Data Catalog with the S3 storage would not meet the requirement of the least latency.

Option B is not the best solution, as manually running the AWS Glue CreatePartition API twice each day would also introduce a significant latency between the time new data is written to S3 and the time the Data Catalog is updated. Moreover, manually running the API would require more operational overhead and human intervention than using code that writes data to S3 to invoke the API automatically.

Option D is not the best solution, as running the MSCK REPAIR TABLE command from the AWS Glue console would also introduce a significant latency between the time new data is written to S3 and the time the Data Catalog is updated. The MSCK REPAIR TABLE command is a SQL command that you can run in the AWS Glue console to add partitions to the Data Catalog based on the S3 object keys that match the partitioning scheme³. However, this command is not meant to be run frequently or in real-time, as it can take a long time to scan the entire S3 bucket and add the partitions. Therefore, using this command to synchronize the Data Catalog with the S3 storage would not meet the requirement of the least latency. References:

? AWS Glue CreatePartition API

? Populating the AWS Glue Data Catalog

? MSCK REPAIR TABLE Command

? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide

NEW QUESTION 10

A data engineer must use AWS services to ingest a dataset into an Amazon S3 data lake. The data engineer profiles the dataset and discovers that the dataset contains personally identifiable information (PII). The data engineer must implement a solution to profile the dataset and obfuscate the PII.

Which solution will meet this requirement with the LEAST operational effort?

- A. Use an Amazon Kinesis Data Firehose delivery stream to process the dataset
- B. Create an AWS Lambda transform function to identify the PII
- C. Use an AWS SDK to obfuscate the PII
- D. Set the S3 data lake as the target for the delivery stream.
- E. Use the Detect PII transform in AWS Glue Studio to identify the PII
- F. Obfuscate the PII
- G. Use an AWS Step Functions state machine to orchestrate a data pipeline to ingest the data into the S3 data lake.
- H. Use the Detect PII transform in AWS Glue Studio to identify the PII
- I. Create a rule in AWS Glue Data Quality to obfuscate the PII
- J. Use an AWS Step Functions state machine to orchestrate a data pipeline to ingest the data into the S3 data lake.
- K. Ingest the dataset into Amazon DynamoDB
- L. Create an AWS Lambda function to identify and obfuscate the PII in the DynamoDB table and to transform the data
- M. Use the same Lambda function to ingest the data into the S3 data lake.

Answer: C

Explanation:

AWS Glue is a fully managed service that provides a serverless data integration platform for data preparation, data cataloging, and data loading. AWS Glue Studio is a graphical interface that allows you to easily author, run, and monitor AWS Glue ETL jobs. AWS Glue Data Quality is a feature that enables you to validate, cleanse, and enrich your data using predefined or custom rules. AWS Step Functions is a service that allows you to coordinate multiple AWS services into serverless workflows.

Using the Detect PII transform in AWS Glue Studio, you can automatically identify and label the PII in your dataset, such as names, addresses, phone numbers, email addresses, etc. You can then create a rule in AWS Glue Data Quality to obfuscate the PII, such as masking, hashing, or replacing the values with dummy data. You can also use other rules to validate and cleanse your data, such as checking for null values, duplicates, outliers, etc. You can then use an AWS Step Functions state machine to orchestrate a data pipeline to ingest the data into the S3 data lake. You can use AWS Glue DataBrew to visually explore and transform the data, AWS Glue crawlers to discover and catalog the data, and AWS Glue jobs to load the data into the S3 data lake.

This solution will meet the requirement with the least operational effort, as it leverages the serverless and managed capabilities of AWS Glue, AWS Glue Studio, AWS Glue Data Quality, and AWS Step Functions. You do not need to write any code to identify or obfuscate the PII, as you can use the built-in transforms and rules in AWS Glue Studio and AWS Glue Data Quality. You also do not need to provision or manage any servers or clusters, as AWS Glue and AWS Step Functions scale automatically based on the demand. The other options are not as efficient as using the Detect PII transform in AWS Glue Studio, creating a rule in AWS Glue Data Quality, and using an AWS Step Functions state machine. Using an Amazon Kinesis Data Firehose delivery stream to process the dataset, creating an AWS Lambda transform function to identify the PII, using an AWS SDK to obfuscate the PII, and setting the S3 data lake as the target for the delivery stream will require more operational effort, as you will need to write and maintain code to identify and obfuscate the PII, as well as manage the Lambda function

and its resources. Using the Detect PII transform in AWS Glue Studio to identify the PII, obfuscating the PII, and using an AWS Step Functions state machine to orchestrate a data pipeline to ingest the data into the S3 data lake will not be as effective as creating a rule in AWS Glue Data Quality to obfuscate the PII, as you will need to manually obfuscate the PII after identifying it, which can be error-prone and time-consuming. Ingesting the dataset into Amazon DynamoDB, creating an AWS Lambda function to identify and obfuscate the PII in the DynamoDB table and to transform the data, and using the same Lambda function to ingest the data into the S3 data lake will require more operational effort, as you will need to write and maintain code to identify and obfuscate the PII, as well as manage the Lambda function and its resources. You will also incur additional costs and complexity by using DynamoDB as an intermediate data store, which may not be necessary for your use case. References:

- ? AWS Glue
- ? AWS Glue Studio
- ? AWS Glue Data Quality
- ? [AWS Step Functions]
- ? [AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide], Chapter 6: Data Integration and Transformation, Section 6.1: AWS Glue

NEW QUESTION 10

A company uses Amazon RDS for MySQL as the database for a critical application. The database workload is mostly writes, with a small number of reads. A data engineer notices that the CPU utilization of the DB instance is very high. The high CPU utilization is slowing down the application. The data engineer must reduce the CPU utilization of the DB Instance.

Which actions should the data engineer take to meet this requirement? (Choose two.)

- A. Use the Performance Insights feature of Amazon RDS to identify queries that have high CPU utilization
- B. Optimize the problematic queries.
- C. Modify the database schema to include additional tables and indexes.
- D. Reboot the RDS DB instance once each week.
- E. Upgrade to a larger instance size.
- F. Implement caching to reduce the database query load.

Answer: AE

Explanation:

Amazon RDS is a fully managed service that provides relational databases in the cloud. Amazon RDS for MySQL is one of the supported database engines that you can use to run your applications. Amazon RDS provides various features and tools to monitor and optimize the performance of your DB instances, such as Performance Insights, Enhanced Monitoring, CloudWatch metrics and alarms, etc.

Using the Performance Insights feature of Amazon RDS to identify queries that have high CPU utilization and optimizing the problematic queries will help reduce the CPU utilization of the DB instance. Performance Insights is a feature that allows you to analyze the load on your DB instance and determine what is causing performance issues. Performance Insights collects, analyzes, and displays database performance data using an interactive dashboard. You can use Performance Insights to identify the top SQL statements, hosts, users, or processes that are consuming the most CPU resources. You can also drill down into the details of each query and see the execution plan, wait events, locks, etc. By using Performance Insights, you can pinpoint the root cause of the high CPU utilization and optimize the queries accordingly. For example, you can rewrite the queries to make them more efficient, add or remove indexes, use prepared statements, etc. Implementing caching to reduce the database query load will also help reduce the CPU utilization of the DB instance. Caching is a technique that allows you to store frequently accessed data in a fast and scalable storage layer, such as Amazon ElastiCache. By using caching, you can reduce the number of requests that hit your database, which in turn reduces the CPU load on your DB instance. Caching also improves the performance and availability of your application, as it reduces the latency and increases the throughput of your data access. You can use caching for various scenarios, such as storing session data, user preferences, application configuration, etc. You can also use caching for read-heavy workloads, such as displaying product details, recommendations, reviews, etc.

The other options are not as effective as using Performance Insights and caching. Modifying the database schema to include additional tables and indexes may or may not improve the CPU utilization, depending on the nature of the workload and the queries. Adding more tables and indexes may increase the complexity and overhead of the database, which may negatively affect the performance. Rebooting the RDS DB instance once each week will not reduce the CPU utilization, as it will not address the underlying cause of the high CPU load. Rebooting may also cause downtime and disruption to your application. Upgrading to a larger instance size may reduce the CPU utilization, but it will also increase the cost and complexity of your solution. Upgrading may also not be necessary if you can optimize the queries and reduce the database load by using caching. References:

- ? Amazon RDS
- ? Performance Insights
- ? Amazon ElastiCache
- ? [AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide], Chapter 3: Data Storage and Management, Section 3.1: Amazon RDS

NEW QUESTION 15

A data engineer must orchestrate a series of Amazon Athena queries that will run every day. Each query can run for more than 15 minutes.

Which combination of steps will meet these requirements MOST cost-effectively? (Choose two.)

- A. Use an AWS Lambda function and the Athena Boto3 client start_query_execution API call to invoke the Athena queries programmatically.
- B. Create an AWS Step Functions workflow and add two state
- C. Add the first state before the Lambda function
- D. Configure the second state as a Wait state to periodically check whether the Athena query has finished using the Athena Boto3 get_query_execution API call
- E. Configure the workflow to invoke the next query when the current query has finished running.
- F. Use an AWS Glue Python shell job and the Athena Boto3 client start_query_execution API call to invoke the Athena queries programmatically.
- G. Use an AWS Glue Python shell script to run a sleep timer that checks every 5 minutes to determine whether the current Athena query has finished running successfully
- H. Configure the Python shell script to invoke the next query when the current query has finished running.
- I. Use Amazon Managed Workflows for Apache Airflow (Amazon MWAA) to orchestrate the Athena queries in AWS Batch.

Answer: AB

Explanation:

Option A and B are the correct answers because they meet the requirements most cost-effectively. Using an AWS Lambda function and the Athena Boto3 client start_query_execution API call to invoke the Athena queries programmatically is a simple and scalable way to orchestrate the queries. Creating an AWS Step Functions workflow and adding two states to check the query status and invoke the next query is a reliable and efficient way to handle the long-running queries. Option C is incorrect because using an AWS Glue Python shell job to invoke the Athena queries programmatically is more expensive than using a Lambda function, as it requires provisioning and running a Glue job for each query.

Option D is incorrect because using an AWS Glue Python shell script to run a sleep timer that checks every 5 minutes to determine whether the current Athena query has finished running successfully is not a cost-effective or reliable way to orchestrate the queries, as it wastes resources and time.

Option E is incorrect because using Amazon Managed Workflows for Apache Airflow (Amazon MWAA) to orchestrate the Athena queries in AWS Batch is an overkill solution that introduces unnecessary complexity and cost, as it requires setting up and managing an Airflow environment and an AWS Batch compute

environment.

References:

- ? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide, Chapter 5: Data Orchestration, Section 5.2: AWS Lambda, Section 5.3: AWS Step Functions, Pages 125-135
- ? Building Batch Data Analytics Solutions on AWS, Module 5: Data Orchestration, Lesson 5.1: AWS Lambda, Lesson 5.2: AWS Step Functions, Pages 1-15
- ? AWS Documentation Overview, AWS Lambda Developer Guide, Working with AWS Lambda Functions, Configuring Function Triggers, Using AWS Lambda with Amazon Athena, Pages 1-4
- ? AWS Documentation Overview, AWS Step Functions Developer Guide, Getting Started, Tutorial: Create a Hello World Workflow, Pages 1-8

NEW QUESTION 20

A financial services company stores financial data in Amazon Redshift. A data engineer wants to run real-time queries on the financial data to support a web-based trading application. The data engineer wants to run the queries from within the trading application.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Establish WebSocket connections to Amazon Redshift.
- B. Use the Amazon Redshift Data API.
- C. Set up Java Database Connectivity (JDBC) connections to Amazon Redshift.
- D. Store frequently accessed data in Amazon S3. Use Amazon S3 Select to run the queries.

Answer: B

Explanation:

The Amazon Redshift Data API is a built-in feature that allows you to run SQL queries on Amazon Redshift data with web services-based applications, such as AWS Lambda, Amazon SageMaker notebooks, and AWS Cloud9. The Data API does not require a persistent connection to your database, and it provides a secure HTTP endpoint and integration with AWS SDKs. You can use the endpoint to run SQL statements without managing connections. The Data API also supports both Amazon Redshift provisioned clusters and Redshift Serverless workgroups. The Data API is the best solution for running real-time queries on the financial data from within the trading application, as it has the least operational overhead compared to the other options.

Option A is not the best solution, as establishing WebSocket connections to Amazon Redshift would require more configuration and maintenance than using the Data API. WebSocket connections are also not supported by Amazon Redshift clusters or serverless workgroups.

Option C is not the best solution, as setting up JDBC connections to Amazon Redshift would also require more configuration and maintenance than using the Data API. JDBC connections are also not supported by Redshift Serverless workgroups.

Option D is not the best solution, as storing frequently accessed data in Amazon S3 and using Amazon S3 Select to run the queries would introduce additional latency and complexity than using the Data API. Amazon S3 Select is also not optimized for real-time queries, as it scans the entire object before returning the results. References:

- ? Using the Amazon Redshift Data API
- ? Calling the Data API
- ? Amazon Redshift Data API Reference
- ? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide

NEW QUESTION 25

A data engineer needs to build an extract, transform, and load (ETL) job. The ETL job will process daily incoming .csv files that users upload to an Amazon S3 bucket. The size of each S3 object is less than 100 MB.

Which solution will meet these requirements MOST cost-effectively?

- A. Write a custom Python applicatio
- B. Host the application on an Amazon Elastic Kubernetes Service (Amazon EKS) cluster.
- C. Write a PySpark ETL scrip
- D. Host the script on an Amazon EMR cluster.
- E. Write an AWS Glue PySpark jo
- F. Use Apache Spark to transform the data.
- G. Write an AWS Glue Python shell jo
- H. Use pandas to transform the data.

Answer: D

Explanation:

AWS Glue is a fully managed serverless ETL service that can handle various data sources and formats, including .csv files in Amazon S3. AWS Glue provides two types of jobs: PySpark and Python shell. PySpark jobs use Apache Spark to process large-scale data in parallel, while Python shell jobs use Python scripts to process small-scale data in a single execution environment. For this requirement, a Python shell job is more suitable and cost-effective, as the size of each S3 object is less than 100 MB, which does not require distributed processing. A Python shell job can use pandas, a popular Python library for data analysis, to transform the .csv data as needed. The other solutions are not optimal or relevant for this requirement. Writing a custom Python application and hosting it on an Amazon EKS cluster would require more effort and resources to set up and manage the Kubernetes environment, as well as to handle the data ingestion and transformation logic. Writing a PySpark ETL script and hosting it on an Amazon EMR cluster would also incur more costs and complexity to provision and configure the EMR cluster, as well as to use Apache Spark for processing small data files. Writing an AWS Glue PySpark job would also be less efficient and economical than a Python shell job, as it would involve unnecessary overhead and charges for using Apache Spark for small data files. References:

- ? AWS Glue
- ? Working with Python Shell Jobs
- ? pandas
- ? [AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide]

NEW QUESTION 29

A company is migrating on-premises workloads to AWS. The company wants to reduce overall operational overhead. The company also wants to explore serverless options.

The company's current workloads use Apache Pig, Apache Oozie, Apache Spark, Apache Hbase, and Apache Flink. The on-premises workloads process petabytes of data in seconds. The company must maintain similar or better performance after the migration to AWS.

Which extract, transform, and load (ETL) service will meet these requirements?

- A. AWS Glue
- B. Amazon EMR
- C. AWS Lambda

D. Amazon Redshift

Answer: A

Explanation:

AWS Glue is a fully managed serverless ETL service that can handle petabytes of data in seconds. AWS Glue can run Apache Spark and Apache Flink jobs without requiring any infrastructure provisioning or management. AWS Glue can also integrate with Apache Pig, Apache Oozie, and Apache Hbase using AWS Glue Data Catalog and AWS Glue workflows. AWS Glue can reduce the overall operational overhead by automating the data discovery, data preparation, and data loading processes. AWS Glue can also optimize the cost and performance of ETL jobs by using AWS Glue Job Bookmarking, AWS Glue Crawlers, and AWS Glue Schema Registry. References:

- ? AWS Glue
- ? AWS Glue Data Catalog
- ? AWS Glue Workflows
- ? [AWS Glue Job Bookmarking]
- ? [AWS Glue Crawlers]
- ? [AWS Glue Schema Registry]
- ? [AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide]

NEW QUESTION 32

A data engineer must build an extract, transform, and load (ETL) pipeline to process and load data from 10 source systems into 10 tables that are in an Amazon Redshift database. All the source systems generate .csv, JSON, or Apache Parquet files every 15 minutes. The source systems all deliver files into one Amazon S3 bucket. The file sizes range from 10 MB to 20 GB. The ETL pipeline must function correctly despite changes to the data schema.

Which data pipeline solutions will meet these requirements? (Choose two.)

- A. Use an Amazon EventBridge rule to run an AWS Glue job every 15 minute
- B. Configure the AWS Glue job to process and load the data into the Amazon Redshift tables.
- C. Use an Amazon EventBridge rule to invoke an AWS Glue workflow job every 15 minute
- D. Configure the AWS Glue workflow to have an on-demand trigger that runs an AWS Glue crawler and then runs an AWS Glue job when the crawler finishes running successful
- E. Configure the AWS Glue job to process and load the data into the Amazon Redshift tables.
- F. Configure an AWS Lambda function to invoke an AWS Glue crawler when a file is loaded into the S3 bucket
- G. Configure an AWS Glue job to process and load the data into the Amazon Redshift table
- H. Create a second Lambda function to run the AWS Glue job
- I. Create an Amazon EventBridge rule to invoke the second Lambda function when the AWS Glue crawler finishes running successfully.
- J. Configure an AWS Lambda function to invoke an AWS Glue workflow when a file is loaded into the S3 bucket
- K. Configure the AWS Glue workflow to have an on-demand trigger that runs an AWS Glue crawler and then runs an AWS Glue job when the crawler finishes running successful
- L. Configure the AWS Glue job to process and load the data into the Amazon Redshift tables.
- M. Configure an AWS Lambda function to invoke an AWS Glue job when a file is loaded into the S3 bucket
- N. Configure the AWS Glue job to read the files from the S3 bucket into an Apache Spark DataFrame
- O. Configure the AWS Glue job to also put smaller partitions of the DataFrame into an Amazon Kinesis Data Firehose delivery stream
- P. Configure the delivery stream to load data into the Amazon Redshift tables.

Answer: AB

Explanation:

Using an Amazon EventBridge rule to run an AWS Glue job or invoke an AWS Glue workflow job every 15 minutes are two possible solutions that will meet the requirements. AWS Glue is a serverless ETL service that can process and load data from various sources to various targets, including Amazon Redshift. AWS Glue can handle different data formats, such as CSV, JSON, and Parquet, and also support schema evolution, meaning it can adapt to changes in the data schema over time. AWS Glue can also leverage Apache Spark to perform distributed processing and transformation of large datasets. AWS Glue integrates with Amazon EventBridge, which is a serverless event bus service that can trigger actions based on rules and schedules. By using an Amazon EventBridge rule, you can invoke an AWS Glue job or workflow every 15 minutes, and configure the job or workflow to run an AWS Glue crawler and then load the data into the Amazon Redshift tables. This way, you can build a cost-effective and scalable ETL pipeline that can handle data from 10 source systems and function correctly despite changes to the data schema.

The other options are not solutions that will meet the requirements. Option C, configuring an AWS Lambda function to invoke an AWS Glue crawler when a file is loaded into the S3 bucket, and creating a second Lambda function to run the AWS Glue job, is not a feasible solution, as it would require a lot of Lambda invocations and coordination. AWS Lambda has some limits on the execution time, memory, and concurrency, which can affect the performance and reliability of the ETL pipeline. Option D, configuring an AWS Lambda function to invoke an AWS Glue workflow when a file is loaded into the S3 bucket, is not a necessary solution, as you can use an Amazon EventBridge rule to invoke the AWS Glue workflow directly, without the need for a Lambda function. Option E, configuring an AWS Lambda function to invoke an AWS Glue job when a file is loaded into the S3 bucket, and configuring the AWS Glue job to put smaller partitions of the DataFrame into an Amazon Kinesis Data Firehose delivery stream, is not a cost-effective solution, as it would incur additional costs for Lambda invocations and data delivery. Moreover, using Amazon Kinesis Data Firehose to load data into Amazon Redshift is not suitable for frequent and small batches of data, as it can cause performance issues and data fragmentation. References:

- ? AWS Glue
- ? Amazon EventBridge
- ? Using AWS Glue to run ETL jobs against non-native JDBC data sources
- ? [AWS Lambda quotas]
- ? [Amazon Kinesis Data Firehose quotas]

NEW QUESTION 34

An airline company is collecting metrics about flight activities for analytics. The company is conducting a proof of concept (POC) test to show how analytics can provide insights that the company can use to increase on-time departures.

The POC test uses objects in Amazon S3 that contain the metrics in .csv format. The POC test uses Amazon Athena to query the data. The data is partitioned in the S3 bucket by date.

As the amount of data increases, the company wants to optimize the storage solution to improve query performance.

Which combination of solutions will meet these requirements? (Choose two.)

- A. Add a randomized string to the beginning of the keys in Amazon S3 to get more throughput across partitions.
- B. Use an S3 bucket that is in the same account that uses Athena to query the data.
- C. Use an S3 bucket that is in the same AWS Region where the company runs Athena queries.
- D. Preprocess the .csv data to JSON format by fetching only the document keys that the query requires.

E. Preprocess the .csv data to Apache Parquet format by fetching only the data blocks that are needed for predicates.

Answer: CE

Explanation:

Using an S3 bucket that is in the same AWS Region where the company runs Athena queries can improve query performance by reducing data transfer latency and costs. Preprocessing the .csv data to Apache Parquet format can also improve query performance by enabling columnar storage, compression, and partitioning, which can reduce the amount of data scanned and fetched by the query. These solutions can optimize the storage solution for the POC test without requiring much effort or changes to the existing data pipeline. The other solutions are not optimal or relevant for this requirement. Adding a randomized string to the beginning of the keys in Amazon S3 can improve the throughput across partitions, but it can also make the data harder to query and manage. Using an S3 bucket that is in the same account that uses Athena to query the data does not have any significant impact on query performance, as long as the proper permissions are granted. Preprocessing the .csv data to JSON format does not offer any benefits over the .csv format, as both are row-based and verbose formats that require more data scanning and fetching than columnar formats like Parquet. References:

- ? Best Practices When Using Athena with AWS Glue
- ? Optimizing Amazon S3 Performance
- ? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide

NEW QUESTION 39

A manufacturing company collects sensor data from its factory floor to monitor and enhance operational efficiency. The company uses Amazon Kinesis Data Streams to publish the data that the sensors collect to a data stream. Then Amazon Kinesis Data Firehose writes the data to an Amazon S3 bucket.

The company needs to display a real-time view of operational efficiency on a large screen in the manufacturing facility.

Which solution will meet these requirements with the LOWEST latency?

- A. Use Amazon Managed Service for Apache Flink (previously known as Amazon Kinesis Data Analytics) to process the sensor data
- B. Use a connector for Apache Flink to write data to an Amazon Timestream database
- C. Use the Timestream database as a source to create a Grafana dashboard.
- D. Configure the S3 bucket to send a notification to an AWS Lambda function when any new object is created
- E. Use the Lambda function to publish the data to Amazon Aurora
- F. Use Aurora as a source to create an Amazon QuickSight dashboard.
- G. Use Amazon Managed Service for Apache Flink (previously known as Amazon Kinesis Data Analytics) to process the sensor data
- H. Create a new Data Firehose delivery stream to publish data directly to an Amazon Timestream database
- I. Use the Timestream database as a source to create an Amazon QuickSight dashboard.
- J. Use AWS Glue bookmarks to read sensor data from the S3 bucket in real time
- K. Publish the data to an Amazon Timestream database
- L. Use the Timestream database as a source to create a Grafana dashboard.

Answer: C

Explanation:

This solution will meet the requirements with the lowest latency because it uses Amazon Managed Service for Apache Flink to process the sensor data in real time and write it to Amazon Timestream, a fast, scalable, and serverless time series database. Amazon Timestream is optimized for storing and analyzing time series data, such as sensor data, and can handle trillions of events per day with millisecond latency. By using Amazon Timestream as a source, you can create an Amazon QuickSight dashboard that displays a real-time view of operational efficiency on a large screen in the manufacturing facility. Amazon QuickSight is a fully managed business intelligence service that can connect to various data sources, including Amazon Timestream, and provide interactive visualizations and insights.

The other options are not optimal for the following reasons:

? A. Use Amazon Managed Service for Apache Flink (previously known as Amazon Kinesis Data Analytics) to process the sensor data. Use a connector for Apache Flink to write data to an Amazon Timestream database. Use the Timestream database as a source to create a Grafana dashboard. This option is similar to option C, but it uses Grafana instead of Amazon QuickSight to create the dashboard. Grafana is an open source visualization tool that can also connect to Amazon Timestream, but it requires additional steps to set up and configure, such as deploying a Grafana server on Amazon EC2, installing the Amazon Timestream plugin, and creating an IAM role for Grafana to access Timestream. These steps can increase the latency and complexity of the solution.

? B. Configure the S3 bucket to send a notification to an AWS Lambda function when any new object is created. Use the Lambda function to publish the data to Amazon Aurora. Use Aurora as a source to create an Amazon QuickSight dashboard. This option is not suitable for displaying a real-time view of operational efficiency, as it introduces unnecessary delays and costs in the data pipeline. First, the sensor data is written to an S3 bucket by Amazon Kinesis Data Firehose, which can have a buffering interval of up to 900 seconds. Then, the S3 bucket sends a notification to a Lambda function, which can incur additional invocation and execution time. Finally, the Lambda function publishes the data to Amazon Aurora, a relational database that is not optimized for time series data and can have higher storage and performance costs than Amazon Timestream.

? D. Use AWS Glue bookmarks to read sensor data from the S3 bucket in real time.

Publish the data to an Amazon Timestream database. Use the Timestream database as a source to create a Grafana dashboard. This option is also not suitable for displaying a real-time view of operational efficiency, as it uses AWS Glue bookmarks to read sensor data from the S3 bucket. AWS Glue bookmarks are a feature that helps AWS Glue jobs and crawlers keep track of the data that has already been processed, so that they can resume from where they left off. However, AWS Glue jobs and crawlers are not designed for real-time data processing, as they can have a minimum frequency of 5 minutes and a variable start-up time. Moreover, this option also uses Grafana instead of Amazon QuickSight to create the dashboard, which can increase the latency and complexity of the solution.

References:

- ? 1: Amazon Managed Streaming for Apache Flink
- ? 2: Amazon Timestream
- ? 3: Amazon QuickSight
- ? : Analyze data in Amazon Timestream using Grafana
- ? : Amazon Kinesis Data Firehose
- ? : Amazon Aurora
- ? : AWS Glue Bookmarks
- ? : AWS Glue Job and Crawler Scheduling

NEW QUESTION 44

A company stores daily records of the financial performance of investment portfolios in .csv format in an Amazon S3 bucket. A data engineer uses AWS Glue crawlers to crawl the S3 data.

The data engineer must make the S3 data accessible daily in the AWS Glue Data Catalog. Which solution will meet these requirements?

- A. Create an IAM role that includes the AmazonS3FullAccess policy
- B. Associate the role with the crawler
- C. Specify the S3 bucket path of the source data as the crawler's data store

- D. Create a daily schedule to run the crawl
- E. Configure the output destination to a new path in the existing S3 bucket.
- F. Create an IAM role that includes the AWSGlueServiceRole policy
- G. Associate the role with the crawler
- H. Specify the S3 bucket path of the source data as the crawler's data store
- I. Create a daily schedule to run the crawl
- J. Specify a database name for the output.
- K. Create an IAM role that includes the AmazonS3FullAccess policy
- L. Associate the role with the crawler
- M. Specify the S3 bucket path of the source data as the crawler's data store
- N. Allocate data processing units (DPUs) to run the crawler every day
- O. Specify a database name for the output.
- P. Create an IAM role that includes the AWSGlueServiceRole policy
- Q. Associate the role with the crawler
- R. Specify the S3 bucket path of the source data as the crawler's data store
- S. Allocate data processing units (DPUs) to run the crawler every day
- T. Configure the output destination to a new path in the existing S3 bucket.

Answer: B

Explanation:

To make the S3 data accessible daily in the AWS Glue Data Catalog, the data engineer needs to create a crawler that can crawl the S3 data and write the metadata to the Data Catalog. The crawler also needs to run on a daily schedule to keep the Data Catalog updated with the latest data. Therefore, the solution must include the following steps:

- ? Create an IAM role that has the necessary permissions to access the S3 data and the Data Catalog. The AWSGlueServiceRole policy is a managed policy that grants these permissions¹.
- ? Associate the role with the crawler.
- ? Specify the S3 bucket path of the source data as the crawler's data store. The crawler will scan the data and infer the schema and format².
- ? Create a daily schedule to run the crawler. The crawler will run at the specified time every day and update the Data Catalog with any changes in the data³.
- ? Specify a database name for the output. The crawler will create or update a table in the Data Catalog under the specified database. The table will contain the metadata about the data in the S3 bucket, such as the location, schema, and classification.

Option B is the only solution that includes all these steps. Therefore, option B is the correct answer.

Option A is incorrect because it configures the output destination to a new path in the existing S3 bucket. This is unnecessary and may cause confusion, as the crawler does not write any data to the S3 bucket, only metadata to the Data Catalog.

Option C is incorrect because it allocates data processing units (DPUs) to run the crawler every day. This is also unnecessary, as DPUs are only used for AWS Glue ETL jobs, not crawlers.

Option D is incorrect because it combines the errors of option A and C. It configures the output destination to a new path in the existing S3 bucket and allocates DPUs to run the crawler every day, both of which are irrelevant for the crawler.

References:

- ? 1: AWS managed (predefined) policies for AWS Glue - AWS Glue
- ? 2: Data Catalog and crawlers in AWS Glue - AWS Glue
- ? 3: Scheduling an AWS Glue crawler - AWS Glue
- ? [4]: Parameters set on Data Catalog tables by crawler - AWS Glue
- ? [5]: AWS Glue pricing - Amazon Web Services (AWS)

NEW QUESTION 46

A data engineer uses Amazon Redshift to run resource-intensive analytics processes once every month. Every month, the data engineer creates a new Redshift provisioned cluster. The data engineer deletes the Redshift provisioned cluster after the analytics processes are complete every month. Before the data engineer deletes the cluster each month, the data engineer unloads backup data from the cluster to an Amazon S3 bucket.

The data engineer needs a solution to run the monthly analytics processes that does not require the data engineer to manage the infrastructure manually.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Step Functions to pause the Redshift cluster when the analytics processes are complete and to resume the cluster to run new processes every month.
- B. Use Amazon Redshift Serverless to automatically process the analytics workload.
- C. Use the AWS CLI to automatically process the analytics workload.
- D. Use AWS CloudFormation templates to automatically process the analytics workload.

Answer: B

Explanation:

Amazon Redshift Serverless is a new feature of Amazon Redshift that enables you to run SQL queries on data in Amazon S3 without provisioning or managing any clusters. You can use Amazon Redshift Serverless to automatically process the analytics workload, as it scales up and down the compute resources based on the query demand, and charges you only for the resources consumed. This solution will meet the requirements with the least operational overhead, as it does not require the data engineer to create, delete, pause, or resume any Redshift clusters, or to manage any infrastructure manually. You can use the Amazon Redshift Data API to run queries from the AWS CLI, AWS SDK, or AWS Lambda functions¹².

The other options are not optimal for the following reasons:

? A. Use Amazon Step Functions to pause the Redshift cluster when the analytics processes are complete and to resume the cluster to run new processes every month. This option is not recommended, as it would still require the data engineer to create and delete a new Redshift provisioned cluster every month, which can incur additional costs and time. Moreover, this option would require the data engineer to use Amazon Step Functions to orchestrate the workflow of pausing and resuming the cluster, which can add complexity and overhead.

? C. Use the AWS CLI to automatically process the analytics workload. This option is vague and does not specify how the AWS CLI is used to process the analytics workload. The AWS CLI can be used to run queries on data in Amazon S3 using Amazon Redshift Serverless, Amazon Athena, or Amazon EMR, but each of these services has different features and benefits. Moreover, this option does not address the requirement of not managing the infrastructure manually, as the data engineer may still need to provision and configure some resources, such as Amazon EMR clusters or Amazon Athena workgroups.

? D. Use AWS CloudFormation templates to automatically process the analytics workload. This option is also vague and does not specify how AWS CloudFormation templates are used to process the analytics workload. AWS CloudFormation is a service that lets you model and provision AWS resources using templates. You can use AWS CloudFormation templates to create and delete a Redshift provisioned cluster every month, or to create and configure other AWS resources, such as Amazon EMR, Amazon Athena, or Amazon Redshift Serverless. However, this option does not address the requirement of not managing the infrastructure manually, as the data engineer may still need to write and maintain the AWS CloudFormation templates, and to monitor the status and performance of the resources.

References:

- ? 1: Amazon Redshift Serverless
- ? 2: Amazon Redshift Data API
- ? : Amazon Step Functions
- ? : AWS CLI
- ? : AWS CloudFormation

NEW QUESTION 47

A healthcare company uses Amazon Kinesis Data Streams to stream real-time health data from wearable devices, hospital equipment, and patient records. A data engineer needs to find a solution to process the streaming data. The data engineer needs to store the data in an Amazon Redshift Serverless warehouse. The solution must support near real-time analytics of the streaming data and the previous day's data. Which solution will meet these requirements with the LEAST operational overhead?

- A. Load data into Amazon Kinesis Data Firehose
- B. Load the data into Amazon Redshift.
- C. Use the streaming ingestion feature of Amazon Redshift.
- D. Load the data into Amazon S3. Use the COPY command to load the data into Amazon Redshift.
- E. Use the Amazon Aurora zero-ETL integration with Amazon Redshift.

Answer: B

Explanation:

The streaming ingestion feature of Amazon Redshift enables you to ingest data from streaming sources, such as Amazon Kinesis Data Streams, into Amazon Redshift tables in near real-time. You can use the streaming ingestion feature to process the streaming data from the wearable devices, hospital equipment, and patient records. The streaming ingestion feature also supports incremental updates, which means you can append new data or update existing data in the Amazon Redshift tables. This way, you can store the data in an Amazon Redshift Serverless warehouse and support near real-time analytics of the streaming data and the previous day's data. This solution meets the requirements with the least operational overhead, as it does not require any additional services or components to ingest and process the streaming data. The other options are either not feasible or not optimal. Loading data into Amazon Kinesis Data Firehose and then into Amazon Redshift (option A) would introduce additional latency and cost, as well as require additional configuration and management. Loading data into Amazon S3 and then using the COPY command to load the data into Amazon Redshift (option C) would also introduce additional latency and cost, as well as require additional storage space and ETL logic. Using the Amazon Aurora zero-ETL integration with Amazon Redshift (option D) would not work, as it requires the data to be stored in Amazon Aurora first, which is not the case for the streaming data from the healthcare company. References:

? Using streaming ingestion with Amazon Redshift

? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide, Chapter 3: Data Ingestion and Transformation, Section 3.5: Amazon Redshift Streaming Ingestion

NEW QUESTION 48

A company uses Amazon RDS to store transactional data. The company runs an RDS DB instance in a private subnet. A developer wrote an AWS Lambda function with default settings to insert, update, or delete data in the DB instance.

The developer needs to give the Lambda function the ability to connect to the DB instance privately without using the public internet.

Which combination of steps will meet this requirement with the LEAST operational overhead? (Choose two.)

- A. Turn on the public access setting for the DB instance.
- B. Update the security group of the DB instance to allow only Lambda function invocations on the database port.
- C. Configure the Lambda function to run in the same subnet that the DB instance uses.
- D. Attach the same security group to the Lambda function and the DB instance.
- E. Include a self-referencing rule that allows access through the database port.
- F. Update the network ACL of the private subnet to include a self-referencing rule that allows access through the database port.

Answer: CD

Explanation:

To enable the Lambda function to connect to the RDS DB instance privately without using the public internet, the best combination of steps is to configure the Lambda function to run in the same subnet that the DB instance uses, and attach the same security group to the Lambda function and the DB instance. This way, the Lambda function and the DB instance can communicate within the same private network, and the security group can allow traffic between them on the database port. This solution has the least operational overhead, as it does not require any changes to the public access setting, the network ACL, or the security group of the DB instance.

The other options are not optimal for the following reasons:

? A. Turn on the public access setting for the DB instance. This option is not recommended, as it would expose the DB instance to the public internet, which can compromise the security and privacy of the data. Moreover, this option would not enable the Lambda function to connect to the DB instance privately, as it would still require the Lambda function to use the public internet to access the DB instance.

? B. Update the security group of the DB instance to allow only Lambda function invocations on the database port. This option is not sufficient, as it would only modify the inbound rules of the security group of the DB instance, but not the outbound rules of the security group of the Lambda function. Moreover, this option would not enable the Lambda function to connect to the DB instance privately, as it would still require the Lambda function to use the public internet to access the DB instance.

? E. Update the network ACL of the private subnet to include a self-referencing rule

that allows access through the database port. This option is not necessary, as the network ACL of the private subnet already allows all traffic within the subnet by default. Moreover, this option would not enable the Lambda function to connect to the DB instance privately, as it would still require the Lambda function to use the public internet to access the DB instance.

References:

? 1: Connecting to an Amazon RDS DB instance

? 2: Configuring a Lambda function to access resources in a VPC

? 3: Working with security groups

? : Network ACLs

NEW QUESTION 50

A company stores details about transactions in an Amazon S3 bucket. The company wants to log all writes to the S3 bucket into another S3 bucket that is in the same AWS Region.

Which solution will meet this requirement with the LEAST operational effort?

- A. Configure an S3 Event Notifications rule for all activities on the transactions S3 bucket to invoke an AWS Lambda function

- B. Program the Lambda function to write the event to Amazon Kinesis Data Firehose
- C. Configure Kinesis Data Firehose to write the event to the logs S3 bucket.
- D. Create a trail of management events in AWS CloudTrail
- E. Configure the trail to receive data from the transactions S3 bucket
- F. Specify an empty prefix and write-only event
- G. Specify the logs S3 bucket as the destination bucket.
- H. Configure an S3 Event Notifications rule for all activities on the transactions S3 bucket to invoke an AWS Lambda function
- I. Program the Lambda function to write the events to the logs S3 bucket.
- J. Create a trail of data events in AWS CloudTrail
- K. Configure the trail to receive data from the transactions S3 bucket
- L. Specify an empty prefix and write-only event
- M. Specify the logs S3 bucket as the destination bucket.

Answer: D

Explanation:

This solution meets the requirement of logging all writes to the S3 bucket into another S3 bucket with the least operational effort. AWS CloudTrail is a service that records the API calls made to AWS services, including Amazon S3. By creating a trail of data events, you can capture the details of the requests that are made to the transactions S3 bucket, such as the requester, the time, the IP address, and the response elements. By specifying an empty prefix and write-only events, you can filter the data events to only include the ones that write to the bucket. By specifying the logs S3 bucket as the destination bucket, you can store the CloudTrail logs in another S3 bucket that is in the same AWS Region. This solution does not require any additional coding or configuration, and it is more scalable and reliable than using S3 Event Notifications and Lambda functions. References:

- ? Logging Amazon S3 API calls using AWS CloudTrail
- ? Creating a trail for data events
- ? Enabling Amazon S3 server access logging

NEW QUESTION 52

A data engineer is configuring an AWS Glue job to read data from an Amazon S3 bucket. The data engineer has set up the necessary AWS Glue connection details and an associated IAM role. However, when the data engineer attempts to run the AWS Glue job, the data engineer receives an error message that indicates that there are problems with the Amazon S3 VPC gateway endpoint.

The data engineer must resolve the error and connect the AWS Glue job to the S3 bucket. Which solution will meet this requirement?

- A. Update the AWS Glue security group to allow inbound traffic from the Amazon S3 VPC gateway endpoint.
- B. Configure an S3 bucket policy to explicitly grant the AWS Glue job permissions to access the S3 bucket.
- C. Review the AWS Glue job code to ensure that the AWS Glue connection details include a fully qualified domain name.
- D. Verify that the VPC's route table includes inbound and outbound routes for the Amazon S3 VPC gateway endpoint.

Answer: D

Explanation:

The error message indicates that the AWS Glue job cannot access the Amazon S3 bucket through the VPC endpoint. This could be because the VPC's route table does not have the necessary routes to direct the traffic to the endpoint. To fix this, the data engineer must verify that the route table has an entry for the Amazon S3 service prefix (com.amazonaws.region.s3) with the target as the VPC endpoint ID. This will allow the AWS Glue job to use the VPC endpoint to access the S3 bucket without going through the internet or a NAT gateway. For more information, see Gateway endpoints. References:

- ? Troubleshoot the AWS Glue error "VPC S3 endpoint validation failed"
- ? Amazon VPC endpoints for Amazon S3
- ? [AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide]

NEW QUESTION 55

A company is planning to use a provisioned Amazon EMR cluster that runs Apache Spark jobs to perform big data analysis. The company requires high reliability. A big data team must follow best practices for running cost-optimized and long-running workloads on Amazon EMR. The team must find a solution that will maintain the company's current level of performance.

Which combination of resources will meet these requirements MOST cost-effectively? (Choose two.)

- A. Use Hadoop Distributed File System (HDFS) as a persistent data store.
- B. Use Amazon S3 as a persistent data store.
- C. Use x86-based instances for core nodes and task nodes.
- D. Use Graviton instances for core nodes and task nodes.
- E. Use Spot Instances for all primary nodes.

Answer: BD

Explanation:

The best combination of resources to meet the requirements of high reliability, cost-optimization, and performance for running Apache Spark jobs on Amazon EMR is to use Amazon S3 as a persistent data store and Graviton instances for core nodes and task nodes.

Amazon S3 is a highly durable, scalable, and secure object storage service that can store any amount of data for a variety of use cases, including big data analytics¹. Amazon S3 is a better choice than HDFS as a persistent data store for Amazon EMR, as it decouples the storage from the compute layer, allowing for more flexibility and cost-efficiency. Amazon S3 also supports data encryption, versioning, lifecycle management, and cross-region replication¹. Amazon EMR integrates seamlessly with Amazon S3, using EMR File System (EMRFS) to access data stored in Amazon S3 buckets². EMRFS also supports consistent view, which enables Amazon EMR to provide read-after-write consistency for Amazon S3 objects that are accessed through EMRFS².

Graviton instances are powered by Arm-based AWS Graviton² processors that deliver up to 40% better price performance over comparable current generation x86-based instances³. Graviton instances are ideal for running workloads that are CPU-bound, memory-bound, or network-bound, such as big data analytics, web servers, and open-source databases³. Graviton instances are compatible with Amazon EMR, and can be used for both core nodes and task nodes. Core nodes are responsible for running the data processing frameworks, such as Apache Spark, and storing data in HDFS or the local file system. Task nodes are optional nodes that can be added to a cluster to increase the processing power and throughput. By using Graviton instances for both core nodes and task nodes, you can achieve higher performance and lower cost than using x86-based instances.

Using Spot Instances for all primary nodes is not a good option, as it can compromise the reliability and availability of the cluster. Spot Instances are spare EC2 instances that are available at up to 90% discount compared to On-Demand prices, but they can be interrupted by EC2 with a two-minute notice when EC2 needs the capacity back. Primary nodes are the nodes that run the cluster software, such as Hadoop, Spark, Hive, and Hue, and are essential for the cluster operation. If a primary node is interrupted by EC2, the cluster will fail or become unstable. Therefore, it is recommended to use On-Demand Instances or Reserved Instances for primary nodes, and use Spot Instances only for task nodes that can tolerate interruptions. References:

- ? Amazon S3 - Cloud Object Storage
- ? EMR File System (EMRFS)
- ? AWS Graviton2 Processor-Powered Amazon EC2 Instances
- ? [Plan and Configure EC2 Instances]
- ? [Amazon EC2 Spot Instances]
- ? [Best Practices for Amazon EMR]

NEW QUESTION 56

A company stores data in a data lake that is in Amazon S3. Some data that the company stores in the data lake contains personally identifiable information (PII). Multiple user groups need to access the raw data. The company must ensure that user groups can access only the PII that they require. Which solution will meet these requirements with the LEAST effort?

- A. Use Amazon Athena to query the dat
- B. Set up AWS Lake Formation and create data filters to establish levels of access for the company's IAM role
- C. Assign each user to the IAM role that matches the user's PII access requirements.
- D. Use Amazon QuickSight to access the dat
- E. Use column-level security features in QuickSight to limit the PII that users can retrieve from Amazon S3 by using Amazon Athen
- F. Define QuickSight access levels based on the PII access requirements of the users.
- G. Build a custom query builder UI that will run Athena queries in the background to access the dat
- H. Create user groups in Amazon Cognit
- I. Assign access levels to the user groups based on the PII access requirements of the users.
- J. Create IAM roles that have different levels of granular acces
- K. Assign the IAM roles to IAM user group
- L. Use an identity-based policy to assign access levels to user groups at the column level.

Answer: A

Explanation:

Amazon Athena is a serverless, interactive query service that enables you to analyze data in Amazon S3 using standard SQL. AWS Lake Formation is a service that helps you build, secure, and manage data lakes on AWS. You can use AWS Lake Formation to create data filters that define the level of access for different IAM roles based on the columns, rows, or tags of the data. By using Amazon Athena to query the data and AWS Lake Formation to create data filters, the company can meet the requirements of ensuring that user groups can access only the PII that they require with the least effort. The solution is to use Amazon Athena to query the data in the data lake that is in Amazon S3. Then, set up AWS Lake Formation and create data filters to establish levels of access for the company's IAM roles. For example, a data filter can allow a user group to access only the columns that contain the PII that they need, such as name and email address, and deny access to the columns that contain the PII that they do not need, such as phone number and social security number. Finally, assign each user to the IAM role that matches the user's PII access requirements. This way, the user groups can access the data in the data lake securely and efficiently. The other options are either not feasible or not optimal. Using Amazon QuickSight to access the data (option B) would require the company to pay for the QuickSight service and to configure the column-level security features for each user. Building a custom query builder UI that will run Athena queries in the background to access the data (option C) would require the company to develop and maintain the UI and to integrate it with Amazon Cognito. Creating IAM roles that have different levels of granular access (option D) would require the company to manage multiple IAM roles and policies and to ensure that they are aligned with the data schema.

References:

- ? Amazon Athena
- ? AWS Lake Formation
- ? AWS Certified Data Engineer - Associate DEA-C01 Complete Study Guide, Chapter 4: Data Analysis and Visualization, Section 4.3: Amazon Athena

NEW QUESTION 61

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-Certified-Data-Engineer-Associate Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-Certified-Data-Engineer-Associate Product From:

<https://www.2passeasy.com/dumps/AWS-Certified-Data-Engineer-Associate/>

Money Back Guarantee

AWS-Certified-Data-Engineer-Associate Practice Exam Features:

- * AWS-Certified-Data-Engineer-Associate Questions and Answers Updated Frequently
- * AWS-Certified-Data-Engineer-Associate Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Data-Engineer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Data-Engineer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year