

Exam Questions 300-710

Securing Networks with Cisco Firepower (SNCF)

<https://www.2passeasy.com/dumps/300-710/>



NEW QUESTION 1

Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: AE

NEW QUESTION 2

What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

NEW QUESTION 3

Which protocol establishes network redundancy in a switched Firepower device deployment?

- A. STP
- B. HSRP
- C. GLBP
- D. VRRP

Answer: A

NEW QUESTION 4

Which two actions can be used in an access control policy rule? (Choose two.)

- A. Block with Reset
- B. Monitor
- C. Analyze
- D. Discover
- E. Block ALL

Answer: AB

NEW QUESTION 5

Which object type supports object overrides?

- A. time range
- B. security group tag
- C. network object
- D. DNS server group

Answer: C

NEW QUESTION 6

What is the benefit of selecting the trace option for packet capture?

- A. The option indicates whether the packet was dropped or successful.
- B. The option indicated whether the destination host responds through a different path.
- C. The option limits the number of packets that are captured.
- D. The option captures details of each packet.

Answer: C

NEW QUESTION 7

Which Cisco Firepower feature is used to reduce the number of events received in a period of time?

- A. rate-limiting
- B. suspending
- C. correlation
- D. thresholding

Answer: D

NEW QUESTION 8

DRAG DROP

Drag and drop the steps to restore an automatic device registration failure on the standby Cisco FMC from the left into the correct order on the right. Not all options are used.

Select and Place:

- A. Mastered
- B. Not Mastered

Answer: A

NEW QUESTION 9

Which command is entered in the Cisco FMC CLI to generate a troubleshooting file?

- A. show running-config
- B. show tech-support chassis
- C. system support diagnostic-cli
- D. sudo sf_troubleshoot.pl

Answer: D

Explanation:

41 Which CLI command is used to control special handling of ClientHello messages?

- A. system support ssl-client-hello-tuning
- B. system support ssl-client-hello-display
- C. system support ssl-client-hello-force-reset
- D. system support ssl-client-hello-enabled

NEW QUESTION 10

Which command is typed at the CLI on the primary Cisco FTD unit to temporarily stop running high-availability?

- A. configure high-availability resume
- B. configure high-availability disable
- C. system support network-options
- D. configure high-availability suspend

Answer: B

NEW QUESTION 10

Within Cisco Firepower Management Center, where does a user add or modify widgets?

- A. dashboard
- B. reporting
- C. context explorer
- D. summary tool

Answer: A

NEW QUESTION 11

A network engineer is configuring URL Filtering on Firepower Threat Defense. Which two port requirements on the Firepower Management Center must be validated to allow communication with the cloud service? (Choose two.)

- A. outbound port TCP/443
- B. inbound port TCP/80
- C. outbound port TCP/8080
- D. inbound port TCP/443
- E. outbound port TCP/80

Answer: AE

NEW QUESTION 12

Which limitation applies to Cisco Firepower Management Center dashboards in a multidomain environment?

- A. Child domains can view but not edit dashboards that originate from an ancestor domain.
- B. Child domains have access to only a limited set of widgets from ancestor domains.
- C. Only the administrator of the top ancestor domain can view dashboards.
- D. Child domains cannot view dashboards that originate from an ancestor domain.

Answer: D

NEW QUESTION 14

Which connector is used to integrate Cisco ISE with Cisco FMC for Rapid Threat Containment?

- A. pxGrid
- B. FTD RTC
- C. FMC RTC
- D. ISEGrid

Answer: A

NEW QUESTION 16

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 300-710 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 300-710 Product From:

<https://www.2passeasy.com/dumps/300-710/>

Money Back Guarantee

300-710 Practice Exam Features:

- * 300-710 Questions and Answers Updated Frequently
- * 300-710 Practice Questions Verified by Expert Senior Certified Staff
- * 300-710 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-710 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year