

300-730 Dumps

Implementing Secure Solutions with Virtual Private Networks (SVPN)

<https://www.certleader.com/300-730-dumps.html>



NEW QUESTION 1

On a FlexVPN hub-and-spoke topology where spoke-to-spoke tunnels are not allowed, which command is needed for the hub to be able to terminate FlexVPN tunnels?

- A. interface virtual-access
- B. ip nhrp redirect
- C. interface tunnel
- D. interface virtual-template

Answer: D

NEW QUESTION 2

Refer to the exhibit.

```
interface: Tunnell
  Crypto map tag: Tunnell-head-0, local addr 192.168.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (0.0.0.0/0.0.0.0/0/0)
remote ident (addr/mask/prot/port): (0.0.0.0/0.0.0.0/0/0)
current_peer 192.168.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 0, #pkts encrypt: 0, #pkts digest: 0
  #pkts decaps: 0, #pkts decrypt: 0, #pkts verify: 0
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0

local crypto endpt.: 192.168.0.1, remote crypto endpt.: 192.168.0.2
plaintext mtu 1438, path mtu 1500, ip mtu 1500, ip mtu idb GigabitEthernet1
current outbound spi: 0x3D05D003(1023791107)
PFS (Y/N): N, DH group: none
```

Which two tunnel types produce the show crypto ipsec sa output seen in the exhibit? (Choose two.)

- A. crypto map
- B. DMVPN
- C. GRE
- D. FlexVPN
- E. VTI

Answer: BE

NEW QUESTION 3

Refer to the exhibit.

```
ASA-4-751015 Local:0.0.0.0:0 Remote:0.0.0.0:0 Username:Unknown SA request
rejected by CAC. Reason: IN-NEGOTIATION SA LIMIT REACHED
```

A customer cannot establish an IKEv2 site-to-site VPN tunnel between two Cisco ASA devices. Based on the syslog message, which action brings up the VPN tunnel?

- A. Reduce the maximum SA limit on the local Cisco ASA.
- B. Increase the maximum in-negotiation SA limit on the local Cisco ASA.
- C. Remove the maximum SA limit on the remote Cisco ASA.
- D. Correct the crypto access list on both Cisco ASA devices.

Answer: B

NEW QUESTION 4

Which two types of web resources or protocols are enabled by default on the Cisco ASA Clientless SSL VPN portal? (Choose two.)

- A. HTTP
- B. ICA (Citrix)
- C. VNC
- D. RDP
- E. CIFS

Answer: DE

Explanation:

Reference: <https://www.cisco.com/c/en/us/td/docs/security/asa/asa94/config-guides/cli/vpn/asa-94-vpn-config/webvpn-configure-gateway.html>

NEW QUESTION 5

Which two features provide headend resiliency for Cisco AnyConnect clients? (Choose two.)

- A. AnyConnect Auto Reconnect
- B. AnyConnect Network Access Manager
- C. AnyConnect Backup Servers
- D. ASA failover
- E. AnyConnect Always On

Answer: CD

NEW QUESTION 6

Refer to the exhibit.



The customer must launch Cisco AnyConnect in the RDP machine. Which IOS configuration accomplishes this task?

- A. **crypto vpn anyconnect profile Profile 1 flash:RDP.xml**
webvpn context Context1
svc platform win seq 1
policy group PolicyGroup1
functions svc-enabled
- B. **crypto vpn anyconnect profile Profile 1 flash:RDP.xml**
webvpn context Context1
browser-attribute import flash:RDP.xml
- C. **crypto vpn anyconnect profile Profile 1 flash:RDP.xml**
webvpn context Context1
policy group PolicyGroup1
svc profile Profile1
- D. **crypto vpn anyconnect profile Profile 1 flash:RDP.xml**
webvpn context Context1
policy group PolicyGroup1
svc module RDP

Answer: C

Explanation:

Reference: <https://community.cisco.com/t5/vpn/starting-anyconnect-vpn-through-rdp-session-on-cisco-891/td-p/2128284>

NEW QUESTION 7

Refer to the exhibit.


```
IKEv2:(SESSION ID = 17,SA ID = 1):Processing IKE_AUTH message
IKEv2:IPSec policy validate request sent for profile CloudOne with psh index 1.

IKEv2:(SESSION ID = 17,SA ID = 1):
IKEv2:(SA ID = 1):[IPsec -> IKEv2] Callback received for the validate proposal - FAILED.

IKEv2-ERROR:(SESSION ID = 17,SA ID = 1):: There was no IPSEC policy found for received TS
IKEv2:(SESSION ID = 17,SA ID = 1):Sending TS unacceptable notify
IKEv2:(SESSION ID = 17,SA ID = 1):Get my authentication method
IKEv2:(SESSION ID = 17,SA ID = 1):My authentication method is 'PSK'
IKEv2:(SESSION ID = 17,SA ID = 1):Get peer's preshared key for 68.72.250.251
IKEv2:(SESSION ID = 17,SA ID = 1):Generate my authentication data
IKEv2:(SESSION ID = 17,SA ID = 1):Use preshared key for id 68.72.250.250, key len 5
IKEv2:[IKEv2 -> Crypto Engine] Generate IKEv2 authentication data
IKEv2:[Crypto Engine -> IKEv2] IKEv2 authentication data generation PASSED
IKEv2:(SESSION ID = 17,SA ID = 1):Get my authentication method
IKEv2:(SESSION ID = 17,SA ID = 1):My authentication method is 'PSK'
IKEv2:(SESSION ID = 17,SA ID = 1):Generating IKE_AUTH message
IKEv2:(SESSION ID = 17,SA ID = 1):Constructing IDr payload: '68.72.250.250' of type 'IPv4 address'
IKEv2:(SESSION ID = 17,SA ID = 1):Building packet for encryption.
Payload contents:
  VID IDr AUTH NOTIFY(TS_UNACCEPTABLE)

IKEv2:(SESSION ID = 17,SA ID = 1):Sending Packet [To 68.72.250.251:500/From 68.72.250.250:500/VRF i0:f0]
Initiator SPI : 3D527B1D50DBEEF4 - Responder SPI : 8C693F77F2656636 Message id: 1
IKEv2 IKE_AUTH Exchange RESPONSE
Payload contents:
  ENCR
```

Based on the debug output, which type of mismatch is preventing the VPN from coming up?

- A. interesting traffic
- B. lifetime
- C. preshared key
- D. PFS

Answer: B

Explanation:

If the responder's policy does not allow it to accept any part of the proposed Traffic Selectors, it responds with a TS_UNACCEPTABLE Notify message.

NEW QUESTION 8

Refer to the exhibit.

HUB configuration:

```
crypto ikev2 profile default
match identity remote fqdn domain cisco.com
identity local fqdn hub.cisco.com
authentication local rsa-sig
authentication remote pre-shared-key cisco
pki trustpoint CA
aaa authorization group cert list default default
virtual-template 1
```

SPOKE 1 configuration:

```
crypto ikev2 profile default
match identity remote fqdn domain cisco.com
identity local fqdn spoke.cisco.com
authentication local rsa-sig
authentication remote pre-shared-key cisco
pki trustpoint CA
aaa authorization group cert list default default
virtual-template 1
```

SPOKE 2 configuration:

```
crypto ikev2 profile default
match identity remote fqdn domain cisco.com
identity local fqdn spoke2.cisco.com
authentication local pre-shared-key flexvpn
authentication remote rsa-sig
pki trustpoint CA
aaa authorization group cert list default default
virtual-template 1
```

What is a result of this configuration?

- A. Spoke 1 fails the authentication because the authentication methods are incorrect.
- B. Spoke 2 passes the authentication to the hub and successfully proceeds to phase 2.
- C. Spoke 2 fails the authentication because the remote authentication method is incorrect.
- D. Spoke 1 passes the authentication to the hub and successfully proceeds to phase 2.

Answer: A

NEW QUESTION 9

Which redundancy protocol must be implemented for IPsec stateless failover to work?

- A. SSO
- B. GLBP
- C. HSRP
- D. VRRP

Answer: C

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/security/vpn/ipsec-negotiation-ike-protocols/17826-ipsec-feat.html>

NEW QUESTION 10

Cisco AnyConnect clients need to transfer large files over the VPN sessions. Which protocol provides the best throughput?

- A. SSL/TLS
- B. L2TP
- C. DTLS
- D. IPsec IKEv1

Answer: C

NEW QUESTION 10

Which feature of GETVPN is a limitation of DMVPN and FlexVPN?

- A. sequence numbers that enable scalable replay checking
- B. enabled use of ESP or AH
- C. design for use over public or private WAN
- D. no requirement for an overlay routing protocol

Answer: D

NEW QUESTION 15

Refer to the exhibit.

```
ip access-list extended CCNP
 permit 192.168.0.10
 permit 192.168.0.11

webvpn gateway SSL_Gateway
 ip address 172.16.0.25 port 443
 ssl trustpoint AnyConnect_Cert
 inservice

webvpn context SSL_Context
 gateway SSL_Gateway

 ssl authenticate verify all
 inservice

policy group SSL_Policy
 functions svc-enabled
  svc address-pool "ACPool" netmask 255.255.255.0
  svc dns-server primary 192.168.0.100
  svc default-domain cisco.com
 default-group-policy SSL_Policy
```

Cisco AnyConnect must be set up on a router to allow users to access internal servers 192.168.0.10 and 192.168.0.11. All other traffic should go out of the client's local NIC. Which command accomplishes this configuration?

- A. svc split include 192.168.0.0 255.255.255.0
- B. svc split exclude 192.168.0.0 255.255.255.0
- C. svc split include acl CCNP
- D. svc split exclude acl CCNP

Answer: C

NEW QUESTION 17

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 300-730 Exam with Our Prep Materials Via below:

<https://www.certleader.com/300-730-dumps.html>