

Exam Questions EX294

Red Hat Certified Engineer (RHCE) exam

<https://www.2passeasy.com/dumps/EX294/>



NEW QUESTION 1

- (Exam Topic 2)

Create a playbook called balance.yml as follows:

* The playbook contains a play that runs on hosts in balancers host group and uses the balancer role.

--> This role configures a service to loadbalance webserver requests between hosts in the webservers host group.curl

--> When implemented, browsing to hosts in the balancers host group (for example

http://node5.example.com)

should produce the following output:

Welcome to node3.example.com on 192.168.10.z

--> Reloading the browser should return output from the alternate web server: Welcome to node4.example.com on 192.168.10.a

* The playbook contains a play that runs on hosts in webservers host group and uses the phphello role.

--> When implemented, browsing to hosts in the webservers host group with the URL / hello.php should produce the following output:

Hello PHP World from FQDN

--> where FQDN is the fully qualified domain name of the host. For example,

browsing

to http://node3.example.com/hello.php, should produce the following output: Hello PHP World from node3.example.com

*

Similarly, browsing to http://node4.example.com/hello.php, should produce the following output:

Hello PHP World from node4.example.com

A. Mastered

B. Not Mastered

Answer: A

Explanation:

Solution as:

```
# pwd
```

```
/home/admin/ansible/
```

```
# vim balancer.yml
```

```
--
```

```
- name: Including phphello role hosts: webservers
```

```
roles:
```

```
- ./roles/phphello
```

```
- name: Including balancer role hosts: balancer
```

```
roles:
```

```
- ./roles/balancer wq!
```

```
# ansible-playbook balancer.yml --syntax-check
```

```
# ansible-playbook balancer.yml
```

NEW QUESTION 2

- (Exam Topic 2)

Rekey an existing Ansible vault as follows:

```
-----
```

*

Download Ansible vault from http:// classroom.example.com /secret.yml to /home/ admin/ansible/

* The current vault password is curabete

* The new vault password is newware

* The vault remains in an encrypted state with the new password

A. Mastered

B. Not Mastered

Answer: A

Explanation:

Solution as:

```
# pwd
```

```
/home/admin/ansible/
```

```
#
```

```
wget http://classroom.example.com/secret.yml
```

```
# chmod 0600 newpassword.txt
```

```
# ansible-vault rekey vault.yml --new-vault-password-file=newpassword.txt
```

NEW QUESTION 3

- (Exam Topic 2)

Use Ansible Galaxy with a requirements file called /home/admin/ansible/roles/ install.yml to download and install roles to /home/admin/ansible/roles from the following URLs:

http://classroom.example.com /role1.tar.gz The name of this role should be balancer

http://classroom.example.com /role2.tar.gz The name of this role should be phphello

A. Mastered

B. Not Mastered

Answer: A

Explanation:

Solution as:

```
# pwd
```

```
/home/admin/ansible/roles
# vim install.yml
--
src: http://classroom.example.com/role1.tar.gz name: balancer
src: http://classroom.example.com/role2.tar.gz name: phphello
wq!
# pwd
/home/admin/ansible
# ansible-galaxy install -r roles/install.yml -p roles
```

NEW QUESTION 4

- (Exam Topic 1)

Create a Shell script /root/program:

The shell script will come back to "user" parameter when you are entering "kernel" parameter.

The shell script will come back to "kernel" when you are entering "user" parameter.

It will output the standard error when this script "usage:/root/program kernel|user" don't input any parameter or the parameter you inputted is entered as the requirements.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
[root@server1 virtual]# cat /root/program
#!/bin/bash
param1="$1"
if [ "$param1" == "kernel" ]; then
echo "user"
elif [ "$param1" == "user" ]; then
echo "kernel"
else
echo "usage:/root/program kernel|user"
if
[root@server1 ~]# chmod +x /root/program
```

NEW QUESTION 5

- (Exam Topic 1)

Create a file in /home/sandy/ansible/ called report.yml. Using this playbook, get a file called report.txt (make it look exactly as below). Copy this file over to all remote hosts at /root/report.txt. Then edit the lines in the file to provide the real information of the hosts. If a disk does not exist then write NONE.

report.txt

```
HOST=inventory hostname
MEMORY=total memory in mb
BIOS=bios version
VDA_DISK_SIZE=disk size
VDB_DISK_SIZE=disk size
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution as:

```
- name: edit file
hosts: all
tasks:
  - name: copy file
    copy: report.txt
    dest: /root/report.txt
  - name: change host
    lineinfile:
      regex: ^HOST
      line: HOST={{ansible_hostname}}
      state: present
      path: /root/report.txt
  - name: change mem
    lineinfile:
      line: MEMORY={{ansible_memtotal_mb}}
      regex: ^MEMORY
      state: present
      path: /root/report.txt
  - name: change bios
    lineinfile:
      line: BIOS={{ansible_bios_version}}
      regex: ^BIOS
      state: present
      path: /root/report.txt
  - name: change vda
    lineinfile:
      line: VDA_DISK_SIZE ={%if ansible_devices.vda is defined%}{{ansible_devices.
vda.size}}{%else%}NONE{%endif%}
      regex: ^VDA_DISK_SIZE
      state: present
      path: /root/report.txt
  - name: change vdb
    lineinfile:
      line: VDB_DISK_SIZE ={%if ansible_devices.vdb is defined%}{{ansible_devices.
vdb.size}}{%else%}NONE{%endif%}
      regex: ^VDB_DISK_SIZE
      state: present
      path: /root/report.txt
```

NEW QUESTION 6

- (Exam Topic 1)

Create a playbook called issue.yml in /home/sandy/ansible which changes the file /etc/issue on all managed nodes: If host is a member of (lev then write "Development" If host is a member of test then write "Test" If host is a member of prod then write "Production"

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution as:

```
---
- name: issue file
  hosts: dev,test,prod
  tasks:
    - name: edit development node
      copy:
        content: Development
        dest: /etc/issue
        when: "dev" in group_names
    - name: edit test node
      copy:
        content: Test
        dest: /etc/issue
        when: "test" in group_names
    - name: edit development node
      copy:
        content: Production
        dest: /etc/issue
        when: "prod" in group_names
...

```

NEW QUESTION 7

- (Exam Topic 1)

Create a file called requirements.yml in /home/sandy/ansible/roles a file called role.yml in /home/sandy/ansible/. The haproxy-role should be used on the proxy host. And when you curl <http://node3.example.com> it should display "Welcome to node4.example.com" and when you curl again "Welcome to node5.example.com" The php-role should be used on the prod host.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution as:

```
- name: install haproxy and php roles
  hosts: all
  vars:
    haproxy_backend_servers:
      - name: web1
        address: node4.example.com
      - name: web2
        address: node5.example.com
  tasks:
    - name: import haproxy
      include_role: haproxy-role
      when: "proxy" in group_names
    - name: import php
      include_role: php-role
      when: "prod" in group_names

```

Check the proxy host by curl <http://node3.example.com>

NEW QUESTION 8

- (Exam Topic 1)

In /home/sandy/ansible/ create a playbook called logvol.yml. In the play create a logical volume called lv0 and make it of size 1500MiB on volume group vg0. If there is not enough space in the volume group print a message "Not enough space for logical volume" and then make a 800MiB lv0 instead. If the volume group still doesn't exist, create a message "Volume group doesn't exist" Create an xfs filesystem on all lv0 logical volumes. Don't mount the logical volume.

- A. Mastered

B. Not Mastered

Answer: A

Explanation:

Solution as:

```
- name: hosts
hosts: all
tasks:
- name: create partition
  parted:
    device: /dev/vdb
    number: 1
    flags: [ lvm ]
    state: present
- name: create vg
  lvg:
    vg: vg0
    pvs: /dev/vdb1
    when: ansible_devices.vdb.partitions.vdb1 is defined
- name: create logical volume
  lvol:
    vg: vg0
    lv: lv0
    size: 1500m
    when: ansible_lvm.vgs.vg0 is defined and ( (ansible_lvm.vgs.vg0.size_g | float) > 1.5)
- name: send message if volume group not large enough
  debug:
    msg: Not enough space for logical volume
    when: ansible_lvm.vgs.vg0 is defined and ( (ansible_lvm.vgs.vg0.size_g | float) < 1.5)
- name: create a smaller logical volume
  lvol:
    vg: vg0
    lv: lv0
    size: 1500m
    when: ansible_lvm.vgs.vg0 is defined and ( (ansible_lvm.vgs.vg0.size_g | float) < 1.5)
- name: create fs
  filesystem:
    dev: /dev/vg0/lv0
    fstype: xfs
    when: ansible_lvm.vgs.vg0 is defined
```

NEW QUESTION 10

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual EX294 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the EX294 Product From:

<https://www.2passeasy.com/dumps/EX294/>

Money Back Guarantee

EX294 Practice Exam Features:

- * EX294 Questions and Answers Updated Frequently
- * EX294 Practice Questions Verified by Expert Senior Certified Staff
- * EX294 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * EX294 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year