

AWS-SysOps Dumps

Amazon AWS Certified SysOps Administrator - Associate

<https://www.certleader.com/AWS-SysOps-dumps.html>



NEW QUESTION 1

- (Topic 1)

Your EC2-Based Multi-tier application includes a monitoring instance that periodically makes application -level read only requests of various application components and if any of those fail more than three times 30 seconds calls CloudWatch to fire an alarm, and the alarm notifies your operations team by email and SMS of a possible application health problem. However, you also need to watch the watcher -the monitoring instance itself - and be notified if it becomes unhealthy.

Which of the following is a simple way to achieve that goal?

- A. Run another monitoring instance that pings the monitoring instance and fires a CloudWatch alarm that notifies your operations team should the primary monitoring instance become unhealthy
- B. Set a CloudWatch alarm based on EC2 system and instance status checks and have the alarm notify your operations team of any detected problem with the monitoring instance
- C. Set a CloudWatch alarm based on the CPU utilization of the monitoring instance and have the alarm notify your operations team if the CPU usage exceeds 50% for more than one minute; then have your monitoring application go into a CPU-bound loop should it detect any application problem
- D. Have the monitoring instances post messages to an SQS queue and then dequeue those messages on another instance should the queue cease to have new messages, the second instance should first terminate the original monitoring instance start another backup monitoring instance and assume the role of the previous monitoring instance and begin adding messages to the SQS queue

Answer: D

NEW QUESTION 2

- (Topic 1)

How can the domain's zone apex for example "myzoneapexdomain.com" be pointed towards an Elastic Load Balancer?

- A. By using an AAAA record
- B. By using an A record
- C. By using an Amazon Route 53 CNAME record
- D. By using an Amazon Route 53 Alias record

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/resource-record-sets-choosing-alias-non-alias.html>

NEW QUESTION 3

- (Topic 1)

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

Answer: C

Explanation:

Explanation: Reference:

<http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 4

- (Topic 1)

A customer has a web application that uses cookie-based sessions to track logged-in users. It is deployed on AWS using ELB and Auto Scaling. The customer observes that when load increases, Auto Scaling launches new instances but the load on the existing instances does not decrease, causing all existing users to have a sluggish experience.

Which two answer choices independently describe a behavior that could be the cause of the sluggish user experience? Choose 2 answers.

- A. ELB's normal behavior sends requests from the same user to the same backend instance
- B. ELB's behavior when sticky sessions are enabled causes ELB to send requests in the same session to the same backend instance
- C. A faulty browser is not honoring the TTL of the ELB DNS name
- D. The web application uses long polling such as comet or websocket
- E. Thereby keeping a connection open to a web server for a long time
- F. The web application uses long polling such as comet or websocket
- G. Thereby keeping a connection open to a web server for a long time

Answer: BD

NEW QUESTION 5

- (Topic 1)

You use S3 to store critical data for your company. Several users within your group currently have full permissions to your S3 buckets. You need to come up with a solution that does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers.

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete

- C. Create a Bucket policy and only allow read only permissions to all users at the bucket level
- D. Enable object life cycle policies and configure the data older than 3 months to be archived in Glacier

Answer: AB

NEW QUESTION 6

- (Topic 1)

You have a server with a 500GB Amazon EBS data volume. The volume is 80% full. You need to back up the volume at regular intervals and be able to re-create the volume in a new Availability Zone in the shortest time possible. All applications using the volume can be paused for a period of a few minutes with no discernible user impact.

Which of the following backup methods will best fulfill your requirements?

- A. Take periodic snapshots of the EBS volume
- B. Use a third party Incremental backup application to back up to Amazon Glacier
- C. Periodically back up all data to a single compressed archive and archive to Amazon S3 using a parallelized multi-part upload
- D. Create another EBS volume in the second Availability Zone attach it to the Amazon EC2 instance, and use a disk manager to mirror the two disks

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-creating-snapshot.html>

NEW QUESTION 7

- (Topic 1)

Your entire AWS infrastructure lives inside of one Amazon VPC. You have an Infrastructure monitoring application running on an Amazon instance in Availability Zone (AZ) A of the region, and another application instance running in AZ B. The monitoring application needs to make use of ICMP ping to confirm network reachability of the instance hosting the application.

Can you configure the security groups for these instances to only allow the ICMP ping to pass from the monitoring instance to the application instance and nothing else? If so how?

- A. No. Two instances in two different AZ's can't talk directly to each other via ICMP ping as that protocol is not allowed across subnet (i.e. broadcast) boundaries.
- B. Yes. Both the monitoring instance and the application instance have to be a part of the same security group, and that security group needs to allow inbound ICMP.
- C. Yes, The security group for the monitoring instance needs to allow outbound ICMP and the application instance's security group needs to allow Inbound ICMP.
- D. Yes, Both the monitoring instance's security group and the application instance's security group need to allow both inbound and outbound ICMP ping packets since ICMP is not a connection-oriented protocol.

Answer: D

NEW QUESTION 8

- (Topic 1)

You have a web application leveraging an Elastic Load Balancer (ELB) in front of the web servers deployed using an Auto Scaling Group. Your database is running on Relational

Database Service (RDS). The application serves out technical articles and responses to them. In general, there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular, resulting in significant traffic increases that cause the site to go down.

What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?

Choose 3 answers.

- A. Leverage CloudFront for the delivery of the article.
- B. Add RDS read-replicas for the read traffic going to your relational database.
- C. Leverage ElastiCache for caching the most frequently used data.
- D. Use SQS to queue up the requests for the technical posts and deliver them out of the queue.
- E. Use Route53 health checks to fail over to an S3 bucket for an error page.

Answer: ACE

NEW QUESTION 9

- (Topic 1)

You are running a database on an EC2 instance, with the data stored on Elastic Block Store (EBS) for persistence. At times throughout the day, you are seeing large variance in the response times of the database queries. Looking into the instance with the `iostat` command, you see a lot of wait time on the disk volume that the database's data is stored on.

What two ways can you improve the performance of the database's storage while maintaining the current persistence of the data?

Choose 2 answers.

- A. Move to an SSD-backed instance.
- B. Move the database to an EBS-Optimized Instance.
- C. Use Provisioned IOPS EBS.
- D. Use the ephemeral storage on an m2.xlarge instance instead.

Answer: AB

NEW QUESTION 10

- (Topic 1)

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance

- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation:

Reference:
<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 10

- (Topic 1)

The majority of your Infrastructure is on premises and you have a small footprint on AWS Your company has decided to roll out a new application that is heavily dependent on low latency connectivity to LOAP for authentication Your security policy requires minimal changes to the company's existing application user management processes.

What option would you implement to successfully launch this application1?

- A. Create a second, independent LOAP server in AWS for your application to use for authentication
- B. Establish a VPN connection so your applications can authenticate against your existing on-premises LDAP servers
- C. Establish a VPN connection between your data center and AWS create a LDAP replica on AWS and configure your application to use the LDAP replica for authentication
- D. Create a second LDAP domain on AWS establish a VPN connection to establish a trust relationship between your new and existing domains and use the new domain for authentication

Answer: D

Explanation:

Reference:
<http://msdn.microsoft.com/en-us/library/azure/jj156090.aspx>

NEW QUESTION 14

- (Topic 1)

Your organization's security policy requires that all privileged users either use frequently rotated passwords or one-time access credentials in addition to username/password.

Which two of the following options would allow an organization to enforce this policy for AWS users?

Choose 2 answers

- A. Configure multi-factor authentication for privileged 1AM users
- B. Create 1AM users for privileged accounts
- C. Implement identity federation between your organization's Identity provider leveraging the 1AM Security Token Service
- D. Enable the 1AM single-use password policy option for privileged users

Answer: CD

NEW QUESTION 18

- (Topic 1)

You have two Elastic Compute Cloud (EC2) instances inside a Virtual Private Cloud (VPC) in the same Availability Zone (AZ) but in different subnets. One instance is running a database and the other instance an application that will interface with the database. You want to confirm that they can talk to each other for your application to work properly.

Which two things do we need to confirm in the VPC settings so that these EC2 instances can communicate inside the VPC? Choose 2 answers

- A. A network ACL that allows communication between the two subnet
- B. Both instances are the same instance class and using the same Key-pai
- C. That the default route is set to a NAT instance or internet Gateway (IGW) for them to communicat
- D. Security groups are set to allow the application host to talk to the database on the right port/protoco

Answer: AD

NEW QUESTION 20

- (Topic 1)

When an EC2 instance that is backed by an S3-based AMI Is terminated, what happens to the data on me root volume?

- A. Data is automatically saved as an E8S volum
- B. Data is automatically saved as an ESS snapsho
- C. Data is automatically delete
- D. Data is unavailable until the instance is restarte

Answer: C

Explanation:

Reference:
<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ComponentsAMIs.html>

NEW QUESTION 23

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group

- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (Mil)

Answer: C

Explanation:

Reference:
<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 27

- (Topic 1)

Which services allow the customer to retain full administrative privileges of the underlying EC2 instances?

Choose 2 answers

- A. Amazon Elastic Map Reduce
- B. Elastic Load Balancing
- C. AWS Elastic Beanstalk
- D. Amazon ElastiCache
- E. Amazon Relational Database service

Answer: AC

NEW QUESTION 32

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation:

Reference:
<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 36

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

Answer: A

NEW QUESTION 41

- (Topic 1)

You have a Linux EC2 web server instance running inside a VPC. The instance is in a public subnet and has an EIP associated with it so you can connect to it over the Internet via HTTP or SSH. The instance was also fully accessible when you last logged in via SSH, and was also serving web requests on port 80.

Now you are not able to SSH into the host nor does it respond to web requests on port 80 that were working fine last time you checked. You have double-checked that all networking configuration parameters (security groups, route tables, IGW, EIP, NACLs, etc) are properly configured (and you haven't made any changes to those anyway since you were last able to reach the instance). You look at the EC2 console and notice that system status check shows "impaired."

Which should be your next step in troubleshooting and attempting to get the instance back to a healthy state so that you can log in again?

- A. Stop and start the instance so that it will be able to be redeployed on a healthy host system that most likely will fix the "impaired" system status
- B. Reboot your instance so that the operating system will have a chance to boot in a clean healthy state that most likely will fix the "impaired" system status
- C. Add another dynamic private IP address to the instance and try to connect via that new path, since the networking stack of the OS may be locked up causing the "impaired" system status
- D. Add another Elastic Network Interface to the instance and try to connect via that new path since the networking stack of the OS may be locked up causing the "impaired" system status
- E. un-map and then re-map the EIP to the instance, since the IGW/VNAT gateway may not be working properly, causing the "impaired" system status

Answer: A

NEW QUESTION 45

- (Topic 2)

A user is accessing RDS from an application. The user has enabled the Multi-AZ feature with the MS SQL RDS DB. During a planned outage, how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB

- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 47

- (Topic 2)

An application is generating a log file every 5 minutes. The log file is not critical but may be required only for verification in case of some major issue. The file should be accessible over the internet whenever required. Which of the below mentioned options is a best possible storage solution for it?

- A. AWS S3
- B. AWS Glacier
- C. AWS RDS
- D. AWS RRS

Answer: D

Explanation:

Amazon S3 stores objects according to their storage class. There are three major storage classes: Standard, Reduced Redundancy Storage and Glacier. Standard is for AWS S3 and provides very high durability. However, the costs are a little higher. Glacier is for archival and the files are not available over the internet. Reduced Redundancy Storage is for less critical files. Reduced Redundancy is little cheaper as it provides less durability in comparison to S3. In this case since the log files are not mission critical files, RRS will be a better option.

NEW QUESTION 49

- (Topic 2)

A user is planning to use AWS Cloudformation. Which of the below mentioned functionalities does not help him to correctly understand Cloudfromation?

- A. Cloudformation follows the DevOps model for the creation of Dev & Test
- B. AWS Cloudfromation does not charge the user for its service but only charges for the AWS resources created with it
- C. Cloudformation works with a wide variety of AWS services, such as EC2, EBS, VPC, IAM, S3, RDS, ELB, etc
- D. CloudFormation provides a set of application bootstrapping scripts which enables the user to install Software

Answer: A

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. It supports a wide variety of AWS services, such as EC2, EBS, AS, ELB, RDS, VPC, etc. It also provides application bootstrapping scripts which enable the user to install software packages or create folders. It is free of the cost and only charges the user for the services created with it. The only challenge is that it does not follow any model, such as DevOps; instead customers can define templates and use them to provision and manage the AWS resources in an orderly way.

NEW QUESTION 53

- (Topic 2)

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

NEW QUESTION 57

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24. and VPN only subnets CIDR (20.0.1.0/24. along with the VPN gateway (vgw-12345. to connect to the user's data centre. Which of the below mentioned options is a valid entry for the main route table in this scenario?

- A. Destination: 20.0.0.0/24 and Target: vgw-12345
- B. Destination: 20.0.0.0/16 and Target: ALL
- C. Destination: 20.0.1.0/16 and Target: vgw-12345
- D. Destination: 0.0.0.0/0 and Target: vgw-12345

Answer: D

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: vgw-12345 (To route all internet traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC.

NEW QUESTION 59

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 61

- (Topic 2)

A system admin is managing buckets, objects and folders with AWS S3. Which of the below mentioned statements is true and should be taken in consideration by the sysadmin?

- A. The folders support only ACL
- B. Both the object and bucket can have an Access Policy but folder cannot have policy
- C. Folders can have a policy
- D. Both the object and bucket can have ACL but folders cannot have ACL

Answer: A

Explanation:

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level. The folders are similar to objects with no content. Thus, folders can have only ACL and cannot have a policy.

NEW QUESTION 66

- (Topic 2)

A user has created an ELB with the availability zone US-East-1A. The user wants to add more zones to ELB to achieve High Availability. How can the user add more zones to the existing ELB?

- A. It is not possible to add more zones to the existing ELB
- B. The only option is to launch instances in different zones and add to ELB
- C. The user should stop the ELB and add zones and instances as required
- D. The user can add zones on the fly from the AWS console

Answer: D

Explanation:

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways:
From the console or CLI, add new zones to ELB;
Launch instances in a separate AZ and add instances to the existing ELB.

NEW QUESTION 70

- (Topic 2)

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Queue Service
- D. AWS Simple Query Service

Answer: C

Explanation:

Amazon Simple Queue Service (SQS. is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to

decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

NEW QUESTION 75

- (Topic 2)

A user has setup an EBS backed instance and a CloudWatch alarm when the CPU utilization is more than 65%. The user has setup the alarm to watch it for 5 periods of 5 minutes each. The CPU utilization is 60% between 9 AM to 6 PM. The user has stopped the EC2 instance for 15 minutes between 11 AM to 11:15 AM. What will be the status of the alarm at 11:30 AM?

- A. Alarm
- B. OK
- C. Insufficient Data
- D. Error

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The state of the alarm will be OK for the whole day. When the user stops the instance for three periods the alarm may not receive the data

NEW QUESTION 79

- (Topic 2)

An organization is planning to create 5 different AWS accounts considering various security requirements. The organization wants to use a single payee account by using the consolidated billing option. Which of the below mentioned statements is true with respect to the above information?

- A. Master (Payee)
- B. account will get only the total bill and cannot see the cost incurred by each account
- C. Master (Payee)
- D. account can view only the AWS billing details of the linked accounts
- E. It is not recommended to use consolidated billing since the payee account will have access to the linked accounts
- F. Each AWS account needs to create an AWS billing policy to provide permission to the payee account

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account. The payee account will not have any other access than billing data of linked accounts.

NEW QUESTION 82

- (Topic 2)

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling group

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 83

- (Topic 2)

An admin is planning to monitor the ELB. Which of the below mentioned services does not help the admin capture the monitoring information about the ELB activity?

- A. ELB Access logs
- B. ELB health check
- C. CloudWatch metrics
- D. ELB API calls with CloudTrail

Answer: B

Explanation:

The admin can capture information about Elastic Load Balancer using either: CloudWatch Metrics ELB Logs files which are stored in the S3 bucket CloudTrail with API calls which can notify the user as well generate logs for each API call. The health check is internally performed by ELB and does not help the admin get the

ELB activity.

NEW QUESTION 87

- (Topic 2)

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- B. The organization should create each user in a separate region so that they have their own URL to login
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

NEW QUESTION 90

- (Topic 2)

A sys admin has created the below mentioned policy and applied to an S3 object named aws.jpg. The aws.jpg is inside a bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmnt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]
}]
```

- A. It is not possible to define a policy at the object level
- B. It will make all the objects of the bucket cloudacademy as public
- C. It will make the bucket cloudacademy as public
- D. the aws.jpg object as public

Answer: A

Explanation:

A system admin can grant permission to the S3 objects or buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level.

NEW QUESTION 94

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 98

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

Answer: C

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

NEW QUESTION 101

- (Topic 2)

A user has launched an EC2 instance from an instance store backed AMI. The infrastructure team wants to create an AMI from the running instance. Which of the below mentioned steps will not be performed while creating the AMI?

- A. Define the AMI launch permissions
- B. Upload the bundled volume
- C. Register the AMI
- D. Bundle the volume

Answer: A

Explanation:

When the user has launched an EC2 instance from an instance store backed AMI, it will need to follow certain steps, such as “Bundling the root volume”, “Uploading the bundled volume” and “Register the AMI”. Once the AMI is created the user can setup the launch permission. However, it is not required to setup during the launch.

NEW QUESTION 102

- (Topic 2)

A user has created a queue named “myqueue” in US-East region with AWS SQS. The user's AWS account ID is 123456789012. If the user wants to perform some action on this queue, which of the below Queue URL should he use?

- A. <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>
- B. <http://sqs.amazonaws.com/123456789012/myqueue>
- C. <http://sq>
- D. 123456789012.us-east-1.amazonaws.com/myqueue
- E. [http:// 123456789012.sq](http://123456789012.sq)
- F. us-east-1.amazonaws.com/myqueue

Answer: A

Explanation:

When creating a new queue in SQS, the user must provide a queue name that is unique within the scope of all queues of user's account. If the user creates queues using both the latest WSDL and a previous version, he will have a single namespace for all his queues. Amazon SQS assigns each queue created by user an identifier called a queue URL, which includes the queue name and other components that Amazon SQS determines. Whenever the user wants to perform an action on a queue, he must provide its queue URL. The queue URL for the account id 123456789012 & queue name “myqueue” in US-East-1 region will be <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>.

NEW QUESTION 103

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department's employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 107

- (Topic 2)

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

Answer: A

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user

should use the on-demand pricing.

NEW QUESTION 109

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25. The user is trying to create the private subnet with CIDR 20.0.0.128/25. Which of the below mentioned statements is true in this scenario?

- A. It will not allow the user to create the private subnet due to a CIDR overlap
- B. It will allow the user to create a private subnet with CIDR as 20.0.0.128/25
- C. This statement is wrong as AWS does not allow CIDR 20.0.0.0/25
- D. It will not allow the user to create a private subnet due to a wrong CIDR range

Answer: B

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. The CIDR block of a subnet can be the same as the CIDR block for the VPC (for a single subnet in the VPC., or a subset (to enable multiple subnets.. If the user creates more than one subnet in a VPC, the CIDR blocks of the subnets must not overlap. Thus, in this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The user can break this CIDR block into two subnets, each supporting 128 IP addresses. One subnet uses the CIDR block 20.0.0.0/25 (for addresses 20.0.0.0 - 20.0.0.127. and the other uses the CIDR block 20.0.0.128/25 (for addresses 20.0.0.128 - 20.0.0.255..

NEW QUESTION 112

- (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

NEW QUESTION 117

- (Topic 2)

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public
- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

Answer: C

Explanation:

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

NEW QUESTION 121

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3. APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value. file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 122

- (Topic 2)

A user is planning to setup notifications on the RDS DB for a snapshot. Which of the below mentioned event categories is not supported by RDS for this snapshot source type?

- A. Backup
- B. Creation
- C. Deletion
- D. Restoration

Answer: A

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event categories for a snapshot source type include: Creation, Deletion, and Restoration. The Backup is a part of DB instance source type.

NEW QUESTION 124

- (Topic 2)

A user has created a web application with Auto Scaling. The user is regularly monitoring the application and he observed that the traffic is highest on Thursday and Friday between 8 AM to 6 PM. What is the best solution to handle scaling in this case?

- A. Add a new instance manually by 8 AM Thursday and terminate the same by 6 PM Friday
- B. Schedule Auto Scaling to scale up by 8 AM Thursday and scale down after 6 PM on Friday
- C. Schedule a policy which may scale up every day at 8 AM and scales down by 6 PM
- D. Configure a batch process to add a instance by 8 AM and remove it by Friday 6 PM

Answer: B

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. In this case the load increases by Thursday and decreases by Friday. Thus, the user can setup the scaling activity based on the predictable traffic patterns of the web application using Auto Scaling scale by Schedule.

NEW QUESTION 129

- (Topic 2)

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI. of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

NEW QUESTION 132

- (Topic 2)

A user wants to make so that whenever the CPU utilization of the AWS EC2 instance is above 90%, the redlight of his bedroom turns on. Which of the below mentioned AWS services is helpful for this purpose?

- A. AWS CloudWatch + AWS SES
- B. AWS CloudWatch + AWS SNS
- C. Non
- D. It is not possible to configure the light with the AWS infrastructure services
- E. AWS CloudWatch and a dedicated software turning on the light

Answer: B

Explanation:

Amazon Simple Notification Service (Amazon SNS. is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS. queues or to any HTTP endpoint. The user can configure some sensor devices at his home which receives data on the HTTP end point (REST calls. and turn on the red light. The user can configure the CloudWatch alarm to send a notification to the AWS SNS HTTP end point (the sensor device. and it will turn the light red when there is an alarm condition.

NEW QUESTION 133

- (Topic 2)

A user has launched an EBS backed EC2 instance. The user has rebooted the instance. Which of the below mentioned statements is not true with respect to the reboot action?

- A. The private and public address remains the same
- B. The Elastic IP remains associated with the instance
- C. The volume is preserved
- D. The instance runs on a new host computer

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use the Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. The instance remains on the same host computer and maintains its public DNS name, private IP address, and any data on its instance store volumes. It typically takes a few minutes for the reboot to complete, but the time it takes to reboot depends on the instance configuration.

NEW QUESTION 137

- (Topic 2)

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB connection draining
- D. ELB auto registration Off

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served.

NEW QUESTION 138

- (Topic 2)

A user is trying to setup a recurring Auto Scaling process. The user has setup one process to scale up every day at 8 am and scale down at 7 PM. The user is trying to setup another recurring process which scales up on the 1st of every month at 8 AM and scales down the same day at 7 PM. What will Auto Scaling do in this scenario?

- A. Auto Scaling will execute both processes but will add just one instance on the 1st
- B. Auto Scaling will add two instances on the 1st of the month
- C. Auto Scaling will schedule both the processes but execute only one process randomly
- D. Auto Scaling will throw an error since there is a conflict in the schedule of two separate Auto Scaling Processes

Answer: D

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. As per Auto Scaling, a scheduled action must have a unique time value. If the user attempts to schedule an activity at a time when another existing activity is already scheduled, the call will be rejected with an error message noting the conflict.

NEW QUESTION 140

- (Topic 2)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
```

- A. 0
- B. 0
- C. 0
- D. 0

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage keys (access and secret access keys. of all IAM users, the organization should set the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
```

```
"Effect": "Allow",
"Action": [
"iam:*AccessKey*",
],
"Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}
]
```

NEW QUESTION 141

- (Topic 2)

A user has setup a web application on EC2. The user is generating a log of the application performance at every second. There are multiple entries for each second. If the user wants to send that data to CloudWatch every minute, what should he do?

- A. The user should send only the data of the 60th second as CloudWatch will map the receive data timezone with the sent data timezone
- B. It is not possible to send the custom metric to CloudWatch every minute
- C. Give CloudWatch the Min, Max, Sum, and SampleCount of a number of every minute
- D. Calculate the average of one minute and send the data to CloudWatch

Answer: C

Explanation:

Amazon CloudWatch aggregates statistics according to the period length that the user has specified while getting data from CloudWatch. The user can publish as many data points as he wants with the same or similar time stamps. CloudWatch aggregates them by the period length when the user calls get statistics about those data points. CloudWatch records the average (sum of all items divided by the number of items. of the values received for every 1-minute period, as well as the number of samples, maximum value, and minimum value for the same time period. CloudWatch will aggregate all the data which have time stamps within a one-minute period.

NEW QUESTION 146

- (Topic 2)

A user has launched a large EBS backed EC2 instance in the US-East-1a region. The user wants to achieve Disaster Recovery (DR. for that instance by creating another small instance in Europe. How can the user achieve DR?

- A. Copy the running instance using the “Instance Copy” command to the EU region
- B. Create an AMI of the instance and copy the AMI to the EU regio
- C. Then launch the instance from the EU AMI
- D. Copy the instance from the US East region to the EU region
- E. Use the “Launch more like this” option to copy the instance from one region to another

Answer: B

Explanation:

To launch an EC2 instance it is required to have an AMI in that region. If the AMI is not available in that region, then create a new AMI or use the copy command to copy the AMI from one region to the other region.

NEW QUESTION 149

- (Topic 2)

A user has configured the Auto Scaling group with the minimum capacity as 3 and the maximum capacity as 5. When the user configures the AS group, how many instances will Auto Scaling launch?

- A. 3
- B. 0
- C. 5
- D. 2

Answer: C

NEW QUESTION 154

- (Topic 2)

A user has configured CloudWatch monitoring on an EBS backed EC2 instance. If the user has not attached any additional device, which of the below mentioned metrics will always show a 0 value?

- A. DiskReadBytes
- B. NetworkIn
- C. NetworkOut
- D. CPUUtilization

Answer: A

Explanation:

CloudWatch is used to monitor AWS as the well custom services. For EC2 when the user is monitoring the EC2 instances, it will capture the 7 Instance level and 3 system check parameters for the EC2 instance. Since this is an EBS backed instance, it will not have ephemeral storage attached to it. Out of the 7 EC2 metrics, the 4 metrics DiskReadOps, DiskWriteOps, DiskReadBytes and DiskWriteBytes are disk related data and available only when there is ephemeral storage attached to an instance. For an EBS backed instance without any additional device, this data will be 0.

NEW QUESTION 158

- (Topic 2)

A user has created numerous EBS volumes. What is the general limit for each AWS account for the maximum number of EBS volumes that can be created?

- A. 10000
- B. 5000
- C. 100
- D. 1000

Answer: B

Explanation:

A user can attach multiple EBS volumes to the same instance within the limits specified by his AWS account. Each AWS account has a limit on the number of Amazon EBS volumes that the user can create, and the total storage available. The default limit for the maximum number of volumes that can be created is 5000.

NEW QUESTION 162

- (Topic 2)

An organization has configured the custom metric upload with CloudWatch. The organization has given permission to its employees to upload data using CLI as well SDK. How can the user track the calls made to CloudWatch?

- A. The user can enable logging with CloudWatch which logs all the activities
- B. Use CloudTrail to monitor the API calls
- C. Create an IAM user and allow each user to log the data using the S3 bucket
- D. Enable detailed monitoring with CloudWatch

Answer: B

Explanation:

AWS CloudTrail is a web service which will allow the user to monitor the calls made to the Amazon CloudWatch API for the organization's account, including calls made by the AWS Management Console, Command Line Interface (CLI), and other services. When CloudTrail logging is turned on, CloudWatch will write log files into the Amazon S3 bucket, which is specified during the CloudTrail configuration.

NEW QUESTION 167

- (Topic 2)

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Elastic Load balancing. Which of the below mentioned statements will help the user understand this functionality better?

- A. ELB sends data to CloudWatch every minute only and does not charge the user
- B. ELB will send data every minute and will charge the user extra
- C. ELB is not supported by CloudWatch
- D. It is not possible to setup detailed monitoring for ELB

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Elastic Load Balancing includes 10 metrics and 2 dimensions, and sends data to CloudWatch every minute. This does not cost extra.

NEW QUESTION 171

- (Topic 2)

A sys admin has created a shopping cart application and hosted it on EC2. The EC2 instances are running behind ELB. The admin wants to ensure that the end user request will always go to the EC2 instance where the user session has been created. How can the admin configure this?

- A. Enable ELB cross zone load balancing
- B. Enable ELB cookie setup
- C. Enable ELB sticky session
- D. Enable ELB connection draining

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. If the sticky session is enabled the first request from the user will be redirected to any of the EC2 instances. But, henceforth, all requests from the same user will be redirected to the same EC2 instance. This ensures that all requests coming from the user during the session will be sent to the same application instance.

NEW QUESTION 172

- (Topic 2)

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

Answer: D

Explanation:

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

NEW QUESTION 177

- (Topic 2)

A user has created a subnet with VPC and launched an EC2 instance in that subnet with only default settings. Which of the below mentioned options is ready to use on the EC2 instance as soon as it is launched?

- A. Elastic IP
- B. Private IP
- C. Public IP
- D. Internet gateway

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC. When the user launches an instance which is not a part of the non-default subnet, it will only have a private IP assigned to it. The instances part of a subnet can communicate with each other but cannot communicate over the internet or to the AWS services, such as RDS / S3.

NEW QUESTION 180

- (Topic 2)

A user is launching an instance. He is on the "Tag the instance" screen. Which of the below mentioned information will not help the user understand the functionality of an AWS tag?

- A. Each tag will have a key and value
- B. The user can apply tags to the S3 bucket
- C. The maximum value of the tag key length is 64 unicode characters
- D. AWS tags are used to find the cost distribution of various resources

Answer: C

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. The maximum size of a tag key is 128 unicode characters.

NEW QUESTION 185

- (Topic 2)

A user has setup an RDS DB with Oracle. The user wants to get notifications when someone modifies the security group of that DB. How can the user configure that?

- A. It is not possible to get the notifications on a change in the security group
- B. Configure SNS to monitor security group changes
- C. Configure event notification on the DB security group
- D. Configure the CloudWatch alarm on the DB for a change in the security group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group. If the user is subscribed to a Configuration Change category for a DB security group, he will be notified when the DB security group is changed.

NEW QUESTION 190

- (Topic 2)

A user is publishing custom metrics to CloudWatch. Which of the below mentioned statements will help the user understand the functionality better?

- A. The user can use the CloudWatch Import tool
- B. The user should be able to see the data in the console after around 15 minutes
- C. If the user is uploading the custom data, the user must supply the namespace, timezone, and metric name as part of the command
- D. The user can view as well as upload data using the console, CLI and APIs

Answer: B

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has

to always include the namespace as a part of the request. However, the other parameters are optional. If the user has uploaded data using CLI, he can view it as a graph inside the console. The data will take around 2 minutes to upload but can be viewed only after around 15 minutes.

NEW QUESTION 191

- (Topic 2)

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. It is not possible to do this with SQS
- B. You can use sequencing information on each message
- C. You can do this with SQS but you also need to use SWF
- D. Messages will arrive in the same order by default

Answer: B

Explanation:

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them.

NEW QUESTION 192

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

NEW QUESTION 195

- (Topic 2)

A user has configured a VPC with a new subnet. The user has created a security group. The user wants to configure that instances of the same subnet communicate with each other. How can the user configure this with the security group?

- A. There is no need for a security group modification as all the instances can communicate with each other inside the same subnet
- B. Configure the subnet as the source in the security group and allow traffic on all the protocols and ports
- C. Configure the security group itself as the source and allow traffic on all the protocols and ports
- D. The user has to use VPC peering to configure this

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. If the user is using the default security group it will have a rule which allows the instances to communicate with other. For a new security group the user has to specify the rule, add it to define the source as the security group itself, and select all the protocols and ports for that source.

NEW QUESTION 198

- (Topic 2)

A sys admin is trying to understand EBS snapshots. Which of the below mentioned statements will not be useful to the admin to understand the concepts about a snapshot?

- A. The snapshot is synchronous
- B. It is recommended to stop the instance before taking a snapshot for consistent data
- C. The snapshot is incremental
- D. The snapshot captures the data that has been written to the hard disk when the snapshot command was executed

Answer: A

Explanation:

The AWS snapshot is a point in time backup of an EBS volume. When the snapshot command is executed it will capture the current state of the data that is written on the drive and take a backup. For a better and consistent snapshot of the root EBS volume, AWS recommends stopping the instance. For additional volumes it is recommended to unmount the device. The snapshots are asynchronous and incremental.

NEW QUESTION 200

- (Topic 2)

A user has launched an EBS backed EC2 instance. What will be the difference while performing the restart or stop/start options on that instance?

- A. For restart it does not charge for an extra hour, while every stop/start it will be charged as a separate hour
- B. Every restart is charged by AWS as a separate hour, while multiple start/stop actions during a single hour will be counted as a single hour
- C. For every restart or start/stop it will be charged as a separate hour
- D. For restart it charges extra only once, while for every stop/start it will be charged as a separate hour

Answer: A

Explanation:

For an EC2 instance launched with an EBS backed AMI, each time the instance state is changed from stop to start/ running, AWS charges a full instance hour, even if these transitions happen multiple times within a single hour. Anyway, rebooting an instance AWS does not charge a new instance billing hour.

NEW QUESTION 201

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 204

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instance
- B. A new DB instance is created in the standby availability zone
- C. The canonical name record (CNAME) is changed from primary to standby
- D. The RDS (Relational Database Service) DB instance reboots

Answer: D

Explanation:

Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html

NEW QUESTION 209

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user wants to convert the AMI to an EBS backed AMI. How can the user convert it?

- A. Attach an EBS volume to the instance and unbundle all the AMI bundled data inside the EBS
- B. A Windows based instance store backed AMI cannot be converted to an EBS backed AMI
- C. It is not possible to convert an instance store backed AMI to an EBS backed AMI
- D. Attach an EBS volume and use the copy command to copy all the ephemeral content to the EBS Volume

Answer: B

Explanation:

Generally when a user has launched an EC2 instance from an instance store backed AMI, it can be converted to an EBS backed AMI provided the user has attached the EBS volume to the instance and unbundles the AMI data to it. However, if the instance is a Windows instance, AWS does not allow this. In this case, since the instance is a Windows instance, the user cannot convert it to an EBS backed AMI.

NEW QUESTION 210

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling terminate process only for a while. What will happen to the availability zone rebalancing process (AZRebalance) during this period?

- A. Auto Scaling will not launch or terminate any instances
- B. Auto Scaling will allow the instances to grow more than the maximum size
- C. Auto Scaling will keep launching instances till the maximum instance size
- D. It is not possible to suspend the terminate process while keeping the launch active

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, Availability Zone Rebalance (AZRebalance. etc. The AZRebalance process type seeks to maintain a balanced number of instances across Availability Zones within a region. If the user suspends the Terminate process, the AZRebalance process can cause the Auto Scaling group to grow up to ten percent larger than the maximum size. This is because Auto Scaling allows groups to temporarily grow larger than the maximum size during rebalancing activities. If Auto Scaling cannot terminate instances, the Auto Scaling group could remain up to ten percent larger than the maximum size until the user resumes the Terminate process type.

NEW QUESTION 213

- (Topic 3)

A user is trying to understand the CloudWatch metrics for the AWS services. It is required that the user should first understand the namespace for the AWS services. Which of the below mentioned is not a valid namespace for the AWS services?

- A. AWS/StorageGateway
- B. AWS/CloudTrail
- C. AWS/ElastiCache
- D. AWS/SWF

Answer: B

Explanation:

Amazon CloudWatch is basically a metrics repository. The AWS product puts metrics into this repository, and the user can retrieve the data or statistics based on those metrics. To distinguish the data for each service, the CloudWatch metric has a namespace. Namespaces are containers for metrics. All AWS services that provide the Amazon CloudWatch data use a namespace string, beginning with "AWS/". All the services which are supported by CloudWatch will have some namespace. CloudWatch does not monitor CloudTrail. Thus, the namespace "AWS/CloudTrail" is incorrect.

NEW QUESTION 216

- (Topic 3)

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
- B. "Effect": "Allow", "Action": ["AccountUsage"], "Resource": "**"
- C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": ""
- D. "Effect": "Allow", "Action": ["aws-portal: ViewBilling"], "Resource": ""

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "aws-portal:ViewUsage"
      ],
      "Resource": ""
    }
  ]
}
```

NEW QUESTION 219

- (Topic 3)

A user has launched 5 instances in EC2-CLASSIC and attached 5 elastic IPs to the five different instances in the US East region. The user is creating a VPC in the same region. The user wants to assign an elastic IP to the VPC instance. How can the user achieve this?

- A. The user has to request AWS to increase the number of elastic IPs associated with the account
- B. AWS allows 10 EC2 Classic IPs per region; so it will allow to allocate new Elastic IPs to the same region
- C. The AWS will not allow to create a new elastic IP in VPC; it will throw an error
- D. The user can allocate a new IP address in VPC as it has a different limit than EC2

Answer: D

Explanation:

Section: (none)

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. A user can have 5 IP addresses per region with EC2 Classic. The user can have 5 separate IPs with VPC in the same region as it has a separate limit than EC2 Classic.

NEW QUESTION 223

- (Topic 3)

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source. AMI. The user can modify the source AMI without affecting the new AMI and vice a versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 224

- (Topic 3)

When an EC2 instance mat is backed by an S3-Dased AMI is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapsho
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volum

Answer: A

NEW QUESTION 227

- (Topic 3)

A user has setup a VPC with CIDR 20.0.0.0/16. The VPC has a private subnet (20.0.1.0/24. and a public subnet (20.0.0.0/24.. The user's data centre has CIDR of 20.0.54.0/24 and 20.1.0.0/24. If the private subnet wants to communicate with the data centre, what will happen?

- A. It will allow traffic communication on both the CIDRs of the data centre
- B. It will not allow traffic with data centre on CIDR 20.1.0.0/24 but allows traffic communication on 20.0.54.0/24
- C. It will not allow traffic communication on any of the data centre CIDRs
- D. It will allow traffic with data centre on CIDR 20.1.0.0/24 but does not allow on 20.0.54.0/24

Answer: D

Explanation:

VPC allows the user to set up a connection between his VPC and corporate or home network data centre. If the user has an IP address prefix in the VPC that overlaps with one of the networks' prefixes, any traffic to the network's prefix is dropped. In this case CIDR 20.0.54.0/24 falls in the VPC's CIDR range of 20.0.0.0/16. Thus, it will not allow traffic on that IP. In the case of 20.1.0.0/24, it does not fall in the VPC's CIDR range. Thus, traffic will be allowed on it.

NEW QUESTION 229

- (Topic 3)

A system admin is planning to encrypt all objects being uploaded to S3 from an application. The system admin does not want to implement his own encryption algorithm; instead he is planning to use server side encryption by supplying his own key (SSE-C.. Which parameter is not required while making a call for SSE-C?

- A. x-amz-server-side-encryption-customer-key-AES-256
- B. x-amz-server-side-encryption-customer-key
- C. x-amz-server-side-encryption-customer-algorithm
- D. x-amz-server-side-encryption-customer-key-MD5

Answer: A

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C.. When the user is supplying his own encryption key, the user has to send the below mentioned parameters as a part of the API calls: x-amz-server-side-encryption-customer-algorithm: Specifies the encryption algorithm x-amz-server-side-encryption-customer-key: To provide the base64-encoded encryption key x-amz-server-side-encryption-customer-key-MD5: To provide the base64-encoded 128-bit MD5 digest of the encryption key

NEW QUESTION 232

- (Topic 3)

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. Which of the below mentioned statements is true with respect to this scenario?

- A. The instance will always have a public DNS attached to the instance by default
- B. The user can directly attach an elastic IP to the instance
- C. The instance will never launch if the public IP is not assigned
- D. The user would need to create an internet gateway and then attach an elastic IP to the instance to connect from internet

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. The user cannot connect to the instance from the internet. If the user wants an elastic IP to connect to the instance from the internet he should create an internet gateway and assign an elastic IP to instance.

NEW QUESTION 234

- (Topic 3)

A user has created an Auto Scaling group with default configurations from CLI. The user wants to setup the CloudWatch alarm on the EC2 instances, which are launched by the Auto Scaling group. The user has setup an alarm to monitor the CPU utilization every minute. Which of the below mentioned statements is true?

- A. It will fetch the data at every minute but the four data points [corresponding to 4 minutes] will not have value since the EC2 basic monitoring metrics are collected every five minutes
- B. It will fetch the data at every minute as detailed monitoring on EC2 will be enabled by the default launch configuration of Auto Scaling
- C. The alarm creation will fail since the user has not enabled detailed monitoring on the EC2 instances
- D. The user has to first enable detailed monitoring on the EC2 instances to support alarm monitoring at every minute

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config using CLI, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, by default detailed monitoring will be enabled for Auto Scaling as well as for all the instances launched by that Auto Scaling group.

NEW QUESTION 238

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

Answer: AB

NEW QUESTION 239

- (Topic 3)

An organization has created one IAM user and applied the below mentioned policy to the user. What entitlements do the IAM users avail with this policy?

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow"
      "Action": [
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics",
        "cloudwatch:Describe*"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "autoscaling:Describe*",
      "Resource": "*"
    }
  ]
}
```

- A. The policy will allow the user to perform all read only activities on the EC2 services
- B. The policy will allow the user to list all the EC2 resources except EBS
- C. The policy will allow the user to perform all read and write activities on the EC2 services
- D. The policy will allow the user to perform all read only activities on the EC2 services except load Balancing

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If an organization wants to setup read only access to EC2 for a particular user, they should mention the action in the IAM policy which entitles the user for Describe rights for EC2, CloudWatch, Auto Scaling and ELB. In the policy shown below, the user will have read only access for EC2 and EBS, CloudWatch and Auto Scaling. Since ELB is not mentioned as a part of the list, the user will not have access to ELB.

```
{
  "Version": "2012-10-17",
```

```
"Statement": [
{
  "Effect": "Allow",
  "Action": "ec2:Describe*",
  "Resource": "*"
},
{
  "Effect": "Allow",
  "Action": [
    "cloudwatch:ListMetrics",
    "cloudwatch:GetMetricStatistics",
    "cloudwatch:Describe*"
  ],
  "Resource": "*"
},
{
  "Effect": "Allow",
  "Action": "autoscaling:Describe*",
  "Resource": "*"
}
]
```

NEW QUESTION 244

- (Topic 3)

An organization has configured two single availability zones. The Auto Scaling groups are configured in separate zones. The user wants to merge the groups such that one group spans across multiple zones. How can the user configure this?

- A. Run the command `as-join-auto-scaling-group` to join the two groups
- B. Run the command `as-update-auto-scaling-group` to configure one group to span across zones and delete the other group
- C. Run the command `as-copy-auto-scaling-group` to join the two groups
- D. Run the command `as-merge-auto-scaling-group` to merge the groups

Answer: B

Explanation:

If the user has configured two separate single availability zone Auto Scaling groups and wants to merge them then he should update one of the groups and delete the other one. While updating the first group it is recommended that the user should increase the size of the minimum, maximum and desired capacity as a summation of both the groups.

NEW QUESTION 247

- (Topic 3)

Your mission is to create a lights-out datacenter environment, and you plan to use AWS OpsWorks to accomplish this. First you created a stack and added an App Server layer with an instance running in it. Next you added an application to the instance, and now you need to deploy a MySQL RDS database instance. Which of the following answers accurately describe how to add a backend database server to an OpsWorks stack? Choose 3 answers

- A. Add a new database layer and then add recipes to the deploy actions of the database and App Server layer
- B. Use OpsWorks' "Clone Stack" feature to create a second RDS stack in another Availability Zone for redundancy in the event of a failure in the Primary A
- C. To switch to the secondary RDS instance, set the `[:database]` attributes to values that are appropriate for your server which you can do by using custom JSON
- D. The variables that characterize the RDS database connection—host, user, and so on—are set using the corresponding values from the deploy JSON's `[:deploy][:app_name][:database]` attribute
- E. Cookbook attributes are stored in a repository, so OpsWorks requires that the `"password": "your_password"` attribute for the RDS instance must be encrypted using at least a 256-bit key
- F. Set up the connection between the app server and the RDS layer by using a custom recipe
- G. The recipe configures the app server as required, typically by creating a configuration file
- H. The recipe gets the connection data such as the host and database name from a set of attributes in the stack configuration and deployment JSON that AWS OpsWorks installs on every instance

Answer: BCE

NEW QUESTION 249

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

- Perform maintenance on standby
- Promote standby to primary
- Perform maintenance on original primary
- Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original

primary, which becomes the new standby.

NEW QUESTION 250

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket
- B. Create a NACL and attach it to the VPC of the bucket
- C. Create an ACL and apply it to all objects in the bucket
- D. Modify the IAM policies of any users that would access the bucket

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 251

- (Topic 3)

A user has setup a CloudWatch alarm on the EC2 instance for CPU utilization. The user has setup to receive a notification on email when the CPU utilization is higher than 60%. The user is running a virus scan on the same instance at a particular time. The user wants to avoid receiving an email at this time. What should the user do?

- A. Remove the alarm
- B. Disable the alarm for a while using CLI
- C. Modify the CPU utilization by removing the email alert
- D. Disable the alarm for a while using the console

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. When the user has setup an alarm and it is known that for some unavoidable event the status may change to Alarm, the user can disable the alarm using the DisableAlarmActions API or from the command line `mon-disable-alarm-actions`.

NEW QUESTION 256

- (Topic 3)

A user has enabled detailed CloudWatch monitoring with the AWS Simple Notification Service. Which of the below mentioned statements helps the user understand detailed monitoring better?

- A. SNS will send data every minute after configuration
- B. There is no need to enable since SNS provides data every minute
- C. AWS CloudWatch does not support monitoring for SNS
- D. SNS cannot provide data every minute

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. The AWS SNS service sends data every 5 minutes. Thus, it supports only the basic monitoring. The user cannot enable detailed monitoring with SNS.

NEW QUESTION 257

- (Topic 3)

A user has created a VPC with the public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The public subnet uses CIDR 20.0.1.0/24. The user is planning to host a web server in the public subnet (port 80) and a DB server in the private subnet (port 3306). The user is configuring a security group for the public subnet (WebSecGrp.) and the private subnet (DBSecGrp.). Which of the below mentioned entries is required in the private subnet database security group (DBSecGrp.)?

- A. Allow Inbound on port 3306 for Source Web Server Security Group (WebSecGrp.)
- B. Allow Inbound on port 3306 from source 20.0.0.0/16
- C. Allow Outbound on port 3306 for Destination Web Server Security Group (WebSecGrp.)
- D. Allow Outbound on port 80 for Destination NAT Instance IP

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet to host the web server and DB server respectively, the user should configure that the instances in the private subnet can receive inbound traffic from the public subnet on the DB port. Thus, configure port 3306 in Inbound with the source as the Web Server Security Group (WebSecGrp.). The user should configure ports 80 and 443 for Destination 0.0.0.0/0 as the route table directs traffic to the NAT instance from the private subnet.

NEW QUESTION 261

- (Topic 3)

An organization has configured Auto Scaling with ELB. One of the instance health check returns the status as Impaired to Auto Scaling. What will Auto Scaling do

in this scenario?

- A. Perform a health check until cool down before declaring that the instance has failed
- B. Terminate the instance and launch a new instance
- C. Notify the user using SNS for the failed state
- D. Notify ELB to stop sending traffic to the impaired instance

Answer: B

Explanation:

The Auto Scaling group determines the health state of each instance periodically by checking the results of the Amazon EC2 instance status checks. If the instance status description shows any other state other than “running” or the system status description shows impaired, Auto Scaling considers the instance to be unhealthy. Thus, it terminates the instance and launches a replacement.

NEW QUESTION 265

- (Topic 3)

You have a proprietary data store on-premises that must be backed up daily by dumping the data store contents to a single compressed 50GB file and sending the file to AWS. Your SLAs state that any dump file backed up within the past 7 days can be retrieved within 2 hours. Your compliance department has stated that all data must be held indefinitely. The time required to restore the data store from a backup is approximately 1 hour. Your on-premise network connection is capable of sustaining 1gbps to AWS.

Which backup methods to AWS would be most cost-effective while still meeting all of your requirements?

- A. Send the daily backup files to Glacier immediately after being generated
- B. Transfer the daily backup files to an EBS volume in AWS and take daily snapshots of the volume
- C. Transfer the daily backup files to S3 and use appropriate bucket lifecycle policies to send to Glacier
- D. Host the backup files on a Storage Gateway with Gateway-Cached Volumes and take daily snapshots

Answer: D

Explanation:

Reference:

<http://aws.amazon.com/storagegateway/faqs/>

NEW QUESTION 268

- (Topic 3)

Which services allow the customer to retain run administrative privileges or the underlying EC2 instances? Choose 2 answers

- A. AWS Elastic Beanstalk
- B. Amazon Elastic Map Reduce
- C. Elastic Load Balancing
- D. Amazon Relational Database Service
- E. Amazon Elasti Cache

Answer: AB

NEW QUESTION 270

- (Topic 3)

How can an EBS volume that is currently attached to an EC2 instance be migrated from one Availability Zone to another?

- A. Simply create a new volume in the other AZ and specify the original volume as the source
- B. Detach the volume, then use the `ec2-migrate-volume` command to move it to another AZ
- C. Create a snapshot of the volume, and create a new volume from the snapshot in the other AZ
- D. Detach the volume and attach it to another EC2 instance in the other AZ

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumes.html>

NEW QUESTION 275

- (Topic 3)

A root account owner has given full access of his S3 bucket to one of the IAM users using the bucket ACL. When the IAM user logs in to the S3 console, which actions can he perform?

- A. He can just view the content of the bucket
- B. He can do all the operations on the bucket
- C. It is not possible to give access to an IAM user using ACL
- D. The IAM user can perform all operations on the bucket using only API/SDK

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users (IAM users) in his account.

NEW QUESTION 277

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms. process for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 278

- (Topic 3)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
{
"Version": "2012-10-17",
"Statement": [{
"Sid": "AllowUsersAllActionsForCredentials",
"Effect": "Allow",
"Action": [
"iam:*LoginProfile",
"iam:*AccessKey*",
"iam:*SigningCertificate*"
],
"Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
}
```

- A. The policy allows the IAM user to modify all IAM user's credentials using the console, SDK, CLI or APIs
- B. The policy will give an invalid resource error
- C. The policy allows the IAM user to modify all credentials using only the console
- D. The policy allows the user to modify all IAM user's password, sign in certificates and access keys using only CLI, SDK or APIs

Answer: D

Explanation:

WS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage credentials (access keys, password, and sing in certificates. of all IAM users, they should set an applicable policy to that user or group of users. The below mentioned policy allows the IAM user to modify the credentials of all IAM user's using only CLI, SDK or APIs. The user cannot use the AWS console for this activity since he does not have list permission for the IAM users.

```
{
"Version": "2012-10-17",
"Statement": [{
"Sid": "AllowUsersAllActionsForCredentials",
"Effect": "Allow"
"Action": [
"iam:*LoginProfile",
"iam:*AccessKey*",
"iam:*SigningCertificate*"
],
"Resource": ["arn:aws:iam::123412341234:user/${aws:username}"]
}]
}
```

Amazon AWS-SysOps : Practice Test

NEW QUESTION 282

- (Topic 3)

An organization has applied the below mentioned policy on an IAM group which has selected the IAM users. What entitlements do the IAM users avail with this policy?

```
{
"Version": "2012-10-17",
"Statement": [
{
"Effect": "Allow",
"Action": "**",
"Resource": "*"
}
]
}
```

- A. The policy is not created correctl
- B. It will throw an error for wrong resource name
- C. The policy is for the grou

- D. Thus, the IAM user cannot have any entitlement to this
- E. It allows full access to all AWS services for the IAM users who are a part of this group
- F. If this policy is applied to the EC2 resource, the users of the group will have full access to the EC2 Resources

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The IAM group allows the organization to specify permissions for a collection of users. With the below mentioned policy, it will allow the group full access (Admin. to all AWS services.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "*",
      "Resource": "*"
    }
  ]
}
```

NEW QUESTION 286

- (Topic 3)

A user is observing the EC2 CPU utilization metric on CloudWatch. The user has observed some interesting patterns while filtering over the 1 week period for a particular hour. The user wants to zoom that data point to a more granular period. How can the user do that easily with CloudWatch?

- A. The user can zoom a particular period by selecting that period with the mouse and then releasing the mouse
- B. The user can zoom a particular period by double clicking on that period with the mouse
- C. The user can zoom a particular period by specifying the aggregation data for that period
- D. The user can zoom a particular period by specifying the period in the Time Range

Answer: A

NEW QUESTION 287

- (Topic 3)

A user is trying to setup a security policy for ELB. The user wants ELB to meet the cipher supported by the client by configuring the server order preference in ELB security policy. Which of the below mentioned preconfigured policies supports this feature?

- A. ELBSecurity Policy-2014-01
- B. ELBSecurity Policy-2011-08
- C. ELBDefault Negotiation Policy
- D. ELBSample- OpenSSLDefault Cipher Policy

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL. negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the load balancer is configured to support the Server Order Preference, then the load balancer gets to select the first cipher in its list that matches any one of the ciphers in the client's list. When the user verifies the preconfigured policies supported by ELB, the policy "ELBSecurity Policy-2014-01" supports server order preference.

NEW QUESTION 288

- (Topic 3)

A user is using Cloudformation to launch an EC2 instance and then configure an application after the instance is launched. The user wants the stack creation of ELB and AutoScaling to wait until the EC2 instance is launched and configured properly. How can the user configure this?

- A. It is not possible that the stack creation will wait until one service is created and launched
- B. The user can use the HoldCondition resource to wait for the creation of the other dependent resources
- C. The user can use the DependentCondition resource to hold the creation of the other dependent resources
- D. The user can use the WaitCondition resource to hold the creation of the other dependent resources

Answer: D

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation provides a WaitCondition resource which acts as a barrier and blocks the creation of other resources until a completion signal is received from an external source, such as a user application or management system.

NEW QUESTION 291

- (Topic 3)

An organization has configured Auto Scaling for hosting their application. The system admin wants to understand the Auto Scaling health check process. If the instance is unhealthy, Auto Scaling launches an instance and terminates the unhealthy instance. What is the order execution?

- A. Auto Scaling launches a new instance first and then terminates the unhealthy instance

- B. Auto Scaling performs the launch and terminate processes in a random order
- C. Auto Scaling launches and terminates the instances simultaneously
- D. Auto Scaling terminates the instance first and then launches a new instance

Answer: D

Explanation:

Auto Scaling keeps checking the health of the instances at regular intervals and marks the instance for replacement when it is unhealthy. The ReplaceUnhealthy process terminates instances which are marked as unhealthy and subsequently creates new instances to replace them. This process first terminates the instance and then launches a new instance.

NEW QUESTION 296

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

NEW QUESTION 297

- (Topic 3)

A user has configured Auto Scaling with the minimum capacity as 2 and the desired capacity as 2. The user is trying to terminate one of the existing instance with the command:

```
as-terminate-instance-in-auto-scaling-group<Instance ID> --decrement-desired-capacity
```

What will Auto Scaling do in this scenario?

- A. Terminates the instance and does not launch a new instance
- B. Terminates the instance and updates the desired capacity to 1
- C. Terminates the instance and updates the desired capacity and minimum size to 1
- D. Throws an error

Answer: D

Explanation:

The Auto Scaling command `as-terminate-instance-in-auto-scaling-group <Instance ID>` will terminate the specific instance ID. The user is required to specify the parameter `--decrement-desired-capacity`. Then Auto Scaling will terminate the instance and decrease the desired capacity by 1. In this case since the minimum size is 2, Auto Scaling will not allow the desired capacity to go below 2. Thus, it will throw an error.

NEW QUESTION 300

- (Topic 3)

An application you maintain consists of multiple EC2 instances in a default tenancy VPC. This application has undergone an internal audit and has been determined to require dedicated hardware for one instance. Your compliance team has given you a week to move this instance to single-tenant hardware. Which process will have minimal impact on your application while complying with this requirement?

- A. Create a new VPC with `tenancy=dedicated` and migrate to the new VPC
- B. Use `ec2-reboot-instances` command line and set the parameter `"dedicated=true"`
- C. Right click on the instance, select properties and check the box for dedicated tenancy
- D. Stop the instance, create an AMI, launch a new instance with `tenancy=dedicated`, and terminate the old instance

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/CommandLineReference/ApiReference-cmd-CreateVpc.html>

NEW QUESTION 301

- (Topic 3)

When you put objects in Amazon S3, what is the indication that an object was successfully stored?

- A. Each S3 account has a special bucket named `_s3_log`
- B. Success codes are written to this bucket with a timestamp and checksum
- C. A success code is inserted into the S3 object metadata
- D. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successful
- E. Amazon S3 is engineered for 99.99999999% durability
- F. Therefore there is no need to confirm that data was inserted

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/API/RESTObjectPUT.html>**NEW QUESTION 303**

- (Topic 3)

A user has created a VPC with the public subnet. The user has created a security group for that VPC. Which of the below mentioned statements is true when a security group is created?

- A. It can connect to the AWS services, such as S3 and RDS by default
- B. It will have all the inbound traffic by default
- C. It will have all the outbound traffic by default
- D. It will by default allow traffic to the internet gateway

Answer: C**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level while ACLs work at the subnet level. When a user creates a security group with AWS VPC, by default it will allow all the outbound traffic but block all inbound traffic.

NEW QUESTION 307

- (Topic 3)

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at rest. If the user is supplying his own keys for encryption (SSE-C), what is recommended to the user for the purpose of security?

- A. The user should not use his own security key as it is not secure
- B. Configure S3 to rotate the user's encryption key at regular intervals
- C. Configure S3 to store the user's keys securely with SSL
- D. Keep rotating the encryption key manually at the client side

Answer: D**Explanation:**

AWS S3 supports client side or server side encryption to encrypt all data at Rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C). Since S3 does not store the encryption keys in SSE-C, it is recommended that the user should manage keys securely and keep rotating them regularly at the client side version.

NEW QUESTION 311

- (Topic 3)

You have private video content in S3 that you want to serve to subscribed users on the Internet. User IDs, credentials, and subscriptions are stored in an Amazon RDS database.

Which configuration will allow you to securely serve private content to your users?

- A. Generate pre-signed URLs for each user as they request access to protected S3 content
- B. Create an IAM user for each subscribed user and assign the GetObject permission to each IAM user
- C. Create an S3 bucket policy that limits access to your private content to only your subscribed users' credentials
- D. Create a CloudFront Origin Identity user for your subscribed users and assign the GetObject permission to this user

Answer: C**Explanation:**

Reference:

<https://java.awsblog.com/post/Tx1VE22EWFR4H86/Accessing-Private-Content-in-Amazon-CloudFront>**NEW QUESTION 312**

- (Topic 3)

A user has launched an RDS PostgreSQL DB with AWS. The user did not specify the maintenance window during creation. The user has configured RDS to update the DB instance type from micro to large. If the user wants to have it during the maintenance window, what will AWS do?

- A. AWS will not allow to update the DB until the maintenance window is configured
- B. AWS will select the default maintenance window if the user has not provided it
- C. AWS will ask the user to specify the maintenance window during the update
- D. It is not possible to change the DB size from micro to large with RDS

Answer: B**Explanation:**

AWS RDS has a compulsory maintenance window which by default is 30 minutes. If the user does not specify the maintenance window during the creation of RDS then AWS will select a 30-minute maintenance window randomly from an 8-hour block of time per region. In this case, Amazon RDS assigns a 30-minute maintenance window on a randomly selected day of the week.

NEW QUESTION 317

- (Topic 3)

A user has a weighing plant. The user measures the weight of some goods every 5 minutes and sends data to AWS CloudWatch for monitoring and tracking. Which of the below mentioned parameters is mandatory for the user to include in the request list?

- A. Value
- B. Namespace
- C. Metric Name
- D. Timezone

Answer: B

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set. The user has to always include the namespace as part of the request. The user can supply a file instead of the metric name. If the user does not supply the timezone, it accepts the current time. If the user is sending the data as a single data point it will have parameters, such as value. However, if the user is sending as an aggregate it will have parameters, such as statistic-values.

NEW QUESTION 322

- (Topic 3)

A user is trying to create an EBS volume with the highest PIOPS supported by EBS. What is the minimum size of EBS required to have the maximum IOPS?

- A. 124
- B. 150
- C. 134
- D. 128

Answer: C

Explanation:

A provisioned IOPS EBS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30.

NEW QUESTION 327

- (Topic 3)

An organization has created 10 IAM users. The organization wants each of the IAM users to have access to a separate DyanmoDB table. All the users are added to the same group and the organization wants to setup a group level policy for this. How can the organization achieve this?

- A. Define the group policy and add a condition which allows the access based on the IAM name
- B. Create a DynamoDB table with the same name as the IAM user name and define the policy rule which grants access based on the DynamoDB ARN using a variable
- C. Create a separate DynamoDB database for each user and configure a policy in the group based on the DB variable
- D. It is not possible to have a group level policy which allows different IAM users to different DynamoDB Tables

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. AWS DynamoDB has only tables and the organization cannot makeseparate databases. The organization should create a table with the same name as the IAM user name and use the ARN of DynamoDB as part of the group policy. The sample policy is shown below:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": ["dynamodb:*"],
    "Resource": "arn:aws:dynamodb:region:account-number-without-hyphens:table/${aws:username}"
  }]
}
```

NEW QUESTION 330

- (Topic 3)

A user has created a mobile application which makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK and root account access/secret access key to connect to DynamoDB from mobile. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create a separate IAM user for each mobile application and provide DynamoDB access with it
- B. The user should create an IAM role with DynamoDB and EC2 acces
- C. Attach the role with EC2 and route all calls from the mobile through EC2
- D. The application should use an IAM role with web identity federation which validates calls to DynamoDB with identity providers, such as Google, Amazon, and Facebook
- E. Create an IAM Role with DynamoDB access and attach it with the mobile application

Answer: C

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is

recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. If the user is creating an app that runs on a mobile phone and makes requests to AWS, the user should not create an IAM user and distribute the user's access key with the app. Instead, he should use an identity provider, such as Login with Amazon, Facebook, or Google to authenticate the users, and then use that identity to get temporary security credentials.

NEW QUESTION 334

- (Topic 3)

A user has moved an object to Glacier using the life cycle rules. The user requests to restore the archive after 6 months. When the restore request is completed the user accesses that archive. Which of the below mentioned statements is not true in this condition?

- A. The archive will be available as an object for the duration specified by the user during the restoration request
- B. The restored object's storage class will be RRS
- C. The user can modify the restoration period only by issuing a new restore request with the updated period
- D. The user needs to pay storage for both RRS (restore
- E. and Glacier (Archiv
- F. Rates

Answer: B

Explanation:

AWS Glacier is an archival service offered by AWS. AWS S3 provides lifecycle rules to archive and restore objects from S3 to Glacier. Once the object is archived their storage class will change to Glacier. If the user sends a request for restore, the storage class will still be Glacier for the restored object. The user will be paying for both the archived copy as well as for the restored object. The object is available only for the duration specified in the restore request and if the user wants to modify that period, he has to raise another restore request with the updated duration.

NEW QUESTION 337

- (Topic 3)

A user has created a Cloudformation stack. The stack creates AWS services, such as EC2 instances, ELB, AutoScaling, and RDS. While creating the stack it created EC2, ELB and AutoScaling but failed to create RDS. What will Cloudformation do in this scenario?

- A. Cloudformation can never throw an error after launching a few services since it verifies all the steps before launching
- B. It will warn the user about the error and ask the user to manually create RDS
- C. Rollback all the changes and terminate all the created services
- D. It will wait for the user's input about the error and correct the mistake after the input

Answer: C

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The AWS Cloudformation stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. If any of the services fails Amazon AWS-SysOps : Practice Test
to launch, Cloudformation will rollback all the changes and terminate or delete all the created services.

NEW QUESTION 342

- (Topic 3)

A user has configured an HTTPS listener on an ELB. The user has not configured any security policy which can help to negotiate SSL between the client and ELB. What will ELB do in this scenario?

- A. By default ELB will select the first version of the security policy
- B. By default ELB will select the latest version of the policy
- C. ELB creation will fail without a security policy
- D. It is not required to have a security policy since SSL is already installed

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the user has created an HTTPS/SSL listener without associating any security policy, Elastic Load Balancing will, by default, associate the latest version of the ELBSecurityPolicy-YYYY-MM with the load balancer.

NEW QUESTION 344

- (Topic 3)

A user is trying to send custom metrics to CloudWatch using the PutMetricData APIs. Which of the below mentioned points should the user needs to take care while sending the data to CloudWatch?

- A. The size of a request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests
- B. The size of a request is limited to 128KB for HTTP GET requests and 64KB for HTTP POST requests
- C. The size of a request is limited to 40KB for HTTP GET requests and 8KB for HTTP POST requests
- D. The size of a request is limited to 16KB for HTTP GET requests and 80KB for HTTP POST requests

Answer: A

Explanation:

With AWS CloudWatch, the user can publish data points for a metric that share not only the same time stamp, but also the same namespace and dimensions. CloudWatch can accept multiple data points in the same PutMetricData call with the same time stamp. The only thing that the user needs to take care of is that the

size of a PutMetricData request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests.

NEW QUESTION 345

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is not true in this scenario?

- A. The VPC will create a routing instance and attach it with a public subnet
- B. The VPC will create two subnets
- C. The VPC will create one internet gateway and attach it to VPC
- D. The VPC will launch one NAT instance with an elastic IP

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. Wizard will also create two subnets with route tables. It will also create an internet gateway and attach it to the VPC.

NEW QUESTION 350

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your AWS-SysOps Exam with Our Prep Materials Via below:

<https://www.certleader.com/AWS-SysOps-dumps.html>