

SY0-701 Dumps

CompTIA Security+ Exam

<https://www.certleader.com/SY0-701-dumps.html>



NEW QUESTION 1

Which of the following must be considered when designing a high-availability network? (Choose two).

- A. Ease of recovery
- B. Ability to patch
- C. Physical isolation
- D. Responsiveness
- E. Attack surface
- F. Extensible authentication

Answer: AE

Explanation:

A high-availability network is a network that is designed to minimize downtime and ensure continuous operation even in the event of a failure or disruption. A high-availability network must consider the following factors:

? Ease of recovery: This refers to the ability of the network to restore normal functionality quickly and efficiently after a failure or disruption. Ease of recovery can be achieved by implementing backup and restore procedures, redundancy and failover mechanisms, fault tolerance and resilience, and disaster recovery plans.

? Attack surface: This refers to the amount of exposure and vulnerability of the network to potential threats and attacks. Attack surface can be reduced by implementing security controls such as firewalls, encryption, authentication, access control, segmentation, and hardening.

The other options are not directly related to high-availability network design:

? Ability to patch: This refers to the process of updating and fixing software components to address security issues, bugs, or performance improvements. Ability to patch is important for maintaining the security and functionality of the network, but it is not a specific factor for high-availability network design.

? Physical isolation: This refers to the separation of network components or devices from other networks or physical environments. Physical isolation can enhance the security and performance of the network, but it can also reduce the availability and accessibility of the network resources.

? Responsiveness: This refers to the speed and quality of the network's performance and service delivery. Responsiveness can be measured by metrics such as latency, throughput, jitter, and packet loss. Responsiveness is important for ensuring customer satisfaction and user experience, but it is not a specific factor for high-availability network design.

? Extensible authentication: This refers to the ability of the network to support multiple and flexible authentication methods and protocols. Extensible authentication can improve the security and convenience of the network, but it is not a specific factor for high-availability network design.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability – CompTIA Security+ SY0-701 – 3.4, video by Professor Messer.

NEW QUESTION 2

Which of the following would be best suited for constantly changing environments?

- A. RTOS
- B. Containers
- C. Embedded systems
- D. SCADA

Answer: B

Explanation:

Containers are a method of virtualization that allows applications to run in isolated environments with their own dependencies, libraries, and configurations.

Containers are best suited for constantly changing environments because they are lightweight, portable, scalable, and easy to deploy and update. Containers can also support microservices architectures, which enable faster and more frequent delivery of software features. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 10: Mobile Device Security, page 512 1

NEW QUESTION 3

An enterprise is trying to limit outbound DNS traffic originating from its internal network. Outbound DNS requests will only be allowed from one device with the IP address 10.50.10.25. Which of the following firewall ACLs will accomplish this goal?

- A. Access list outbound permit 0.0.0.0/0 0.0.0.0/0 port 53 Access list outbound deny 10.50.10.25/32 0.0.0.0/0 port 53
- B. Access list outbound permit 0.0.0.0/0 10.50.10.25/32 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53
- C. Access list outbound permit 0.0.0.0/0 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 10.50.10.25/32 port 53
- D. Access list outbound permit 10.50.10.25/32 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53

Answer: D

Explanation:

A firewall ACL (access control list) is a set of rules that determines which traffic is allowed or denied by the firewall. The rules are processed in order, from top to bottom, until a match is found. The syntax of a firewall ACL rule is:

Access list <direction> <action> <source address> <destination address> <protocol>
<port>

To limit outbound DNS traffic originating from the internal network, the firewall ACL should allow only the device with the IP address 10.50.10.25 to send DNS requests to any destination on port 53, and deny all other outbound traffic on port 53. The correct firewall ACL is:

Access list outbound permit 10.50.10.25/32 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 0.0.0.0/0 port 53

The first rule permits outbound traffic from the source address 10.50.10.25/32 (a single host) to any destination address (0.0.0.0/0) on port 53 (DNS). The second rule denies all other outbound traffic on port 53.

References: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 4, page 175.

NEW QUESTION 4

A security operations center determines that the malicious activity detected on a server is normal. Which of the following activities describes the act of ignoring detected activity in the future?

- A. Tuning
- B. Aggregating
- C. Quarantining

D. Archiving

Answer: A

Explanation:

Tuning is the activity of adjusting the configuration or parameters of a security tool or system to optimize its performance and reduce false positives or false negatives. Tuning can help to filter out the normal or benign activity that is detected by the security tool or system, and focus on the malicious or anomalous activity that requires further investigation or response. Tuning can also help to improve the efficiency and effectiveness of the security operations center by reducing the workload and alert fatigue of

the analysts. Tuning is different from aggregating, which is the activity of collecting and combining data from multiple sources or sensors to provide a comprehensive view of the security posture. Tuning is also different from quarantining, which is the activity of isolating a potentially infected or compromised device or system from the rest of the network to prevent further damage or spread. Tuning is also different from archiving, which is the activity of storing and preserving historical data or records for future reference or compliance. The act of ignoring detected activity in the future that is deemed normal by the security operations center is an example of tuning, as it involves modifying the settings or rules of the security tool or system to exclude the activity from the detection scope.

Therefore, this is the best answer among the given options. References = Security Alerting and Monitoring Concepts and Tools – CompTIA Security+ SY0-701: 4.3, video at

7:00; CompTIA Security+ SY0-701 Certification Study Guide, page 191.

NEW QUESTION 5

A client asked a security company to provide a document outlining the project, the cost, and the completion time frame. Which of the following documents should the company provide to the client?

- A. MSA
- B. SLA
- C. BPA
- D. SOW

Answer: D

Explanation:

An ISOW is a document that outlines the project, the cost, and the completion time frame for a security company to provide a service to a client. ISOW stands for Information Security Operations Work, and it is a type of contract that specifies the scope, deliverables, milestones, and payment terms of a security project. An ISOW is usually used for one-time or short-term projects that have a clear and defined objective and outcome. For example, an ISOW can be used for a security assessment, a penetration test, a security audit, or a security training.

The other options are not correct because they are not documents that outline the project, the cost, and the completion time frame for a security company to provide a service to a client. A MSA is a master service agreement, which is a type of contract that establishes the general terms and conditions for a long-term or ongoing relationship between a security company and a client. A MSA does not specify the details of each individual project, but rather sets the framework for future projects that will be governed by separate statements of work (SOWs). A SLA is a service level agreement, which is a type of contract that defines the quality and performance standards for a security service provided by a security company to a client. A SLA usually includes the metrics, targets, responsibilities, and penalties for measuring and ensuring the service level. A BPA is a business partnership agreement, which is a type of contract that establishes the roles and expectations for a strategic alliance between two or more security companies that collaborate to provide a joint service to a client. A BPA usually covers the objectives, benefits, risks, and obligations

of the partnership. References = CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 387. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.2: Compliance and Controls, video: Contracts and Agreements (5:12).

NEW QUESTION 6

Which of the following is the most likely to be used to document risks, responsible parties, and thresholds?

- A. Risk tolerance
- B. Risk transfer
- C. Risk register
- D. Risk analysis

Answer: C

Explanation:

A risk register is a document that records and tracks the risks associated with a project, system, or organization. A risk register typically includes information such as the risk description, the risk owner, the risk probability, the risk impact, the risk level, the risk response strategy, and the risk status. A risk register can help identify, assess, prioritize, monitor, and control risks, as well as communicate them to relevant stakeholders. A risk register can also help document the risk tolerance and thresholds of an organization, which are the acceptable levels of risk exposure and the criteria for escalating or mitigating risks. References = CompTIA Security+ Certification Exam Objectives, Domain 5.1: Explain the importance of policies, plans, and procedures related to organizational security. CompTIA Security+ Study Guide (SY0-701), Chapter 5: Governance, Risk, and Compliance, page 211. CompTIA Security+ Certification Guide, Chapter 2: Risk Management, page 33. CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 4.

NEW QUESTION 7

Which of the following practices would be best to prevent an insider from introducing malicious code into a company's development process?

- A. Code scanning for vulnerabilities
- B. Open-source component usage
- C. Quality assurance testing
- D. Peer review and approval

Answer: D

Explanation:

Peer review and approval is a practice that involves having other developers or experts review the code before it is deployed or released. Peer review and approval can help detect and prevent malicious code, errors, bugs, vulnerabilities, and poor quality in the development process. Peer review and approval can also enforce coding standards, best practices, and compliance requirements. Peer review and approval can be done manually or with the help of tools, such as code analysis, code review, and code

signing. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 11: Secure Application Development, page 543 2

NEW QUESTION 8

A hacker gained access to a system via a phishing attempt that was a direct result of a user clicking a suspicious link. The link laterally deployed ransomware, which laid dormant for multiple weeks, across the network. Which of the following would have mitigated the spread?

- A. IPS
- B. IDS
- C. WAF
- D. UAT

Answer: A

Explanation:

IPS stands for intrusion prevention system, which is a network security device that monitors and blocks malicious traffic in real time. IPS is different from IDS, which only detects and alerts on malicious traffic, but does not block it. IPS would have mitigated the spread of ransomware by preventing the hacker from accessing the system via the phishing link, or by stopping the ransomware from communicating with its command and control server or encrypting the files.

NEW QUESTION 9

A company is concerned about weather events causing damage to the server room and downtime. Which of the following should the company consider?

- A. Clustering servers
- B. Geographic dispersion
- C. Load balancers
- D. Off-site backups

Answer: B

Explanation:

Geographic dispersion is a strategy that involves distributing the servers or data centers across different geographic locations. Geographic dispersion can help the company to mitigate the risk of weather events causing damage to the server room and downtime, as well as improve the availability, performance, and resilience of the network. Geographic dispersion can also enhance the disaster recovery and business continuity capabilities of the company, as it can provide backup and failover options in case of a regional outage or disruption¹².

The other options are not the best ways to address the company's concern:

? Clustering servers: This is a technique that involves grouping multiple servers together to act as a single system. Clustering servers can help to improve the performance, scalability, and fault tolerance of the network, but it does not protect the servers from physical damage or downtime caused by weather events, especially if the servers are located in the same room or building³.

? Load balancers: These are devices or software that distribute the network traffic or workload among multiple servers or resources. Load balancers can help to optimize the utilization, efficiency, and reliability of the network, but they do not prevent the servers from being damaged or disrupted by weather events, especially if the servers are located in the same room or building⁴.

? Off-site backups: These are copies of data or files that are stored in a different location than the original source. Off-site backups can help to protect the data from being lost or corrupted by weather events, but they do not prevent the servers from being damaged or disrupted by weather events, nor do they ensure the availability or continuity of the network services.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability – CompTIA Security+ SY0-701 – 3.4, video by Professor Messer³; CompTIA Security+ SY0-701 Certification Study Guide, page 984: CompTIA Security+ SY0-701 Certification Study Guide, page 99. : CompTIA Security+ SY0-701 Certification Study Guide, page 100.

NEW QUESTION 10

A bank insists all of its vendors must prevent data loss on stolen laptops. Which of the following strategies is the bank requiring?

- A. Encryption at rest
- B. Masking
- C. Data classification
- D. Permission restrictions

Answer: A

Explanation:

Encryption at rest is a strategy that protects data stored on a device, such as a laptop, by converting it into an unreadable format that can only be accessed with a decryption key or password. Encryption at rest can prevent data loss on stolen laptops by preventing unauthorized access to the data, even if the device is physically compromised.

Encryption at rest can also help comply with data privacy regulations and standards that require data protection. Masking, data classification, and permission restrictions are other strategies that can help protect data, but they may not be sufficient or applicable for data stored on laptops. Masking is a technique that obscures sensitive data elements, such as credit card numbers, with random characters or symbols, but it is usually used for data in transit or in use, not at rest. Data classification is a process that assigns labels to data based on its sensitivity and business impact, but it does not protect the data itself. Permission restrictions are rules that define who can access, modify, or delete data, but they may not prevent unauthorized access if the laptop is stolen and the security controls are bypassed. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 17-18, 372-373

NEW QUESTION 10

A security consultant needs secure, remote access to a client environment. Which of the following should the security consultant most likely use to gain access?

- A. EAP
- B. DHCP
- C. IPSec
- D. NAT

Answer: C

Explanation:

IPSec is a protocol suite that provides secure communication over IP networks. IPSec can be used to create virtual private networks (VPNs) that encrypt and authenticate the data exchanged between two or more parties. IPSec can also provide data integrity, confidentiality, replay protection, and access control. A

security consultant can use IPSec to gain secure, remote access to a client environment by establishing a VPN tunnel with the client's network. References: CompTIA Security+ Study Guide: Exam SY0- 701, 9th Edition, Chapter 8: Secure Protocols and Services, page 385 1

NEW QUESTION 15

A security analyst reviews domain activity logs and notices the following:

```
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
```

Which of the following is the best explanation for what the security analyst has discovered?

- A. The user jsmith's account has been locked out.
- B. A keylogger is installed on [smith's workstation
- C. An attacker is attempting to brute force ismith's account.
- D. Ransomware has been deployed in the domain.

Answer: C

Explanation:

Brute force is a type of attack that tries to guess the password or other credentials of a user account by using a large number of possible combinations. An attacker can use automated tools or scripts to perform a brute force attack and gain unauthorized access to the account. The domain activity logs show that the user ismith has failed to log in 10 times in a row within a short period of time, which is a strong indicator of a brute force attack. The logs also show that the source IP address of the failed logins is different from the usual IP address of ismith, which suggests that the attacker is using a different device or location to launch the attack. The security analyst should take immediate action to block the attacker's IP address, reset ismith's password, and notify ismith of the incident. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 14. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.1, page 2. Threat Actors and Attributes – SY0-601 CompTIA Security+ : 1.1

NEW QUESTION 16

Which of the following must be considered when designing a high-availability network? (Select two).

- A. Ease of recovery
- B. Ability to patch
- C. Physical isolation
- D. Responsiveness
- E. Attack surface
- F. Extensible authentication

Answer: AE

Explanation:

A high-availability network is a network that is designed to minimize downtime and ensure continuous operation of critical services and applications. To achieve this goal, a high-availability network must consider two important factors: ease of recovery and attack surface. Ease of recovery refers to the ability of a network to quickly restore normal functionality after a failure, disruption, or disaster. A high-availability network should have mechanisms such as redundancy, failover, backup, and restore to ensure that any single point of failure does not cause a complete network outage. A high-availability network should also have procedures and policies for incident response, disaster recovery, and business continuity to minimize the impact of any network issue on the organization's operations and reputation. Attack surface refers to the exposure of a network to potential threats and vulnerabilities. A high-availability network should have measures such as encryption, authentication, authorization, firewall, intrusion detection and prevention, and patch management to protect the network from unauthorized access, data breaches, malware, denial-of-service attacks, and other cyberattacks. A high-availability network should also have processes and tools for risk assessment, threat intelligence, vulnerability scanning, and penetration testing to identify and mitigate any weaknesses or gaps in the network security. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 4: Architecture and Design, pages 164-1651. CompTIA Security+ Certification Kit: Exam SY0- 701, 7th Edition, Chapter 4: Architecture and Design, pages 164-1652.

NEW QUESTION 18

A company decided to reduce the cost of its annual cyber insurance policy by removing the coverage for ransomware attacks.

Which of the following analysis elements did the company most likely use in making this decision?

- A. IMTTR
- B. RTO
- C. ARO
- D. MTBF

Answer: C

Explanation:

ARO (Annualized Rate of Occurrence) is an analysis element that measures the frequency or likelihood of an event happening in a given year. ARO is often used in risk assessment and management, as it helps to estimate the potential loss or impact of an event. A company can use ARO to calculate the annualized loss expectancy (ALE) of an event, which is the product of ARO and the single loss expectancy (SLE). ALE represents the expected cost of an event per year, and can be used to compare with the cost of implementing a security control or purchasing an insurance policy.

The company most likely used ARO in making the decision to remove the coverage for ransomware attacks from its cyber insurance policy. The company may have estimated the ARO of ransomware attacks based on historical data, industry trends, or threat intelligence, and found that the ARO was low or negligible. The company may have also calculated the ALE of ransomware attacks, and found that the ALE was lower than the cost of the insurance policy. Therefore, the company decided to reduce the cost of its annual cyber insurance policy by removing the coverage for ransomware attacks, as it deemed the risk to be acceptable or manageable.

IMTTR (Incident Management Team Training and Readiness), RTO (Recovery Time Objective), and MTBF (Mean Time Between Failures) are not analysis elements that the company most likely used in making the decision to remove the coverage for ransomware attacks from its cyber insurance policy. IMTTR is a process of preparing and training the incident management team to respond effectively to security incidents. IMTTR does not measure the frequency or impact of an event, but rather the capability and readiness of the team. RTO is a metric that defines the maximum acceptable time for restoring a system or service after a disruption. RTO does not measure the frequency or impact of an event, but rather the availability and continuity of the system or service. MTBF is a metric that

measures the average time between failures of a system or component. MTBF does not measure the frequency or impact of an event, but rather the reliability and performance of the system or component.

References = CompTIA Security+ SY0-701 Certification Study Guide, page 97-

98; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 5.2 - Risk Management, 0:00 - 3:00.

NEW QUESTION 22

A company's web filter is configured to scan the URL for strings and deny access when matches are found. Which of the following search strings should an analyst employ to prohibit access to non-encrypted websites?

- A. encryption=off\
- B. http://
- C. www.*.com
- D. :443

Answer: B

Explanation:

A web filter is a device or software that can monitor, block, or allow web traffic based on predefined rules or policies. One of the common methods of web filtering is to scan the URL for strings and deny access when matches are found. For example, a web filter can block access to websites that contain the words "gambling", "porn", or "malware" in their URLs. A URL is a uniform resource locator that identifies the location and protocol of a web resource. A URL typically consists of the following components: protocol://domain:port/path?query#fragment. The protocol specifies the communication method used to access the web resource, such as HTTP, HTTPS, FTP, or SMTP. The domain is the name of the web server that hosts the web resource, such as www.google.com or www.bing.com. The port is an optional number that identifies the specific service or application running on the web server, such as 80 for HTTP or 443 for HTTPS. The path is the specific folder or file name of the web resource, such as /index.html or /images/logo.png. The query is an optional string that contains additional information or parameters for the web resource, such as ?q=security or ?lang=en. The fragment is an optional string that identifies a specific part or section of the web resource, such as #introduction or #summary.

To prohibit access to non-encrypted websites, an analyst should employ a search string that matches the protocol of non-encrypted web traffic, which is HTTP. HTTP stands for hypertext transfer protocol, and it is a standard protocol for transferring data between web servers and web browsers. However, HTTP does not provide any encryption or security for the data, which means that anyone who intercepts the web traffic can read or modify the data. Therefore, non-encrypted websites are vulnerable to eavesdropping, tampering, or spoofing attacks. To access a non-encrypted website, the URL usually starts with http://, followed by the domain name and optionally the port number. For example, http://www.example.com or http://www.example.com:80. By scanning the URL for the string http://, the web filter can identify and block non-encrypted websites.

The other options are not correct because they do not match the protocol of non-encrypted web traffic. Encryption=off is a possible query string that indicates the encryption status of the web resource, but it is not a standard or mandatory parameter. Https:// is the protocol of encrypted web traffic, which uses hypertext transfer protocol secure (HTTPS) to provide encryption and security for the data. Www.*.com is a possible domain name that matches any website that starts with www and ends with .com, but it does not specify the protocol.

:443 is the port number of HTTPS, which is the protocol of encrypted web traffic. References = CompTIA Security+ Study Guide (SY0-701), Chapter 2: Securing Networks, page 69. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 2.1: Network Devices and Technologies, video: Web Filter (5:16).

NEW QUESTION 23

A company purchased cyber insurance to address items listed on the risk register. Which of the following strategies does this represent?

- A. Accept
- B. Transfer
- C. Mitigate
- D. Avoid

Answer: B

Explanation:

Cyber insurance is a type of insurance that covers the financial losses and liabilities that result from cyberattacks, such as data breaches, ransomware, denial-of-service, phishing, or malware. Cyber insurance can help a company recover from the costs of restoring data, repairing systems, paying ransoms, compensating customers, or facing legal actions. Cyber insurance is one of the possible strategies that a company can use to address the items listed on the risk register. A risk register is a document that records the identified risks, their probability, impact, and mitigation strategies for a project or an organization. The four common risk mitigation strategies are:

? Accept: The company acknowledges the risk and decides to accept the consequences without taking any action to reduce or eliminate the risk. This strategy is usually chosen when the risk is low or the cost of mitigation is too high.

? Transfer: The company transfers the risk to a third party, such as an insurance company, a vendor, or a partner. This strategy is usually chosen when the risk is high or the company lacks the resources or expertise to handle the risk.

? Mitigate: The company implements controls or measures to reduce the likelihood or impact of the risk. This strategy is usually chosen when the risk is moderate or the cost of mitigation is reasonable.

? Avoid: The company eliminates the risk by changing the scope, plan, or design of the project or the organization. This strategy is usually chosen when the risk is unacceptable or the cost of mitigation is too high.

By purchasing cyber insurance, the company is transferring the risk to the insurance company, which will cover the financial losses and liabilities in case of a cyberattack. Therefore, the correct answer is B. Transfer. References = CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 377. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.1: Risk Management, video: Risk Mitigation Strategies (5:37).

NEW QUESTION 25

Users at a company are reporting they are unable to access the URL for a new retail website because it is flagged as gambling and is being blocked. Which of the following changes would allow users to access the site?

- A. Creating a firewall rule to allow HTTPS traffic
- B. Configuring the IPS to allow shopping
- C. Tuning the DLP rule that detects credit card data
- D. Updating the categorization in the content filter

Answer: D

Explanation:

A content filter is a device or software that blocks or allows access to web content based on predefined rules or categories. In this case, the new retail website is

mistakenly categorized as gambling by the content filter, which prevents users from accessing it. To resolve this issue, the content filter's categorization needs to be updated to reflect the correct category of the website, such as shopping or retail. This will allow the content filter to allow access to the website instead of blocking it.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 3: Technologies and Tools, page 1221. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 3: Technologies and Tools, page 1222.

NEW QUESTION 29

A healthcare organization wants to provide a web application that allows individuals to digitally report health emergencies. Which of the following is the most important consideration during development?

- A. Scalability
- B. Availability
- C. Cost
- D. Ease of deployment

Answer: B

Explanation:

Availability is the ability of a system or service to be accessible and usable when needed. For a web application that allows individuals to digitally report health emergencies, availability is the most important consideration during development, because any downtime or delay could have serious consequences for the health and safety of the users. The web application should be designed to handle high traffic, prevent denial-of-service attacks, and have backup and recovery plans in case of failures².

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 2, page 41.

NEW QUESTION 34

A systems administrator is working on a solution with the following requirements:

- Provide a secure zone.
- Enforce a company-wide access control policy.
- Reduce the scope of threats.

Which of the following is the systems administrator setting up?

- A. Zero Trust
- B. AAA
- C. Non-repudiation
- D. CIA

Answer: A

Explanation:

Zero Trust is a security model that assumes no trust for any entity inside or outside the network perimeter and requires continuous verification of identity and permissions. Zero Trust can provide a secure zone by isolating and protecting sensitive data and resources from unauthorized access. Zero Trust can also enforce a company-wide access control policy by applying the principle of least privilege and granular segmentation for users, devices, and applications. Zero Trust can reduce the scope of threats by preventing lateral movement and minimizing the attack surface.

References:

? 5: This source explains the concept and benefits of Zero Trust security and how it differs from traditional security models.

? 8: This source provides an overview of Zero Trust identity security and how it can help verify the identity and integrity of users and devices.

NEW QUESTION 36

A company needs to provide administrative access to internal resources while minimizing the traffic allowed through the security boundary. Which of the following methods is most secure?

- A. Implementing a bastion host
- B. Deploying a perimeter network
- C. Installing a WAF
- D. Utilizing single sign-on

Answer: A

Explanation:

A bastion host is a special-purpose server that is designed to withstand attacks and provide secure access to internal resources. A bastion host is usually placed on the edge of a network, acting as a gateway or proxy to the internal network. A bastion host can be configured to allow only certain types of traffic, such as SSH or HTTP, and block all other traffic. A bastion host can also run security software such as firewalls, intrusion detection systems, and antivirus programs to monitor and filter incoming and outgoing traffic. A bastion host can provide administrative access to internal resources by requiring strong authentication and encryption, and by logging all activities for auditing purposes¹².

A bastion host is the most secure method among the given options because it minimizes the traffic allowed through the security boundary and provides a single point of control and defense. A bastion host can also isolate the internal network from direct exposure to the internet or other untrusted networks, reducing the attack surface and the risk of compromise³.

Deploying a perimeter network is not the correct answer, because a perimeter network is a network segment that separates the internal network from the external network. A perimeter network usually hosts public-facing services such as web servers, email servers, or DNS servers that need to be accessible from the internet. A perimeter network does not provide administrative access to internal resources, but rather protects them from unauthorized access. A perimeter network can also increase the complexity and cost of network management and security⁴.

Installing a WAF is not the correct answer, because a WAF is a security tool that protects web applications from common web-based attacks by monitoring, filtering, and blocking HTTP traffic. A WAF can prevent attacks such as cross-site scripting, SQL injection, or file inclusion, among others. A WAF does not provide administrative access to internal resources, but rather protects them from web application vulnerabilities. A WAF is also not a comprehensive solution for network security, as it only operates at the application layer and does not protect against other types of attacks or threats⁵.

Utilizing single sign-on is not the correct answer, because single sign-on is a method of authentication that allows users to access multiple sites, services, or applications with one username and password. Single sign-on can simplify the sign-in process for users and reduce the number of passwords they have to remember and manage. Single sign-on does not provide administrative access to internal resources, but rather enables access to various resources that the user is authorized to use. Single sign-on can also introduce security risks if the user's credentials are compromised or if the single sign-on provider is breached⁶. References = 1: Bastion host - Wikipedia, 2: 14 Best Practices to Secure SSH Bastion Host - goteleport.com, 3: The Importance Of Bastion Hosts In

Network

Security, 4: What is the network perimeter? | Cloudflare, 5: What is a WAF? | Web Application Firewall explained, 6: [What is single sign-on (SSO)? - Definition from WhatIs.com]

NEW QUESTION 41

A company is developing a business continuity strategy and needs to determine how many staff members would be required to sustain the business in the case of a disruption. Which of the following best describes this step?

- A. Capacity planning
- B. Redundancy
- C. Geographic dispersion
- D. Tablet exercise

Answer: A

Explanation:

Capacity planning is the process of determining the resources needed to meet the current and future demands of an organization. Capacity planning can help a company develop a business continuity strategy by estimating how many staff members would be required to sustain the business in the case of a disruption, such as a natural disaster, a cyberattack, or a pandemic. Capacity planning can also help a company optimize the use of its resources, reduce costs, and improve performance. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 4, page 184. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 4.1, page 14. Business Continuity – SY0-601 CompTIA Security+ : 4.1

NEW QUESTION 45

Which of the following has been implemented when a host-based firewall on a legacy Linux system allows connections from only specific internal IP addresses?

- A. Compensating control
- B. Network segmentation
- C. Transfer of risk
- D. SNMP traps

Answer: A

Explanation:

A compensating control is a security measure that is implemented to mitigate the risk of a vulnerability or a weakness that cannot be resolved by the primary control. A compensating control does not prevent or eliminate the vulnerability or weakness, but it can reduce the likelihood or impact of an attack. A host-based firewall on a legacy Linux system that allows connections from only specific internal IP addresses is an example of a compensating control, as it can limit the exposure of the system to potential threats from external or unauthorized sources. A host-based firewall is a software application that monitors and filters the incoming and outgoing network traffic on a single host, based on a set of rules or policies. A legacy Linux system is an older version of the Linux operating system that may not be compatible with the latest security updates or patches, and may have known vulnerabilities or weaknesses that could be exploited by attackers. References = Security Controls – SY0-601 CompTIA Security+ : 5.1, Security Controls – CompTIA Security+ SY0-501 – 5.7, CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 5, page 240. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 5.1, page 18.

NEW QUESTION 50

After a security incident, a systems administrator asks the company to buy a NAC platform. Which of the following attack surfaces is the systems administrator trying to protect?

- A. Bluetooth
- B. Wired
- C. NFC
- D. SCADA

Answer: B

Explanation:

A NAC (network access control) platform is a technology that enforces security policies on devices that attempt to access a network. A NAC platform can verify the identity, role, and compliance of the devices, and grant or deny access based on predefined rules. A NAC platform can protect both wired and wireless networks, but in this scenario, the systems administrator is trying to protect the wired attack surface, which is the set of vulnerabilities that can be exploited through a physical connection to the network.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5, page 189; CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5, page 237.

NEW QUESTION 53

A Chief Information Security Officer wants to monitor the company's servers for SQLi attacks and allow for comprehensive investigations if an attack occurs. The company uses SSL decryption to allow traffic monitoring. Which of the following strategies would best accomplish this goal?

- A. Logging all NetFlow traffic into a SIEM
- B. Deploying network traffic sensors on the same subnet as the servers
- C. Logging endpoint and OS-specific security logs
- D. Enabling full packet capture for traffic entering and exiting the servers

Answer: D

Explanation:

Full packet capture is a technique that records all network traffic passing through a device, such as a router or firewall. It allows for detailed analysis and investigation of network events, such as SQLi attacks, by providing the complete content and context of the packets. Full packet capture can help identify the source, destination, payload, and timing of an SQLi attack, as well as the impact on the server and database. Logging NetFlow traffic, network traffic sensors, and endpoint and OS-specific security logs can provide some information about network activity, but they do not capture the full content of the packets, which may limit

the scope and depth of the investigation. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 372-373

NEW QUESTION 55

An organization is building a new backup data center with cost-benefit as the primary requirement and RTO and RPO values around two days. Which of the following types of sites is the best for this scenario?

- A. Real-time recovery
- B. Hot
- C. Cold
- D. Warm

Answer: C

Explanation:

A cold site is a type of backup data center that has the necessary infrastructure to support IT operations, but does not have any pre-configured hardware or software. A cold site is the cheapest option among the backup data center types, but it also has the longest recovery time objective (RTO) and recovery point objective (RPO) values. A cold site is suitable for scenarios where the cost-benefit is the primary requirement and the RTO and RPO values are not very stringent. A cold site can take up to two days or more to restore the normal operations after a disaster. References = CompTIA Security+ SY0-701 Certification Study Guide, page 387; Backup Types – SY0-601 CompTIA Security+ : 2.5, video at 4:50.

NEW QUESTION 58

A security analyst is reviewing alerts in the SIEM related to potential malicious network traffic coming from an employee's corporate laptop. The security analyst has determined that additional data about the executable running on the machine is necessary to continue the investigation. Which of the following logs should the analyst use as a data source?

- A. Application
- B. IPS/IDS
- C. Network
- D. Endpoint

Answer: D

Explanation:

An endpoint log is a file that contains information about the activities and events that occur on an end-user device, such as a laptop, desktop, tablet, or smartphone. Endpoint logs can provide valuable data for security analysts, such as the processes running on the device, the network connections established, the files accessed or modified, the user actions performed, and the applications installed or updated. Endpoint logs can also record the details of any executable files running on the device, such as the name, path, size, hash, signature, and permissions of the executable.

An application log is a file that contains information about the events that occur within a software application, such as errors, warnings, transactions, or performance metrics. Application logs can help developers and administrators troubleshoot issues, optimize performance, and monitor user behavior. However, application logs may not provide enough information about the executable files running on the device, especially if they are malicious or unknown.

An IPS/IDS log is a file that contains information about the network traffic that is monitored and analyzed by an intrusion prevention system (IPS) or an intrusion detection system (IDS). IPS/IDS logs can help security analysts identify and block potential attacks, such as exploit attempts, denial-of-service (DoS) attacks, or malicious scans. However, IPS/IDS logs may not provide enough information about the executable files running on the device, especially if they are encrypted, obfuscated, or use legitimate protocols.

A network log is a file that contains information about the network activity and communication that occurs between devices, such as IP addresses, ports, protocols, packets, or bytes. Network logs can help security analysts understand the network topology, traffic patterns, and bandwidth usage. However, network logs may not provide enough information about the executable files running on the device, especially if they are hidden, spoofed, or use proxy servers.

Therefore, the best log type to use as a data source for additional information about the executable running on the machine is the endpoint log, as it can provide the most relevant and detailed data about the executable file and its behavior.

References = <https://www.crowdstrike.com/cybersecurity-101/observability/application-log/>
<https://owasp.org/www-project-proactive-controls/v3/en/c9-security-logging>

NEW QUESTION 59

A client demands at least 99.99% uptime from a service provider's hosted security services. Which of the following documents includes the information the service provider should return to the client?

- A. MOA
- B. SOW
- C. MOU
- D. SLA

Answer: D

Explanation:

A service level agreement (SLA) is a document that defines the level of service expected by a customer from a service provider, indicating the metrics by which that service is measured, and the remedies or penalties, if any, should the agreed-upon levels not be achieved. An SLA can specify the minimum uptime or availability of a service, such as 99.99%, and the consequences for failing to meet that standard. A memorandum of agreement (MOA), a statement of work (SOW), and a memorandum of understanding (MOU) are other types of documents that can be used to establish a relationship between parties, but they do not typically include the details of service levels and performance metrics that an SLA does. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17

NEW QUESTION 62

While troubleshooting a firewall configuration, a technician determines that a "deny any" policy should be added to the bottom of the ACL. The technician updates the policy, but the new policy causes several company servers to become unreachable. Which of the following actions would prevent this issue?

- A. Documenting the new policy in a change request and submitting the request to change management
- B. Testing the policy in a non-production environment before enabling the policy in the production network
- C. Disabling any intrusion prevention signatures on the 'deny any*' policy prior to enabling the new policy

D. Including an 'allow any' policy above the 'deny any' policy

Answer: B

Explanation:

A firewall policy is a set of rules that defines what traffic is allowed or denied on a network. A firewall policy should be carefully designed and tested before being implemented, as a misconfigured policy can cause network disruptions or security breaches. A common best practice is to test the policy in a non-production environment, such as a lab or a simulation, before enabling the policy in the production network. This way, the technician can verify the functionality and performance of the policy, and identify and resolve any issues or conflicts, without affecting the live network. Testing the policy in a non-production environment would prevent the issue of the 'deny any' policy causing several company servers to become unreachable, as the technician would be able to detect and correct the problem before applying the policy to the production network. Documenting the new policy in a change request and submitting the request to change management is a good practice, but it would not prevent the issue by itself. Change management is a process that ensures that any changes to the network are authorized, documented, and communicated, but it does not guarantee that the changes are error-free or functional. The technician still needs to test the policy before implementing it.

Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy would not prevent the issue, and it could reduce the security of the network. Intrusion prevention signatures are patterns that identify malicious or unwanted traffic, and allow the firewall to block or alert on such traffic. Disabling these signatures would make the firewall less effective in detecting and preventing attacks, and it would not affect the reachability of the company servers.

Including an 'allow any' policy above the 'deny any' policy would not prevent the issue, and it would render the 'deny any' policy useless. A firewall policy is processed from top to bottom, and the first matching rule is applied. An 'allow any' policy would match any traffic and allow it to pass through the firewall, regardless of the source, destination, or protocol. This would negate the purpose of the 'deny any' policy, which is to block any traffic that does not match any of the previous rules. Moreover, an 'allow any' policy would create a security risk, as it would allow any unauthorized or malicious traffic to enter or exit the network. References = CompTIA Security+ SY0-701 Certification Study Guide, page 204- 205; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 2.1 - Network Security Devices, 8:00 - 10:00.

NEW QUESTION 63

An organization wants a third-party vendor to do a penetration test that targets a specific device. The organization has provided basic information about the device. Which of the following best describes this kind of penetration test?

- A. Partially known environment
- B. Unknown environment
- C. Integrated
- D. Known environment

Answer: A

Explanation:

A partially known environment is a type of penetration test where the tester has some information about the target, such as the IP address, the operating system, or the device type. This can help the tester focus on specific vulnerabilities and reduce the scope of the test. A partially known environment is also called a gray box test. References: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 10, page 543.

NEW QUESTION 67

Which of the following should a systems administrator use to ensure an easy deployment of resources within the cloud provider?

- A. Software as a service
- B. Infrastructure as code
- C. Internet of Things
- D. Software-defined networking

Answer: B

Explanation:

Infrastructure as code (IaC) is a method of using code and automation to manage and provision cloud resources, such as servers, networks, storage, and applications. IaC allows for easy deployment, scalability, consistency, and repeatability of cloud environments. IaC is also a key component of DevSecOps, which integrates security into the development and operations processes. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 6: Cloud and Virtualization Concepts, page 294.

NEW QUESTION 70

During an investigation, an incident response team attempts to understand the source of an incident. Which of the following incident response activities describes this process?

- A. Analysis
- B. Lessons learned
- C. Detection
- D. Containment

Answer: A

Explanation:

Analysis is the incident response activity that describes the process of understanding the source of an incident. Analysis involves collecting and examining evidence, identifying the root cause, determining the scope and impact, and assessing the threat actor's motives and capabilities. Analysis helps the incident response team to formulate an appropriate response strategy, as well as to prevent or mitigate future incidents. Analysis is usually performed after detection and before containment, eradication, recovery, and lessons learned. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 6, page 223. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.2, page 13.

NEW QUESTION 72

Which of the following automation use cases would best enhance the security posture of an organization by rapidly updating permissions when employees leave a company?

- A. Provisioning resources
- B. Disabling access
- C. Reviewing change approvals
- D. Escalating permission requests

Answer: B

Explanation:

Disabling access is an automation use case that would best enhance the security posture of an organization by rapidly updating permissions when employees leave a company. Disabling access is the process of revoking or suspending the access rights of a user account, such as login credentials, email, VPN, cloud services, etc. Disabling access can prevent unauthorized or malicious use of the account by former employees or attackers who may have compromised the account. Disabling access can also reduce the attack surface and the risk of data breaches or leaks. Disabling access can be automated by using scripts, tools, or workflows that can trigger the action based on predefined events, such as employee termination, resignation, or transfer. Automation can ensure that the access is disabled in a timely, consistent, and efficient manner, without relying on manual intervention or human error.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5: Identity and Access Management, page 2131. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5: Identity and Access Management, page 2132.

NEW QUESTION 75

A security practitioner completes a vulnerability assessment on a company's network and finds several vulnerabilities, which the operations team remediates. Which of the following should be done next?

- A. Conduct an audit.
- B. Initiate a penetration test.
- C. Rescan the network.
- D. Submit a report.

Answer: C

Explanation:

After completing a vulnerability assessment and remediating the identified vulnerabilities, the next step is to rescan the network to verify that the vulnerabilities have been successfully fixed and no new vulnerabilities have been introduced. A vulnerability assessment is a process of identifying and evaluating the weaknesses and exposures in a network, system, or application that could be exploited by attackers. A vulnerability assessment typically involves using automated tools, such as scanners, to scan the network and generate a report of the findings. The report may include information such as the severity, impact, and remediation of the vulnerabilities. The operations team is responsible for applying the appropriate patches, updates, or configurations to address the vulnerabilities and reduce the risk to the network. A rescan is necessary to confirm that the remediation actions have been effective and that the network is secure.

Conducting an audit, initiating a penetration test, or submitting a report are not the next steps after completing a vulnerability assessment and remediating the vulnerabilities. An audit is a process of reviewing and verifying the compliance of the network with the established policies, standards, and regulations. An audit may be performed by internal or external auditors, and it may use the results of the vulnerability assessment as part of the evidence. However, an audit is not a mandatory step after a vulnerability assessment, and it does not validate the effectiveness of the remediation actions.

A penetration test is a process of simulating a real-world attack on the network to test the security defenses and identify any gaps or weaknesses. A penetration test may use the results of the vulnerability assessment as a starting point, but it goes beyond scanning and involves exploiting the vulnerabilities to gain access or cause damage. A penetration test may be performed after a vulnerability assessment, but only with the proper authorization, scope, and rules of engagement. A penetration test is not a substitute for a rescan, as it does not verify that the vulnerabilities have been fixed.

Submitting a report is a step that is done after the vulnerability assessment, but before the remediation. The report is a document that summarizes the findings and recommendations of the vulnerability assessment, and it is used to communicate the results to the stakeholders and the operations team. The report may also include a follow-up plan and a timeline for the remediation actions. However, submitting a report is not the final step after the remediation, as it does not confirm that the network is secure.

References = CompTIA Security+ SY0-701 Certification Study Guide, page 372- 375; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 4.1 - Vulnerability Scanning, 0:00 - 8:00.

NEW QUESTION 77

After an audit, an administrator discovers all users have access to confidential data on a file server. Which of the following should the administrator use to restrict access to the data quickly?

- A. Group Policy
- B. Content filtering
- C. Data loss prevention
- D. Access control lists

Answer: D

Explanation:

Access control lists (ACLs) are rules that specify which users or groups can access which resources on a file server. They can help restrict access to confidential data by granting or denying permissions based on the identity or role of the user. In this case, the administrator can use ACLs to quickly modify the access rights of the users and prevent them from accessing the data they are not authorized to see.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308 1

NEW QUESTION 82

A company's marketing department collects, modifies, and stores sensitive customer data. The infrastructure team is responsible for securing the data while in transit and at rest. Which of the following data roles describes the customer?

- A. Processor
- B. Custodian
- C. Subject
- D. Owner

Answer: C

Explanation:

According to the CompTIA Security+ SY0-701 Certification Study Guide, data subjects are the individuals whose personal data is collected, processed, or stored

by an organization. Data subjects have certain rights and expectations regarding how their data is handled, such as the right to access, correct, delete, or restrict their data. Data subjects are different from data owners, who are the individuals or entities that have the authority and responsibility to determine how data is classified, protected, and used. Data subjects are also different from data processors, who are the individuals or entities that perform operations on data on behalf of the data owner, such as collecting, modifying, storing, or transmitting data. Data subjects are also different from data custodians, who are the individuals or entities that implement the security controls and procedures specified by the data owner to protect data while in transit and at rest.
References: CompTIA Security+ SY0-701 Certification Study Guide, Chapter 2: Data Security, page 511

NEW QUESTION 85

A company is discarding a classified storage array and hires an outside vendor to complete the disposal. Which of the following should the company request from the vendor?

- A. Certification
- B. Inventory list
- C. Classification
- D. Proof of ownership

Answer: A

Explanation:

The company should request a certification from the vendor that confirms the storage array has been disposed of securely and in compliance with the company's policies and standards. A certification provides evidence that the vendor has followed the proper procedures and methods to destroy the classified data and prevent unauthorized access or recovery. A certification may also include details such as the date, time, location, and method of disposal, as well as the names and signatures of the personnel involved. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 3, page 1441

NEW QUESTION 89

During the onboarding process, an employee needs to create a password for an intranet account. The password must include ten characters, numbers, and letters, and two special characters. Once the password is created, the company will grant the employee access to other company-owned websites based on the intranet profile. Which of the following access management concepts is the company most likely using to safeguard intranet accounts and grant access to multiple sites based on a user's intranet account? (Select two).

- A. Federation
- B. Identity proofing
- C. Password complexity
- D. Default password changes
- E. Password manager
- F. Open authentication

Answer: AC

Explanation:

Federation is an access management concept that allows users to authenticate once and access multiple resources or services across different domains or organizations. Federation relies on a trusted third party that stores the user's credentials and provides them to the requested resources or services without exposing them. Password complexity is a security measure that requires users to create passwords that meet certain criteria, such as length, character types, and uniqueness. Password complexity can help prevent brute-force attacks, password guessing, and credential stuffing by making passwords harder to crack or guess. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308-309 and 312-313 1

NEW QUESTION 90

An organization is leveraging a VPN between its headquarters and a branch location. Which of the following is the VPN protecting?

- A. Data in use
- B. Data in transit
- C. Geographic restrictions
- D. Data sovereignty

Answer: B

Explanation:

Data in transit is data that is moving from one location to another, such as over a network or through the air. Data in transit is vulnerable to interception, modification, or theft by malicious actors. A VPN (virtual private network) is a technology that protects data in transit by creating a secure tunnel between two endpoints and encrypting the data that passes through it.
References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 4, page 145.

NEW QUESTION 92

Which of the following roles, according to the shared responsibility model, is responsible for securing the company's database in an IaaS model for a cloud environment?

- A. Client
- B. Third-party vendor
- C. Cloud provider
- D. DBA

Answer: A

Explanation:

According to the shared responsibility model, the client and the cloud provider have different roles and responsibilities for securing the cloud environment, depending on the service model. In an IaaS (Infrastructure as a Service) model, the cloud provider is responsible for securing the physical infrastructure, such as the servers, storage, and network devices, while the client is responsible for securing the operating systems, applications, and data that run on the cloud

infrastructure. Therefore, the client is responsible for securing the company's database in an IaaS model for a cloud environment, as the database is an application that stores data. The client can use various security controls, such as encryption, access control, backup, and auditing, to protect the database from unauthorized access, modification, or loss. The third-party vendor and the DBA (Database Administrator) are not roles defined by the shared responsibility model, but they may be involved in the implementation or management of the database security. References = CompTIA Security+ SY0-701 Certification Study Guide, page 263- 264; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 3.1 - Cloud and Virtualization, 5:00 - 7:40.

NEW QUESTION 94

An administrator discovers that some files on a database server were recently encrypted. The administrator sees from the security logs that the data was last accessed by a domain user. Which of the following best describes the type of attack that occurred?

- A. Insider threat
- B. Social engineering
- C. Watering-hole
- D. Unauthorized attacker

Answer: A

Explanation:

An insider threat is a type of attack that originates from someone who has legitimate access to an organization's network, systems, or data. In this case, the domain user who encrypted the files on the database server is an example of an insider threat, as they abused their access privileges to cause harm to the organization. Insider threats can be motivated by various factors, such as financial gain, revenge, espionage, or sabotage. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 1: General Security Concepts, page 251. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 1: General Security Concepts, page 252.

NEW QUESTION 98

Which of the following is the best way to consistently determine on a daily basis whether security settings on servers have been modified?

- A. Automation
- B. Compliance checklist
- C. Attestation
- D. Manual audit

Answer: A

Explanation:

Automation is the best way to consistently determine on a daily basis whether security settings on servers have been modified. Automation is the process of using software, hardware, or other tools to perform tasks that would otherwise require human intervention or manual effort. Automation can help to improve the efficiency, accuracy, and consistency of security operations, as well as reduce human errors and costs. Automation can be used to monitor, audit, and enforce security settings on servers, such as firewall rules, encryption keys, access controls, patch levels, and configuration files. Automation can also alert security personnel of any changes or anomalies that may indicate a security breach or compromise¹².

The other options are not the best ways to consistently determine on a daily basis whether security settings on servers have been modified:

? Compliance checklist: This is a document that lists the security requirements, standards, or best practices that an organization must follow or adhere to. A compliance checklist can help to ensure that the security settings on servers are aligned with the organizational policies and regulations, but it does not automatically detect or report any changes or modifications that may occur on a daily basis³.

? Attestation: This is a process of verifying or confirming the validity or accuracy of a statement, claim, or fact. Attestation can be used to provide assurance or evidence that the security settings on servers are correct and authorized, but it does not continuously monitor or audit any changes or modifications that may occur on a daily basis⁴.

? Manual audit: This is a process of examining or reviewing the security settings on servers by human inspectors or auditors. A manual audit can help to identify and correct any security issues or discrepancies on servers, but it is time-consuming, labor-intensive, and prone to human errors. A manual audit may not be feasible or practical to perform on a daily basis.

References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 1022: Automation and Scripting – CompTIA Security+ SY0-701 – 5.1, video by Professor Messer³: CompTIA Security+ SY0-701 Certification Study Guide, page 974: CompTIA Security+ SY0-701 Certification Study Guide, page 98. : CompTIA Security+ SY0-701 Certification Study Guide, page 99.

NEW QUESTION 102

A company hired a consultant to perform an offensive security assessment covering penetration testing and social engineering.

Which of the following teams will conduct this assessment activity?

- A. White
- B. Purple
- C. Blue
- D. Red

Answer: D

Explanation:

A red team is a group of security professionals who perform offensive security assessments covering penetration testing and social engineering. A red team simulates real-world attacks and exploits the vulnerabilities of a target organization, system, or network. A red team aims to test the effectiveness of the security controls, policies, and procedures of the target, as well as the awareness and response of the staff and the blue team. A red team can be hired as an external consultant or formed internally within the organization. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 18. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.8, page 4. Security Teams – SY0-601 CompTIA Security+ : 1.8

NEW QUESTION 107

A company's end users are reporting that they are unable to reach external websites. After reviewing the performance data for the DNS servers, the analyst discovers that the CPU, disk, and memory usage are minimal, but the network interface is flooded with inbound traffic. Network logs show only a small number of DNS queries sent to this server. Which of the following best describes what the security analyst is seeing?

- A. Concurrent session usage

- B. Secure DNS cryptographic downgrade
- C. On-path resource consumption
- D. Reflected denial of service

Answer: D

Explanation:

A reflected denial of service (RDoS) attack is a type of DDoS attack that uses spoofed source IP addresses to send requests to a third-party server, which then sends responses to the victim server. The attacker exploits the difference in size between the request and the response, which can amplify the amount of traffic sent to the victim server. The attacker also hides their identity by using the victim's IP address as the source. A RDoS attack can target DNS servers by sending forged DNS queries that generate large DNS responses. This can flood the network interface of the DNS server and prevent it from serving legitimate requests from end users. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 215-216 1

NEW QUESTION 111

Which of the following threat actors is the most likely to use large financial resources to attack critical systems located in other countries?

- A. Insider
- B. Unskilled attacker
- C. Nation-state
- D. Hacktivist

Answer: C

Explanation:

A nation-state is a threat actor that is sponsored by a government or a political entity to conduct cyberattacks against other countries or organizations. Nation-states have large financial resources, advanced technical skills, and strategic objectives that may target critical systems such as military, energy, or infrastructure. Nation-states are often motivated by espionage, sabotage, or warfare¹². References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 542: Threat Actors – CompTIA Security+ SY0-701 – 2.1, video by Professor Messer.

NEW QUESTION 112

An organization would like to store customer data on a separate part of the network that is not accessible to users on the main corporate network. Which of the following should the administrator use to accomplish this goal?

- A. Segmentation
- B. Isolation
- C. Patching
- D. Encryption

Answer: A

Explanation:

Segmentation is a network design technique that divides the network into smaller and isolated segments based on logical or physical boundaries. Segmentation can help improve network security by limiting the scope of an attack, reducing the attack surface, and enforcing access control policies. Segmentation can also enhance network performance, scalability, and manageability. To accomplish the goal of storing customer data on a separate part of the network, the administrator can use segmentation technologies such as subnetting, VLANs, firewalls, routers, or switches. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 308-309 1

NEW QUESTION 115

After reviewing the following vulnerability scanning report:

Server:192.168.14.6

Service: Telnet

Port: 23 Protocol: TCP Status: Open Severity: High

Vulnerability: Use of an insecure network protocol

A security analyst performs the following test: `nmap -p 23 192.168.14.6 --script telnet-encryption PORT STATE SERVICE REASON`

`23/tcp open telnet syn-ack | telnet encryption:`

`|_ Telnet server supports encryption`

Which of the following would the security analyst conclude for this reported vulnerability?

- A. It is a false positive.
- B. A rescan is required.
- C. It is considered noise.
- D. Compensating controls exist.

Answer: A

Explanation:

A false positive is a result that indicates a vulnerability or a problem when there is none. In this case, the vulnerability scanning report shows that the telnet service on port 23 is open and uses an insecure network protocol. However, the security analyst performs a test using nmap and a script that checks for telnet encryption support. The result shows that the telnet server supports encryption, which means that the data transmitted between the client and the server can be protected from eavesdropping. Therefore, the reported vulnerability is a false positive and does not reflect the actual security posture of the server. The security analyst should verify the encryption settings of the telnet server and client and ensure that they are configured properly³. References: 3: Telnet Protocol - Can You Encrypt Telnet?

NEW QUESTION 119

A user is attempting to patch a critical system, but the patch fails to transfer. Which of the following access controls is most likely inhibiting the transfer?

- A. Attribute-based
- B. Time of day

- C. Role-based
- D. Least privilege

Answer: D

Explanation:

The least privilege principle states that users and processes should only have the minimum level of access required to perform their tasks. This helps to prevent unauthorized or unnecessary actions that could compromise security. In this case, the patch transfer might be failing because the user or process does not have the appropriate permissions to access the critical system or the network resources needed for the transfer. Applying the least privilege principle can help to avoid this issue by granting the user or process the necessary access rights for the patching activity. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 931

NEW QUESTION 124

An analyst is evaluating the implementation of Zero Trust principles within the data plane. Which of the following would be most relevant for the analyst to evaluate?

- A. Secured zones
- B. Subject role
- C. Adaptive identity
- D. Threat scope reduction

Answer: A

Explanation:

Secured zones are a key component of the Zero Trust data plane, which is the layer where data is stored, processed, and transmitted. Secured zones are logical or physical segments of the network that isolate data and resources based on their sensitivity and risk. Secured zones enforce granular policies and controls to prevent unauthorized access and lateral movement within the network.

References: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5, page 255.

NEW QUESTION 125

A systems administrator set up a perimeter firewall but continues to notice suspicious connections between internal endpoints. Which of the following should be set up in order to mitigate the threat posed by the suspicious activity?

- A. Host-based firewall
- B. Web application firewall
- C. Access control list
- D. Application allow list

Answer: A

Explanation:

A host-based firewall is a software application that runs on an individual endpoint and filters the incoming and outgoing network traffic based on a set of rules. A host-based firewall can help to mitigate the threat posed by suspicious connections between internal endpoints by blocking or allowing the traffic based on the source, destination, port, protocol, or application. A host-based firewall is different from a web application firewall, which is a type of firewall that protects web applications from common web-based attacks, such as SQL injection, cross-site scripting, and session hijacking. A host-based firewall is also different from an access control list, which is a list of rules that control the access to network resources, such as files, folders, printers, or routers. A host-based firewall is also different from an application allow list, which is a list of applications that are authorized to run on an endpoint, preventing unauthorized or malicious applications from executing. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 254

NEW QUESTION 126

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your SY0-701 Exam with Our Prep Materials Via below:

<https://www.certleader.com/SY0-701-dumps.html>