

Exam Questions SOA-C02

AWS Certified SysOps Administrator - Associate (SOA-C02)

<https://www.2passeasy.com/dumps/SOA-C02/>



NEW QUESTION 1

- (Exam Topic 1)

A SysOps administrator receives an alert from Amazon GuardDuty about suspicious network activity on an Amazon EC2 instance. The GuardDuty finding lists a new external IP address as a traffic destination. The SysOps administrator does not recognize the external IP address. The SysOps administrator must block traffic to the external IP address that GuardDuty identified.

Which solution will meet this requirement?

- A. Create a new security group to block traffic to the external IP address
- B. Assign the new security group to the EC2 instance.
- C. Use VPC flow logs with Amazon Athena to block traffic to the external IP address.
- D. Create a network ACL
- E. Add an outbound deny rule for traffic to the external IP address.
- F. Create a new security group to block traffic to the external IP address
- G. Assign the new security group to the entire VPC.

Answer: C

Explanation:

<https://docs.aws.amazon.com/vpc/latest/userguide/vpc-network-acls.html>

NEW QUESTION 2

- (Exam Topic 1)

A company has an application that is running on Amazon EC2 instances in a VPC. The application needs access to download software updates from the internet. The VPC has public subnets and private subnets. The company's security policy requires all EC2 instances to be deployed in private subnets

What should a SysOps administrator do to meet those requirements?

- A. Add an internet gateway to the VPC. In the route table for the private subnets, add a route to the internet gateway.
- B. Add a NAT gateway to a private subnet
- C. In the route table for the private subnets, add a route to the NAT gateway.
- D. Add a NAT gateway to a public subnet. In the route table for the private subnets, add a route to the NAT gateway.
- E. Add two internet gateways to the VPC
- F. In the route table for the private subnets and public subnets, add a route to each internet gateway.

Answer: C

NEW QUESTION 3

- (Exam Topic 1)

A company creates a new member account by using AWS Organizations. A SysOps administrator needs to add AWS Business Support to the new account. Which combination of steps must the SysOps administrator take to meet this requirement? (Select TWO.)

- A. Sign in to the new account by using IAM credentials
- B. Change the support plan.
- C. Sign in to the new account by using root user credentials
- D. Change the support plan.
- E. Use the AWS Support API to change the support plan.
- F. Reset the password of the account root user.
- G. Create an IAM user that has administrator privileges in the new account.

Answer: BE

Explanation:

The best combination of steps to meet this requirement is to sign in to the new account by using root user credentials and change the support plan, and to create an IAM user that has administrator privileges in the new account.

Signing in to the new account by using root user credentials will allow the SysOps administrator to access the account and change the support plan to AWS Business Support. Additionally, creating an IAM user that has administrator privileges in the new account will ensure that the SysOps administrator has the necessary access to manage the account and make changes to the support plan if necessary.

Reference:

[1] https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_accounts_access.html#orgs_ma

NEW QUESTION 4

- (Exam Topic 1)

A company applies user-defined tags to resources that are associated with the company's AWS workloads. Twenty days after applying the tags, the company notices that it cannot use the tags to filter views in the AWS Cost Explorer console.

What is the reason for this issue?

- A. It takes at least 30 days to be able to use tags to filter views in Cost Explorer.
- B. The company has not activated the user-defined tags for cost allocation.
- C. The company has not created an AWS Cost and Usage Report
- D. The company has not created a usage budget in AWS Budgets

Answer: B

NEW QUESTION 5

- (Exam Topic 1)

A SysOps administrator applies the following policy to an AWS CloudFormation stack:

```
{
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "Update:*",
      "Principal": "*",
      "Resource": ["LogicalResourceId/Production*"]
    },
    {
      "Effect": "Allow",
      "Action": "Update:*",
      "Principal": "*",
      "Resource": "*"
    }
  ]
}
```

What is the result of this policy?

- A. Users that assume an IAM role with a logical ID that begins with "Production" are prevented from running the update-stack command.
- B. Users can update all resources in the stack except for resources that have a logical ID that begins with "Production".
- C. Users can update all resources in the stack except for resources that have an attribute that begins with "Production".
- D. Users in an IAM group with a logical ID that begins with "Production" are prevented from running the update-stack command.

Answer: B

NEW QUESTION 6

- (Exam Topic 1)

A company runs a website from Sydney, Australia. Users in the United States (US) and Europe are reporting that images and videos are taking a long time to load. However, local testing in Australia indicates no performance issues. The website has a large amount of static content in the form of images and videos that are stored in Amazon S3.

Which solution will result in the MOST improvement in the user experience for users in the US and Europe?

- A. Configure AWS PrivateLink for Amazon S3.
- B. Configure S3 Transfer Acceleration.
- C. Create an Amazon CloudFront distribution.
- D. Distribute the static content to the CloudFront edge locations.
- E. Create an Amazon API Gateway API in each AWS Region.
- F. Cache the content locally.

Answer: D

NEW QUESTION 7

- (Exam Topic 1)

An application team uses an Amazon Aurora MySQL DB cluster with one Aurora Replica. The application team notices that the application read performance degrades when user connections exceed 200. The number of user connections is typically consistent around 180, with occasional sudden increases above 200 connections. The application team wants the application to automatically scale as user demand increases or decreases.

Which solution will meet these requirements?

- A. Migrate to a new Aurora multi-master DB cluster.
- B. Modify the application database connection string.
- C. Modify the DB cluster by changing to serverless mode whenever user connections exceed 200.
- D. Create an auto scaling policy with a target metric of 195 DatabaseConnections.
- E. Modify the DB cluster by increasing the Aurora Replica instance size.

Answer: C

NEW QUESTION 8

- (Exam Topic 1)

A company has a policy that requires all Amazon EC2 instances to have a specific set of tags. If an EC2 instance does not have the required tags, the noncompliant instance should be terminated.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to send all EC2 instance state changes to an AWS Lambda function to determine if each instance is compliant.
- B. Terminate any noncompliant instances.
- C. Create an IAM policy that enforces all EC2 instance tag requirements.
- D. If the required tags are not in place for an instance, the policy will terminate the noncompliant instance.
- E. Create an AWS Lambda function to determine if each EC2 instance is compliant and terminate an instance if it is noncompliant.
- F. Schedule the Lambda function to invoke every 5 minutes.
- G. Create an AWS Config rule to check if the required tags are present.
- H. If an EC2 instance is noncompliant, invoke an AWS Systems Manager Automation document to terminate the instance.

Answer: D

Explanation:

<https://docs.aws.amazon.com/systems-manager/latest/userguide/systems-manager-automation.html>

NEW QUESTION 9

- (Exam Topic 1)

A company needs to archive all audit logs for 10 years. The company must protect the logs from any future edits. Which solution will meet these requirements?

- A. Store the data in an Amazon Elastic Block Store (Amazon EBS) volume
- B. Configure AWS Key Management Service (AWS KMS) encryption.
- C. Store the data in an Amazon S3 Glacier vault
- D. Configure a vault lock policy for write-once, read-many (WORM) access.
- E. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure server-side encryption.
- F. Store the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA). Configure multi-factor authentication (MFA).

Answer: B

Explanation:

To meet the requirements of the workload, a company should store the data in an Amazon S3 Glacier vault and configure a vault lock policy for write-once, read-many (WORM) access. This will ensure that the data is stored securely and cannot be edited in the future. The other solutions (storing the data in an Amazon Elastic Block Store (Amazon EBS) volume and configuring AWS Key Management Service (AWS KMS) encryption, storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring server-side encryption, or storing the data in Amazon S3 Standard-Infrequent Access (S3 Standard-IA) and configuring multi-factor authentication (MFA)) will not meet the requirements, as they do not provide a way to protect the audit logs from future edits.

https://docs.aws.amazon.com/zh_tw/AmazonS3/latest/userguide/object-lock.html

NEW QUESTION 10

- (Exam Topic 1)

A company website contains a web tier and a database tier on AWS. The web tier consists of Amazon EC2 instances that run in an Auto Scaling group across two Availability Zones. The database tier runs on an Amazon RDS for MySQL Multi-AZ DB instance. The database subnet network ACLs are restricted to only the web subnets that need access to the database. The web subnets use the default network ACL with the default rules.

The company's operations team has added a third subnet to the Auto Scaling group configuration. After an Auto Scaling event occurs, some users report that they intermittently receive an error message. The error message states that the server cannot connect to the database. The operations team has confirmed that the route tables are correct and that the required ports are open on all security groups.

Which combination of actions should a SysOps administrator take so that the web servers can communicate with the DB instance? (Select TWO.)

- A. On the default ACL
- B. create inbound Allow rules of type TCP with the ephemeral port range and the source as the database subnets.
- C. On the default ACL, create outbound Allow rules of type MySQL/Aurora (3306). Specify the destinations as the database subnets.
- D. On the network ACLs for the database subnets, create an inbound Allow rule of type MySQL/Aurora (3306). Specify the source as the third web subnet.
- E. On the network ACLs for the database subnets, create an outbound Allow rule of type TCP with the ephemeral port range and the destination as the third web subnet.
- F. On the network ACLs for the database subnets, create an outbound Allow rule of type MySQL/Aurora (3306). Specify the destination as the third web subnet.

Answer: CD

NEW QUESTION 10

- (Exam Topic 1)

The security team is concerned because the number of AWS Identity and Access Management (IAM) policies being used in the environment is increasing. The team tasked a SysOps administrator to report on the current number of IAM policies in use and the total available IAM policies.

Which AWS service should the administrator use to check how current IAM policy usage compares to current service limits?

- A. AWS Trusted Advisor
- B. Amazon Inspector
- C. AWS Config
- D. AWS Organizations

Answer: A

NEW QUESTION 15

- (Exam Topic 1)

A company is running a website on Amazon EC2 instances behind an Application Load Balancer (ALB). The company configured an Amazon CloudFront distribution and set the ALB as the origin. The company created an Amazon Route 53 CNAME record to send all traffic through the CloudFront distribution. As an unintended side effect, mobile users are now being served the desktop version of the website.

Which action should a SysOps administrator take to resolve this issue?

- A. Configure the CloudFront distribution behavior to forward the User-Agent header.
- B. Configure the CloudFront distribution origin setting
- C. Add a User-Agent header to the list of origin custom headers.
- D. Enable IPv6 on the AL
- E. Update the CloudFront distribution origin settings to use the dualstack endpoint.
- F. Enable IPv6 on the CloudFront distributio
- G. Update the Route 53 record to use the dualstack endpoint.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/header-caching.html#header-caching->

NEW QUESTION 20

- (Exam Topic 1)

A company stores its data in an Amazon S3 bucket. The company is required to classify the data and find any sensitive personal information in its S3 files. Which solution will meet these requirements?

- A. Create an AWS Config rule to discover sensitive personal information in the S3 files and mark them as noncompliant.
- B. Create an S3 event-driven artificial intelligence/machine learning (AI/ML) pipeline to classify sensitive personal information by using Amazon Recognition.
- C. Enable Amazon GuardDut
- D. Configure S3 protection to monitor all data inside Amazon S3.
- E. Enable Amazon Maci
- F. Create a discovery job that uses the managed data identifier.

Answer: D

Explanation:

Amazon Macie is a security service designed to help organizations find, classify, and protect sensitive data stored in Amazon S3. Amazon Macie uses machine learning to automatically discover, classify, and protect sensitive data in Amazon S3. Creating a discovery job with the managed data identifier will allow Macie to identify sensitive personal information in the S3 files and classify it accordingly. Enabling AWS Config and Amazon GuardDuty will not help with this requirement as they are not designed to automatically classify and protect data.

NEW QUESTION 23

- (Exam Topic 1)

A company has deployed AWS Security Hub and AWS Config in a newly implemented organization in AWS Organizations. A SysOps administrator must implement a solution to restrict all member accounts in the organization from deploying Amazon EC2 resources in the ap-southeast-2 Region. The solution must be implemented from a single point and must govern an current and future accounts. The use of root credentials also must be restricted in member accounts. Which AWS feature should the SysOps administrator use to meet these requirements?

- A. AWS Config aggregator
- B. IAM user permissions boundaries
- C. AWS Organizations service control policies (SCPs)
- D. AWS Security Hub conformance packs

Answer: C

NEW QUESTION 24

- (Exam Topic 1)

A SysOps administrator recently configured Amazon S3 Cross-Region Replication on an S3 bucket Which of the following does this feature replicate to the destination S3 bucket by default?

- A. Objects in the source S3 bucket for which the bucket owner does not have permissions
- B. Objects that are stored in S3 Glacier
- C. Objects that existed before replication was configured
- D. Object metadata

Answer: B

NEW QUESTION 28

- (Exam Topic 1)

A company runs a stateless application that is hosted on an Amazon EC2 instance. Users are reporting performance issues. A SysOps administrator reviews the Amazon CloudWatch metrics for the application and notices that the instance's CPU utilization frequently reaches 90% during business hours. What is the MOST operationally efficient solution that will improve the application's responsiveness?

- A. Configure CloudWatch logging on the EC2 instance
- B. Configure a CloudWatch alarm for CPU utilization to alert the SysOps administrator when CPU utilization goes above 90%.
- C. Configure an AWS Client VPN connection to allow the application users to connect directly to the EC2 instance private IP address to reduce latency.
- D. Create an Auto Scaling group, and assign it to an Application Load Balance
- E. Configure a target tracking scaling policy that is based on the average CPU utilization of the Auto Scaling group.
- F. Create a CloudWatch alarm that activates when the EC2 instance's CPU utilization goes above 80%. Configure the alarm to invoke an AWS Lambda function that vertically scales the instance.

Answer: C

NEW QUESTION 30

- (Exam Topic 1)

A company has two VPC networks named VPC A and VPC B. The VPC A CIDR block is 10.0.0.0/16 and the VPC B CIDR block is 172.31.0.0/16. The company wants to establish a VPC peering connection named pcx-12345 between both VPCs. Which rules should appear in the route table of VPC A after configuration? (Select TWO.)

- A. Destination: 10.0.0.0/16, Target: Local
- B. Destination: 172.31.0.0/16, Target: Local
- C. Destination: 10.0.0.0/16, Target: pcx-12345
- D. Destination: 172.31.0.0/16, Target: pcx-12345
- E. Destination: 10.0.0.0/16, Target: 172.31.0.0/16

Answer: AD

Explanation:

<https://docs.aws.amazon.com/vpc/latest/peering/vpc-peering-routing.html>

NEW QUESTION 33

- (Exam Topic 1)

A SysOps administrator needs to create alerts that are based on the read and write metrics of Amazon Elastic Block Store (Amazon EBS) volumes that are attached to an Amazon EC2 instance. The SysOps administrator creates and enables Amazon CloudWatch alarms for the DiskReadBytes metric and the DiskWriteBytes metric.

A custom monitoring tool that is installed on the EC2 instance with the same alarm configuration indicates that the volume metrics have exceeded the threshold. However, the CloudWatch alarms were not in ALARM state.

Which action will ensure that the CloudWatch alarms function correctly?

- A. Install and configure the CloudWatch agent on the EC2 instance to capture the desired metrics.
- B. Install and configure AWS Systems Manager Agent on the EC2 instance to capture the desired metrics.
- C. Reconfigure the CloudWatch alarms to use the VolumeReadBytes metric and the VolumeWriteBytes metric for the EBS volumes.
- D. Reconfigure the CloudWatch alarms to use the VolumeReadBytes metric and the VolumeWriteBytes metric for the EC2 instance.

Answer: A

NEW QUESTION 38

- (Exam Topic 1)

A SysOps administrator wants to manage a web server application with AWS Elastic Beanstalk. The Elastic Beanstalk service must maintain full capacity for new deployments at all times.

Which deployment policies satisfy this requirement? (Select TWO.)

- A. All at once
- B. Immutable
- C. Rebuild
- D. Rolling
- E. Rolling with additional batch

Answer: BE

Explanation:

<https://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.rolling-version-deploy.html>

NEW QUESTION 40

- (Exam Topic 1)

A company needs to implement a managed file system to host Windows file shares for users on premises. Resources in the AWS Cloud also need access to the data on these file shares. A SysOps administrator needs to present the user file shares on premises and make the user file shares available on AWS with minimum latency.

What should the SysOps administrator do to meet these requirements?

- A. Set up an Amazon S3 File Gateway.
- B. Set up an AWS Direct Connect connection.
- C. Use AWS DataSync to automate data transfers between the existing file servers and AWS.
- D. Set up an Amazon FSx File Gateway.

Answer: D

Explanation:

Amazon FSx provides a fully managed file system that is optimized for Windows-based workloads and can be used to create file shares that can be accessed both on premises and in the AWS Cloud. The file shares that are created in Amazon FSx are highly available and can be accessed with low latency. Additionally, Amazon FSx supports Windows-based authentication, making it easy to integrate with existing Windows user accounts.

References:

[1] <https://aws.amazon.com/fsx/>

[2] <https://aws.amazon.com/storage/file-storage/>

[3] <https://docs.aws.a>

NEW QUESTION 43

- (Exam Topic 1)

A SysOps administrator has created a VPC that contains a public subnet and a private subnet. Amazon EC2 instances that were launched in the private subnet cannot access the internet. The default network ACL is active on all subnets in the VPC, and all security groups allow all outbound traffic:

Which solution will provide the EC2 instances in the private subnet with access to the internet?

- A. Create a NAT gateway in the public subne
- B. Create a route from the private subnet to the NAT gateway.
- C. Create a NAT gateway in the public subne
- D. Create a route from the public subnet to the NAT gateway.
- E. Create a NAT gateway in the private subne
- F. Create a route from the public subnet to the NAT gateway.
- G. Create a NAT gateway in the private subne
- H. Create a route from the private subnet to the NAT gateway.

Answer: A

Explanation:

NAT Gateway resides in public subnet, and traffic should be routed from private subnet to NAT Gateway: <https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

NEW QUESTION 47

- (Exam Topic 1)

A company wants to build a solution for its business-critical Amazon RDS for MySQL database. The database requires high availability across different geographic locations. A SysOps administrator must build a solution to handle a disaster recovery (DR) scenario with the lowest recovery time objective (RTO) and recovery point objective (RPO).

Which solution meets these requirements?

- A. Create automated snapshots of the database on a schedule
- B. Copy the snapshots to the DR Region.
- C. Create a cross-Region read replica for the database.
- D. Create a Multi-AZ read replica for the database.
- E. Schedule AWS Lambda functions to create snapshots of the source database and to copy the snapshots to a DR Region.

Answer: B

NEW QUESTION 51

- (Exam Topic 1)

A company uses AWS Organizations to manage its AWS accounts. A SysOps administrator must create a backup strategy for all Amazon EC2 instances across all the company's AWS accounts.

Which solution will meet these requirements in the MOST operationally efficient way?

- A. Deploy an AWS Lambda function to each account to run EC2 instance snapshots on a scheduled basis.
- B. Create an AWS CloudFormation stack set in the management account to add an AutoBackup=True tag to every EC2 instance
- C. Use AWS Backup in the management account to deploy policies for all accounts and resources.
- D. Use a service control policy (SCP) to run EC2 instance snapshots on a scheduled basis in each account.

Answer: B

NEW QUESTION 54

- (Exam Topic 1)

A company wants to create an automated solution for all accounts managed by AWS Organizations to detect any security groups that use 0.0.0.0/0 as the source address for inbound traffic. The company also wants to automatically remediate any noncompliant security groups by restricting access to a specific CIDR block that corresponds with the company's intranet.

- A. Create an AWS Config rule to detect noncompliant security groups
- B. Set up automatic remediation to change the 0.0.0.0/0 source address to the approved CIDR block.
- C. Create an IAM policy to deny the creation of security groups that have 0.0.0.0/0 as the source address. Attach this IAM policy to every user in the company.
- D. Create an AWS Lambda function to inspect new and existing security groups, check for a noncompliant (0.0.0.0/0) source address, and change the source address to the approved CIDR block.
- E. Create a service control policy (SCP) for the organizational unit (OU) to deny the creation of security groups that have the 0.0.0.0/0 source address
- F. Set up automatic remediation to change the 0.0.0.0/0 source address to the approved CIDR block.

Answer: A

NEW QUESTION 58

- (Exam Topic 1)

A company uses an Amazon S3 bucket to store data files. The S3 bucket contains hundreds of objects. The company needs to replace a tag on all the objects in the S3 bucket with another tag.

What is the MOST operationally efficient way to meet this requirement?

- A. Use S3 Batch Operation
- B. Specify the operation to replace all object tags.
- C. Use the AWS CLI to get the tags for each object
- D. Save the tags in a list
- E. Use S3 Batch Operations. Specify the operation to delete all object tags
- F. Use the AWS CLI and the list to retag the objects.
- G. Use the AWS CLI to get the tags for each object
- H. Save the tags in a list
- I. Use the AWS CLI and the list to remove the object tags
- J. Use the AWS CLI and the list to retag the objects.
- K. Use the AWS CLI to copy the objects to another S3 bucket
- L. Add the new tag to the copied objects. Delete the original objects.

Answer: A

Explanation:

Ref. <https://aws.amazon.com/es/blogs/storage/adding-and-removing-object-tags-with-s3-batch-operations/>

NEW QUESTION 62

- (Exam Topic 1)

A company is running an application on premises and wants to use AWS for data backup. All of the data must be available locally. The backup application can write only to block-based storage that is compatible with the Portable Operating System Interface (POSIX)

Which backup solution will meet these requirements?

- A. Configure the backup software to use Amazon S3 as the target for the data backups
- B. Configure the backup software to use Amazon S3 Glacier as the target for the data backups
- C. Use AWS Storage Gateway, and configure it to use gateway-cached volumes
- D. Use AWS Storage Gateway, and configure it to use gateway-stored volumes

Answer: D

Explanation:

<https://docs.aws.amazon.com/storagegateway/latest/userguide/StorageGatewayConcepts.html>

NEW QUESTION 64

- (Exam Topic 1)

A company uses AWS Organizations to manage multiple AWS accounts with consolidated billing enabled. Organization member account owners want the benefits of Reserved Instances (RIs) but do not want to share RIs with other accounts. Which solution will meet these requirements?

- A. Purchase RIs in individual member account
- B. Disable RI discount sharing in the management account.
- C. Purchase RIs in individual member account
- D. Disable RI discount sharing in the member accounts.
- E. Purchase RIs in the management account
- F. Disable RI discount sharing in the management account.
- G. Purchase RIs in the management account
- H. Disable RI discount sharing in the member accounts.

Answer: A

Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/ec2-ri-consolidated-billing/>

RI discounts apply to accounts in an organization's consolidated billing family depending upon whether RI sharing is turned on or off for the accounts. By default, RI sharing for all accounts in an organization is turned on. The management account of an organization can change this setting by turning off RI sharing for an account. The capacity reservation for an RI applies only to the account the RI was purchased on, no matter whether RI sharing is turned on or off.

NEW QUESTION 65

- (Exam Topic 1)

A company with multiple AWS accounts needs to obtain recommendations for AWS Lambda functions and identify optimal resource configurations for each Lambda function. How should a SysOps administrator provide these recommendations?

- A. Create an AWS Serverless Application Repository and export the Lambda function recommendations.
- B. Enable AWS Compute Optimizer and export the Lambda function recommendations
- C. Enable all features of AWS Organization and export the recommendations from AWS CloudTrailInsights.
- D. Run AWS Trusted Advisor and export the Lambda function recommendations

Answer: B

NEW QUESTION 67

- (Exam Topic 1)

A company is hosting applications on Amazon EC2 instances. The company is hosting a database on an Amazon RDS for PostgreSQL DB instance. The company requires all connections to the DB instance to be encrypted. What should a SysOps administrator do to meet this requirement?

- A. Allow SSL connections to the database by using an inbound security group rule.
- B. Encrypt the database by using an AWS Key Management Service (AWS KMS) encryption key.
- C. Enforce SSL connections to the database by using a custom parameter group.
- D. Patch the database with SSL/TLS by using a custom PostgreSQL extension.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/PostgreSQL.Concepts.General.SSL.htm> Amazon RDS supports SSL/TLS encryption for connections to the database, and this can be enabled by creating a custom parameter group and setting the `rds.force_ssl` parameter to 1. This will ensure that all connections to the database are encrypted, protecting the data and maintaining compliance with the company's requirements.

NEW QUESTION 70

- (Exam Topic 1)

A company runs a web application on three Amazon EC2 instances behind an Application Load Balancer (ALB). The company notices that random periods of increased traffic cause a degradation in the application's performance. A SysOps administrator must scale the application to meet the increased traffic. Which solution meets these requirements?

- A. Create an Amazon CloudWatch alarm to monitor application latency and increase the size of each EC2 instance if the desired threshold is reached.
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to monitor application latency and add an EC2 instance to the ALB if the desired threshold is reached.
- C. Deploy the application to an Auto Scaling group of EC2 instances with a target tracking scaling policy. Attach the ALB to the Auto Scaling group.
- D. Deploy the application to an Auto Scaling group of EC2 instances with a scheduled scaling policy. Attach the ALB to the Auto Scaling group.

Answer: C

Explanation:

docs.aws.amazon.com/autoscaling/ec2/userguide/as-scaling-target-tracking.html

NEW QUESTION 74

- (Exam Topic 1)

A company uses AWS CloudFormation to deploy its application infrastructure. Recently, a user accidentally changed a property of a database in a CloudFormation template and performed a stack update that caused an interruption to the application. A SysOps administrator must determine how to modify the deployment process to allow the DevOps team to continue to deploy the infrastructure, but prevent against accidental modifications to specific resources. Which solution will meet these requirements?

- A. Set up an AWS Config rule to alert based on changes to any CloudFormation stack. An AWS Lambda function can then describe the stack to determine if any protected resources were modified and cancel the operation.
- B. Set up an Amazon CloudWatch Events event with a rule to trigger based on any CloudFormation API call. An AWS Lambda function can then describe the stack to determine if any protected resources were modified and cancel the operation.
- C. Launch the CloudFormation templates using a stack policy with an explicit allow for all resources and an explicit deny of the protected resources with an action of Update.
- D. Attach an IAM policy to the DevOps team role that prevents a CloudFormation stack from updating, with a condition based on the specific Amazon Resource Names (ARNs) of the protected resources.

Answer: B

NEW QUESTION 79

- (Exam Topic 1)

A SysOps administrator is tasked with analyzing database performance. The database runs on a single Amazon RDS D6 instance. The SysOps administrator finds that, during times of peak traffic, resources on the database are over utilized due to the amount of read traffic. Which actions should the SysOps administrator take to improve RDS performance? (Select TWO.)

- A. Add a read replica.
- B. Modify the application to use Amazon ElastiCache for Memcached.
- C. Migrate the database from RDS to Amazon DynamoDB.
- D. Migrate the database to Amazon EC2 with enhanced networking enabled.
- E. Upgrade the database to a Multi-AZ deployment.

Answer: AB

NEW QUESTION 80

- (Exam Topic 1)

A SysOps administrator launches an Amazon EC2 Linux instance in a public subnet. When the instance is running, the SysOps administrator obtains the public IP address and attempts to remotely connect to the instance multiple times. However, the SysOps administrator always receives a timeout error. Which action will allow the SysOps administrator to remotely connect to the instance?

- A. Add a route table entry in the public subnet for the SysOps administrator's IP address.
- B. Add an outbound network ACL rule to allow TCP port 22 for the SysOps administrator's IP address.
- C. Modify the instance security group to allow inbound SSH traffic from the SysOps administrator's IP address.
- D. Modify the instance security group to allow outbound SSH traffic to the SysOps administrator's IP address.

Answer: C

NEW QUESTION 85

- (Exam Topic 1)

An organization created an Amazon Elastic File System (Amazon EFS) volume with a file system ID of fs-85ba4Kc. and it is actively used by 10 Amazon EC2 hosts. The organization has become concerned that the file system is not encrypted. How can this be resolved?

- A. Enable encryption on each host's connection to the Amazon EFS volume. Each connection must be recreated for encryption to take effect.
- B. Enable encryption on the existing EFS volume by using the AWS Command Line Interface.
- C. Enable encryption on each host's local drive. Restart each host to encrypt the drive.
- D. Enable encryption on a newly created volume and copy all data from the original volume. Reconnect each host to the new volume.

Answer: D

Explanation:

<https://docs.aws.amazon.com/efs/latest/ug/encryption.html>

Amazon EFS supports two forms of encryption for file systems, encryption of data in transit and encryption at rest. You can enable encryption of data at rest when creating an Amazon EFS file system. You can enable encryption of data in transit when you mount the file system.

NEW QUESTION 89

- (Exam Topic 1)

A SysOps administrator is unable to authenticate an AWS CLI call to an AWS service. Which of the following is the cause of this issue?

- A. The IAM password is incorrect.
- B. The server certificate is missing.
- C. The SSH key pair is incorrect.
- D. There is no access key.

Answer: C

NEW QUESTION 90

- (Exam Topic 1)

A company has an AWS CloudFormation template that creates an Amazon S3 bucket. A user authenticates to the corporate AWS account with their Active Directory credentials and attempts to deploy the CloudFormation template. However, the stack creation fails. Which factors could cause this failure? (Select TWO.)

- A. The user's IAM policy does not allow the cloudformation:CreateStack action.
- B. The user's IAM policy does not allow the cloudformation:CreateStackSet action.
- C. The user's IAM policy does not allow the s3:CreateBucket action.
- D. The user's IAM policy explicitly denies the s3:ListBucket action.
- E. The user's IAM policy explicitly denies the s3:PutObject action

Answer: AC

NEW QUESTION 91

- (Exam Topic 1)

A SysOps administrator has successfully deployed a VPC with an AWS Cloud Formation template. The SysOps administrator wants to deploy the same template across multiple accounts that are managed through AWS Organizations.

Which solution will meet this requirement with the LEAST operational overhead?

- A. Assume the OrganizationAccountAccessRole IAM role from the management account
- B. Deploy the template in each of the accounts
- C. Create an AWS Lambda function to assume a role in each account. Deploy the template by using the AWS CloudFormation CreateStack API call.
- D. Create an AWS Lambda function to query for a list of accounts. Deploy the template by using the AWS CloudFormation CreateStack API call.
- E. Use AWS CloudFormation StackSets from the management account to deploy the template in each of the accounts

Answer: D

Explanation:

AWS CloudFormation StackSets extends the capability of stacks by enabling you to create, update, or delete stacks across multiple accounts and AWS Regions.

NEW QUESTION 93

- (Exam Topic 1)

A company's reporting job that used to run in 15 minutes is now taking an hour to run. An application generates the reports. The application runs on Amazon EC2 instances and extracts data from an Amazon RDS for MySQL database.

A SysOps administrator checks the Amazon CloudWatch dashboard for the RDS instance and notices that the Read IOPS metrics are high, even when the reports are not running. The SysOps administrator needs to improve the performance and the availability of the RDS instance.

Which solution will meet these requirements?

- A. Configure an Amazon ElastiCache cluster in front of the RDS instance.
- B. Update the reporting job to query the ElastiCache cluster.
- C. Deploy an RDS read replica.
- D. Update the reporting job to query the reader endpoint.
- E. Create an Amazon CloudFront distribution.
- F. Set the RDS instance as the origin.
- G. Update the reporting job to query the CloudFront distribution.
- H. Increase the size of the RDS instance.

Answer: B

Explanation:

Using an RDS read replica will improve the performance and availability of the RDS instance by offloading read queries to the replica. This will also ensure that the reporting job completes in a timely manner and does not affect the performance of other queries that might be running on the RDS instance. Additionally, updating the reporting job to query the reader endpoint will ensure that all read queries are directed to the read replica.

Reference: [1] https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_ReadRepl.html

NEW QUESTION 95

- (Exam Topic 1)

A company is using an Amazon Aurora MySQL DB cluster that has point-in-time recovery, backtracking, and automatic backup enabled. A SysOps administrator needs to be able to roll back the DB cluster to a specific recovery point within the previous 72 hours. Restores must be completed in the same production DB cluster.

Which solution will meet these requirements?

- A. Create an Aurora Replica.
- B. Promote the replica to replace the primary DB instance.
- C. Create an AWS Lambda function to restore an automatic backup to the existing DB cluster.
- D. Use backtracking to rewind the existing DB cluster to the desired recovery point.
- E. Use point-in-time recovery to restore the existing DB cluster to the desired recovery point.

Answer: C

Explanation:

"The limit for a backtrack window is 72 hours....Backtracking is only available for DB clusters that were created with the Backtrack feature enabled....Backtracking "rewinds" the DB cluster to the time you specify. Backtracking is not a replacement for backing up your DB cluster so that you can restore it to a point in time....You can backtrack a DB cluster quickly. Restoring a DB cluster to a point in time launches a new DB cluster and restores it from backup data or a DB cluster snapshot, which can take hours."

<https://docs.aws.amazon.com/AmazonRDS/latest/AuroraUserGuide/AuroraMySQL.Managing.Backtrack.html>

NEW QUESTION 97

- (Exam Topic 1)

A company must ensure that any objects uploaded to an S3 bucket are encrypted. Which of the following actions will meet this requirement? (Choose two.)

- A. Implement AWS Shield to protect against unencrypted objects stored in S3 buckets.
- B. Implement Object access control list (ACL) to deny unencrypted objects from being uploaded to the S3 bucket.
- C. Implement Amazon S3 default encryption to make sure that any object being uploaded is encrypted before it is stored.

- D. Implement Amazon Inspector to inspect objects uploaded to the S3 bucket to make sure that they are encrypted.
- E. Implement S3 bucket policies to deny unencrypted objects from being uploaded to the buckets.

Answer: CE

Explanation:

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/default-bucket-encryption.html>

You can set the default encryption behavior on an Amazon S3 bucket so that all objects are encrypted when they are stored in the bucket. The objects are encrypted using server-side encryption with either Amazon S3-managed keys (SSE-S3) or AWS Key Management Service (AWS KMS) customer master keys (CMKs).

<https://aws.amazon.com/blogs/security/how-to-prevent-uploads-of-unencrypted-objects-to-amazon-s3/> How to Prevent Uploads of Unencrypted Objects to Amazon S3#

By using an S3 bucket policy, you can enforce the encryption requirement when users upload objects, instead of assigning a restrictive IAM policy to all users.

NEW QUESTION 100

- (Exam Topic 1)

A SysOps administrator receives notification that an application that is running on Amazon EC2 instances has failed to authenticate to an Amazon RDS database. To troubleshoot, the SysOps administrator needs to investigate AWS Secrets Manager password rotation. Which Amazon CloudWatch log will provide insight into the password rotation?

- A. AWS CloudTrail logs
- B. EC2 instance application logs
- C. AWS Lambda function logs
- D. RDS database logs

Answer: B

NEW QUESTION 103

- (Exam Topic 1)

A company recently acquired another corporation and all of that corporation's AWS accounts. A financial analyst needs the cost data from these accounts. A SysOps administrator uses Cost Explorer to generate cost and usage reports. The SysOps administrator notices that "No Tagkey" represents 20% of the monthly cost.

What should the SysOps administrator do to tag the "No Tagkey" resources?

- A. Add the accounts to AWS Organization
- B. Use a service control policy (SCP) to tag all the untagged resources.
- C. Use an AWS Config rule to find the untagged resource
- D. Set the remediation action to terminate the resources.
- E. Use Cost Explorer to find and tag all the untagged resources.
- F. Use Tag Editor to find and tag all the untagged resources.

Answer: D

Explanation:

"You can add tags to resources when you create the resource. You can use the resource's service console or API to add, change, or remove those tags one resource at a time. To add tags to—or edit or delete tags of—multiple resources at once, use Tag Editor. With Tag Editor, you search for the resources that you want to tag, and then manage tags for the resources in your search results." <https://docs.aws.amazon.com/ARG/latest/userguide/tag-editor.html>

NEW QUESTION 108

- (Exam Topic 1)

A SysOps administrator must create a solution that automatically shuts down any Amazon EC2 instances that have less than 10% average CPU utilization for 60 minutes or more.

Which solution will meet this requirement in the MOST operationally efficient manner?

- A. Implement a cron job on each EC2 instance to run once every 60 minutes and calculate the current CPU utilization
- B. Initiate an instance shutdown if CPU utilization is less than 10%.
- C. Implement an Amazon CloudWatch alarm for each EC2 instance to monitor average CPU utilization. Set the period at 1 hour, and set the threshold at 10%. Configure an EC2 action on the alarm to stop the instance.
- D. Install the unified Amazon CloudWatch agent on each EC2 instance, and enable the Basic level predefined metric set
- E. Log CPU utilization every 60 minutes, and initiate an instance shutdown if CPU utilization is less than 10%.
- F. Use AWS Systems Manager Run Command to get CPU utilization from each EC2 instance every 60 minutes
- G. Initiate an instance shutdown if CPU utilization is less than 10%.

Answer: B

Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/monitoring/UsingAlarmActions.html>

NEW QUESTION 109

- (Exam Topic 1)

A company asks a SysOps administrator to ensure that AWS CloudTrail files are not tampered with after they are created. Currently, the company uses AWS Identity and Access Management (IAM) to restrict access to specific trails. The company's security team needs the ability to trace the integrity of each file. What is the MOST operationally efficient solution that meets these requirements?

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule that invokes an AWS Lambda function when a new file is delivered
- B. Configure the Lambda function to compute an MD5 hash check on the file and store the result in an Amazon DynamoDB table
- C. The security team can use the values that are stored in DynamoDB to verify the integrity of the delivered files.
- D. Create an AWS Lambda function that is invoked each time a new file is delivered to the CloudTrail bucket

- E. Configure the Lambda function to compute an MD5 hash check on the file and store the result as a tag in an Amazon S3 object.
- F. The security team can use the information in the tag to verify the integrity of the delivered files.
- G. Enable the CloudTrail file integrity feature on an Amazon S3 bucket.
- H. Create an IAM policy that grants the security team access to the file integrity logs that are stored in the S3 bucket.
- I. Enable the CloudTrail file integrity feature on the trail.
- J. The security team can use the digest file that is created by CloudTrail to verify the integrity of the delivered files.

Answer: D

Explanation:

<https://docs.aws.amazon.com/awsccloudtrail/latest/userguide/cloudtrail-log-file-validation-intro.html> "When you enable log file integrity validation, CloudTrail creates a hash for every log file that it delivers.

Every hour, CloudTrail also creates and delivers a file that references the log files for the last hour and contains a hash of each. This file is called a digest file. Validated log files are invaluable in security and forensic investigations"

NEW QUESTION 110

- (Exam Topic 1)

A user working in the Amazon EC2 console increased the size of an Amazon Elastic Block Store (Amazon EBS) volume attached to an Amazon EC2 Windows instance. The change is not reflected in the file system.

What should a SysOps administrator do to resolve this issue?

- A. Extend the file system with operating system-level tools to use the new storage capacity.
- B. Reattach the EBS volume to the EC2 instance.
- C. Reboot the EC2 instance that is attached to the EBS volume.
- D. Take a snapshot of the EBS volume.
- E. Replace the original volume with a volume that is created from the snapshot.

Answer: B

NEW QUESTION 112

- (Exam Topic 1)

A company uses AWS Organizations to manage multiple AWS accounts. The company's SysOps team has been using a manual process to create and manage IAM roles. The team requires an automated solution to create and manage the necessary IAM roles for multiple AWS accounts.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create AWS CloudFormation template.
- B. Reuse the templates to create the necessary IAM roles in each of the AWS accounts.
- C. Use AWS Directory Service with AWS Organizations to automatically associate the necessary IAM roles with Microsoft Active Directory users.
- D. Use AWS Resource Access Manager with AWS Organizations to deploy and manage shared resources across the AWS accounts.
- E. Use AWS CloudFormation StackSets with AWS Organizations to deploy and manage IAM roles for the AWS accounts.

Answer: D

NEW QUESTION 115

- (Exam Topic 1)

A company has deployed a web application in a VPC that has subnets in three Availability Zones. The company launches three Amazon EC2 instances from an EC2 Auto Scaling group behind an Application Load Balancer (ALB).

A SysOps administrator notices that two of the EC2 instances are in the same Availability Zone, rather than being distributed evenly across all three Availability Zones. There are no errors in the Auto Scaling group's activity history.

What is the MOST likely reason for the unexpected placement of EC2 instances?

- A. One Availability Zone did not have sufficient capacity for the requested EC2 instance type.
- B. The ALB was configured for only two Availability Zones.
- C. The Auto Scaling group was configured for only two Availability Zones.
- D. Amazon EC2 Auto Scaling randomly placed the instances in Availability Zones.

Answer: C

Explanation:

the autoscaling group is responsible to add the instances in the subnets

NEW QUESTION 120

- (Exam Topic 1)

An organization is running multiple applications for their customers. Each application is deployed by running a base AWS CloudFormation template that configures a new VPC. All applications are run in the same AWS account and AWS Region. A SysOps administrator has noticed that when trying to deploy the same AWS CloudFormation stack, it fails to deploy. What is likely to be the problem?

- A. The Amazon Machine image used is not available in that region.
- B. The AWS CloudFormation template needs to be updated to the latest version.
- C. The VPC configuration parameters have changed and must be updated in the template.
- D. The account has reached the default limit for VPCs allowed.

Answer: D

NEW QUESTION 121

- (Exam Topic 1)

A company hosts several write-intensive applications. These applications use a MySQL database that runs on a single Amazon EC2 instance. The company asks a SysOps administrator to implement a highly available database solution that is ideal for multi-tenant workloads.

Which solution should the SysOps administrator implement to meet these requirements?

- A. Create a second EC2 instance for MySQL
- B. Configure the second instance to be a read replica.
- C. Migrate the database to an Amazon Aurora DB cluster
- D. Add an Aurora Replica.
- E. Migrate the database to an Amazon Aurora multi-master DB cluster.
- F. Migrate the database to an Amazon RDS for MySQL DB instance.

Answer: C

NEW QUESTION 126

- (Exam Topic 1)

A company is managing multiple AWS accounts in AWS Organizations. The company is reviewing internal security of its AWS environment. The company's security administrator has their own AWS account and wants to review the VPC configuration of developer AWS accounts.

Which solution will meet these requirements in the MOST secure manner?

- A. Create an IAM policy in each developer account that has read-only access related to VPC resources. Assign the policy to an IAM user.
- B. Share the user credentials with the security administrator.
- C. Create an IAM policy in each developer account that has administrator access to all Amazon EC2 actions, including VPC actions.
- D. Assign the policy to an IAM user.
- E. Share the user credentials with the security administrator.
- F. Create an IAM policy in each developer account that has administrator access related to VPC resources. Assign the policy to a cross-account IAM role.
- G. Ask the security administrator to assume the role from their account.
- H. Create an IAM policy in each developer account that has read-only access related to VPC resources. Assign the policy to a cross-account IAM role. Ask the security administrator to assume the role from their account.

Answer: D

NEW QUESTION 130

- (Exam Topic 1)

An ecommerce company uses an Amazon ElastiCache for Memcached cluster for in-memory caching of popular product queries on the shopping site. When viewing recent Amazon CloudWatch metrics data for the ElastiCache cluster, the SysOps administrator notices a large number of evictions.

Which of the following actions will reduce these evictions? (Choose two.)

- A. Add an additional node to the ElastiCache cluster.
- B. Increase the ElastiCache time to live (TTL).
- C. Increase the individual node size inside the ElastiCache cluster.
- D. Put an Elastic Load Balancer in front of the ElastiCache cluster.
- E. Use Amazon Simple Queue Service (Amazon SQS) to decouple the ElastiCache cluster.

Answer: AC

Explanation:

<https://d1.awsstatic.com/training-and-certification/docs-sysops-associate/AWS-Certified-SysOps-Administrator>

NEW QUESTION 131

- (Exam Topic 1)

A company has mandated the use of multi-factor authentication (MFA) for all IAM users, and requires users to make all API calls using the CLI. However, users are not prompted to enter MFA tokens, and are able to run CLI commands without MFA. In an attempt to enforce MFA, the company attached an IAM policy to all users that denies API calls that have not been authenticated with MFA.

What additional step must be taken to ensure that API calls are authenticated using MFA?

- A. Enable MFA on IAM roles, and require IAM users to use role credentials to sign API calls.
- B. Ask the IAM users to log into the AWS Management Console with MFA before making API calls using the CLI.
- C. Restrict the IAM users to use of the console, as MFA is not supported for CLI use.
- D. Require users to use temporary credentials from the get-session token command to sign API calls.

Answer: D

NEW QUESTION 134

- (Exam Topic 1)

A company manages an application that uses Amazon ElastiCache for Redis with two extra-large nodes spread across two different Availability Zones. The company's IT team discovers that the ElastiCache for Redis cluster has 75% freeable memory. The application must maintain high availability.

What is the MOST cost-effective way to resize the cluster?

- A. Decrease the number of nodes in the ElastiCache for Redis cluster from 2 to 1.
- B. Deploy a new ElastiCache for Redis cluster that uses large node type.
- C. Migrate the data from the original cluster to the new cluster.
- D. After the process is complete, shut down the original cluster.
- E. Deploy a new ElastiCache for Redis cluster that uses large node type.
- F. Take a backup from the original cluster, and restore the backup in the new cluster.
- G. After the process is complete, shut down the original cluster.
- H. Perform an online resizing for the ElastiCache for Redis cluster.
- I. Change the node types from extra-large nodes to large nodes.

Answer: D

Explanation:

<https://docs.aws.amazon.com/AmazonElastiCache/latest/red-ug/scaling-redis-cluster-mode-enabled.html> As demand on your clusters changes, you might decide to improve performance or reduce costs by changing the number of shards in your Redis (cluster mode enabled) cluster. We recommend using online horizontal scaling to do so, because it allows your cluster to continue serving requests during the scaling process.

<https://docs.aws.amazon.com/AmazonElastiCache/latest/red-ug/redis-cluster-vertical-scaling-scaling-down.html>

NEW QUESTION 138

- (Exam Topic 1)

A company has a critical serverless application that uses multiple AWS Lambda functions. Each Lambda function generates 1 GB of log data daily in its own Amazon CloudWatch Logs log group. The company's security team asks for a count of application errors, grouped by type, across all of the log groups. What should a SysOps administrator do to meet this requirement?

- A. Perform a CloudWatch Logs Insights query that uses the stats command and count function.
- B. Perform a CloudWatch Logs search that uses the groupby keyword and count function.
- C. Perform an Amazon Athena query that uses the SELECT and GROUP BY keywords.
- D. Perform an Amazon RDS query that uses the SELECT and GROUP BY keywords.

Answer: A

NEW QUESTION 143

- (Exam Topic 1)

A SysOps administrator needs to delete an AWS CloudFormation stack that is no longer in use. The CloudFormation stack is in the DELETE_FAILED state. The SysOps administrator has validated the permissions that are required to delete the Cloud Formation stack.

- A. The configured timeout to delete the stack was too low for the delete operation to complete.
- B. The stack contains nested stacks that must be manually deleted fast.
- C. The stack was deployed with the -disable rollback option.
- D. There are additional resources associated with a security group in the stack
- E. There are Amazon S3 buckets that still contain objects in the stack.

Answer: DE

NEW QUESTION 144

- (Exam Topic 1)

A company is running a flash sale on its website. The website is hosted on burstable performance Amazon EC2 instances in an Auto Scaling group. The Auto Scaling group is configured to launch instances when the CPU utilization is above 70%.

A couple of hours into the sale, users report slow load times and error messages for refused connections. A SysOps administrator reviews Amazon CloudWatch metrics and notices that the CPU utilization is at 20% across the entire fleet of instances.

The SysOps administrator must restore the website's functionality without making changes to the network infrastructure.

Which solution will meet these requirements?

- A. Activate unlimited mode for the instances in the Auto Scaling group.
- B. Implement an Amazon CloudFront distribution to offload the traffic from the Auto Scaling group.
- C. Move the website to a different AWS Region that is closer to the users.
- D. Reduce the desired size of the Auto Scaling group to artificially increase CPU average utilization.

Answer: B

Explanation:

Implement an Amazon CloudFront distribution to offload the traffic from the Auto Scaling group does not breach the requirement of no changes in the network infrastructure. Reason is that cloudfront is a distribution that allows you to distribute content using a worldwide network of edge locations that provide low latency and high data transfer speeds. It plug in to existing setup, not changes to it.

NEW QUESTION 147

- (Exam Topic 1)

A company plans to deploy a database on an Amazon Aurora MySQL DB cluster. The database will store data for a demonstration environment. The data must be reset on a daily basis.

What is the MOST operationally efficient solution that meets these requirements?

- A. Create a manual snapshot of the DB cluster after the data has been populate
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function on a daily basi
- C. Configure the function to restore the snapshot and then delete the previous DB cluster.
- D. Enable the Backtrack feature during the creation of the DB cluste
- E. Specify a target backtrack window of 48 hour
- F. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function on a daily basi
- G. Configure the function to perform a backtrack operation.
- H. Export a manual snapshot of the DB cluster to an Amazon S3 bucket after the data has been populated.Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function on a daily basi
- I. Configure the function to restore the snapshot from Amazon S3.
- J. Set the DB cluster backup retention period to 2 day
- K. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function on a daily basi
- L. Configure the function to restore the DB cluster to a point in time and then delete the previous DB cluster.

Answer: D

Explanation:

Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke an AWS Lambda function on a daily basis. Configure the function to restore the DB cluster to a point in time and then delete the previous DB cluster. This is the most operationally efficient solution that meets the requirements, as it will allow the company to reset the database on a daily basis without having to manually take and restore snapshots. The other solutions (creating a manual snapshot of the DB cluster, enabling the Backtrack feature, or exporting a manual snapshot of the DB cluster to Amazon S3) will require additional steps and resources to reset the

database on a daily basis.

NEW QUESTION 150

- (Exam Topic 1)

A company is using an Amazon DynamoDB table for data. A SysOps administrator must configure replication of the table to another AWS Region for disaster recovery.

What should the SysOps administrator do to meet this requirement?

- A. Enable DynamoDB Accelerator (DAX).
- B. Enable DynamoDB Streams, and add a global secondary index (GSI).
- C. Enable DynamoDB Streams, and add a global table Region.
- D. Enable point-in-time recovery.

Answer: C

NEW QUESTION 154

- (Exam Topic 1)

A company stores critical data in Amazon S3 buckets. A SysOps administrator must build a solution to record all S3 API activity. Which action will meet this requirement?

- A. Configure S3 bucket metrics to record object access logs
- B. Create an AWS CloudTrail trail to log data events for all S3 objects
- C. Enable S3 server access logging for each S3 bucket
- D. Use AWS IAM Access Analyzer for Amazon S3 to store object access logs.

Answer: B

NEW QUESTION 158

- (Exam Topic 1)

A company's IT department noticed an increase in the spend of their developer AWS account. There are over 50 developers using the account, and the finance team wants to determine the service costs incurred by each developer.

What should a SysOps administrator do to collect this information? (Select TWO.)

- A. Activate the createdBy tag in the account.
- B. Analyze the usage with Amazon CloudWatch dashboards.
- C. Analyze the usage with Cost Explorer.
- D. Configure AWS Trusted Advisor to track resource usage.
- E. Create a billing alarm in AWS Budgets.

Answer: AC

NEW QUESTION 163

- (Exam Topic 1)

An application runs on multiple Amazon EC2 instances in an Auto Scaling group. The Auto Scaling group is configured to use the latest version of a launch template. A SysOps administrator must devise a solution that centrally manages the application logs and retains the logs for no more than 90 days.

Which solution will meet these requirements?

- A. Launch an Amazon Machine Image (AMI) that is preconfigured with the Amazon CloudWatch Logs agent to send logs to an Amazon S3 bucket. Apply a 90-day S3 Lifecycle policy on the S3 bucket to expire the application logs.
- B. Launch an Amazon Machine Image (AMI) that is preconfigured with the Amazon CloudWatch Logs agent to send logs to a log group. Create an Amazon EventBridge (Amazon CloudWatch Events) scheduled rule to perform an instance refresh every 90 days.
- C. Update the launch template user data to install and configure the Amazon CloudWatch Logs agent to send logs to a log group. Configure the retention period on the log group to be 90 days.
- D. Update the launch template user data to install and configure the Amazon CloudWatch Logs agent to send logs to a log group. Set the log rotation configuration of the EC2 instances to 90 days.

Answer: C

NEW QUESTION 166

- (Exam Topic 1)

A company has launched a social media website that gives users the ability to upload images directly to a centralized Amazon S3 bucket. The website is popular in areas that are geographically distant from the AWS Region where the S3 bucket is located. Users are reporting that uploads are slow. A SysOps administrator must improve the upload speed.

What should the SysOps administrator do to meet these requirements?

- A. Create S3 access points in Regions that are closer to the users.
- B. Create an accelerator in AWS Global Accelerator for the S3 bucket.
- C. Enable S3 Transfer Acceleration on the S3 bucket.
- D. Enable cross-origin resource sharing (CORS) on the S3 bucket.

Answer: C

Explanation:

You might want to use Transfer Acceleration on a bucket for various reasons: ->Your customers upload to a centralized bucket from all over the world. ->You transfer gigabytes to terabytes of data on a regular basis across continents. ->You can't use all of your available bandwidth over the internet when uploading to Amazon S3." <https://docs.aws.amazon.com/AmazonS3/latest/userguide/transfer-acceleration.html>

NEW QUESTION 170

- (Exam Topic 1)

A company uses Amazon S3 to aggregate raw video footage from various media teams across the US. The company recently expanded into new geographies in Europe and Australia. The technical teams located in Europe and Australia reported delays when uploading large video tiles into the destination S3 bucket in the United States.

What are the MOST cost-effective ways to increase upload speeds into the S3 bucket? (Select TWO.)

- A. Create multiple AWS Direct Connect connections between AWS and branch offices in Europe and Australia for file uploads into the destination S3 bucket
- B. Create multiple AWS Site-to-Site VPN connections between AWS and branch offices in Europe and Australia for file uploads into the destination S3 bucket.
- C. Use Amazon S3 Transfer Acceleration for file uploads into the destination S3 bucket.
- D. Use AWS Global Accelerator for file uploads into the destination S3 bucket from the branch offices in Europe and Australia.
- E. Use multipart uploads for file uploads into the destination S3 bucket from the branch offices in Europe and Australia.

Answer: CE

NEW QUESTION 174

- (Exam Topic 1)

A company's SysOps administrator has created an Amazon EC2 instance with custom software that will be used as a template for all new EC2 instances across multiple AWS accounts. The Amazon Elastic Block Store (Amazon EBS) volumes that are attached to the EC2 instance are encrypted with AWS managed keys. The SysOps administrator creates an Amazon Machine Image (AMI) of the custom EC2 instance and plans to share the AMI with the company's other AWS accounts. The company requires that all AMIs are encrypted with AWS Key Management Service (AWS KMS) keys and that only authorized AWS accounts can access the shared AMIs.

Which solution will securely share the AMI with the other AWS accounts?

- A. In the account where the AMI was created, create a customer master key (CMK). Modify the key policy to provide kms:DescribeKey, kms:ReEncrypt, kms:CreateGrant, and kms:Decrypt permissions to the AWS accounts that the AMI will be shared with.
- B. Modify the AMI permissions to specify the AWS account numbers that the AMI will be shared with.
- C. In the account where the AMI was created, create a customer master key (CMK). Modify the key policy to provide kms:DescribeKey, kms:ReEncrypt*, kms:CreateGrant, and kms:Decrypt permissions to the AWS accounts that the AMI will be shared with.
- D. Create a copy of the AMI.
- E. and specify the CMK.
- F. Modify the permissions on the copied AMI to specify the AWS account numbers that the AMI will be shared with.
- G. In the account where the AMI was created, create a customer master key (CMK). Modify the key policy to provide kms:DescribeKey, kms:ReEncrypt, kms:CreateGrant, and kms:Decrypt permissions to the AWS accounts that the AMI will be shared with.
- H. Create a copy of the AMI.
- I. and specify the CMK.
- J. Modify the permissions on the copied AMI to make it public.
- K. In the account where the AMI was created, modify the key policy of the AWS managed key to provide kms:DescribeKey, kms:ReEncrypt, kms:CreateGrant, and kms:Decrypt permissions to the AWS accounts that the AMI will be shared with.
- L. kms:ReEncrypt, kms:CreateGrant, and kms:Decrypt permissions to the AWS accounts that the AMI will be shared with.
- M. Modify the AMI permissions to specify the AWS account numbers that the AMI will be shared with.

Answer: B

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/sharingamis-explicit.html>

NEW QUESTION 179

- (Exam Topic 1)

A company has a public website that recently experienced problems. Some links led to missing webpages, and other links rendered incorrect webpages. The application infrastructure was running properly, and all the provisioned resources were healthy. Application logs and dashboards did not show any errors, and no monitoring alarms were raised. Systems administrators were not aware of any problems until end users reported the issues.

The company needs to proactively monitor the website for such issues in the future and must implement a solution as soon as possible.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Rewrite the application to surface a custom error to the application log when issues occur. Automatically parse logs for error.
- B. Create an Amazon CloudWatch alarm to provide alerts when issues are detected.
- C. Create an AWS Lambda function to test the website.
- D. Configure the Lambda function to emit an Amazon CloudWatch custom metric when errors are detected.
- E. Configure a CloudWatch alarm to provide alerts when issues are detected.
- F. Create an Amazon CloudWatch Synthetic canary.
- G. Use the CloudWatch Synthetic Recorder plugin to generate the script for the canary run.
- H. Configure the canary in line with requirements.
- I. Create an alarm to provide alerts when issues are detected.

Answer: A

NEW QUESTION 180

- (Exam Topic 1)

A company's public website is hosted in an Amazon S3 bucket in the us-east-1 Region behind an Amazon CloudFront distribution. The company wants to ensure that the website is protected from DDoS attacks. A SysOps administrator needs to deploy a solution that gives the company the ability to maintain control over the rate limit at which DDoS protections are applied.

Which solution will meet these requirements?

- A. Deploy a global-scoped AWS WAF web ACL with an allow default action.
- B. Configure an AWS WAF rate-based rule to block matching traffic.
- C. Associate the web ACL with the CloudFront distribution.
- D. Deploy an AWS WAF web ACL with an allow default action in us-east-1. Configure an AWS WAF rate-based rule to block matching traffic.
- E. Associate the web ACL with the S3 bucket.
- F. Deploy a global-scoped AWS WAF web ACL with a block default action.
- G. Configure an AWS WAF rate-based rule to allow matching traffic.

- H. Associate the web ACL with the CloudFront distribution.
- I. Deploy an AWS WAF web ACL with a block default action in us-east-1. Configure an AWS WAF rate-based rule to allow matching traffic.
- J. Associate the web ACL with the S3 bucket.

Answer: B

NEW QUESTION 182

- (Exam Topic 1)

A company uses Amazon Route 53 to manage the public DNS records for the domain example.com. The company deploys an Amazon CloudFront distribution to deliver static assets for a new corporate website. The company wants to create a subdomain that is named "static" and must route traffic for the subdomain to the CloudFront distribution.

How should a SysOps administrator create a new record for the subdomain in Route 53?

- A. Create a CNAME record
- B. Enter static.cloudfront.net as the record name
- C. Enter the CloudFront distribution's public IP address as the value.
- D. Create a CNAME record
- E. Enter static.example.com as the record name
- F. Enter the CloudFront distribution's private IP address as the value.
- G. Create an A record
- H. Enter static.cloudfront.net as the record name
- I. Enter the CloudFront distribution's ID as an alias target.
- J. Create an A record
- K. Enter static.example.com as the record name
- L. Enter the CloudFront distribution's domain name as an alias target.

Answer: D

Explanation:

<https://docs.aws.amazon.com/Route53/latest/DeveloperGuide/routing-to-cloudfront-distribution.html>

NEW QUESTION 186

- (Exam Topic 1)

A company's SysOps administrator regularly checks the AWS Personal Health Dashboard in each of the company's accounts. The accounts are part of an organization in AWS Organizations. The company recently added 10 more accounts to the organization. The SysOps administrator must consolidate the alerts from each account's Personal Health Dashboard.

Which solution will meet this requirement with the LEAST amount of effort?

- A. Enable organizational view in AWS Health.
- B. Configure the Personal Health Dashboard in each account to forward events to a central AWS CloudTrail log.
- C. Create an AWS Lambda function to query the AWS Health API and to write all events to an Amazon DynamoDB table.
- D. Use the AWS Health API to write events to an Amazon DynamoDB table.

Answer: A

Explanation:

Enabling the organizational view in AWS Health will allow the SysOps administrator to consolidate the alerts from each account's Personal Health Dashboard. It will also provide the administrator with a single view of all the accounts in the organization, allowing them to easily monitor the health of all the accounts in the organization.

Reference:

[1] <https://aws.amazon.com/premiumsupport/knowledge-center/organizational-view-health-dashboard/>

NEW QUESTION 189

- (Exam Topic 1)

A company is trying to connect two applications. One application runs in an on-premises data center that has a hostname of host1.onprem.private. The other application runs on an Amazon EC2 instance that has a hostname of host1.awscloud.private. An AWS Site-to-Site VPN connection is in place between the on-premises network and AWS.

The application that runs in the data center tries to connect to the application that runs on the EC2 instance, but DNS resolution fails. A SysOps administrator must implement DNS resolution between on-premises and AWS resources.

Which solution allows the on-premises application to resolve the EC2 instance hostname?

- A. Set up an Amazon Route 53 inbound resolver endpoint with a forwarding rule for the onprem.private hosted zone
- B. Associate the resolver with the VPC of the EC2 instance
- C. Configure the on-premises DNS resolver to forward onprem.private DNS queries to the inbound resolver endpoint.
- D. Set up an Amazon Route 53 inbound resolver endpoint
- E. Associate the resolver with the VPC of the EC2 instance
- F. Configure the on-premises DNS resolver to forward awscloud.private DNS queries to the inbound resolver endpoint.
- G. Set up an Amazon Route 53 outbound resolver endpoint with a forwarding rule for the onprem.private hosted zone
- H. Associate the resolver with the AWS Region of the EC2 instance
- I. Configure the on-premises DNS resolver to forward onprem.private DNS queries to the outbound resolver endpoint.
- J. Set up an Amazon Route 53 outbound resolver endpoint
- K. Associate the resolver with the AWS Region of the EC2 instance
- L. Configure the on-premises DNS resolver to forward awscloud.private DNS queries to the outbound resolver endpoint.

Answer: C

NEW QUESTION 194

- (Exam Topic 1)

A SysOps administrator is creating two AWS CloudFormation templates. The first template will create a VPC with associated resources, such as subnets, route

tables, and an internet gateway. The second template will deploy application resources within the VPC that was created by the first template. The second template should refer to the resources created by the first template.

How can this be accomplished with the LEAST amount of administrative effort?

- A. Add an export field to the outputs of the first template and import the values in the second template.
- B. Create a custom resource that queries the stack created by the first template and retrieves the required values.
- C. Create a mapping in the first template that is referenced by the second template.
- D. Input the names of resources in the first template and refer to those names in the second template as a parameter.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/using-cfn-stack-exports.html>

NEW QUESTION 197

- (Exam Topic 1)

A SysOps administrator is designing a solution for an Amazon RDS for PostgreSQL DB instance. Database credentials must be stored and rotated monthly. The applications that connect to the DB instance send write-intensive traffic with variable client connections that sometimes increase significantly in a short period of time. Which solution should a SysOps administrator choose to meet these requirements?

- A. Configure AWS Key Management Service (AWS KMS) to automatically rotate the keys for the DB instance.
- B. Use RDS Proxy to handle the increases in database connections.
- C. Configure AWS Key Management Service (AWS KMS) to automatically rotate the keys for the DB instance.
- D. Use RDS read replicas to handle the increases in database connections.
- E. Configure AWS Secrets Manager to automatically rotate the credentials for the DB instance.
- F. Use RDS Proxy to handle the increases in database connections.
- G. Configure AWS Secrets Manager to automatically rotate the credentials for the DB instance.
- H. Use RDS read replicas to handle the increases in database connections.

Answer: A

NEW QUESTION 198

- (Exam Topic 1)

A company's backend infrastructure contains an Amazon EC2 instance in a private subnet. The private subnet has a route to the internet through a NAT gateway in a public subnet. The instance must allow connectivity to a secure web server on the internet to retrieve data at regular intervals. The client software times out with an error message that indicates that the client software could not establish the TCP connection. What should a SysOps administrator do to resolve this error?

- A. Add an inbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP, Source - 0.0.0.0/0.
- B. Add an inbound rule to the security group for the EC2 instance with the following parameters: Type - HTTPS, Source - 0.0.0.0/0.
- C. Add an outbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP, Destination - 0.0.0.0/0.
- D. Add an outbound rule to the security group for the EC2 instance with the following parameters: Type - HTTP
- E. Destination - 0.0.0.0/0.

Answer: D

NEW QUESTION 202

- (Exam Topic 1)

A company is creating a new multi-account architecture. A Sysops administrator must implement a login solution to centrally manage user access and permissions across all AWS accounts. The solution must be integrated with AWS Organizations and must be connected to a third-party Security Assertion Markup Language (SAML) 2.0 identity provider (IdP).

What should the SysOps administrator do to meet these requirements?

- A. Configure an Amazon Cognito user pool
- B. Integrate the user pool with the third-party IdP.
- C. Enable and configure AWS Single Sign-On with the third-party IdP.
- D. Federate the third-party IdP with AWS Identity and Access Management (IAM) for each AWS account in the organization.
- E. Integrate the third-party IdP directly with AWS Organizations.

Answer: A

NEW QUESTION 204

- (Exam Topic 1)

A SysOps administrator is attempting to download patches from the internet into an instance in a private subnet. An internet gateway exists for the VPC, and a NAT gateway has been deployed on the public subnet; however, the instance has no internet connectivity. The resources deployed into the private subnet must be inaccessible directly from the public internet.

Public Subnet (10.0.1.0/24) Route Table

Destination	Target
10.0.0.0/16	local
0.0.0.0/0	IGW

Private Subnet (10.0.2.0/24) Route Table

Destination	Target
10.0.0.0/16	local

What should be added to the private subnet's route table in order to address this issue, given the information provided?

- A. 0.0.0.0/0 IGW
- B. 0.0.0.0/0 NAT
- C. 10.0.1.0/24 IGW
- D. 10.0.1.0/24 NAT

Answer: B

NEW QUESTION 209

- (Exam Topic 1)

A recent audit found that most resources belonging to the development team were in violation of patch compliance standards. The resources were properly tagged. Which service should be used to quickly remediate the issue and bring the resources back into compliance?

- A. AWS Config
- B. Amazon Inspector
- C. AWS Trusted Advisor
- D. AWS Systems Manager

Answer: D

NEW QUESTION 212

- (Exam Topic 1)

A company has a critical serverless application that uses multiple AWS Lambda functions. Each Lambda function generates 1 GB of log data daily in its own Amazon CloudWatch Logs log group. The company's security team asks for a count of application errors, grouped by type, across all of the log groups. What should a SysOps administrator do to meet this requirement?

- A. Perform a CloudWatch Logs Insights query that uses the stats command and count function.
- B. Perform a CloudWatch Logs search that uses the groupby keyword and count function.
- C. Perform an Amazon Athena query that uses the SELECT and GROUP BY keywords.
- D. Perform an Amazon RDS query that uses the SELECT and GROUP BY keywords.

Answer: A

NEW QUESTION 214

- (Exam Topic 1)

A company is using an AWS KMS customer master key (CMK) with imported key material. The company references the CMK by its alias in the Java application to encrypt data. The CMK must be rotated every 6 months. What is the process to rotate the key?

- A. Enable automatic key rotation for the CMK and specify a period of 6 months.
- B. Create a new CMK with new imported material, and update the key alias to point to the new CMK.
- C. Delete the current key material, and import new material into the existing CMK.
- D. Import a copy of the existing key material into a new CMK as a backup, and set the rotation schedule for 6 months.

Answer: B

NEW QUESTION 219

- (Exam Topic 1)

A company is using Amazon Elastic Container Service (Amazon ECS) to run a containerized application on Amazon EC2 instances. A SysOps administrator needs to monitor only traffic flows between the ECS tasks.

Which combination of steps should the SysOps administrator take to meet this requirement? (Select TWO.)

- A. Configure Amazon CloudWatch Logs on the elastic network interface of each task.
- B. Configure VPC Flow Logs on the elastic network interface of each task.
- C. Specify the awsvpc network mode in the task definition.
- D. Specify the bridge network mode in the task definition.
- E. Specify the host network mode in the task definition.

Answer: AE

NEW QUESTION 223

- (Exam Topic 1)

A company is using Amazon CloudFront to serve static content for its web application to its users. The CloudFront distribution uses an existing on-premises website as a custom origin.

The company requires the use of TLS between CloudFront and the origin server. This configuration has worked as expected for several months. However, users are now experiencing HTTP 502 (Bad Gateway) errors when they view webpages that include content from the CloudFront distribution.

What should a SysOps administrator do to resolve this problem?

- A. Examine the expiration date on the certificate on the origin site.
- B. Validate that the certificate has not expired.
- C. Replace the certificate if necessary.
- D. Examine the hostname on the certificate on the origin site.
- E. Validate that the hostname matches one of the hostnames on the CloudFront distribution.
- F. Replace the certificate if necessary.
- G. Examine the firewall rules that are associated with the origin server.
- H. Validate that port 443 is open for inbound traffic from the internet.
- I. Create an inbound rule if necessary.
- J. Examine the network ACL rules that are associated with the CloudFront distribution.
- K. Validate that port 443 is open for outbound traffic to the origin server.

L. Create an outbound rule if necessary.

Answer: A

Explanation:

HTTP 502 errors from CloudFront can occur because of the following reasons:

There's an SSL negotiation failure because the origin is using SSL/TLS protocols and ciphers that aren't supported by CloudFront.

There's an SSL negotiation failure because the SSL certificate on the origin is expired or invalid, or because the certificate chain is invalid.

There's a host header mismatch in the SSL negotiation between your CloudFront distribution and the custom origin.

The custom origin isn't responding on the ports specified in the origin settings of the CloudFront distribution. The custom origin is ending the connection to CloudFront too quickly.

<https://aws.amazon.com/premiumsupport/knowledge-center/resolve-cloudfront-connection-error/>

NEW QUESTION 227

- (Exam Topic 1)

A large company is using AWS Organizations to manage its multi-account AWS environment. According to company policy, all users should have read-level access to a particular Amazon S3 bucket in a central account. The S3 bucket data should not be available outside the organization. A SysOps administrator must set up the permissions and add a bucket policy to the S3 bucket.

Which parameters should be specified to accomplish this in the MOST efficient manner?

- A. Specify '*' as the principal and PrincipalOrgId as a condition.
- B. Specify all account numbers as the principal.
- C. Specify PrincipalOrgId as the principal.
- D. Specify the organization's management account as the principal.

Answer: C

NEW QUESTION 232

- (Exam Topic 1)

A company has a simple web application that runs on a set of Amazon EC2 instances behind an Elastic Load Balancer in the eu-west-2 Region. Amazon Route 53 holds a DNS record for the application with a simple routing policy. Users from all over the world access the application through their web browsers.

The company needs to create additional copies of the application in the us-east-1 Region and in the ap-south-1 Region. The company must direct users to the Region that provides the fastest response times when the users load the application.

What should a SysOps administrator do to meet these requirements?

- A. In each new Region, create a new Elastic Load Balancer and a new set of EC2 Instances to run a copy of the applicatio
- B. Transition to a geolocation routing policy.
- C. In each new Region, create a copy of the application on new EC2 instance
- D. Add these new EC2 instances to the Elastic Load Balancer in eu-west-2. Transition to a latency routing policy.
- E. In each new Region, create a copy of the application on new EC2 instance
- F. Add these new EC2 instances to the Elastic Load Balancer in eu-west-2. Transition to a multivalued routing policy.
- G. In each new Region, create a new Elastic Load Balancer and a new set of EC2 instances to run a copy of the applicatio
- H. Transition to a latency routing policy.

Answer: B

NEW QUESTION 233

- (Exam Topic 1)

A company stores sensitive data in an Amazon S3 bucket. The company must log all access attempts to the S3 bucket. The company's risk team must receive immediate notification about any delete events.

Which solution will meet these requirements?

- A. Enable S3 server access logging for audit log
- B. Set up an Amazon Simple Notification Service (Amazon SNS) notification for the S3 bucket
- C. Select DeleteObject for the event type for the alert system.
- D. Enable S3 server access logging for audit log
- E. Launch an Amazon EC2 instance for the alert system. Run a cron job on the EC2 instance to download the access logs each day and to scan for a DeleteObject event.
- F. Use Amazon CloudWatch Logs for audit log
- G. Use Amazon CloudWatch alarms with an Amazon Simple Notification Service (Amazon SNS) notification for the alert system.
- H. Use Amazon CloudWatch Logs for audit log
- I. Launch an Amazon EC2 instance for the alert system. Run a cron job on the EC2 instance each day to compare the list of the items with the list from the previous day
- J. Configure the cron job to send a notification if an item is missing.

Answer: A

Explanation:

To meet the requirements of logging all access attempts to the S3 bucket and receiving immediate notification about any delete events, the company can enable S3 server access logging and set up an Amazon Simple Notification Service (Amazon SNS) notification for the S3 bucket. The S3 server access logs will record all access attempts to the bucket, including delete events, and the SNS notification can be configured to send an alert when a DeleteObject event occurs.

NEW QUESTION 238

- (Exam Topic 1)

A large company is using AWS Organizations to manage hundreds of AWS accounts across multiple AWS Regions. The company has turned on AWS Config throughout the organization.

The company requires all Amazon S3 buckets to block public read access. A SysOps administrator must generate a monthly report that shows all the S3 buckets and whether they comply with this requirement.

Which combination of steps should the SysOps administrator take to collect this data? (Select TWO).

- A. Create an AWS Config aggregator in an aggregator account
- B. Use the organization as the source. Retrieve the compliance data from the aggregator.
- C. Create an AWS Config aggregator in each account
- D. Use an S3 bucket in an aggregator account as the destination
- E. Retrieve the compliance data from the S3 bucket
- F. Edit the AWS Config policy in AWS Organization
- G. Use the organization's management account to turn on the s3-bucket-public-read-prohibited rule for the entire organization.
- H. Use the AWS Config compliance report from the organization's management account
- I. Filter the results by resource, and select Amazon S3.
- J. Use the AWS Config API to apply the s3-bucket-public-read-prohibited rule in all accounts for all available Regions.

Answer: CD

NEW QUESTION 243

- (Exam Topic 1)

A development team recently deployed a new version of a web application to production. After the release, penetration testing revealed a cross-site scripting vulnerability that could expose user data.

Which AWS service will mitigate this issue?

- A. AWS Shield Standard
- B. AWS WAF
- C. Elastic Load Balancing
- D. Amazon Cognito

Answer: A

NEW QUESTION 246

- (Exam Topic 1)

A company runs a web application on three Amazon EC2 instances behind an Application Load Balancer (ALB). The company notices that random periods of increased traffic cause a degradation in the application's performance. A SysOps administrator must scale the application to meet the increased traffic. Which solution meets these requirements?

- A. Create an Amazon CloudWatch alarm to monitor application latency and increase the size of each EC2 instance if the desired threshold is reached.
- B. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to monitor application latency and add an EC2 instance to the ALB if the desired threshold is reached.
- C. Deploy the application to an Auto Scaling group of EC2 instances with a target tracking scaling policy. Attach the ALB to the Auto Scaling group.
- D. Deploy the application to an Auto Scaling group of EC2 instances with a scheduled scaling policy. Attach the ALB to the Auto Scaling group.

Answer: C

NEW QUESTION 251

- (Exam Topic 1)

An application accesses data through a file system interface. The application runs on Amazon EC2 instances in multiple Availability Zones, all of which must share the same data. While the amount of data is currently small, the company anticipates that it will grow to tens of terabytes over the lifetime of the application.

What is the MOST scalable storage solution to fulfill this requirement?

- A. Connect a large Amazon EBS volume to multiple instances and schedule snapshots.
- B. Deploy Amazon EFS in the VPC and create mount targets in multiple subnets.
- C. Launch an EC2 instance and share data using SMB/CIFS or NFS.
- D. Deploy an AWS Storage Gateway cached volume on Amazon EC2.

Answer: B

NEW QUESTION 252

- (Exam Topic 1)

A SysOps administrator must manage the security of an AWS account. Recently an IAM user's access key was mistakenly uploaded to a public code repository. The SysOps administrator must identify anything that was changed by using this access key.

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to send all IAM events to an AWS Lambda function for analysis
- B. Query Amazon EC2 logs by using Amazon CloudWatch Logs Insights for all events related to the compromised access key within the suspected timeframe
- C. Search AWS CloudTrail event history for all events initiated with the compromised access key within the suspected timeframe
- D. Search VPC Flow Logs for all events initiated with the compromised access key within the suspected timeframe.

Answer: C

NEW QUESTION 256

- (Exam Topic 1)

A SysOps administrator is configuring an application on Amazon EC2 instances for a company. Teams in other countries will use the application over the internet. The company requires the application endpoint to have a static public IP address.

How should the SysOps administrator deploy the application to meet this requirement?

- A. Behind an Amazon API Gateway API
- B. Behind an Application Load Balancer
- C. Behind an internet-facing Network Load Balancer
- D. In an Amazon CloudFront distribution

Answer: C

NEW QUESTION 260

- (Exam Topic 1)

A SysOps administrator is trying to set up an Amazon Route 53 domain name to route traffic to a website hosted on Amazon S3. The domain name of the website is `www.anycompany.com` and the S3 bucket name is `anycompany-static`. After the record set is set up in Route 53, the domain name `www.anycompany.com` does not seem to work, and the static website is not displayed in the browser.

Which of the following is a cause of this?

- A. The S3 bucket must be configured with Amazon CloudFront first.
- B. The Route 53 record set must have an IAM role that allows access to the S3 bucket.
- C. The Route 53 record set must be in the same region as the S3 bucket.
- D. The S3 bucket name must match the record set name in Route 53.

Answer: D

NEW QUESTION 263

- (Exam Topic 1)

A SysOps administrator has launched a large general purpose Amazon EC2 instance to regularly process large data files. The instance has an attached 1 TB General Purpose SSD (gp2) Amazon Elastic Block Store (Amazon EBS) volume. The instance also is EBS-optimized. To save costs, the SysOps administrator stops the instance each evening and restarts the instance each morning.

When data processing is active, Amazon CloudWatch metrics on the instance show a consistent 3,000 VolumeReadOps. The SysOps administrator must improve the I/O performance while ensuring data integrity.

Which action will meet these requirements?

- A. Change the instance type to a large, burstable, general purpose instance.
- B. Change the instance type to an extra large general purpose instance.
- C. Increase the EBS volume to a 2 TB General Purpose SSD (gp2) volume.
- D. Move the data that resides on the EBS volume to the instance store.

Answer: C

NEW QUESTION 268

- (Exam Topic 1)

A SysOps administrator has Nocked public access to all company Amazon S3 buckets. The SysOps administrator wants to be notified when an S3 bucket becomes publicly readable in the future.

What is the MOST operationally efficient way to meet this requirement?

- A. Create an AWS Lambda function that periodically checks the public access settings for each S3 bucket. Set up Amazon Simple Notification Service (Amazon SNS) to send notifications.
- B. Create a cron script that uses the S3 API to check the public access settings for each S3 bucket.
- C. Set up Amazon Simple Notification Service (Amazon SNS) to send notifications.
- D. Enable S3 Event notifications for each S3 bucket.
- E. Subscribe S3 Event Notifications to an Amazon Simple Notification Service (Amazon SNS) topic.
- F. Enable the `s3-bucket-public-read-prohibited` managed rule in AWS Config.
- G. Subscribe the AWS Config rule to an Amazon Simple Notification Service (Amazon SNS) topic.

Answer: D

NEW QUESTION 269

- (Exam Topic 1)

A SysOps administrator needs to configure automatic rotation for Amazon RDS database credentials. The credentials must rotate every 30 days. The solution must integrate with Amazon RDS.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Store the credentials in AWS Systems Manager Parameter Store as a secure string.
- B. Configure automatic rotation with a rotation interval of 30 days.
- C. Store the credentials in AWS Secrets Manager.
- D. Configure automatic rotation with a rotation interval of 30 days.
- E. Store the credentials in a file in an Amazon S3 bucket.
- F. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.
- G. Store the credentials in AWS Secrets Manager.
- H. Deploy an AWS Lambda function to automatically rotate the credentials every 30 days.

Answer: B

Explanation:

Storing the credentials in AWS Secrets Manager and configuring automatic rotation with a rotation interval of 30 days is the most efficient way to meet the requirements with the least operational overhead. AWS Secrets Manager automatically rotates the credentials at the specified interval, so there is no need for an additional AWS Lambda function or manual rotation. Additionally, Secrets Manager is integrated with Amazon RDS, so the credentials can be easily used with the RDS database.

NEW QUESTION 271

- (Exam Topic 1)

A company has an Amazon CloudFront distribution that uses an Amazon S3 bucket as its origin. During a review of the access logs, the company determines that some requests are going directly to the S3 bucket by using the website hosting endpoint. A SysOps administrator must secure the S3 bucket to allow requests only from CloudFront.

What should the SysOps administrator do to meet this requirement?

- A. Create an origin access identity (OAI) in CloudFront.
- B. Associate the OAI with the distribution.

- C. Remove access to and from other principals in the S3 bucket polic
- D. Update the S3 bucket policy to allow access only from the OAI.
- E. Create an origin access identity (OAI) in CloudFron
- F. Associate the OAI with the distributio
- G. Update the S3 bucket policy to allow access only from the OA
- H. Create a new origin, and specify the S3 bucket as the new origi
- I. Update the distribution behavior to use the new origi
- J. Remove the existing origin.
- K. Create an origin access identity (OAI) in CloudFron
- L. Associate the OAI with the distributio
- M. Update the S3 bucket policy to allow access only from the OA
- N. Disable website hostin
- O. Create a new origin, and specify the S3 bucket as the new origi
- P. Update the distribution behavior to use the new origi
- Q. Remove the existing origin.
- R. Update the S3 bucket policy to allow access only from the CloudFront distributio
- S. Remove access to and from other principals in the S3 bucket polic
- T. Disable website hostin
- . Create a new origin, and specify the S3 bucket as the new origi
- . Update the distribution behavior to use the new origi
- . Remove the existing origin.

Answer: A

NEW QUESTION 273

- (Exam Topic 1)

A SysOps administrator needs to track the costs of data transfer between AWS Regions. The SysOps administrator must implement a solution to send alerts to an email distribution list when transfer costs reach 75% of a specific threshold.

What should the SysOps administrator do to meet these requirements?

- A. Create an AWS Cost and Usage Repor
- B. Analyze the results in Amazon Athen
- C. Configure an alarm to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic when costs reach 75% of the threshol
- D. Subscribe the email distribution list to the topic.
- E. Create an Amazon CloudWatch billing alarm to detect when costs reach 75% of the threshold. Configure the alarm to publish a message to an Amazon Simple Notification Service (Amazon SNS) topi
- F. Subscribe the email distribution list to the topic.
- G. Use AWS Budgets to create a cost budget for data transfer cost
- H. Set an alert at 75% of the budgeted amoun
- I. Configure the budget to send a notification to the email distribution list when costs reach 75% of the threshold.
- J. Set up a VPC flow lo
- K. Set up a subscription filter to an AWS Lambda function to analyze data transfer. Configure the Lambda function to send a notification to the email distribution list when costs reach 75% of the threshold.

Answer: B

Explanation:

The reason is that it uses the Amazon CloudWatch billing alarm which is a built-in service specifically designed to monitor and alert on cost usage of your AWS account, which makes it a more suitable solution for this use case. The alarm can be configured to detect when costs reach 75% of the threshold and when it is triggered, it can publish a message to an Amazon Simple Notification Service (Amazon SNS) topic. The email distribution list can be subscribed to the topic, so that they will receive the alerts when costs reach 75% of the threshold.

AWS Budgets allows you to track and manage your costs, but it doesn't specifically focus on data transfer costs between regions, and it might not provide as much granularity as CloudWatch Alarms.

NEW QUESTION 277

- (Exam Topic 1)

A company uses an Amazon CloudFront distribution to deliver its website Traffic logs for the website must be centrally stored and all data must be encrypted at rest

Which solution will meet these requirements?

- A. Create an Amazon OpenSearch Service (Amazon ElastiSearch Service) domain with internet access and server-side encryption that uses the default AWS managed key Configure CloudFront to use the Amazon OpenSearch Service (Amazon Elasticsearch Service) domain as a log destination
- B. Create an Amazon OpenSearch Service (Amazon Elasticsearch Service) domain with VPC access and server-side encryption that uses AES-256 Configure CloudFront to use the Amazon OpenSearch Service (Amazon ElastiSearch Service) domain as a log destination
- C. Create an Amazon S3 bucket that is configured with default server side encryption that uses AES-256 Configure CloudFront to use the S3 bucket as a log destination
- D. Create an Amazon S3 bucket that is configured with no default encryption Enable encryption in the CloudFront distribution and use the S3 bucket as a log destination

Answer: C

NEW QUESTION 281

- (Exam Topic 1)

A company's customers are reporting increased latency while accessing static web content from Amazon S3 A SysOps administrator observed a very high rate of read operations on a particular S3 bucket

What will minimize latency by reducing load on the S3 bucket?

- A. Migrate the S3 bucket to a region that is closer to end users' geographic locations
- B. Use cross-region replication to replicate all of the data to another region
- C. Create an Amazon CloudFront distribution with the S3 bucket as the origin.

D. Use Amazon ElastiCache to cache data being served from Amazon S3

Answer: C

NEW QUESTION 283

- (Exam Topic 1)

A company uses Amazon Elasticsearch Service (Amazon ES) to analyze sales and customer usage data. Members of the company's geographically dispersed sales team are traveling. They need to log in to Kibana by using their existing corporate credentials that are stored in Active Directory. The company has deployed Active Directory Federation Services (AD FS) to enable authentication to cloud services. Which solution will meet these requirements?

- A. Configure Active Directory as an authentication provider in Amazon E
- B. Add the Active Directory server's domain name to Amazon E
- C. Configure Kibana to use Amazon ES authentication.
- D. Deploy an Amazon Cognito user pool
- E. Configure Active Directory as an external identity provider for the user pool
- F. Enable Amazon Cognito authentication for Kibana on Amazon ES.
- G. Enable Active Directory user authentication in Kibana
- H. Create an IP-based custom domain access policy in Amazon ES that includes the Active Directory server's IP address.
- I. Establish a trust relationship with Kibana on the Active Directory server
- J. Enable Active Directory user authentication in Kibana
- K. Add the Active Directory server's IP address to Kibana.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/security/how-to-enable-secure-access-to-kibana-using-aws-single-sign-on/> <https://docs.aws.amazon.com/elasticsearch-service/latest/developerguide/es-cognito-auth.html>

NEW QUESTION 287

- (Exam Topic 1)

A company's SysOps administrator deploys four new Amazon EC2 instances by using the standard Amazon Linux 2 Amazon Machine Image (AMI). The company needs to be able to use AWS Systems Manager to manage the instances. The SysOps administrator notices that the instances do not appear in the Systems Manager console.

What must the SysOps administrator do to resolve this issue?

- A. Connect to each instance by using SSH. Install Systems Manager Agent on each instance. Configure Systems Manager Agent to start automatically when the instances start up.
- B. Use AWS Certificate Manager (ACM) to create a TLS certificate. Import the certificate into each instance. Configure Systems Manager Agent to use the TLS certificate for secure communications.
- C. Connect to each instance by using SSH. Create an ssm-user account. Add the ssm-user account to the /etc/sudoers.d directory.
- D. Attach an IAM instance profile to the instances. Ensure that the instance profile contains the AmazonSSMManagedInstanceCore policy.

Answer: D

NEW QUESTION 288

- (Exam Topic 1)

A company is expanding globally and needs to back up data on Amazon Elastic Block Store (Amazon EBS) volumes to a different AWS Region. Most of the EBS volumes that store the data are encrypted, but some of the EBS volumes are unencrypted. The company needs the backup data from all the EBS volumes to be encrypted.

Which solution will meet these requirements with the LEAST management overhead?

- A. Configure a lifecycle policy in Amazon Data Lifecycle Manager (Amazon DLM) to create the EBS volume snapshots with cross-Region backups enabled.
- B. Encrypt the snapshot copies by using AWS Key Management Service (AWS KMS).
- C. Create a point-in-time snapshot of the EBS volume.
- D. When the snapshot status is COMPLETED, copy the snapshots to another Region and set the Encrypted parameter to False.
- E. Create a point-in-time snapshot of the EBS volume.
- F. Copy the snapshots to an Amazon S3 bucket that uses server-side encryption.
- G. Turn on S3 Cross-Region Replication on the S3 bucket.
- H. Schedule an AWS Lambda function with the Python runtime.
- I. Configure the Lambda function to create the EBS volume snapshots, encrypt the unencrypted snapshots, and copy the snapshots to another Region.

Answer: A

Explanation:

Encrypt the snapshot copies by using AWS Key Management Service (AWS KMS). This solution will allow the company to automatically create encrypted snapshots of the EBS volumes and copy them to different AWS Regions with minimal effort.

NEW QUESTION 291

- (Exam Topic 1)

A SysOps administrator must ensure that a company's Amazon EC2 instances auto scale as expected. The SysOps administrator configures an Amazon EC2 Auto Scaling Lifecycle hook to send an event to Amazon EventBridge (Amazon CloudWatch Events), which then invokes an AWS Lambda function to configure the EC2 instances. When the configuration is complete, the Lambda function calls the complete Lifecycle-action event to put the EC2 instances into service. In testing, the SysOps administrator discovers that the Lambda function is not invoked when the EC2 instances auto scale.

What should the SysOps administrator do to resolve this issue?

- A. Add a permission to the Lambda function so that it can be invoked by the EventBridge (CloudWatch Events) rule.
- B. Change the lifecycle hook action to CONTINUE if the lifecycle hook experiences a failure or timeout.
- C. Configure a retry policy in the EventBridge (CloudWatch Events) rule to retry the Lambda function invocation upon failure.
- D. Update the Lambda function execution role so that it has permission to call the complete lifecycle-action event.

Answer: D

NEW QUESTION 294

- (Exam Topic 1)

A Sysops administrator creates an Amazon Elastic Kubernetes Service (Amazon EKS) cluster that uses AWS Fargate. The cluster is deployed successfully. The Sysops administrator needs to manage the cluster by using the kubectl command line tool.

Which of the following must be configured on the Sysops administrator's machine so that kubectl can communicate with the cluster API server?

- A. The kubeconfig file
- B. The kube-proxy Amazon EKS add-on
- C. The Fargate profile
- D. The eks-connector.yaml file

Answer: A

Explanation:

The kubeconfig file is a configuration file used to store cluster authentication information, which is required to make requests to the Amazon EKS cluster API server. The kubeconfig file will need to be configured on the SysOps administrator's machine in order for kubectl to be able to communicate with the cluster API server.

<https://aws.amazon.com/blogs/developer/running-a-kubernetes-job-in-amazon-eks-on-aws-fargate-using-aws-ste>

NEW QUESTION 298

- (Exam Topic 1)

A company is running an application on a fleet of Amazon EC2 instances behind an Application Load Balancer (ALB). The EC2 instances are launched by an Auto Scaling group and are automatically registered in a target group. A SysOps administrator must set up a notification to alert application owners when targets fail health checks.

What should the SysOps administrator do to meet these requirements?

- A. Create an Amazon CloudWatch alarm on the UnHealthyHostCount metri
- B. Configure an action to send an Amazon Simple Notification Service (Amazon SNS) notification when the metric is greater than 0.
- C. Configure an Amazon EC2 Auto Scaling custom lifecycle action to send an Amazon Simple Notification Service (Amazon SNS) notification when an instance is in the Pending:Wait state.
- D. Update the Auto Scaling grou
- E. Configure an activity notification to send an Amazon Simple Notification Service (Amazon SNS) notification for the Unhealthy event type.
- F. Update the ALB health check to send an Amazon Simple Notification Service (Amazon SNS) notification when an instance is unhealthy.

Answer: A

NEW QUESTION 302

- (Exam Topic 1)

A company is planning to host its stateful web-based applications on AWS. A SysOps administrator is using an Auto Scaling group of Amazon EC2 instances. The web applications will run 24 hours a day 7 days a week throughout the year. The company must be able to change the instance type within the same instance family later in the year based on the traffic and usage patterns.

Which EC2 instance purchasing option will meet these requirements MOST cost-effectively?

- A. Convertible Reserved Instances
- B. On-Demand instances
- C. Spot instances
- D. Standard Reserved instances

Answer: A

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ri-convertible-exchange.html>

NEW QUESTION 304

- (Exam Topic 1)

An existing, deployed solution uses Amazon EC2 instances with Amazon EBS General Purpose SSD volumes, an Amazon RDS PostgreSQL database, an Amazon EFS file system, and static objects stored in an Amazon S3 bucket. The Security team now mandates that at-rest encryption be turned on immediately for all aspects of the application, without creating new resources and without any downtime.

To satisfy the requirements, which one of these services can the SysOps administrator enable at-rest encryption on?

- A. EBS General Purpose SSD volumes
- B. RDS PostgreSQL database
- C. Amazon EFS file systems
- D. S3 objects within a bucket

Answer: D

Explanation:

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/UsingEncryption.html>

NEW QUESTION 307

- (Exam Topic 1)

A company is expanding its use of AWS services across its portfolios. The company wants to provision AWS accounts for each team to ensure a separation of business processes for security compliance and billing. Account creation and bootstrapping should be completed in a scalable and efficient way so new accounts are created with a defined baseline and governance guardrails in place. A SysOps administrator needs to design a provisioning process that saves time and resources.

Which action should be taken to meet these requirements?

- A. Automate using AWS Elastic Beanstalk to provision the AWS accounts set up infrastructure and integrate with AWS Organizations
- B. Create bootstrapping scripts in AWS OpsWorks and combine them with AWS CloudFormation templates to provision accounts and infrastructure
- C. Use AWS Config to provision accounts and deploy instances using AWS Service Catalog
- D. Use AWS Control Tower to create a template in Account Factory and use the template to provision new accounts

Answer: D

NEW QUESTION 308

- (Exam Topic 1)

A company wants to collect data from an application to use for analytics. For the first 90 days, the data will be infrequently accessed but must remain highly available. During this time, the company's analytics team requires access to the data in milliseconds. However, after 90 days, the company must retain the data for the long term at a lower cost. The retrieval time after 90 days must be less than 5 hours.

Which solution will meet these requirements MOST cost-effectively?

- A. Store the data in S3 Standard-Infrequent Access (S3 Standard-IA) for the first 90 day
- B. Set up an S3 Lifecycle rule to move the data to S3 Glacier Flexible Retrieval after 90 days.
- C. Store the data in S3 One Zone-Infrequent Access (S3 One Zone-IA) for the first 90 day
- D. Set up an S3 Lifecycle rule to move the data to S3 Glacier Deep Archive after 90 days.
- E. Store the data in S3 Standard for the first 90 day
- F. Set up an S3 Lifecycle rule to move the data to S3 Glacier Flexible Retrieval after 90 days.
- G. Store the data in S3 Standard for the first 90 day
- H. Set up an S3 Lifecycle rule to move the data to S3 Glacier Deep Archive after 90 days.

Answer: A

Explanation:

Glacier Deep Archive retrieval time more than 5 hours (it's 12 hours), so B&D out. S3 Standard IA is cheaper than S3 Standard.
<https://aws.amazon.com/tw/s3/pricing/>

NEW QUESTION 312

- (Exam Topic 1)

A data storage company provides a service that gives users the ability to upload and download files as needed. The files are stored in Amazon S3 Standard and must be immediately retrievable for 1 year. Users access files frequently during the first 30 days after the files are stored. Users rarely access files after 30 days. The company's SysOps administrator must use S3 Lifecycle policies to implement a solution that maintains object availability and minimizes cost. Which solution will meet these requirements?

- A. Move objects to S3 Glacier after 30 days.
- B. Move objects to S3 One Zone-Infrequent Access (S3 One Zone-IA) after 30 days.
- C. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) after 30 days.
- D. Move objects to S3 Standard-Infrequent Access (S3 Standard-IA) immediately.

Answer: C

Explanation:

<https://aws.amazon.com/s3/storage-classes/>

NEW QUESTION 314

- (Exam Topic 1)

A company has attached the following policy to an IAM user:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "rds:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    },
    {
      "Effect": "Deny",
      "NotAction": [
        "ec2:*",
        "s3:GetObject"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "ec2:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "ec2:Region": "us-east-1"
        }
      }
    },
    {
      "Effect": "Deny",
      "NotAction": [
        "ec2:*",
        "s3:GetObject"
      ],
      "Resource": "*"
    }
  ]
}
```

Which of the following actions are allowed for the IAM user?

- A. Amazon RDS DescribeDBInstances action in the us-east-1 Region
- B. Amazon S3 Putobject operation in a bucket named testbucket
- C. Amazon EC2 Describe Instances action in the us-east-1 Region
- D. Amazon EC2 AttachNetworkinterface action in the eu-west-1 Region

Answer: C

NEW QUESTION 315

- (Exam Topic 1)

A company plans to migrate several of its high performance computing (HPC) virtual machines (VMs) to Amazon EC2 instances on AWS. A SysOps administrator must identify a placement group for this deployment. The strategy must minimize network latency and must maximize network throughput between the HPC VMs. Which strategy should the SysOps administrator choose to meet these requirements?

- A. Deploy the instances in a cluster placement group in one Availability Zone.
- B. Deploy the instances in a partition placement group in two Availability Zones
- C. Deploy the instances in a partition placement group in one Availability Zone
- D. Deploy the instances in a spread placement group in two Availability Zones

Answer: A

NEW QUESTION 318

- (Exam Topic 1)

A company runs an application on Amazon EC2 instances. The EC2 instances are in an Auto Scaling group and run behind an Application Load Balancer (ALB). The application experiences errors when total requests exceed 100 requests per second. A SysOps administrator must collect information about total requests for a 2-week period to determine when requests exceeded this threshold.

What should the SysOps administrator do to collect this data?

- A. Use the ALB's RequestCount metri
- B. Configure a time range of 2 weeks and a period of 1 minute. Examine the chart to determine peak traffic times and volumes.
- C. Use Amazon CloudWatch metric math to generate a sum of request counts for all the EC2 instances over a 2-week perio
- D. Sort by a 1-minute interval.
- E. Create Amazon CloudWatch custom metrics on the EC2 launch configuration templates to create aggregated request metrics across all the EC2 instances.
- F. Create an Amazon EventBridge (Amazon CloudWatch Events) rul
- G. Configure an EC2 event matching pattern that creates a metric that is based on EC2 request
- H. Display the data in a graph.

Answer: A

Explanation:

Using the ALB's RequestCount metric will allow the SysOps administrator to collect information about total requests for a 2-week period and determine when requests exceeded the threshold of 100 requests per second. Configuring a time range of 2 weeks and a period of 1 minute will ensure that the data can be accurately examined to determine peak traffic times and volumes.

NEW QUESTION 321

- (Exam Topic 1)

A recent organizational audit uncovered an existing Amazon RDS database that is not currently configured for high availability. Given the critical nature of this database, it must be configured for high availability as soon as possible.

How can this requirement be met?

- A. Switch to an active/passive database pair using the create-db-instance-read-replica with the --availability-zone flag.
- B. Specify high availability when creating a new RDS instance, and live-migrate the data.
- C. Modify the RDS instance using the console to include the Multi-AZ option.
- D. Use the modify-db-instance command with the --na flag.

Answer: C

NEW QUESTION 323

- (Exam Topic 1)

A team of On-call engineers frequently needs to connect to Amazon EC2 Instances in a private subnet to troubleshoot and run commands. The Instances use either the latest AWS-provided Windows Amazon Machine Images (AMIs) or Amazon Linux AMIs.

The team has an existing IAM role for authorization. A SysOps administrator must provide the team with access to the Instances by granting IAM permissions to this. Which solution will meet this requirement?

- A. Add a statement to the IAM role policy to allow the ssm:StartSession action on the instance
- B. Instruct the team to use AWS Systems Manager Session Manager to connect to the Instances by using the assumed IAM role.
- C. Associate an Elastic IP address and a security group with each instanc
- D. Add the engineers' IP addresses to the security group inbound rule
- E. Add a statement to the IAM role policy to allow the ec2:AuthorizeSecurityGroupIngress action so that the team can connect to the Instances.
- F. Create a bastion host with an EC2 Instance, and associate the bastion host with the VP
- G. Add a statement to the IAM role policy to allow the ec2:CreateVpnConnection action on the bastion hos
- H. Instruct the team to use the bastion host endpoint to connect to the instances. D Create an internet-facing Network Load Balance
- I. Use two listener
- J. Forward port 22 to a target group of Linux instance
- K. Forward port 3389 to a target group of Windows Instance
- L. Add a statement to the IAM role policy to allow the ec2:CreateRoute action so that the team can connect to the Instances.

Answer: A

NEW QUESTION 328

- (Exam Topic 1)

With the threat of ransomware viruses encrypting and holding company data hostage, which action should be taken to protect an Amazon S3 bucket?

- A. Deny Pos
- B. Pu
- C. and Delete on the bucket.
- D. Enable server-side encryption on the bucket.
- E. Enable Amazon S3 versioning on the bucket.
- F. Enable snapshots on the bucket.

Answer: B

NEW QUESTION 329

- (Exam Topic 1)

A SysOps administrator created an AWS CloudFormation template that provisions Amazon EC2 instances, an Elastic Load Balancer (ELB), and an Amazon RDS DB instance. During stack creation, the creation of the EC2 instances and the creation of the ELB are successful. However, the creation of the DB instance fails. What is the default behavior of CloudFormation in this scenario?

- A. CloudFormation will roll back the stack and delete the stack.
- B. CloudFormation will roll back the stack but will not delete the stack.
- C. CloudFormation will prompt the user to roll back the stack or continue.
- D. CloudFormation will successfully complete the stack but will report a failed status for the DB instance.

Answer: C

NEW QUESTION 334

- (Exam Topic 1)

A company's VPC has connectivity to an on-premises data center through an AWS Site-to-Site VPN. The company needs Amazon EC2 instances in the VPC to send DNS queries for example.com to the DNS servers in the data center.

Which solution will meet these requirements?

- A. Create an Amazon Route 53 Resolver inbound endpoint Create a conditional forwarding rule on the on-premises DNS servers to forward DNS requests for example.com to the inbound endpoints.
- B. Create an Amazon Route 53 Resolver inbound endpoint Create a forwarding rule on the resolver that sends all queries for example.com to the on-premises DNS server
- C. Associate this rule with the VPC.
- D. Create an Amazon Route 53 Resolver outbound endpoint Create a conditional forwarding rule on the on-premises DNS servers to forward DNS requests for example.com to the outbound endpoints
- E. Create an Amazon Route 53 Resolver outbound endpoint
- F. Create a forwarding rule on the resolver that sends all queries for example.com to the on-premises DNS servers Associate this rule with the VPC.

Answer: C

NEW QUESTION 339

- (Exam Topic 1)

A SysOps administrator is using AWS Systems Manager Patch Manager to patch a fleet of Amazon EC2 instances. The SysOps administrator has configured a patch baseline and a maintenance window. The SysOps administrator also has used an instance tag to identify which instances to patch.

The SysOps administrator must give Systems Manager the ability to access the EC2 instances. Which additional action must the SysOps administrator perform to meet this requirement?

- A. Add an inbound rule to the instances' security group.
- B. Attach an IAM instance profile with access to Systems Manager to the instances.
- C. Create a Systems Manager activation Then activate the fleet of instances.
- D. Manually specify the instances to patch Instead of using tag-based selection.

Answer: A

NEW QUESTION 344

- (Exam Topic 1)

A SysOps administrator is deploying a test site running on Amazon EC2 instances. The application requires both incoming and outgoing connectivity to the internet.

Which combination of steps are required to provide internet connectivity to the EC2 instances? (Choose two.)

- A. Add a NAT gateway to a public subnet.
- B. Attach a private address to the elastic network interface on the EC2 instance.
- C. Attach an Elastic IP address to the internet gateway.
- D. Add an entry to the route table for the subnet that points to an internet gateway.
- E. Create an internet gateway and attach it to a VPC.

Answer: DE

Explanation:

https://docs.aws.amazon.com/vpc/latest/userguide/VPC_Internet_Gateway.html

NEW QUESTION 346

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual SOA-C02 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the SOA-C02 Product From:

<https://www.2passeasy.com/dumps/SOA-C02/>

Money Back Guarantee

SOA-C02 Practice Exam Features:

- * SOA-C02 Questions and Answers Updated Frequently
- * SOA-C02 Practice Questions Verified by Expert Senior Certified Staff
- * SOA-C02 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * SOA-C02 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year