

Oracle

Exam Questions 1z0-082

Oracle Database Administration I



NEW QUESTION 1

Table EMPLOYEES contains columns including EMPLOYEE_ID, JOB_ID and SALARY. Only the EMPLOYEE_ID column is indexed. Rows exist for employees 100 and 200. Examine this statement:

```
UPDATE employees
   SET (job_id, salary) =
      (SELECT job_id, salary
       FROM employees
       WHERE employee_id = 200)
 WHERE employee_id = 100;
```

Which two statements are true? (Choose two.)

- A. Employee 100 will have SALARY set to the same value as the SALARY of employee 200
- B. Employee 200 will have JOB_ID set to the same value as the JOB_ID of employee 100
- C. Employee 200 will have SALARY set to the same value as the SALARY of employee 100
- D. Employee 100 will have JOB_ID set to the same value as the JOB_ID of employee 200
- E. Employees 100 and 200 will have the same JOB_ID as before the update command
- F. Employees 100 and 200 will have the same SALARY as before the update command

Answer: AB

NEW QUESTION 2

Examine this description of the TRANSACTIONS table:

Name	Null?	Type
-----	-----	-----
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_DATE		DATE
AMOUNT		NUMBER (10, 2)
CUSTOMER_ID		VARCHAR2 (6)

Which two SQL statements execute successfully? (Choose two.)

- A. SELECT customer_id AS "CUSTOMER-ID", transaction_date AS DATE, amount + 100 "DUES" FROM transactions;
- B. SELECT customer_id AS "CUSTOMER-ID", transaction_date AS "DATE", amount + 100 DUES FROM transactions;
- C. SELECT customer_id AS CUSTOMER-ID, transaction_date AS TRANS_DATE, amount + 100 "DUES AMOUNT" FROM transactions;
- D. SELECT customer_id CUSTID, transaction_date TRANS_DATE, amount + 100 DUES FROM transactions;
- E. SELECT customer_id AS 'CUSTOMER-ID', transaction_date AS DATE, amount + 100 'DUES AMOUNT' FROM transactions;

Answer: BD

NEW QUESTION 3

You execute this command:

```
[oracle@host01 ~]$ expdp system/oracle \
> FULL=Y \
> DUMPFILE=exp_db_full.dmp \
> PARALLEL=4 \
> LOGFILE=exp_db_full.log \
> JOB_NAME=exp_db_full
```

During the export operation, you detach from the job by using CTRL+C and then execute this command: Export> STOP_JOB=immediate

Are you sure you wish to stop the job ([yes]/no): yes

Which two statements are true about the job? (Choose two.)

- A. You can no longer monitor it
- B. You can reattach to it and monitor it
- C. It is paused and can be resumed
- D. It continues to run in the background
- E. It terminates

Answer: AE

NEW QUESTION 4

Which three statements are true about advanced connection options supported by Oracle Net for connection to Oracle Database instances? (Choose three.)

- A. Connect Time Failover requires the use of Transparent Application Failover (TAF)
- B. Source Routing requires the use of a name server
- C. Source Routing enables the use of Connection Manager (CMAN) which enables network traffic to be routed through a firewall
- D. Load Balancing can balance the number of connections to dispatchers when using a Shared Server configuration
- E. Load Balancing requires the use of a name server

F. Connect Time Failover requires the connect string to have two or more listener addresses configured

Answer: BCF

NEW QUESTION 5

You have been tasked to create a table for a banking application. One of the columns must meet three requirements:

- Be stored in a format supporting date arithmetic without using conversion functions
- Store a loan period of up to 10 years
- Be used for calculating interest for the number of days the loan remains unpaid Which data type should you use?

- A. INTERVAL YEAR TO MONTH
- B. INTERVAL DAY TO SECOND
- C. TIMESTAMP WITH LOCAL TIMEZONE
- D. TIMESTAMP
- E. TIMESTAMP WITH TIMEZONE

Answer: B

NEW QUESTION 6

The CUSTOMERS table has a CUST_CREDIT_LIMIT column of data type NUMBER. Which two queries execute successfully? (Choose two.)

- A. SELECT NVL(cust_credit_limit * .15, 'Not Available') FROM customers;
- B. SELECT NVL2(cust_credit_limit * .15, 'Not Available') FROM customers;
- C. SELECT NVL(TO_CHAR(cust_credit_limit * .15), 'Not Available') FROM customers;
- D. SELECT TO_CHAR(NVL(cust_credit_limit * .15, 'Not Available')) FROM customers;
- E. SELECT NVL2(cust_credit_limit, TO_CHAR(cust_credit_limit * .15), 'Not Available') FROM customers;

Answer: BC

NEW QUESTION 7

Which two statements are true about space-saving features in an Oracle Database? (Choose two.)

- A. Private Temporary Tables (PTTS) store metadata in memory only
- B. An index created with the UNUSABLE attribute has no segment
- C. If they exist for a session, Private Temporary Tables (PTTs) are always dropped at the next COMMIT OR ROLLBACK statement
- D. An index that is altered to be UNUSABLE will retain its segment
- E. A table that is truncated will always have its segment removed

Answer: BC

NEW QUESTION 8

You execute this command:

```
CREATE BIGFILE TABLESPACE big_tbs
    DATAFILE '/u01/oracle/data/big_f1.dbf'
    SIZE 20G;
```

Sufficient storage is available in filesystem /u01.

Which two statements are true about the BIG_TBS tablespace? (Choose two.)

- A. AUTOEXTEND is possible for the datafile
- B. It must be bigger than the largest SMALLFILE tablespace
- C. Additional data files may not be added
- D. It will be a dictionary-managed tablespace by default
- E. It will always have a 32K blocksize

Answer: AB

NEW QUESTION 9

Which statement is true about the INTERSECT operator used in compound queries?

- A. Multiple INTERSECT operators are not possible in the same SQL statement
- B. It processes NULLs in the selected columns
- C. INTERSECT is of lower precedence than UNION or UNION ALL
- D. It ignores NULLs

Answer: B

NEW QUESTION 10

In your data center, Oracle Managed Files (OMF) is used for all databases. All tablespaces are smallfile tablespaces.

SALES_Q1 is a permanent user-defined tablespace in the SALES database.

Examine this command which is about to be issued by a DBA logged in to the SALES database: ALTER TABLESPACE sales_q1 ADD DATAFILE;

Which are two actions, either one of which you could take to ensure that the command executes successfully? (Choose two.)

- A. Ensure that DB_RECOVERY_FILE_DEST and DB_CREATE_FILE_DEST each specify with at least 50 Mb of available space.
- B. Specify a path in the DATAFILE clause of the command specifying a location with at least 100M of available space.

- C. Ensure that DB_CREATE_FILE_DEST specifies a location with at least 100 Mb of available space.
- D. Add the AUTOEXTEND ON clause with NEXT set to 100M.
- E. Ensure that DB_RECOVERY_FILE_DEST and DB_CREATE_FILE_DEST each specify locations with at least 50 Mb of available space.

Answer: BD

NEW QUESTION 10

Which two statements are true about the PMON background process? (Choose two.)

- A. It registers database services with all local and remote listeners known to the database instance
- B. It frees resources held by abnormally terminated processes
- C. It records checkpoint information in the control file
- D. It frees unused temporary segments
- E. It kills sessions that exceed idle time

Answer: AB

NEW QUESTION 15

Which four statements are true regarding primary and foreign key constraints and the effect they can have on table data? (Choose four.)

- A. A table can have only one primary key but multiple foreign keys
- B. A table can have only one primary key and foreign key
- C. The foreign key columns and parent table primary key columns must have the same names
- D. It is possible for child rows that have a foreign key to remain in the child table at the time the parent row is deleted
- E. It is possible for child rows that have a foreign key to be deleted automatically from the child table at the time the parent row is deleted
- F. Only the primary key can be defined at the column and table level
- G. Primary key and foreign key constraints can be defined at both the column and table level

Answer: ACEG

NEW QUESTION 19

The SALES_Q1 and USERS tablespaces exist in one of your databases and TEMP is a temporary tablespace. Segment creation is not deferred. You execute this command:

```
CREATE USER sales
  IDENTIFIED BY sales_123
  DEFAULT TABLESPACE sales_q1
  TEMPORARY TABLESPACE temp
  QUOTA 5M ON users;
```

Which three statements must be true so that the SALES user can create tables in SALES_Q1? (Choose three.)

- A. The sales user must have a quota on the TEMP tablespace
- B. The sales user must have a quota on the SALES_Q1 tablespace to hold the initial extents of all tables they plan to create in their schema
- C. The sales user must have been granted the CREATE SESSION privilege
- D. The sales user must have their quota on the users tablespace removed
- E. The sales user must have a quota on the SALES_Q1 tablespace to hold all the rows to be inserted into any table in their schema
- F. The sales user must have been granted the CREATE TABLE privilege

Answer: BDF

NEW QUESTION 22

The INVOICE table has a QTY_SOLD column of data type NUMBER and an INVOICE_DATE column of data type DATE.

NLS_DATE_FORMAT is set to DD-MON-RR.

Which two are true about data type conversions involving these columns in query expressions? (Choose two.)

- A. CONCAT (qty_sold, invoice_date) : requires explicit conversion
- B. invoice_date = '15-march-2019' : uses implicit conversion
- C. invoice_date > '01-02-2019' : uses implicit conversion
- D. qty_sold BETWEEN '101' AND '110' : uses implicit conversion
- E. qty_sold = '0554982' uses implicit conversion

Answer: BD

NEW QUESTION 27

Which three functions are performed by dispatchers in a shared server configuration? (Choose three.)

- A. writing inbound request to the common request queue from all shared server connections
- B. checking for outbound shared server responses on the common outbound response queue
- C. receiving inbound requests from processes using shared server connections
- D. sending each connection input request to the appropriate shared server input queue
- E. broadcasting shared server session responses back to requesters on all connections
- F. sending shared server session responses back to requesters on the appropriate connection

Answer: ACD

NEW QUESTION 30

Which two statements are true regarding a SAVEPOINT? (Choose two.)

- A. Rolling back to a SAVEPOINT can undo a CREATE INDEX statement
- B. Rolling back to a SAVEPOINT can undo a TRUNCATE statement
- C. Only one SAVEPOINT may be issued in a transaction
- D. A SAVEPOINT does not issue a COMMIT
- E. Rolling back to a SAVEPOINT can undo a DELETE statement

Answer: DE

NEW QUESTION 31

The EMPLOYEES table contains columns EMP_ID of data type NUMBER and HIRE_DATE of data type DATE.

You want to display the date of the first Monday after the completion of six months since hiring.

The NLS_TERRITORY parameter is set to AMERICA in the session and, therefore, Sunday is the first day on the week.

Which query can be used?

- A. SELECT emp_id, ADD_MONTHS(hire_date, 6), NEXT_DAY('MONDAY') FROM employees;
- B. SELECT emp_id, NEXT_DAY(ADD_MONTHS(hire_date, 6), 'MONDAY') FROM employees;
- C. SELECT emp_id, NEXT_DAY(MONTHS_BETWEEN(hire_date, SYSDATE), 6) FROM employees;
- D. SELECT emp_id, NEXT_DAY(ADD_MONTHS(hire_date, 6), 1) FROM employees;

Answer: B

NEW QUESTION 33

Which three statements are true about single-row functions? (Choose three.)

- A. They can be used only in the WHERE clause of a SELECT statement
- B. The argument can be a column name, variable, literal or an expression
- C. The data type returned can be different from the data type of the argument
- D. They can be nested to any level
- E. They can accept only one argument
- F. They return a single result row per table

Answer: BCF

NEW QUESTION 34

Which statement is true about aggregate functions?

- A. Aggregate functions can be nested to any number of levels
- B. The AVG function implicitly converts NULLS to zero
- C. Aggregate functions can be used in any clause of a SELECT statement
- D. The MAX and MIN functions can be used on columns with character data types

Answer: A

NEW QUESTION 37

Which three statements are true about a self-join? (Choose three.)

- A. The ON clause must be used
- B. The query must use two different aliases for the table
- C. It must be an equi join
- D. It must be an inner join
- E. The ON clause can be used
- F. It can be an outer join

Answer: BDE

NEW QUESTION 41

Examine these commands:


```
[oracle@host01 ~]$ sqlplus u1/oracle
SQL> SELECT * FROM emp;
ENO          ENAME          DN
-----
1            Alan            2
2            Ben             2

SQL> exit
[oracle@host01 ~]$ cat emp.dat

3,Curl,4
4,Bob,4
[oracle@host01 ~]$ sqlldr u1/oracle TABLE=emp
```

Which two statements are true about the sqlldr execution? (Choose two.)

- A. It overwrites data in EMP with data in EMP.DAT
- B. It uses the database buffer cache to load data
- C. It generates a log that contains control file entries, which can be used with normal SQL*Loader operations
- D. It generates a sql script that it uses to load data from EMP.DAT to EMP
- E. It appends data from EMP.DAT to EMP

Answer: BD

NEW QUESTION 46

Which three statements are true about table data storage in an Oracle Database? (Choose three.)

- A. Data block headers contain their own Data Block Address (DBA)
- B. A table row piece can be chained across several database blocks
- C. Multiple row pieces from the same row may be stored in different database blocks
- D. Multiple row pieces from the same row may be stored in the same block
- E. Data block free space is always contiguous in the middle of the block
- F. Index block free space is always contiguous in the middle of the block

Answer: BCE

NEW QUESTION 51

In one of your databases, you create a user, HR, and then execute this command: GRANT CREATE SESSION TO hr WITH ADMIN OPTION;
Which three actions can HR perform? (Choose three.)

- A. Revoke the CREATE SESSION privilege from other users
- B. Revoke the CREATE SESSION privilege from user HR
- C. Log in to the database instance
- D. Grant the CREATE SESSION privilege with ADMIN OPTION to other users
- E. Execute DDL statements in the HR schema
- F. Execute DML statements in the HR schema

Answer: ADE

NEW QUESTION 54

Which two statements are true about the rules of precedence for operators? (Choose two.)

- A. The concatenation operator || is always evaluated before addition and subtraction in an expression
- B. NULLS influence the precedence of operators in an expression
- C. The + binary operator has the highest precedence in an expression in a SQL statement
- D. Arithmetic operators with equal precedence are evaluated from left to right within an expression
- E. Multiple parentheses can be used to override the default precedence of operators in an expression

Answer: CE

NEW QUESTION 58

You need to calculate the number of days from 1st January 2019 until today. Dates are stored in the default format of DD-MON-RR.
Which two queries give the required output? (Choose two.)

- A. SELECT TO_CHAR(SYSDATE, 'DD-MON-YYYY') - '01-JAN-2019' FROM DUAL;
- B. SELECT ROUND(SYSDATE - '01-JAN-2019') FROM DUAL;
- C. SELECT ROUND(SYSDATE - TO_DATE('01/JANUARY/2019')) FROM DUAL;
- D. SELECT TO_DATE(SYSDATE, 'DD/MONTH/YYYY') - '01/JANUARY/2019' FROM DUAL;
- E. SELECT SYSDATE - TO_DATE('01-JANUARY-2019') FROM DUAL;

Answer: AB

NEW QUESTION 62

Examine the description of the PROMOTIONS table:

Name	Null?	Type

PROMO_ID	NOT NULL	NUMBER (6)
PROMO_NAME	NOT NULL	VARCHAR2 (30)
PROMO_CATEGORY	NOT NULL	VARCHAR2 (30)
PROMO_COST	NOT NULL	NUMBER (10,2)

You want to display the unique promotion costs in each promotion category. Which two queries can be used? (Choose two.)

- A. SELECT promo_cost, promo_category FROM promotions ORDER BY 1;
- B. SELECT DISTINCT promo_cost || ' in ' || DISTINCT promo_category FROM promotions ORDER BY 1;
- C. SELECT DISTINCT promo_category || ' has ' || promo_cost AS COSTS FROM promotions ORDER BY 1;
- D. SELECT promo_category, DISTINCT promo_cost FROM promotions ORDER BY 2;
- E. SELECT DISTINCT promo_category, promo_cost FROM promotions ORDER BY 1;

Answer: DE

NEW QUESTION 67

Examine the description of the CUSTOMERS table:

```
CREATE TABLE sales1 (prod_id, cust_id, quantity_sold, price)
AS
SELECT product_id, customer_id, quantity_sold, price
FROM sales
WHERE 1 = 1;
```

For customers whose income level has a value, you want to display the first name and due amount as 5% of their credit limit. Customers whose due amount is null should not be displayed.

Which query should be used?

- A. SELECT cust_first_name, cust_credit_limit * .05 AS DUE_AMOUNT FROM customers WHERE cust_incoms_level IS NOT NULL AND due_amount IS NOT NULL;
- B. SELECT cust_first_name, cust_credit_limit * .05 AS DUE_AMOUNT FROM customers WHERE cust_income_level != NULL AND cust_credit_level != NULL;
- C. SELECT cust_first_name, cust_credit_limit * .05 AS DUE_AMOUNT FROM customers WHERE cust_income_level <> NULL AND due_amount <> NULL;
- D. SELECT cust_first_name, cust_credit_limit * .05 AS DUE_AMOUNT FROM customers WHERE cust_income_level != NULL AND due_amount != NULL;
- E. SELECT cust_first_name, cust_credit_limit * .05 AS DUE_AMOUNT FROM customers WHERE cust_income_level IS NOT NULL AND cust_credit_limit IS NOT NULL;

Answer: E

NEW QUESTION 69

What is true about non-equijoin statement performance? (Choose two.)

- A. Table aliases can improve performance
- B. The BETWEEN condition always performs better than using the >= and <= conditions
- C. The join syntax used makes no difference to performance
- D. The BETWEEN condition always performs less well than using the >= and <= conditions
- E. The Oracle join syntax performs better than the SQL:1999 compliant ANSI join syntax

Answer: AE

NEW QUESTION 70

Which two are true about shrinking a segment online? (Choose two.)

- A. It is not possible to shrink either indexes or Index Organized Tables (IOTs)
- B. It always eliminates all migrated rows if any exist in the table
- C. To shrink a table it must have a PRIMARY KEY constraint
- D. To shrink a table it must have a UNIQUE KEY constraint
- E. To shrink a table it must have row movement enabled
- F. It must be in a tablespace that uses Automatic Segment Space Management (ASSM)

Answer: CE

NEW QUESTION 73

Which two statements are true about the results of using the INTERSECT operator in compound queries? (Choose two.)

- A. Column names in each SELECT in the compound query can be different
- B. The number of columns in each SELECT in the compound query can be different
- C. Reversing the order of the intersected tables can sometimes affect the output
- D. INTERSECT returns rows common to both sides of the compound query
- E. INTERSECT ignores NULLs

Answer: AE

NEW QUESTION 78

In one of your databases, the user HR has the password HRMGR.

You want to connect to a database instance whose listener listens on port 1531 by using this statement: CONNECT HR/HRMGR@orcl

No name server is used.

Which statement is true about ORCL?

- A. It must be the value of the SERVICE_NAMES parameter on the client side
- B. It must resolve to a valid connect descriptor in the server's tnsnames.ora file
- C. It must resolve to a valid connect descriptor in the client's tnsnames.ora file
- D. It must be the name of the database to whose instance HR wishes to connect
- E. It must be the name of the server running the database to whose instance HR wishes to connect

Answer: E

NEW QUESTION 83

Which two statements are true about Enterprise Manager Database Express? (Choose two.)

- A. It is available only when the database is open
- B. It can be used to perform database recovery
- C. The same port number can be used for Database Express configurations for databases on different hosts
- D. It can be used to switch a database into ARCHIVELOGMODE
- E. The same port number can be used for multiple Database Express configurations for multiple databases on the same host

Answer: DE

NEW QUESTION 87

Which two statements are true about UNDO and REDO? (Choose two.)

- A. The generation of UNDO generates REDO
- B. DML modifies Oracle database objects and only generates UNDO
- C. The generation of REDO generates UNDO
- D. DML modifies Oracle database objects and only generates REDO

Answer: AC

NEW QUESTION 90

Evaluate these commands which execute successfully:

Name	Null?	Type
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_TYPE		VARCHAR2 (3)
BORROWED_DATE		DATE
BOOK_ID		VARCHAR2 (6)
MEMBER_ID		VARCHAR2 (6)

Which two statements are true about the ORD_ITEMS table and the ORD_SEQ sequence? (Choose two.)

- A. If sequence ORD_SEQ is dropped then the default value for column ORD_NO will be NULL for rows inserted into ORD_ITEMS
- B. Any user inserting rows into table ORD_ITEMS must have been granted access to sequence ORD_SEQ
- C. Column ORD_NO gets the next number from sequence ORD_SEQ whenever a row is inserted into ORD_ITEMS and no explicit value is given for ORD_NO
- D. Sequence ORD_SEQ cycles back to 1 after every 5000 numbers and can cycle 20 times
- E. Sequence ORD_SEQ is guaranteed not to generate duplicate numbers

Answer: BE

NEW QUESTION 94

A script abc.sql must be executed to perform a job.

A database user HR, who is defined in this database, executes this command:

\$ sqlplus hr/hr@orcl @abc.sql What will happen upon execution?

- A. The command succeeds and HR will be connected to the orcl and abc.sql databases
- B. The command succeeds and HR will be connected to the orcl database instance, and the abc.sql script will be executed
- C. The command fails because the script must refer to the full path name
- D. The command fails and reports an error because @ is used twice

Answer: B

NEW QUESTION 99

Which three Oracle database space management features will work with both Dictionary and Locally managed tablespaces? (Choose three.)

- A. Oracle Managed Files (OMF)
- B. Online table segment shrink
- C. Online index segment shrink
- D. Automatic data file extension (AUTOEXTEND)
- E. Capacity planning growth reports based on historical data in the Automatic Workload Repository (AWR)

Answer: ADE

NEW QUESTION 104

Which two statements are true regarding the UNION and UNION ALL operators? (Choose two.)

- A. Duplicates are eliminated automatically by the UNION ALL operator
- B. The number of columns selected in each SELECT statement must be identical
- C. The names of columns selected in each SELECT statement must be identical
- D. The output is sorted by the UNION ALL operator
- E. NULLS are not ignored during duplicate checking

Answer: BE

NEW QUESTION 106

Which three statements are true about the DESCRIBE command? (Choose three.)

- A. It displays the PRIMARY KEY constraint for any column or columns that have that constraint
- B. It can be used from SQL Developer
- C. It displays the NOT NULL constraint for any columns that have that constraint
- D. It can be used to display the structure of an existing view
- E. It displays all constraints that are defined for each column
- F. It can be used only from SQL *Plus

Answer: CDF

NEW QUESTION 110

In one of your databases, user KING is:

- \1. Not a DBA user
 - \2. An operating system (OS) user
- Examine this command and its output:

```
SHOW PARAMETER OS_AUTHENT_PREFIX

NAME                                TYPE                                VALUE
-----                                -                                -
os_authent_prefix                    string                              OPS$
```

What must you do so that KING is authenticated by the OS when connecting to the database instance?

- A. Set OS_AUTHENT_PREFIX to OPS\$
- B. Have the OS administrator add KING to the OSDBA group
- C. Grant DBA to KING
- D. Unset REMOTE_LOGIN_PASSWORDFILE
- E. Alter user KING to be IDENTIFIED EXTERNALLY

Answer: D

NEW QUESTION 111

The ORCL database has RESUMABLE TIMEOUT = 7200 and DEFERRED_SEGMENT_CREATION = FALSE

User U1 has a 1 MB quota in tablespace DATA. U1 executes this command:

```
SQL> CREATE TABLE t1 AS
(SELECT object_name, sharing, created FROM dba_objects);
```

U1 complains that the command is taking too long to execute.

In the alert log, the database administrator (DBA) finds this: 2017-03-06T12:15:17.183438+05:30

statement in resumable session 'User U1(136), Session 1, Instance 1' was suspended due to ORA-01536: space quota exceeded for tablespace 'DATA'

Which are three actions any one of which the DBA could take to resume the session? (Choose three.)

- A. Add a data file to DATA
- B. Drop other U1 objects in DATA
- C. Increase U1's quota sufficiently in DATA
- D. Set DEFERRED_SEGMENT_CREATION to TRUE
- E. Grant UNLIMITED TABLESPACE to U1
- F. Set AUTOEXTEND ON for data files in DATA

Answer: CDF

NEW QUESTION 112

Which three statements are true concerning logical and physical database structures? (Choose three.)

- A. All tablespaces may have one or more data files
- B. The extents of a segment must always reside in the same datafile
- C. A smallfile tablespace might be bigger than a bigfile tablespace
- D. A segment can span multiple data files in some tablespaces
- E. A segment's blocks can be of different sizes
- F. A segment might have only one extent
- G. Segments can span multiple tablespaces

Answer: CFG

NEW QUESTION 114

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

1z0-082 Practice Exam Features:

- * 1z0-082 Questions and Answers Updated Frequently
- * 1z0-082 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-082 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-082 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 1z0-082 Practice Test Here](#)